

MODEL HIPA08104050

8-10.5GHz Power Amplifier

■ Features

- Ultra Wide Band: 8-10.5GHz
- Gain: 40dB
- Output Power Psat: 50dBm
- Bias: Vd=30V;Id=8A

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	8-10.5			GHz
Small Signal Gain	40	42		dB
Gain Flatness		±1.5	±2	dB
Input VSWR		1.5	2.0	-
Output Power P-1 (CW)	49			dBm
Saturated Output Power Past	50			dBm
NF		10		dB
Spurious		-60		dBc
Input Max Power(no damage)			15	dBm
Control TTL	Enable: TTL "High" Disable: TTL "Low"			
DC Current (Vcc=+30V) (@Pout=100W)		8		A
Function	Over Current & Over temperature protection			
Impedance	50			Ω
Input Output Connector	SMA-k/N-K			
Material	Aluminium			
Weight	4kg			
Outline Size	120mmX55mmX160mm			

Environmental Conditions

Environmental Specifications:

- ※ Operational Temperature -25°C~+65°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)

Pin#	Pin Function
1,2,3	Vdc
4,5,6	GND
7	Enable: TTL "High" Disable: TTL "Low"
8,9	NC

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. HiMicrowave technologies co., Ltd. reserves the right to change the above information without notice.

*****Heat Sink required during operation*****