

MODEL HIPA08184037AC

8-18GHz Power Amplifier



■ Features

- Ultra Wide Band: 8-18GHz
- Gain: 40dB
- Output Power Psat: 37dBm
- Bias: 110~220V/50~60Hz

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	8-18			GHz
Small Signal Gain	40			dB
Gain Flatness		± 2.5	± 3.5	dB
Input VSWR		1.5	2.0	-
Output Power for 1 dB Compression (P1dB)	35	36		dBm
Saturated Output Power (Psat)	37	38		dBm
Harmonic Rejection		15		dB
Input Max Power(no damage)			+5	dBm
Internally Generated Spurious		-60		dBc
Supply Voltage	110~220V/50Hz			
Impedance	50			Ω
Input Output Connector	SMA-k/SMA-K			
Material	Aluminum			
Weight	1.5kg			

Environmental Conditions

Environmental Specifications:

- ※ Operational Temperature -25°C~+70°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)

