

MODEL HIPA17432130

17-43GHz Power Amplifier



Note: The photo is for illustration purposes only.
Please refer to outline drawing

■ Features

- Ultra Wide Band: 17-43GHz
- Gain: 20dB
- Output Power: 31dBm
- High Output IP3: 40dBm

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	17-43			GHz
Gain	20	21		dB
Gain Flatness		±2.5		dB
Input VSWR		2.0		dB
Output VSWR		2.0		dB
Output Power for 1 dB Compression (P1dB)		30		dBm
Saturated Output Power (Psat)	28	31		dBm
Spurious		-50		dBc
Second Harmonic			-15	dBc
Input Max Power(no damage)			15	dBm
DC Current (Vcc=+12V)		1000		mA
Impedance	50			Ω
Input Output Connector	2.92			
Material	Aluminum/Conductive oxide			
Weight	50g			
Size	50mmX55mmX12mm			
Package Sealing	General Sealing (Standard) Hermetically Seal(Optional)			

Environmental Conditions

Environmental Specifications:


※ Operational Temperature	-25°C~+85°C
※ Storage Temperature	-55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. HiMicrowave technologies co., Ltd. reserves the right to change the above information without notice.

*****Heat Sink required during operation*****