



MODEL HIPA18401622

18-40GHz Broadband Power Amplifier

■ Features

- Ultra Wide Band: 18-40GHz
- Gain: 17dB
- Output Power Psat: 25dBm
- Bias: Vd=12V;Id=0.4A

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	18-40			GHz
Small Signal Gain	16	17		dB
Gain Flatness		±1	±2	dB
Input VSWR		2.0	2.5	-
Output VSWR		2.0	2.5	-
Output Power for 1 dB Compression (P1dB)	22			dBm
Saturated Output Power (Psat)		23		dBm
Input Max Power(no damage)			15	dBm
DC Current (Vcc=+9~+15V) (@Pout=0.3W)		0.4	0.6	A
Impedance	50			Ω
Input Output Connector	2.92mm-Female			
Material	Aluminum/Gold Plated			
Weight	30g			
Dimension	28.8mmX28.8mmX12.7mm			

Environmental Conditions

Environmental Specifications:


※ Operational Temperature	-25°C~+85°C
※ Storage Temperature	-55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. HiMicrowave technologies co., Ltd. reserves the right to change the above information without notice.

*****Heat Sink required during operation*****

■ Performance Plot

