


MODEL HIPA23352028

23-35GHz Broadband Power Amplifier



Note: The photo is for illustration purposes only.
Please refer to outline drawing

■ Features

- Ultra Wide Band: 23-35GHz
- Gain: 20dB
- Output Power Psat: 28dBm
- Bias: Vd=12V;Id=0.5A

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	23-35			GHz
Small Signal Gain		20		dB
Gain Flatness		± 2.0		dB
Input VSWR		2.0		-
Output VSWR		2.0		-
Output Power for 1 dB Compression (P1dB)		28		dBm
Saturated Output Power (Psat)		29		dBm
Input Max Power(no damage)			15	dBm
DC Current (Vcc=+6~15V)		500	1000	A
Impedance	50			Ω
Input Output Connector	2.92			
Material	Aluminum/Gold Painting			
Weight	200g			
Dimension	50mmX45mmX12mm			

Environmental Conditions

Environmental Specifications:


- ※ Operational Temperature $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- ※ Storage Temperature $-55^{\circ}\text{C} \sim +125^{\circ}\text{C}$



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. HiMicrowave technologies co., Ltd. reserves the right to change the above information without notice.

*****Heat Sink required during operation*****