


MODEL HIPA37391537

37-39GHz Power Amplifier



Note: The photo is for illustration purposes only.
Please refer to outline drawing

■ Features

- Ultra Wide Band: 37-39GHz
- Gain: 15dB
- Output Power Psat: 38dBm
- Bias: Vd=12V;Id=2A

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	37-39			GHz
Small Signal Gain		15		dB
Gain Flatness		±1		dB
Input VSWR		2.0		-
Output Power for 1 dB Compression (P1dB)		37		dBm
Saturated Output Power (Psat)		38		dBm
Input Max Power(no damage)			25	dBm
Internally Generated Spurious		-60		dBc
DC Current (Vcc=+12V) (@Pout=10W)		2	3	A
Impedance	50			Ω
Input Output Connector	WR22			
Material	Aluminum			
Weight	200g			
Dimension	Gold Plated			

□ Environmental Conditions

Environmental Specificatons:

※ Operational Temperature -25°C~+70°C


※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

□ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. HIMicrowave technologies co., Ltd. reserves the right to change the above information without notice.

Heat Sink required during operation