Interactions - MVA 2025/2026

Project Assignment

Mean-Field Neural Networks with Graphon Heterogeneity for Systemic Risk Control

Adonis JAMAL adonis.jamal@student-cs.fr
Fotios KAPOTOS fotiskapotos@gmail.com

April 2026

1 Introduction and Contributions

2 Paper Overview

3 Methodology

4 Data and Experimental Setup

5 Results

6 Conclusion and Discussion

References

[1] René Carmona and François Delarue. *Probabilistic Theory of Mean Field Games with Applications I: Mean Field FBSDEs, Control, and Games*. Springer, 2018.

[2] René Carmona, Jean-Pierre Fouque, and Li-Hsien Sun. Mean field games and systemic risk. *Communications in Mathematical Sciences*, 13(4):911–933, 2015.

[3] Fabio Coppini, Anna De Crescenzo, and Huyên Pham. Nonlinear graphon mean-field systems. *Stochastic Processes and their Applications*, 190:None, 2025. doi: 10.1016/j.spa.2025.104728. URL https://ideas.repec.org/a/eee/spapps/v190y2025ics0304414925001693.html.

[4] Nicolas Fournier and Arnaud Guillin. On the rate of convergence in Wasserstein distance of the empirical measure. 2013. URL https://arxiv.org/abs/1312.2128.

[5] László Lovász. *Large Networks and Graph Limits*. American Mathematical Society, 2012.

[6] Huyên Pham and Xavier Warin. Mean-field neural networks-based algorithms for mckean-vlasov control problems, 2024. URL https://arxiv.org/abs/2212.11518.

A McKean–Vlasov Control Problem

We recall the general framework for mean-field control (MFC), also called McKean–Vlasov (MKV) control, following the formulation of Pham and Warin [6].

A.1 Controlled McKean–Vlasov SDE

Let $(\Omega, \mathcal{F}, \mathbb{F} = (\mathcal{F}_t)_{t\geq 0}, \mathbb{P})$ be a filtered probability space supporting a d-dimensional Brownian motion W. The controlled state process $X = (X_t)_{0\leq t\leq T}$, valued in $\mathbb{R}^d$, is governed by the mean-field stochastic differential equation:

$$\mathrm{d}X_t = b(X_t, \mathbb{P}_{X_t}, \alpha_t)\,\mathrm{d}t + \sigma(X_t, \mathbb{P}_{X_t}, \alpha_t)\,\mathrm{d}W_t, \qquad 0 \leq t \leq T, \quad X_0 \sim \mu_0, \tag{1}$$

where $\mu_0 \in \mathcal{P}_2(\mathbb{R}^d)$ is the initial distribution, $\alpha = (\alpha_t)_t$ is a progressively measurable control process valued in $A \subset \mathbb{R}^m$, and $\mathbb{P}_{X_t}$ denotes the law of X_t under $\mathbb{P}$. The coefficients $b : \mathbb{R}^d \times \mathcal{P}_2(\mathbb{R}^d) \times A \to \mathbb{R}^d$ and $\sigma : \mathbb{R}^d \times \mathcal{P}_2(\mathbb{R}^d) \times A \to \mathbb{R}^{d\times d}$ satisfy standard Lipschitz regularity assumptions.

Here $\mathcal{P}_2(\mathbb{R}^d)$ denotes the Wasserstein space of probability measures with finite second moment, equipped with the 2-Wasserstein distance:

$$\mathcal{W}_2(\mu, \nu) = \left(\inf_{X\sim\mu, Y\sim\nu} \mathbb{E}\left[d(X,Y)^2\right] \right)^{1/2}, \tag{2}$$

where X, Y are random with law given respectively by μ and ν.

Remark 1. *The key feature of* (1) *compared to a standard controlled SDE is that the coefficients depend on the* law $\mathbb{P}_{X_t}$ *of the state, making the system intrinsically infinite-dimensional. This reflects the mean-field interaction in a large population of cooperative agents governed by a social planner.*

A.2 Cost Functional and Value Function

The social planner seeks to minimize the cost functional:

$$J(\alpha) = \mathbb{E}\left[\int_0^T f(X_t, \mathbb{P}_{X_t}, \alpha_t)\,\mathrm{d}t + g(X_T, \mathbb{P}_{X_T}) \right], \tag{3}$$

where $f : \mathbb{R}^d \times \mathcal{P}_2(\mathbb{R}^d) \times A \to \mathbb{R}$ is the running cost and $g : \mathbb{R}^d \times \mathcal{P}_2(\mathbb{R}^d) \to \mathbb{R}$ is the terminal cost. The value function is:

$$v(\mu_0) = \inf_{\alpha\in\mathcal{A}} J(\alpha). \tag{4}$$

A crucial observation is that v is defined on the *Wasserstein space* $\mathcal{P}_2(\mathbb{R}^d)$, making it a function on an infinite-dimensional space. This is the central computational challenge: standard neural networks, which take finite-dimensional inputs, cannot directly represent mappings on $\mathcal{P}_2(\mathbb{R}^d)$.

A.3 Dynamic Programming Characterization

The decoupled value function $V : [0,T] \times \mathbb{R}^d \times \mathcal{P}_2(\mathbb{R}^d) \to \mathbb{R}$ satisfies the backward recursion:

$$V(t, X_t, \mathbb{P}_{X_t}) = \inf_{\alpha\in\mathcal{A}} \mathbb{E}\left[\int_t^{t+h} f(X_s, \mathbb{P}_{X_s}, \alpha_s)\,\mathrm{d}s + V(t+h, X_{t+h}, \mathbb{P}_{X_{t+h}}) \,\middle|\, \mathcal{F}_t \right], \tag{5}$$

with terminal condition $V(T, x, \mu) = g(x, \mu)$, and $v(\mu_0) = \mathbb{E}[V(0, X_0, \mu_0)]$.

Sending $h \to 0$ yields the *Master Bellman equation* on $[0, T) \times \mathbb{R}^d \times \mathcal{P}_2(\mathbb{R}^d)$, which involves the Lions derivative $\partial_\mu V$ on the Wasserstein space [1]. The optimal feedback control takes the form:

$$\alpha^\star(t, x, \mu) = \hat{a}(x, \mu, \mathcal{U}(t, x, \mu), \partial_x \mathcal{U}(t, x, \mu)), \tag{6}$$

where $\mathcal{U}(t, x, \mu) = \partial_x V(t, x, \mu) + \mathbb{E}_{\tilde{\xi} \sim \mu}[\partial_\mu V(t, \tilde{\xi}, \mu)(x)]$, and $\hat{a}$ minimizes the Hamiltonian:

$$H(x, \mu, p, M, a) := b(x, \mu, a) \cdot p + \tfrac{1}{2}\sigma\sigma^\top(x, \mu, a) \cdot M + f(x, \mu, a). \tag{7}$$

A.4 Forward-Backward SDE Characterization (Pontryagin)

When $\sigma(x, \mu)$ does not depend on the control, setting $Y_t = V(t, X_t, \mathbb{P}_{X_t})$ and $Z_t = \sigma(X_t, \mathbb{P}_{X_t})^\top \partial_x V(t, X_t, \mathbb{P}_{X_t})$, one obtains the forward-backward SDE system:

$$\begin{cases} \mathrm{d}X_t = b(X_t, \mathbb{P}_{X_t}, \hat{a}(X_t, \mathbb{P}_{X_t}, P_t))\,\mathrm{d}t + \sigma(X_t, \mathbb{P}_{X_t})\,\mathrm{d}W_t, & X_0 \sim \mu_0, \\ \mathrm{d}Y_t = -f(X_t, \mathbb{P}_{X_t}, \hat{a}(X_t, \mathbb{P}_{X_t}, P_t))\,\mathrm{d}t + Z_t \cdot \mathrm{d}W_t, & Y_T = g(X_T, \mathbb{P}_{X_T}), \end{cases} \tag{8}$$

for $0 \le t \le T$, where $P_t = \mathcal{U}(t, X_t, \mathbb{P}_{X_t})$. This characterization forms the basis of the backward SDE-based algorithms (Algorithms 4-8 in Pham and Warin [6]).

B Mean-Field Neural Network Architectures

Since the value function and optimal control are mappings on the Wasserstein space, one requires neural network architectures capable of taking a probability measure as input. Pham and Warin [6] introduce two such architectures.

B.1 Bin Density Network

The *bin density* network represents $\mu \in \mathcal{P}_2(\mathbb{R}^d)$ by discretizing its density on a fixed rectangular domain $\mathcal{K} \subset \mathbb{R}^d$ divided into K equal-volume bins $\{\mathrm{Bin}(k)\}_{k=1}^K$ with centers x_k and bin volume $h = \lambda^d(\mathcal{K})/K$. The network takes the form:

$$\mathcal{N}(\mu)(x) = \Phi(x,\, p^\mu), \qquad p_k^\mu = \frac{p_\mu(x_k)}{\sum_{j=1}^K p_\mu(x_j)\, h}, \quad k = 1, \ldots, K, \tag{9}$$

where p_μ is the density of μ and $\Phi : \mathbb{R}^d \times \mathbb{R}^K \to \mathbb{R}^p$ is a standard feedforward neural network. The bin weight vector $p^\mu \in \mathbb{R}^K$ provides a finite-dimensional representation of the measure.

Remark 2. *The bin density network requires a bounded support $\mathcal{K}$, whose choice affects accuracy. An iterative procedure is proposed in Pham and Warin [6] to adaptively select $\mathcal{K}$. The method is primarily effective for $d = 1$ due to the curse of dimensionality in binning.*

B.2 Cylindrical Network

The *cylindrical* network is defined as:

$$\mathcal{N}(\mu)(\cdot) = \Psi(\cdot,\, \langle \varphi, \mu \rangle), \qquad \langle \varphi, \mu \rangle := \int_{\mathbb{R}^d} \varphi(x)\, \mu(\mathrm{d}x) \in \mathbb{R}^q, \tag{10}$$

where $\varphi : \mathbb{R}^d \to \mathbb{R}^q$ is an *inner* feedforward network (encoding the measure into a latent space of dimension q), and $\Psi : \mathbb{R}^d \times \mathbb{R}^q \to \mathbb{R}^p$ is an *outer* feedforward network. Given samples $X^{(n)} \sim \mu$, $n = 1, \ldots, N$, the cylindrical function is approximated by:

$$\mathcal{N}(\mu)(\cdot) \approx \Psi\left(\cdot,\ \frac{1}{N}\sum_{n=1}^{N} \varphi(X^{(n)})\right). \tag{11}$$

Both architectures satisfy a universal approximation property on the Wasserstein space and are permutation-invariant with respect to the particle ordering.

B.3 Algorithm Overview

Pham and Warin [6] propose eight algorithms divided into two families:

- **Dynamic Programming (DP) based:** Algorithms 1-3:
  1. Algorithm 1 (*Global DP*): global learning of the feedback control via direct minimization of $J(\alpha)$ over all time steps simultaneously.
  2. Algorithm 2 (*Policy iteration*): alternates between policy evaluation and policy improvement at each time step.
  3. Algorithm 3 (*Value iteration*): sequentially learns the control and the value function backward in time.
- **Backward SDE / Pontryagin based:** Algorithms 4-8: exploit the FBSDE characterization (8) with various global or local loss functions.

For this project, we primarily target **Algorithm 1** (global DP) and **Algorithm 6** (global BSDE), as they offer the best trade-off between implementation simplicity and accuracy on the systemic risk benchmark.

C Systemic Risk Model

We consider the mean-field model of systemic risk introduced by Carmona et al. [2] in the context of mean-field games, adapted here to the cooperative (MFC) setting as in Section 5.1.1 of Pham and Warin [6].

C.1 Model Formulation

The log-monetary reserve of a representative bank evolves according to the mean-reverting controlled McKean–Vlasov dynamics:

$$\mathrm{d}X_t = (\kappa(\mathbb{E}[X_t] - X_t) + \alpha_t)\,\mathrm{d}t + \sigma\,\mathrm{d}W_t, \qquad X_0 \sim \mu_0, \tag{12}$$

where $\kappa > 0$ is the mean-reversion rate reflecting inter-bank lending, $\sigma > 0$ is the volatility, and α_t is the rate of borrowing/lending to a central bank (the control).

The parameter κ governs the strength of interaction: each bank's log-reserve is pulled toward the population mean $\mathbb{E}[X_t]$. In the N-bank finite system, this corresponds to a fully connected (complete graph) interaction where each bank i is influenced by $\bar{X}_t^N = \frac{1}{N}\sum_{j=1}^{N} X_t^{j,N}$.

C.2 Cost Functional

The central bank (social planner) minimizes:

$$J(\alpha) = \mathbb{E}\left[\int_0^T \tilde{f}(X_t, \mathbb{E}[X_t], \alpha_t)\,\mathrm{d}t + \tilde{g}(X_T, \mathbb{E}[X_T])\right] \to v(\mu_0) = \inf_{\alpha} J(\alpha), \tag{13}$$

with running and terminal costs:

$$\tilde{f}(x, \bar{x}, a) = \frac{1}{2}a^2 - qa(\bar{x} - x) + \frac{\eta}{2}(\bar{x} - x)^2, \qquad \tilde{g}(x, \bar{x}) = \frac{c}{2}(x - \bar{x})^2, \tag{14}$$

where $q, \eta, c > 0$ with $q^2 \leq \eta$. The term $\frac{1}{2}a^2$ penalizes the control effort, the term $-qa(\bar{x} - x)$ incentivizes banks far from the mean to borrow/lend more, and the terminal cost penalizes dispersion around the mean at maturity. The convexity of the objective function with respect to the control process ensures the convergence of the global algorithm in the linear-quadratic example.

C.3 Analytical Solution

This linear-quadratic (LQ) problem admits an analytical solution via a Riccati equation [1]:

$$v(t, \mu) = \int_{\mathbb{R}} V(t, x, \mu)\,\mu(\mathrm{d}x) = Q_t \int_{\mathbb{R}} (x - \bar{\mu})^2\,\mu(\mathrm{d}x) + \sigma^2 \int_t^T Q_s\,\mathrm{d}s, \tag{15}$$

where $\bar{\mu} = \int x\,\mu(\mathrm{d}x)$ and Q_t solves a Riccati ODE involving κ, q, η, c. The analytical value serves as a ground-truth benchmark for validating the neural network algorithms.

C.4 Benchmark Parameters

Following Pham and Warin [6], the standard test parameters are $\sigma = 1$, $\kappa = 0.6$, $q = 0.8$, $T = 0.2$, $c = 2$, $\eta = 2$. In the current implementation, the six benchmark initial laws are matched exactly as follows, with $Y, \bar{Y} \sim \mathcal{N}(0, 1)$ independent, $P \sim \text{Bernoulli}(1/2)$, and $U \sim \text{Unif}(0, 1)$:

$$\begin{aligned}
&\text{Case 1: } X_0 = 0.2Y,\\
&\text{Case 2: } X_0 = 0.3 + 0.05Y,\\
&\text{Case 3: } X_0 = 0.05Y,\\
&\text{Case 4: } X_0 = P(-k + \theta Y) + (1 - P)(k + \theta\bar{Y}), \quad k = \frac{\sqrt{3}}{10},\ \theta = 0.1,\\
&\text{Case 5: } X_0 = P(-k + \theta Y) + (1 - P)(-k + \theta\bar{Y}), \quad k = 0.25,\ \theta = 0.1,\\
&\text{Case 6: } X_0 = (-\mathbf{1}_{\{\lfloor 3U \rfloor = 0\}}k + \mathbf{1}_{\{\lfloor 3U \rfloor = 1\}}k) + \theta Y, \quad k = 0.3,\ \theta = 0.07.
\end{aligned}$$

For these laws, the analytical values computed from the Riccati formula are approximately 0.4849 for Cases 1 and 4, 0.3625 for Cases 2 and 3, 0.3870 for Case 5, and 0.5662 for Case 6. The equalities $v(0, \mu_0^{(1)}) = v(0, \mu_0^{(4)})$ and $v(0, \mu_0^{(2)}) = v(0, \mu_0^{(3)})$ follow from the fact that the LQ value depends only on the initial variance.

Remark 3 (Cascade interpretation)**.** *When the interaction parameter κ is large relative to the volatility, the mean-reverting force creates strong coupling. In the uncontrolled discrete system ($\alpha \equiv 0$), if a subset of banks crosses a default threshold θ (i.e., $X_t^i < \theta$), the resulting drop in $\bar{X}_t^N$ pulls all remaining banks downward, potentially triggering a* cascade *or* avalanche *of defaults. This systemic risk mechanism is what the control aims to mitigate.*

C.5 Exact Implementation Choices and Preliminary Sweep

The current repository now exposes the two Pham–Warin algorithms targeted in this project using the same modeling choices as in the benchmark setup. Algorithm 1 is implemented as a global control-learning method: a time-dependent mean-field neural network $\mathcal{N}_\theta(t,\mu)(x)$ is trained by simulating the Euler scheme for the particle system and minimizing the empirical counterpart of the full objective $J(\alpha)$. Algorithm 6 is implemented as a global MKV BSDE method for the systemic-risk adjoint system, learning an initial adjoint map $\mathcal{U}_\theta(\mu)(x)$ together with a time-dependent process network $\mathcal{Z}_\theta(t,\mu)(x)$, and recovering the induced control through

$$\alpha_t^\star \approx q(\mathbb{E}[X_t] - X_t) - P_t.$$

On the architecture side, the cylindrical encoder uses the empirical average of an inner feature map, while the bin encoder now uses hard histogram counts on a fixed support interval rather than a smoothed Gaussian proxy.

To obtain a first implementation-level comparison, we ran a moderate local sweep on CPU over all six benchmark cases, both encoders, and both algorithms, with $N = 64$ particles, $N_T = 12$ time steps, batch size 8, and 60 optimization iterations per run. This is intentionally smaller than the paper's full training budget, so the numbers below should be read as consistency checks rather than direct reproductions of the published tables. The main qualitative outcome is that Algorithm 1 behaves similarly with the two encoders at this scale, while Algorithm 6 is more stable with the bin encoder, which is consistent with the observation reported by Pham and Warin [6] on difficult one-dimensional benchmarks.

Method and encoder	Average final training loss	Average induced policy cost
Algorithm 1 + bins	0.1622	–
Algorithm 1 + cylindrical	0.1617	–
Algorithm 6 + bins	0.0127	0.1606
Algorithm 6 + cylindrical	0.0276	0.1644

Table 1: Moderate local benchmark sweep for the current implementation across Cases 1-6. The induced policy cost is reported only for Algorithm 6, where the learned adjoint induces the feedback control.

These runs indicate that the repository now matches the paper at the level of benchmark laws, encoder choice, and algorithmic interface, while a higher-budget experiment remains necessary to compare quantitatively against the published Pham–Warin tables.

D Nonlinear Graphon Mean-Field Systems

We summarize the framework of Coppini et al. [3], which extends classical mean-field limits to heterogeneous particle systems on graphs.

D.1 Graphons

A *graphon* is a measurable symmetric function $G : [0,1]^2 \to [0,1]$. It arises as the limit of sequences of dense graphs in the cut-distance topology [5]. Given an N-vertex graph with adjacency matrix

(a_{ij}), the associated step-function graphon is:

$$G_N(u,v) = a_{\lceil Nu \rceil, \lceil Nv \rceil}, \qquad (u,v) \in [0,1]^2. \tag{16}$$

The graphon encodes heterogeneous interaction weights: $G(u,v)$ measures the strength of interaction between agents with labels u and v.

D.2 Nonlinear Graphon Particle System

Consider a system of N interacting particles where particle i has label $u_i = i/N \in [0,1]$. Its state $X^{i,N}$ evolves as:

$$\mathrm{d}X_t^{i,N} = b\Big(X_t^{i,N}, \hat{\mu}_t^{i,N}\Big)\,\mathrm{d}t + \sigma\Big(X_t^{i,N}, \hat{\mu}_t^{i,N}\Big)\,\mathrm{d}W_t^i, \qquad 0 \le t \le T, \qquad i = 1, \dots, N, \tag{17}$$

where $\hat{\mu}_t^{i,N}$ is the *local empirical measure* of particle i:

$$\hat{\mu}_t^{i,N} = \frac{\sum_{j=1}^N G(u_i, u_j)\,\delta_{X_t^{j,N}}}{\sum_{j=1}^N G(u_i, u_j)}. \tag{18}$$

The key feature is that the interaction of particle i with the population is weighted by the graphon G: strongly connected agents (high $G(u_i, u_j)$) contribute more to the local measure than weakly connected ones.

Remark 4. *When $G \equiv 1$, the local empirical measure reduces to the standard empirical measure $\hat{\mu}_t^N = \frac{1}{N}\sum_{j=1}^N \delta_{X_t^{j,N}}$, recovering the classical homogeneous mean-field setting.*

The drift and diffusion coefficients $b, \sigma : \mathbb{R}^d \times \mathcal{P}_2(\mathbb{R}^d) \to \mathbb{R}^d$ (resp. $\mathbb{R}^{d\times d}$) satisfy Lipschitz regularity:

Assumption 1. *There exists $K > 0$ such that $|b(x,\mu) - b(x',\mu')| + |\sigma(x,\mu) - \sigma(x',\mu')| \le K(|x - x'| + \mathcal{W}_2(\mu,\mu'))$ for all $x, x' \in \mathbb{R}^d$ and $\mu, \mu' \in \mathcal{P}_2(\mathbb{R}^d)$.*

D.3 Fubini Extension and Limit System

When $N \to \infty$, the limit system consists of an *uncountable* family of processes $(X_t^u)_{u\in[0,1]}$ indexed by the label u. To rigorously define this infinite collection, Coppini et al. [3] use a *Fubini extension* of the standard probability space.

Definition 1 (Fubini extension, Coppini et al. [3, Definition 3.1])**.** *An extension $([0,1] \times \Omega, \mathcal{I} \otimes \mathcal{F}, \lambda \otimes \mathbb{P})$ of the product space is a* Fubini extension *if for every $\mathcal{I} \otimes \mathcal{F}$-measurable process $f : [0,1] \times \Omega \to \mathbb{R}$ that is integrable:*

1. *$u \mapsto f(u,\omega)$ is $\mathcal{I}$-measurable for $\mathbb{P}$-a.e. ω,*
2. *$\omega \mapsto f(u,\omega)$ is $\mathcal{F}$-measurable for λ-a.e. u,*
3. *The Fubini theorem holds: $\int_{[0,1]\times\Omega} f\,\mathrm{d}(\lambda \otimes \mathbb{P}) = \int_{[0,1]} \left(\int_\Omega f(u,\omega)\,\mathrm{d}\mathbb{P}(\omega)\right)\mathrm{d}\lambda(u)$.*

The limit system on this extended space reads: for λ-a.e. $u \in [0,1]$,

$$\mathrm{d}X_t^u = b(X_t^u, \mu_t^u)\,\mathrm{d}t + \sigma(X_t^u, \mu_t^u)\,\mathrm{d}W_t^u, \qquad X_0^u \sim \mu_0^u, \tag{19}$$

where $\mu_t^u \in \mathcal{P}_2(\mathbb{R}^d)$ is the *graphon-weighted law*:

$$\mu_t^u = \frac{\int_0^1 G(u,v)\, \mathbb{P}_{X_t^v}\, \mathrm{d}v}{\int_0^1 G(u,v)\, \mathrm{d}v}, \tag{20}$$

and $(W^u)_{u\in[0,1]}$ is a family of independent Brownian motions on the Fubini extension.

D.4 Main Convergence Results

Theorem 1 (Law of Large Numbers, Coppini et al. [3, Theorem 4.1])**.** *Under Assumption 1 and standard regularity on G and the initial conditions, the local empirical measures converge:*

$$\lim_{N\to\infty} \frac{1}{N} \sum_{i=1}^{N} \mathbb{E}\left[\sup_{0\le t\le T} \left| X_t^{i,N} - X_t^{u_i} \right| \right] = \lim_{N\to\infty} \frac{1}{N} \sum_{i=1}^{N} \mathbb{E}\left[\int_0^t \mathcal{W}_2^2([G_N \delta_s^N]^{u_i}, [G\mu_s]^{u_i}) ds \right] = 0, \tag{21}$$

where μ_t^u is the graphon-weighted law from the limit system (19).

Theorem 2 (Propagation of Chaos, Coppini et al. [3, Theorem 4.2])**.** *Under the same assumptions, for any finite collection of labels $u_1, \dots, u_k \in [0,1]$, the joint law of $(X^{u_1,N}, \dots, X^{u_k,N})$ converges to the product law $\mathbb{P}_{X^{u_1}} \otimes \cdots \otimes \mathbb{P}_{X^{u_k}}$ as $N \to \infty$. In other words, particles with distinct labels become asymptotically independent, each governed by the nonlinear process (19).*

The convergence rate depends on the dimension d and matches the Fournier–Guillin rate [4] for the convergence of empirical measures in Wasserstein distance.

E Mean-Field Control of Non-Exchangeable Systems

We summarize the theoretical contribution of **?**], which establishes the dynamic programming principle for MFC problems with graphon-structured heterogeneous interactions.

E.1 Controlled Graphon Particle System

The controlled dynamics of particle $i \in \{1, \dots, N\}$ in the graphon system with heterogeneous coefficients is:

$$\mathrm{d}X_t^{i,N} = b\left(u_i, X_t^{i,N}, \alpha_t^{i,N}, \frac{1}{N_i} \sum_{j=1}^{N} G(u_i,u_j)\, \delta_{X_t^{j,N}} \right) \mathrm{d}t + \sigma\left(u_i, X_t^{i,N}, \alpha_t^{i,N}, \frac{1}{N_i} \sum_{j=1}^{N} G(u_i,u_j)\, \delta_{X_t^{j,N}} \right) \mathrm{d}W_t^{u_i}, \tag{22}$$

where $u_i = i/N$ is the label, $N_i = \sum_{j=1}^{N} G(u_i,u_j)$ is the degree, and $\alpha^{i,N}$ is the control for agent i. Note that the coefficients b and σ now explicitly depend on the label u_i, allowing for agent heterogeneity beyond the graphon interaction structure.

E.2 Mean-Field Limit and Cost Functional

In the $N \to \infty$ limit, the social planner minimizes the cost functional over the continuum of agents:

$$J(\boldsymbol{\alpha}) = \int_0^1 r(u)\, \mathbb{E}\left[\int_0^T f(u, X_t^u, \alpha_t^u, \mu_t^u)\, \mathrm{d}t + g(u, X_T^u, \mu_T^u) \right] \mathrm{d}u, \tag{23}$$

where $r : [0,1] \to \mathbb{R}_+$ is a label-weighting function, and the state and graphon-weighted law $(\mu_t^u)_{u,t}$ are defined as in (19)–(20). The collection of marginal laws $\boldsymbol{\mu}_t = (\mu_t^u)_{u\in[0,1]}$ lives in the space $L^2_\lambda(\mathcal{P}_2(\mathbb{R}^d))$, the set of L^2-functions from $[0,1]$ into the Wasserstein space.

E.3 Law Invariance and Value Function

A key result of **?**] is the *law invariance property*: the value function depends on the state of the system only through the collection of marginal laws $\boldsymbol{\mu} = (\mathbb{P}_{X^u})_{u\in[0,1]}$. This allows defining:

$$v(t, \boldsymbol{\mu}) = \inf_{\boldsymbol{\alpha}} J_{t,\boldsymbol{\mu}}(\boldsymbol{\alpha}), \tag{24}$$

where $\boldsymbol{\mu} \in L^2_\lambda(\mathcal{P}_2(\mathbb{R}^d))$ is the initial collection of laws at time t.

E.4 Dynamic Programming Principle

Theorem 3 (DPP, **?** , Theorem 4.1]). *Under standard regularity assumptions, the value function v satisfies the dynamic programming principle: for all $0 \le t \le s \le T$ and $\boldsymbol{\mu} \in L^2_\lambda(\mathcal{P}_2(\mathbb{R}^d))$,*

$$v(t, \boldsymbol{\mu}) = \inf_{\boldsymbol{\alpha}} \left\{ \int_0^1 r(u)\, \mathbb{E}\left[\int_t^s f(u, X^u_r, \alpha^u_r, \mu^u_r)\, \mathrm{d}r \right] \mathrm{d}u + v(s, \boldsymbol{\mu}_s) \right\}. \tag{25}$$

Moreover, **?**] derive a chain rule for smooth functions along flows of marginal laws, and prove that v is a viscosity solution to a Bellman equation on $L^2_\lambda(\mathcal{P}_2(\mathbb{R}^d))$.

Remark 5 (Open problem). *While* **?** *] establish the theoretical DPP and Bellman equation for graphon MFC,* no numerical algorithm *has been proposed to solve these problems computationally. This project aims to bridge this gap by extending the mean-field neural network algorithms of Pham and Warin [6] to the graphon-heterogeneous setting.*

F Project Formulation: Heterogeneous Systemic Risk

We now combine the elements from the preceding sections to formulate the specific model studied in this project.

F.1 Heterogeneous Systemic Risk SDE

We extend the systemic risk model of Section C by introducing agent labels $u \in [0,1]$ and a graphon interaction structure. The log-monetary reserve of agent u evolves as:

$$\mathrm{d}X^u_t = (\kappa(u)\,(\langle \mu^u_t, \mathrm{id}\rangle - X^u_t) + \alpha^u_t)\,\mathrm{d}t + \sigma(u)\,\mathrm{d}W^u_t, \qquad X^u_0 \sim \mu^u_0, \tag{26}$$

where $\kappa(u)$ and $\sigma(u)$ are label-dependent parameters, μ^u_t is the graphon-weighted local measure (20), and $\langle \mu^u_t, \mathrm{id}\rangle = \int x\, \mu^u_t(\mathrm{d}x)$ is the local weighted mean perceived by agent u.

F.2 Core-Periphery Graphon

We choose a *core-periphery* block graphon as the interaction structure:

$$G(u,v) = \begin{cases} q_{cc} & \text{if } u, v \in [0,p], \\ q_{cp} & \text{if } u \in [0,p], v \in (p,1] \text{ or vice versa}, \\ q_{pp} & \text{if } u, v \in (p,1], \end{cases} \tag{27}$$

where $p \in (0,1)$ is the fraction of core (hub) agents, and $q_{cc} > q_{cp} > q_{pp}$ reflects the stylized fact that core banks are strongly interconnected, have moderate connections to peripheral banks, and peripheral banks interact weakly with each other.

Remark 6. *This graphon is a step-function with three blocks. It captures the key heterogeneity of financial networks (a dense core of systemically important institutions surrounded by a sparser periphery) while remaining simple enough for systematic analysis. Hub agents ($u \in [0, p]$) have higher effective degree and therefore perceive a denser local empirical measure.*

F.3 Modified Cost Functional

The social planner minimizes:

$$J(\boldsymbol{\alpha}) = \int_0^1 r(u)\, \mathbb{E}\left[\int_0^T \left(\frac{1}{2}(\alpha_t^u)^2 - q\,\alpha_t^u\big(\langle \mu_t^u, \mathrm{id}\rangle - X_t^u\big) + \frac{\eta}{2}\big(\langle \mu_t^u, \mathrm{id}\rangle - X_t^u\big)^2\right) \mathrm{d}t + \frac{c}{2}\big(X_T^u - \langle \mu_T^u, \mathrm{id}\rangle\big)^2\right] \mathrm{d}u, \tag{28}$$

with $r(u)$ a label-weighting function (e.g. $r \equiv 1$ for uniform weighting, or $r(u)$ proportional to the degree for degree-weighted social welfare).

F.4 Modified Neural Network Input

To learn the label-dependent optimal control $\alpha^\star(t, x, u, \mu^u)$, we modify the mean-field neural network architectures of Section B by concatenating the label u to the input:

- **Bin density**: $\mathcal{N}(\mu^u)(t, x, u) = \Phi(t, x, u, p^{\mu^u})$ where p^{μ^u} is the bin weight of the *local* empirical measure,
- **Cylindrical**: $\mathcal{N}(\mu^u)(t, x, u) = \Psi\Big(t, x, u, \frac{1}{N_i}\sum_{j=1}^N G(u, u_j)\,\varphi(X^j)\Big)$.

The key insight is that the network must learn a *family* of control policies indexed by the label u, rather than a single policy. This is computationally feasible because the label space $[0, 1]$ is one-dimensional, and the network can smoothly interpolate across labels.

F.5 Connection to Course Concepts

This formulation connects to the core themes of the Interactions course:

- **Agent-Based Models**: the discrete N-bank system (22) is an ABM with heterogeneous interactions on a network.
- **Emergence**: cascading defaults arise as emergent phenomena from local interactions when the control is insufficient or mis-specified.
- **Interacting Particle Systems**: the graphon particle system (17) is an IPS whose macroscopic behavior is described by the graphon mean-field limit.
- **Mean-field approximation**: the gap between the finite-N ABM and the infinite-population limit quantifies when the mean-field approximation breaks down, particularly under heterogeneity.