




Legend

-  Work Area
-  Safety Buffer
-  Cone

Road Authority shall approve usage of this TGS.

VMS MESSAGES

**BURNING
OFF
AHEAD**

**DRIVE
CAREFULLY**

**VMS are optional and messages may change to suit works.
To be installed minimum 2D from first temporary work signage**



REPEATER SIGNAGE TO BE PLACED EVERY 500m, AT INTERSECTIONS, CURVES AND CRESTS.

GENERAL NOTES:

- This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
- All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
- The positioning of signs, lengths of tapers or markings shall be:
 - Minimum 10% less than the distances or lengths given.
 - Maximum 25% more than the distances or lengths given.
- Supervisor shall undertake risk assessment to determine appropriate temporary speed restriction.
- When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.
- Drive slowly can be swapped with Smoke Hazard, or Burning Off.
- Use of Fold up signs and Swing signs acceptable in narrow, very low volume tracks <50 VPD

DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGGTM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson

AWTM Cert. No: KTS-AWTM-19-47786-01

Signed: *Cheryl Johnson*

Reviewed by: Brad Brooksby


AWTM Cert. No: AUS-AWTM-19-1183-06

Signed: *Brad Brooksby*

Reset Speed to original Speed Zone



20m SAFETY BUFFER



WORK AREA

20m SAFETY BUFFER



OR



2D

2D



VALUE OF DIMENSION 'D'

Speed of Traffic km/h	Dimension 'D' m
55 or less	15
56 to 65	45
70	140
80	160
90	180
100	200
110	220



2D

2D



OR



Side roads may be sealed or unsealed and may be posted or derestricted.

Reset Speed to original Speed Zone

3.0m - 6.0m



2D



OR



Reset Speed to original Speed Zone

BURNING OFF

**90km/h-110km/h POSTED SPEED
WORKING 3m-6m from TRAFFIC.**

DATE: 24/03/2021

REV No: 13

DBCA - 21 - 02