


## Legend



Road Authority shall approve usage of this TGS.

## VMS MESSAGES

**BURNING  
OFF  
AHEAD**

**MOBILE  
PLANT  
AHEAD**

**VMS are optional and messages may change to suit works.**

## GENERAL NOTES:

1. This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
2. All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
3. All existing speed zone signage within the temporary speed zone shall be covered with suitable opaque material for the duration of the stage and covers to be removed on completion of works each day. Unless otherwise noted.
4. Minimum traffic lane width of 3.2m is to be maintained past the worksite at all times.
5. The positioning of signs, lengths of tapers or markings shall be:
  - a) Minimum 10% less than the distances or lengths given.
  - b) Maximum 25% more than the distances or lengths given.
6. Supervisor shall undertake risk assessment to determine appropriate temporary speed restriction.
7. The symbolic worker signs shall be installed only when on-foot personnel will be visible to passing traffic.
8. When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.

## DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGGTM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson

AWTM Cert. No: KTS-AWTM-19-47786-01


Signed: *Cheryl Johnson*

Reviewed by: Brad Brooksby

AWTM Cert. No: AUS-AWTM-16-1183-05

Signed: *Brad Brooksby*

Reset Speed to original Speed Zone



**DETOUR**

## GENERAL NOTES:

1. This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
2. All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
3. All existing speed zone signage within the temporary speed zone shall be covered with suitable opaque material for the duration of the stage and covers to be removed on completion of works each day. Unless otherwise noted.
4. Minimum traffic lane width of 3.2m is to be maintained past the worksite at all times.
5. The positioning of signs, lengths of tapers or markings shall be:
  - a) Minimum 10% less than the distances or lengths given.
  - b) Maximum 25% more than the distances or lengths given.
6. Supervisor shall undertake risk assessment to determine appropriate temporary speed restriction.
7. The symbolic worker signs shall be installed only when on-foot personnel will be visible to passing traffic.
8. When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.

## DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGGTM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson

AWTM Cert. No: KTS-AWTM-19-47786-01

Signed: *Cheryl Johnson*


Reviewed by: Brad Brooksby

AWTM Cert. No: AUS-AWTM-16-1183-05

Signed: *Brad Brooksby*



VALUE OF DIMENSION 'D'

Speed of Traffic km/h	Dimension 'D' m
55 or less	15
56 to 65	45
70	140
80	160
90	180
100	200
110	220



Side roads may be sealed or unsealed and may be posted or derestricted

Reset Speed to original Speed Zone



Reset Speed to original Speed Zone

**LOCAL GOVERNMENT ROADS <500 VPD  
BURNING OFF 90km/h - 110km/h POSTED SPEED  
FULL ROAD CLOSURE**

DATE: 24/03/2021

REV No: 13

DBCA - 21 - 18