

LEGEND

- WORK AREA
- SAFETY BUFFER
- CONES

STOP HERE ON RED SIGNAL
BURNING OFF

CONES MAY BE PLACED ALONG EDGE TO REDUCE LANE WIDTH TO MAX 3.5m

THRESHOLD

BURNING OFF 40

SMOKE HAZARD

REPEATER SIGNAGE TO BE PLACED EVERY 500m, AT INTERSECTIONS, CURVS AND CRESTS

OR

40

REPEATER SIGNAGE MAY BE A STAND ALONE 600x600

GENERAL NOTES:

- THIS TGS IS ONLY TO BE USED AS PART OF THIS GENERIC TRAFFIC MANAGEMENT PLAN
- ALL SIGN LOCATIONS ARE TO BE CHECKED PRIOR TO SETOUT AND POSITIONS ADJUSTED TO ALLOW FOR SPECIFIC SITE CONSTRAINTS SUCH AS VEGETATION, OTHER SIGNS, ROADSIDE FURNITURE AND SUFFICIENT SPACE ON SHOULDERS/EMERGENCY LANES.
- THE POSITIONS OF SIGNS, LENGTH OF TAPERS OR MARKING SHALL BE:
 - MINIMUM 10% LESS THAN THE DISTANCES OR LENGTHS GIVEN,
 - MAXIMUM 25% MORE THAN THE DISTANCES OR LENGTHS GIVEN.
- WHEN USING MMS ENSURE TWO 5mm THICK CORE FLUTE SIGNS ARE USED BACK TO BACK IN THE FRAME TO HELP PREVENT THE SIGN FROM BLOWING OUT
- DRIVE SLOWLY CAN BE SWAPPED WITH SMOKE HAZARD, OR BURNING OFF.
- USE OF FOLD UP SIGNS AND SWING SIGNS AND SIGNS ON ONE SIDE OF THE ROAD MAY BE ACCEPTABLE IN NARROW, VERY LOW VOLUME TRACKS <50 VPD
- SUPERVISOR SHALL UNDERTAKE RISK ASSESSMENT TO DETERMINE APPROPRIATE TEMPORARY SPEED RESTRICTION
- THE WORKER SYMBOLIC SIGNS SHALL BE INSTALLED ONLY WHEN ON-FOOT PERSONNEL WILL BE VISIBLE TO PASSING TRAFFIC, OTHERWISE REPLACE WITH BURNING OFF OR SMOKE HAZARD SIGN
- ALL EXISTING SPEED ZONE SIGNAGE WITHIN THE TEMPORARY SPEED ZONE SHALL BE COVERED WITH SUITABLE OPAQUE MATERIAL FOR THE DURATION OF THE WORKS AND COVERS TO BE REMOVED ON COMPLETION OF WORKS EACH DAY UNLESS OTHERWISE NOTED.
- MINIMUM TRAFFIC LANE WIDTH OF 3.5m IS TO BE MAINTAINED PAST THE WORKSITE AT ALL TIMES

DISCLAIMER:

IT IS THE RESPONSIBILITY OF THE USER OF THIS TRAFFIC GUIDANCE SCHEME TO CONFIRM THE APPROPRIATENESS OR OTHERWISE FOR THE INTENDED WORK SITE BASED ON RIGOROUS RISK ASSESSMENT AND REVIEW OF THE REQUIREMENTS OF THE AS1742.3 AND MAIN ROADS WA TRAFFIC MANAGEMENT FOR WORKS ON ROADS CoP AND THE AGTMM. ALL RESPONSIBILITY WILL REMAIN WITH THE USER TO ENSURE COMPLIANCE WITH RELEVANT STANDARDS AND THE PROVISION OF THE NECESSARY LEVEL OF PROTECTION FOR WORK PERSONNEL AND WORK SITE.

DRAWN: CAMERON OLSON
AWTM CERT. No: KTS-AWTM-21-49061-02
SIGNED:

DRAWN: MATTHEW BYRNE
AWTM CERT. No: AUS-AWTM-21-01367-04
SIGNED:

ROAD AUTHORITY SHALL APPROVE USAGE OF THIS TGS

REINSTATE POSTED SPEED

END OF BURN ?
DRIVE SAFELY

30m
20m
5km MAX WORK AREA
20m
30m
TAPER

80m
80m
160m
45m
45m
6m

DRIVE SLOWLY
BURNING OFF
40
DO NOT OVERTAKE
PREPARE TO STOP
DO NOT OVERTAKE
PREPARE TO STOP
REDUCE SPEED
BURNING OFF
STOP HERE ON RED SIGNAL

SECONDARY PREPARE TO STOP SPACING BASED ON ANTICIPATED END OF QUEUE PLUS 2x OF TABLE A SPACING, TRAFFIC CONTROLLERS SHALL MONITOR END OF QUEUE

SIDE ROADS MAY BE SEALED OR UNSEALED AND MAY BE POSTED OR DERESTRICTED

REINSTATE POSTED SPEED OR USE END 40 IF DERESTRICTED

END OF BURN ?
DRIVE SAFELY

6m
45m
45m
160m
80m
80m

STOP HERE ON RED SIGNAL
BURNING OFF
SMOKE HAZARD
40
BURNING OFF
REDUCE SPEED
PREPARE TO STOP
DO NOT OVERTAKE
60
DRIVE SLOWLY
BURNING OFF
DRIVE SLOWLY

CONE SPACING SHALL BE 4m

SECONDARY PREPARE TO STOP SPACING BASED ON ANTICIPATED END OF QUEUE PLUS 2x OF TABLE A SPACING, TRAFFIC CONTROLLERS SHALL MONITOR END OF QUEUE

REINSTATE POSTED SPEED

END OF BURN ?
DRIVE SAFELY

GOVERNMENT OF WESTERN AUSTRALIA

TABLE A

POSTED SPEED km/h	SIGN SPACING m
70	70
80	80

BURNING OFF WITH TRAFFIC CONTROL
70km/h - 80km/h POSTED SPEED
WORKING WITHIN 1.2m FROM TRAFFIC

DATE: 26/05/2023

REV No: 0

BURN-23-14