

Legend


Road Authority shall approve usage of this TGS.



REPEATER SIGNAGE TO BE PLACED EVERY 500m, AT INTERSECTIONS, CURVES AND CRESTS.



REPEATER SIGNAGE MAY BE A STAND ALONE 600x600



Reset Speed to original Speed Zone



PTS may be removed when low traffic volume and/or low speed

Prepare to Stop spacing based on anticipated end of queue plus 2 x Sign Spacing. Traffic Controllers shall monitor end of queue.

GENERAL NOTES:

1. This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
2. All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
3. All existing speed zone signage within the temporary speed zone shall be covered with suitable opaque material for the duration of the stage and covers to be removed on completion of works each day. Unless otherwise noted.
4. Minimum traffic lane width of 3.2m is to be maintained past the worksite at all times.
5. The positioning of signs, lengths of tapers or markings shall be:
 - a) Minimum 10% less than the distances or lengths given.
 - b) Maximum 25% more than the distances or lengths given.
6. Supervisor shall undertake risk assessment to determine appropriate temporary speed restriction.
7. The symbolic worker signs shall be installed only when on-foot personnel will be visible to passing traffic.
8. When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.
9. Drive slowly can be swapped with Smoke Hazard, or Burning Off.
10. Use of Fold up signs and Swing signs acceptable in narrow, very low volume tracks <50 VPD.
11. 20KM MAX WORK AREA.

DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGTGM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson
AWTM Cert. No: KTS-AWTM-19-47786-01
Signed: *cherylann*

Reviewed by: Brad Brooksby
AWTM Cert. No: AUS-AWTM-16-1183-07
Signed: *Brad Brooksby*



Escort Vehicle



To be displayed on the back of the rear of the Escort Vehicle.


Optional Tail Vehicle

Escort and Tail vehicle to be driven by Department personnel with radio communication.




SIGN SPACING

Speed of Traffic km/h	Distance (m)
55 or less	15m
56 to 65	45m
Greater than 65	Speed of traffic in km/h



Side roads may be sealed or unsealed and may be posted or derestricted.

Reset Speed to original Speed Zone



PTS may be removed when low traffic volume and/or low speed



Reset Speed to original Speed Zone

**BURNING OFF
70km/h-80km/h POSTED SPEED
WITH TC AND ESCORT VEHICLE**

DATE: 24/02/2022

REV No: 14

DBCA - 22 - 15