

Legend

- Work Area
- Safety Buffer
- Cone

Road Authority shall approve usage of this TGS.

VMS MESSAGES

**BURNING
OFF
AHEAD**

**MOBILE
PLANT
AHEAD**

VMS are optional and messages may change to suit works.
To be installed minimum 2 x sign spacing from first temporary work signage

60 km/h temporary speed restriction shall be used when worker working between 1.2 – 3.0 m from traffic lane.



REPEATER SIGNAGE TO BE PLACED AT INTERSECTIONS.

GENERAL NOTES:

1. This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
2. All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
3. All existing speed zone signage within the temporary speed zone shall be covered with suitable opaque material for the duration of the stage and covers to be removed on completion of works each day. Unless otherwise noted.
4. Minimum traffic lane width of 3.2m is to be maintained past the worksite at all times.
5. The positioning of signs, lengths of tapers or markings shall be:
 - a) Minimum 10% less than the distances or lengths given.
 - b) Maximum 25% more than the distances or lengths given.
6. Supervisor shall undertake risk assessment to determine appropriate temporary speed restriction.
7. The symbolic worker signs shall be installed only when on-foot personnel will be visible to passing traffic.
8. When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.

DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGTGM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson

AWTM Cert. No: KTS-AWTM-19-47786-01


Signed: *cherylann*

Reviewed by: Brad Brooksby

AWTM Cert. No: AUS-AWTM-16-1183-07

Signed: *Brad Brooksby*

Reset Speed to original Speed Zone



MIN 2 x Sign Spacing

Lead Vehicle



Work Vehicle




Shadow Vehicle



Tail Vehicle

MIN 2 x Sign Spacing



Reset Speed to original Speed Zone

180m - 220m
Open Road Area

40m

180m - 220m
Open Road Area

SIGN SPACING

Speed of Traffic km/h	Distance (m)
55 or less	15m
56 to 65	45m
Greater than 65	Speed of traffic in km/h

**BURNING OFF
70km/h-80km/h POSTED SPEED
MOBILE WORKS OPERATIONS**

DATE: 24/02/2022

REV No: 14

DBCA - 22 - 17