

Road Authority shall approve usage of this TGS.



Signage can be multi changeable

ОВ

08

300m

• •

160m

NEKGE

NOKKS

NEKGE

Reset Speed to original Speed Zone

SEDUCE SPEED


DAHEAD

(09

Side roads may be sealed or unsealed and may be posted or derestricted.

MOKKS

NERGE



Reset Speed to original Speed Zone

END ?
BURN ?

DRIVE SAFELY

20m SAFETY BUFFER

DRIVE SLOWLY

WORK AREA

20m

SAFETY BUFFER

VFRGE

VERGE

OR

Signage can be multi changeable

60

80

160m

300m

E SAFELY (2)

NERGE WORKS 60

VERGE WORKS 60

VERGE 80

VERGE 80

VERGE 80

VERGE 80

DRIVE SLOWILY

-300m-

Signage can be multi changeable

NEXT



Reset Speed to original Speed Zone

• •

VERGE WORKS 60

DRIVE SLOWLY

REPEATER SIGNAGE TO BE PLACED EVERY 500m AND AT INTERSECTIONS.

GENERAL NOTES:

This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
 All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.

- 3. The positioning of signs, lengths of tapers or markings shall be:
- a) Minimum 10% less than the distances or lengths given.
- b) Maximum 25% more than the distances or lengths given.
- When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.
- 5. Use of Fold up signs and Swing signs acceptable in narrow, very low volume tracks <50 VPD.

DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGGTM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson

AWTM Cert. No: KTS-AWTM-19-47786-01

Signed: cherylann

Reviewed by: Brad Brooksby AWTM Cert. No: AUS-AWTM-16-1183-05

Signed: El brodyle

VALUE OF DIMENSION 'D'

Speed of Traffic km/h m

55 or less 15

66 to 65 45

70 140

80 160

90 180

100 200

110 220

VERGE

(60)

FUEL MODIFICATION
ALL POSTED SPEED ROADS
1.2 TO 3M FROM TRAFFIC

DATE: 24/03/2021 REV No: 13

DBCA - 21 - 23