


Legend

Road Authority shall approve usage of this TGS.



SPEED RESTRICTION



To be used when pit is used frequently used.



GENERAL NOTES:

1. This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
2. All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
3. All existing speed zone signage within the temporary speed zone shall be covered with suitable opaque material for the duration of the stage and covers to be removed on completion of works each day. Unless otherwise noted.
4. All plant used on site must be fitted with an audible reverse and flashing beacons.
5. When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.
- 6.. Use of Fold up signs and Swing signs acceptable in narrow, very low volume tracks <50 VPD.

DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGGTM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson

AWTM Cert. No: KTS-AWTM-19-47786-01

Signed: *Cheryl Johnson*

Reviewed by: Brad Brooksby

AWTM Cert. No: AUS-AWTM-16-1183-05

Signed: *Brad Brooksby*

VALUE OF DIMENSION 'D'

Speed of Traffic km/h	Dimension 'D' m
55 or less	15
56 to 65	45
70	140
80	160
90	180
100	200
110	220

TRUCK MOVEMENTS

DATE: 24/03/2021

REV No: 13

DBCA - 21 - 20