

LEGEND


- WORK AREA
- SAFETY BUFFER
- CONES

VMS MESSAGES

**BURNING
OFF
AHEAD**


**DRIVE
CAREFULLY**

VMS ARE OPTIONAL AND MESSAGES MAY CHANGE TO SUIT WORKS. REFER TO TABLE A FOR MINIMUM DISTANCE TO BE INSTALLED FROM FIRST TEMPORARY WORK SIGN



REPEATER SIGNAGE TO BE PLACED EVERY 500m, AT INTERSECTIONS, CURVS AND CRESTS

OR




REPEATER SIGNAGE MAY BE A STAND ALONE 600x600


GENERAL NOTES:

- THIS TGS IS ONLY TO BE USED AS PART OF THIS GENERIC TRAFFIC MANAGEMENT PLAN
- ALL SIGN LOCATIONS ARE TO BE CHECKED PRIOR TO SETOUT AND POSITIONS ADJUSTED TO ALLOW FOR SPECIFIC SITE CONSTRAINTS SUCH AS VEGETATION, OTHER SIGNS, ROADSIDE FURNITURE AND SUFFICIENT SPACE ON SHOULDERS/EMERGENCY LANES.
- THE POSITIONS OF SIGNS, LENGTH OF TAPERS OR MARKING SHALL BE:
 - MINIMUM 10% LESS THAN THE DISTANCES OR LENGTHS GIVEN,
 - MAXIMUM 25% MORE THAN THE DISTANCES OR LENGTHS GIVEN.
- WHEN USING MMS ENSURE TWO 5mm THICK CORE FLUTE SIGNS ARE USED BACK TO BACK IN THE FRAME TO HELP PREVENT THE SIGN FROM BLOWING OUT
- DRIVE SLOWLY CAN BE SWAPPED WITH SMOKE HAZARD, OR BURNING OFF.
- USE OF FOLD UP SIGNS AND SWING SIGNS AND SIGNS ON ONE SIDE OF THE ROAD MAY BE ACCEPTABLE IN NARROW, VERY LOW VOLUME TRACKS <50 VPD
- SUPERVISOR SHALL UNDERTAKE RISK ASSESSMENT TO DETERMINE APPROPRIATE TEMPORARY SPEED RESTRICTION
- THE WORKER SYMBOLIC SIGNS SHALL BE INSTALLED ONLY WHEN ON-FOOT PERSONNEL WILL BE VISIBLE TO PASSING TRAFFIC, OTHERWISE REPLACE WITH BURNING OFF OR SMOKE HAZARD SIGN
- ALL EXISTING SPEED ZONE SIGNAGE WITHIN THE TEMPORARY SPEED ZONE SHALL BE COVERED WITH SUITABLE OPAQUE MATERIAL FOR THE DURATION OF THE WORKS AND COVERS TO BE REMOVED ON COMPLETION OF WORKS EACH DAY UNLESS OTHERWISE NOTED.


DISCLAIMER:

IT IS THE RESPONSIBILITY OF THE USER OF THIS TRAFFIC GUIDANCE SCHEME TO CONFIRM THE APPROPRIATENESS OR OTHERWISE FOR THE INTENDED WORK SITE BASED ON RIGOROUS RISK ASSESSMENT AND REVIEW OF THE REQUIREMENTS OF THE AS1742.3 AND MAIN ROADS WA TRAFFIC MANAGEMENT FOR WORKS ON ROADS CoP AND THE AGTTM. ALL RESPONSIBILITY WILL REMAIN WITH THE USER TO ENSURE COMPLIANCE WITH RELEVANT STANDARDS AND THE PROVISION OF THE NECESSARY LEVEL OF PROTECTION FOR WORK PERSONNEL AND WORK SITE.


DRAWN: CAMERON OLSON
AWTM CERT. No: KTS-AWTM-21-49061-02
SIGNED: 

DRAWN: MATTHEW BYRNE
AWTM CERT. No: AUS-AWTM-21-01367-04
SIGNED: 


ROAD AUTHORITY SHALL APPROVE
USAGE OF THIS TGS



REINSTATE POSTED SPEED OR USE END 80 IF DERESTRICTED




20m BUFFER



WORK AREA

20m BUFFER



160m

300m


REFER TABLE A

VMS

300m

160m

REFER TABLE A




SMOKE HAZARD BURNING OFF AHEAD 60 OR SMOKE HAZARD BURNING OFF 80

REDUCE SPEED 09

1.2m - 3.0m

SIDE ROADS MAY BE SEALED OR UNSEALED AND MAY BE POSTED OR DERESTRICTED

REINSTATE POSTED SPEED OR USE END 80 IF DERESTRICTED



160m

300m

DRIVE SLOWLY 60

REDUCE SPEED 60

60 AHEAD

BURNING OFF SMOKE HAZARD

OR

BURNING OFF 80 SMOKE HAZARD

DRIVE SAFELY

END OF BURN ?

REINSTATE POSTED SPEED OR USE END 80 IF DERESTRICTED

TABLE A

POSTED SPEED km/h	SIGN SPACING m
90	180
100	200
110	220

BURNING OFF
90km/h - 110km/h POSTED SPEED
WORKING 1.2m - 3m FROM TRAFFIC

DATE: 26/05/2023

REV No: 0

BURN-23-03