




Legend	
	Work Area
	Safety Buffer
	Cone

Road Authority shall approve usage of this TGS.



VMS MESSAGES	
<b>BURNING OFF AHEAD</b>	<b>DRIVE CAREFULLY</b>

VMS are optional and messages may change to suit works.  
To be installed minimum 2 x sign spacing from first temporary work signage

REPEATER SIGNAGE TO BE PLACED EVERY 500m, AT INTERSECTIONS, CURVES AND CRESTS.

REPEATER SIGNAGE MAY BE A STAND ALONE 600x600

#### GENERAL NOTES:

1. This TGS is only to be used as part of the DBCA Generic Traffic Management Plan.
2. All sign locations are to be checked prior to setout and positions adjusted to allow for specific site constraints such as vegetation, other signs, roadside furniture and sufficient space on shoulders/emergency lanes.
3. All existing speed zone signage within the temporary speed zone shall be covered with suitable opaque material for the duration of the stage and covers to be removed on completion of works each day. Unless otherwise noted.
4. Minimum traffic lane width of 3.2m is to be maintained past the worksite at all times.
5. The positioning of signs, lengths of tapers or markings shall be:
  - a) Minimum 10% less than the distances or lengths given.
  - b) Maximum 25% more than the distances or lengths given.
6. Supervisor shall undertake risk assessment to determine appropriate temporary speed restriction.
7. The symbolic worker signs shall be installed only when on-foot personnel will be visible to passing traffic.
8. When using MMS two 5mm thick core flute signs back to back in the MM frame to help prevent the sign from blowing out.
9. Drive slowly can be swapped with Smoke Hazard, or Burning Off.
10. Use of Fold up signs and Swing signs acceptable in narrow, very low volume roads <50 VPD

#### DISCLAIMER:

It is the responsibility of the user of this traffic guidance scheme to confirm the appropriateness or otherwise for the intended work site based on rigorous risk assessment, review of the requirements of AS1742.3 and Main Roads WA Traffic Management for Works on Roads CoP and AGGTM. All responsibility will remain with the user to ensure compliance with relevant standards and the provision of the necessary level of protection for work personnel and work site.

Drawn: Cheryl Johnson  
AWTM Cert. No: KTS-AWTM-19-47786-01  
Signed: *Cheryl Johnson*

Reviewed by: Brad Brooksby  
AWTM Cert. No: AUS-AWTM-19-1183-07  
Signed: *Brad Brooksby*

SIGN SPACING	
Speed of Traffic km/h	Distance (m)
55 or less	15m
56 to 65	45m
Greater than 65	Speed of traffic in km/h

BURNING OFF 70km/h - 80km/h POSTED SPEED WORKING WITHIN 1.2m OF TRAFFIC		
DATE: 24/02/2022	REV No: 14	DBCA - 22 - 06

Reset Speed to original Speed Zone

20m SAFETY BUFFER

WORK AREA

20m SAFETY BUFFER

OR

2 x Sign Spacing



2 x Sign Spacing

200m

OR

90m

Side roads may be sealed or unsealed and may be posted or derestricted.

>1.2m

Reset Speed to original Speed Zone

90m

OR

Reset Speed to original Speed Zone

200m

200m