

a ranked alphabet

arity 2




arity 1



arity 0



a tree



this node has a label of arity 2,
and therefore it has 2 children

this node is child 2
(children are ordered)




A tree t over $\Sigma^{[2]}$




$\text{unfold}_1(t)$



$\text{unfold}_2(t)$






t



substitute(t)









=

a term of arity 3




lines leaving at the bottom of the box
represent variables

dangling edges represent unused variables




$\mathsf{T}f$
 \mapsto





\mapsto





a term




ancestor equivalence




descendant equivalence










\mapsto



a factorisation equivalence



a tree



a term that
represents a
part of the tree



input alphabet

arity 2



arity 1



arity 0





output alphabet

arity 2



arity 0





two copies of the input tree,
connected by a binary node
in the root





input alphabet

arity 2



arity 1



arity 0



output alphabet

arity 2




arity 1



arity 0




arity 2



arity 0












a term of arity 4



a term of arity 0








satisfies (*)


(*)

If the root has arity n ,
and $1 \leq i < j \leq n$, then
all ports of the j -th
subterm of the root are
after all ports of the
 i -th subterm of the root



violates (*)


a register update




Variable $i.j$ represents register i in the j -th argument of the register update.

In the dual, this variable is mapped to the i -th edge which enters the j -th port of the reducer.


its dual




input



output




register r




letters of the output alphabet


register s



register r



register s




copy 2 of register s

copy 1 of register r












factors without
branching nodes




factors with
branching nodes







a term of matrix powers



its term unfolding








linear



we only count
variables used
in their scope


variable z can be used twice because it is free

not linear




not linear
because
variable z
is used twice


a λ -term of size $O(n)$




its normal form of size $O(2^n)$




variables



λ -term of type o



@



$\lambda x.$





r





placeholder for the term
stored in the unique register
of the 2nd child












the root is from Σ


all children are from Γ




input




output







\mapsto



a register update



its dual




A diagram illustrating a tree structure. The root node is red. It has two children: a red node on the left and a blue node on the right. The red node has two children: a blue node on the left and a white node on the right. The blue node has two children: a blue node on the left and a white node on the right. A yellow circle labeled r_1 is highlighted around the blue node that is the right child of the red node. A blue circle labeled r_2 is highlighted around the blue node that is the left child of the root. A dashed orange line connects r_1 and r_2 .


[illegible]

a non-port node is represented by a variable, corresponding to the label, applied to the children of the node



- the variables representing the ports are bound outside



the i -th port is represented by a variable x_i of type \mathbf{o}


























































the subbranch
corresponding to
an internal edge




the subbranch
corresponding to
an external edge



a branch can be visualised as
a term with a distinguished
root-to-port path







a tuple of k identity terms
with all their ports folded
into one


$$\Sigma = \{ \text{blue circle with stem}, \text{red circle}, \text{white circle} \}$$

$$a \in \Sigma^{[2]}$$




$$b \in \Sigma^{[2]}$$







a shallow term of matrix powers



its shallow unfolding





twist of port 1

1

2


3



1

2

3



twist of port 1

1

2



1

2