Agents Among Us: Identifying Deceptive Agents in a Multi-Agent Social Deduction Environment

Kevin Kurian
University of Florida
kuriankevin@ufl.edu

Aryan Patel
University of Florida
aryan.patel@ufl.edu

Ray Chen
University of Florida
chenz1@ufl.edu

Chibuzor Okocha
University of Florida
c.okocha@ufl.edu

Christan Grant
University of Florida
christan@ufl.edu

***Abstract*—This paper studies whether LLM agents can detect deception across scale in multi-turn dialogue at a voting level, a question that evaluations of social deduction games typically don't address by relying on game win rate as a common metric, obscuring underlying behavior. With granular metrics, researchers could determine whether failures stem from missing evidence or reasoning failures, tracking how deception detection evolves across individual turns instead of as a game outcome. Studying this requires an environment that records important agent decisions, such as voting, across many games. We present this via Agents Among Us, a highly customizable framework for probing deceptive reasoning among LLM agents. The system features a modular engine with local game states, an architecture supporting heterogeneous open-weight agents, and a logging pipeline that captures per-turn and per-vote data. It includes "observers" that monitor agent suspicion in real time. Its interactive web frontend enables practitioners to design experiments via a built-in prompt editor and monitor live game simulations through visualizations of suspicion and the game map. The architecture is decoupled from the frontend to support benchmarking across thousands of runs. With this system, we generated a corpus of 10,134 games comprising 23,233 discussion rounds and 289,614 utterances from 19 open-weight models. Using this framework, we evaluate the performance discrepancies that exist when agents operate within the pressure induced by the game environment. We find there to be a noticeable gap between open-weight models and frontier models. Open-weight models float above random chance at 50% F_1, while the top frontier models match the performance of observer models, reaching about 86% F_1. These evaluations show how the system serves as a testbed to isolate factors that influence generative social reasoning in a partial-information setting. The framework, dataset, live demo, and website are publicly available at https://ufdatastudio.com/projects/agents-among-us.**

***Index Terms*—Multi-agent systems, Social deduction, Large Language Models, Deception detection**

I. Introduction

Large language models (LLMs) are increasingly deployed as autonomous agents in settings requiring complex social and adversarial navigation. Social deduction games are frequent testbeds for these capabilities. Such studies often rely on aggregate outcomes like win rates [1]–[4]. Recent frameworks demonstrate that binary metrics capture final outcomes while obscuring the internal reasoning process [5]. For instance, an agent might win a game despite making poor logical decisions, rendering overall win rates misleading [6]. This motivates why we choose to evaluate models on a voting basis in order to capture their logic during gameplay [7]. Consequently, we ask: **Can LLM agents effectively detect deception in multi-turn dialogue, and how that changes across model scale with and without live game context?**

We introduce *Agents Among Us*, a live game simulation built on an open-source framework that supports localized agent game states, automated state management, and an interactive user interface. The system includes a dataset of 10,134 games and approximately 290,000 utterances, providing 1:1 data parity between observer and agent voting. Furthermore, we provide an observer pipeline that allows researchers to train supervised role detectors from game logs and re-inject them back into the game to provide real-time "suspicion" scores against which agent reasoning can be measured.

Our evaluation shows that deception detection depends on model scale. Observers identify deceptive agents with 85% F_1, while open-weight agents struggle to achieve the same level of performance, peaking at only 56% F_1, and offline models perform at about the online average of 50%. Offline evaluations show that open-weight models fail to improve performance when evaluating isolated game transcripts, pointing to reasoning failures rather than a lack of textual evidence. However, evaluations on proprietary models suggest that this limitation may be a product of scale. Despite a smaller sample size, GPT-5.1 and Claude Opus 4.8 reached similar accuracy to observers, near 86% F_1 in online gameplay. When evaluated offline as judges on individual transcripts, their performance drops to around 61% F_1 and 63% F_1. This contrast indicates that stronger models are capable of leveraging context provided by live gameplay to improve their ability to detect deception.

Agents Among Us decouples passive text evaluation from active decision-making. By providing a reproducible environment for quantifying the limits of standalone generative reasoning, this framework enables the community to move beyond aggregate win rates toward a more granular understanding of social reasoning trajectories in this deduction game.

The contributions of this paper are as follows:

- **Framework:** An open-source simulation platform for running controlled multi-agent social deduction experiments at scale (Section III).
- **Dataset:** A corpus of 10,134 games and approximately 290,000 utterances from 19 open-weight models (Section IV).
- **Observers:** A supervised role-detection pipeline trained on game logs that re-injects real-time suspicion scores into the game loop as a diagnostic (Section IV).




Fig. 1: Architecture of Agents Among Us. In the online simulation (blue), game setup (1) defines the crew composition, roles, and round limits. The game engine (2) advances each round through Movement, Discussion, and Voting over a shared game state. Decoupled inference workers (3) serve agent decisions asynchronously across GPUs and nodes. The logging manager (4) writes actions, transcripts, votes, and statistics to the game log (5). Offline (orange), preprocesses discussion logs (6), then a classifier is trained on them (7), and the resulting observer (8) produces suspicion scores that are re-injected into the game as a real-time diagnostic.

- **Model Scale:** The ability to noticeably leverage game context for deception detection emerges with top frontier models, not gradually across model sizes. (Section V).

II. Related Work

A. LLMs in Games and Social Deduction

Large language models are increasingly used for reasoning, planning, and role-play in interactive game environments [8], [9]. In the context of social deduction, frameworks such as [1], [2] evaluate agentic deception, theory of mind, and persuasion. [10] categorizes deception and falsehoods in multi-agent communication. However, these systems primarily report aggregate success through game win-rates, deception success, or Elo ratings. They also rely on smaller-scale evaluations (hundreds of games rather than thousands). They demonstrate that models can generate deceptive text, but do not isolate whether agents can effectively use the discourse to make optimal decisions. Our system differentiates itself by incorporating a direct, per-vote evaluation as a means to compare generative in-game reasoning with offline observers.

B. Interpretability and Prediction in Social Deduction Games

Detecting hidden roles and deception from dialogue is a well-studied NLP task [11], [12]. Previous research on games like Werewolf and Avalon uses support vector machines and neural networks to predict adversarial roles from multi-turn conversation logs [13], [14]. More recently, frameworks have used LLMs as offline multiple-choice probes to detect deception from transcripts [15]. These classifiers are typically treated as standalone NLP benchmarks rather than interactive baselines [3]. We integrate the observers into the generative simulation loop, training on the same dialogue logs produced by agents during deliberation.

C. Practical Game AI and Multi-Agent Systems

Traditional multi-agent game AI relies on rule-based systems, behavior trees and reinforcement learning (RL) to achieve optimal play [16], [17]. Recent hybrid approaches have extended this by training language models using multi-agent RL to improve win-rates and communication in social deduction

settings [18]. Rather than optimizing agent policies to maximize win-rates, our system freezes the LLMs to benchmark their zero-shot social inference. RL may improve gameplay, but our architecture prioritizes a repeatable environment to evaluate how off-the-shelf models interact and are monitored.

III. Agents Among Us System

The system is a modular simulation framework, shown in Figure 1. It evaluates multi-agent reasoning under the constraints of the game Among Us. It consists of a game engine, the LLM agents participating, data logging, and an observer pipeline.

A. Game Overview

Agents Among Us is built based on the social deduction game Among Us. Each game consists of a crew of agents, of which a majority are honest crewmates and a small number are adversarial imposters known as Byzantines. Play alternates between a movement phase, in which agents navigate a map of interconnected rooms, and a discussion and voting phase, triggered when an agent reports an eliminated player or calls an emergency meeting. During discussion, agents exchange statements in a structured sequence before voting to eject a suspect. A crew wins by ejecting all imposters; imposters win by eliminating enough crewmates to reach parity. The game runs for a set number of rounds. Algorithm 1 summarizes the loop.

B. Game Engine and State Management

The engine maintains a central game state tracking global variables (currentround, phase, ejections) and per-agent statistics (correct votes, bodies reported). During phase transitions, the engine writes game data seen by each agent to their memory, separating the global ground truth from each agent's partial observation. What they see depends on their current room, role, and history.

C. Agents

To simulate continuous participation, the system provides short and long-term memory depending on the game's phase. The game engine acts as a central controller, writing agent responses and actions to agent-specific text logs. Agents read these files to isolate relevant events, dynamically assembling their context based on the active game phase:

a) Movement Phase: The context window here is more localized. Agents are provided with their current round's action log, their current room occupants, and the availability of adjacent rooms to formulate a single-word movement or reporting command. We set the temperature to 0.1 for deterministic output.

b) Discussion Phase: The context window expands to facilitate social reasoning. The system injects the agent's personal action memory from the previous round, the global results log of past ejections, and the ongoing conversational transcript of the current meeting. We set the temperature to 1 for variety in discussions. We note the importance of this phase as shown in Table VI.

Algorithm 1 Agents Among Us Game Loop.

Require: agents A (Hon. & Byz.), room map, R rounds, T movement ticks, m statements per agent

for $r \leftarrow 1$ **to** R **do**
Movement phase
  for $t \leftarrow 1$ **to** T **do**
    for each active agent a **do**
      a observes current & adjacent rooms, players
      a chooses an available action:
        if Byz, TAG Hon. in the same room
        REPORT a body in the same room
        BUTTON if in the Cafeteria (once per game)
        MOVE to an adjacent room
    end for
    execute TAG (eliminate the co-located target)
    if some agent chose REPORT or BUTTON **then**
      call a meeting; **break**
    end if
    execute remaining MOVES
  end for
  if OUTCOME is decided **then return** outcome
  end if
  if a meeting was called **then**
Discussion phase
    caller speaks first, then every active agent for m
Voting phase
    each active agent votes for a suspect or SKIP
    eject the agent with the most votes (barring a tie)
    if OUTCOME is decided **then return** outcome
    end if
  end if
end for
return crew win ▷ round limit reached

function OUTCOME
  return crew win if $|\text{Byz}| = 0$; Byz win if $|\text{Byz}| \geq |\text{Honest}|$; else undecided
end function

c) Voting Phase: To isolate social inference, the agent's personal movement and action memory are excluded from the prompt. The voting context window strictly contains the global results log and a filtered discussion transcript covering the past three discussion rounds. Here we set the temperature to default.

The phase-dependent structure is configurable, the amount of information each phase exposes can be adjusted to understand how context availability affects reasoning. Team composition and game length (default is 10 rounds) can also be adjusted for homogenous/heterogenous teams of models.

D. Role-Specific Prompting

To ensure model neutrality and maximize agency in LLMs, prompts are structured objectively, focusing on game rules rather than prescriptive strategies. Both roles receive a system



Fig. 2: The user interface provides a real-time visualization of the game state, featuring a dynamic map of agent locations, an active discussion window, and an agent status table that includes live suspicion scores from the observer pipeline. In this view, active agents are currently located in Storage, Admin, and Upper Engine.

prompt defining ship connectivity, victory conditions, and instructions to avoid pleasantries or internal reasoning.

a) Honest agents: Prompts emphasize information gain and location verification. During discussions, agents are tasked with building consensus to eject suspects based on observed inconsistencies or incriminating behaviors.

b) Byzantine agents: Prompts provide the identities of teammates to facilitate coordination. The primary objective is to eliminate crewmates while redirecting suspicion to avoid ejection. To mitigate safety-alignment restrictions that trigger refusals when tasked with "killing" or violence, the system employs the term **TAG** as a substitute for kill.

E. LLM Inference and Distributed System

The system processes all agent reasoning locally using Hugging Face transformers. Models are quantized to 4-bit precision to fit within memory constraints. The inference module parses the raw textual response, filtering excessive reasoning to isolate the agent's final chosen action.

To handle the heavy load of multi-agent simulation, the architecture decouples inference from the main game loop. A dedicated worker script processes generation requests asynchronously. This allows researchers to distribute agent inference across a single or multiple GPUs/compute nodes.

F. Logging

A logging manager records complete action histories and discussion transcripts, compiling game statistics and voting records. We generated initial datasets by running four distinct experiment configurations. We extracted the resulting discussion logs to train classical machine learning classifiers. We then embedded these trained models back into the live game engine as part of the observer module.

During new simulations, this observer reads the live discussion log for a given round. It applies preprocessing to remove stopwords, and normalize entity names and locations. The observer evaluates the same textual evidence provided to the active LLM players. The observer then outputs a real-time suspicion probability for each agent to see specific instances where reasoning diverges from textual evidence.

G. Human Participation and Hybrid Agents

Within the interface, the user has the option to participate in the game alongside other LLM agents in all phases of the game. Upon selecting the option to participate, roles are anonymized. Users also have the option to make agents hybrid. As a hybrid agent, LLMs add a pretrained classifier to their toolchain to assist in their voting, improving performance without finetuning. The classifiers evaluate discussion logs sequentially using pruning. For each agent statement, the classifier computes a suspicion probability, P_t, and determines the vector shift relative to the prior state.

If this shift meets a dynamically calculated threshold based on the number of surviving players, the statement is deemed strategically significant. These updates assist agents by filtering context, removing low-confidence dialogue to focus on major shifts in probability and anchoring the votes with the scores in an attempt to counter deception. The performance of hybrid agents can be seen in Table VI.

IV. Experiments

A. Dataset Generation

We generated 11,000 games across two classes of open-weight models: 10 Middleweight models (60–82B parameters) and 10 Lightweight models (7–20B parameters). Crews consisted of 2 imposters and 8 crewmates. We executed 100 games for each of the 20 homogeneous model compositions and 100 games for every imposter pair within a weight class (90 heterogeneous compositions), giving 110 compositions in total. One Lightweight model is absent from the final dataset because its games terminated before any meeting was called, leaving 19 models. Excluding the 866 games that concluded without discussion, the final dataset comprises 10,134 games, yielding 23,233 discussion rounds and 289,614 utterances. The number of discussions per game is shown in Table VII.

We also look at performance of seven proprietary models under the same game mechanics and rules. Due to API constraints and cost, evaluations with these models consist of one homogenous composition per model alongside a mixed composition for 20 games, resulting in 90 total games.

Discussion logs were preprocessed to remove stopwords and mask game-specific entities (room locations, agent identifiers). Alongside the processed text, each sample included two structural features: a flag indicating whether the agent initiated the meeting and whether the utterance was an opening or follow-up statement.

B. Observer Experimental Setup

Six classical machine learning classifiers were evaluated as offline observers, trained and tested as shown in Table VIII. To address the inherent 8:2 class imbalance (213,332 crewmate vs. 76,282 imposter statements), classifiers were trained on balanced subsets of open-weight logs via random undersampling. Training occurred on individual text samples, but testing simulated an in-game vote at the round level. The observer averaged suspicion probabilities across all statements in a round to identify a top suspect, using a dynamic confidence threshold optimized on the training data to either cast a vote or abstain. Active LLM players were evaluated on the exact same test masks and round structures.

C. Metrics

To accurately capture voting behavior within the multi-agent action space, we define task-specific decision outcomes. The three distinct voting actions for an honest agent are defined as follows: **Correct Accusation (CA):** an honest agent correctly votes for an imposter; **False Accusation (FA):** an honest agent incorrectly votes for a fellow crewmate; and **Skipped Vote (SV):** an honest agent skips the vote, failing to identify an imposter when given the opportunity. The agent must select a specific target or choose to skip.

A random baseline, framed as guessing between the three possible outcomes, was calculated to contextualize model performance. Let V represent the number of valid target players in a given round, and I represent the number of active imposters. Including the "skip" action, the total action space size is $V+1$. The expected probabilities of the random baseline are:

$$\mathbb{E}[\text{CA}] = \frac{I}{V+1}; \quad \mathbb{E}[\text{FA}] = \frac{V-I}{V+1}; \quad \mathbb{E}[\text{SV}] = \frac{1}{V+1}. \tag{1}$$

Using these action outcomes, we define two primary behavioral metrics: *Accusation Accuracy* (Acu), which measures the correctness of an agent's votes, and *Voting Aggressiveness* (Agr), which quantifies the agent's proactivity in voting to eject rather than abstaining:

$$\text{Acu} = \frac{\text{CA}}{\text{CA}+\text{FA}} \quad \text{and} \quad \text{Agr} = \frac{\text{CA}}{\text{CA}+\text{SV}} \tag{2}$$

The random guessing baseline for Accusation Accuracy (Acu_{rand}) simplifies as follows:

$$\text{Acu}_{\text{rand}} = \frac{\mathbb{E}[\text{CA}]}{\mathbb{E}[\text{CA}]+\mathbb{E}[\text{FA}]} = \frac{\frac{I}{V+1}}{\frac{I}{V+1}+\frac{V-I}{V+1}} = \frac{I}{V} \tag{3}$$

Similarly, the random guessing baseline for Voting Aggressiveness (Agr_{rand}) is derived by isolating correct accusations against strategic abstentions:

$$\text{Agr}_{\text{rand}} = \frac{\mathbb{E}[\text{CA}]}{\mathbb{E}[\text{CA}]+\mathbb{E}[\text{SV}]} = \frac{\frac{I}{V+1}}{\frac{I}{V+1}+\frac{1}{V+1}} = \frac{I}{I+1} \tag{4}$$

The final performance baseline ($F_{1\text{-rand}}$) is calculated as the harmonic mean of accuracy and aggressiveness:

$$F_{1\text{-rand}} = 2 \cdot \frac{\text{Acu}_{\text{rand}} \cdot \text{Agr}_{\text{rand}}}{\text{Acu}_{\text{rand}} + \text{Agr}_{\text{rand}}} \tag{5}$$

V. Results

A. Model Performance

The evaluation in Table I shows a discrepancy between passive detection and active execution. Linear models, including SGD and SVM, achieved the highest F_1. They averaged about **85%** F_1 across all games. Tree-based methods performed lower, with Random Forest averaging 79.89% F_1. We use observer modules as a diagnostic tool to verify that informative text features exist within the discourse. Model performance varied by scale and deployment setting. Open-weight agents averaged 50.39% F_1 online and about 49% offline (Table I), with per-model results in Table X. Proprietary frontier models averaged 64.8% F_1 across seven models (Table II), but the distribution was bimodal: GPT-5.1 and Claude Opus 4.8 reached 86.4% and 85.8%, matching the observer, while the remaining five models (Claude Sonnet 4.6, Claude Haiku 4.5, Nova Pro, Grok-4, Nova Lite) ranged from 38% – 62%. When evaluated offline as judges on 2000 sampled round instances (the same input the observer sees), the top two models dropped to 60.9% and 63.0% F_1 (Table I), beating the open-weight judges but staying below the observer; adding five in-context examples did not improve performance (Table IX).

Table I: Performance (F_1 Score %) across all games, contrasting observers (top) with LLM agents. Bold indicates the top performers in each block. Open-weight agents score near 50% F_1 whether online or offline, below the trained observers; the strongest frontier agents reach observer-level F_1 in-game. Judges (offline) read a single round, the same input as the observers. Per-model breakdowns are in Table X (open-weight) and Table II (frontier).

Model	Accusation Acu. (%)	Voting Agr. (%)	F_1 Score (%)
Observers			
Logistic Regression	80.00	91.24	85.25
SGD	80.00	92.00	**85.58**
SVM	79.00	92.00	85.00
MLP	78.00	92.00	84.42
XGBoost	77.00	92.00	83.83
Random Forest	77.00	83.00	79.89
Open-weight agents (online)			
Lightweight avg. (7–20B)	35.3	72.9	47.6
Middleweight avg. (60–82B)	39.8	80.5	**53.3**
Overall avg.	37.40 ± 4.20	77.00 ± 9.30	50.39 ± 4.4
Frontier agents (online)			
GPT-5.1	78.4	96.2	**86.4**
Claude Opus 4.8	76.5	97.8	85.8
Overall avg. (7 models)	51.7 ± 6.8	86.3 ± 4.5	64.8 ± 6.0
Judges (offline)			
Mixtral-8x7B-Instruct	32.83	99.92	49.43
Qwen3-14B-Instruct	32.65	95.91	48.66
GPT-5.1	44.0	99.0	60.9
Claude Opus 4.8	46.0	100.0	**63.0**
Baseline (Random)	30.40 ± 0.80	62.80 ± 0.70	40.58 ± 0.63




Fig. 3: Local interpretable model-agnostic explanations (LIME) for Role utterances. Blue highlights indicate features the observer associates with the crewmate, and orange highlights indicate features associated with the imposter. Probabilities indicate the observer's confidence in the assigned role.

Table II: Per-model frontier results (F_1 Score %) across all frontier games, sorted by F_1; F_1 shown with a 95% CI. The random baseline is 38–41% per model.

Model	Accusation Acu. (%)	Voting Agr. (%)	F_1 (%)
OpenAI/GPT-5.1	78.4	96.2	**86.4±17.1**
Anthropic/Claude-Opus-4.8	76.5	97.8	85.8±8.9
Anthropic/Claude-Sonnet-4.6	44.7	100.0	61.8±12.7
Anthropic/Claude-Haiku-4.5	48.9	83.5	61.6±12.3
Amazon/Nova-Pro	50.0	78.7	61.2±13.5
xAI/Grok-4	43.8	87.5	58.3±13.5
Amazon/Nova-Lite	29.7	53.6	38.2±18.8

B. Prompt Ablations

The role prompts do not give the two roles the same vocabulary. Some terms appear in one prompt only. For example, Byzantine agents alone are told about **teammates**, and honest agents alone about the option to **skip** votes. Either group could let a classifier key on prompt wording rather than behavioral indicators in the text. We test this by deleting the role-linked words and retraining (Table III), in three stages: game-action words, strategy words, then room and player placeholders, about two thirds of all tokens. F_1 drops by roughly five points—the top observer falls from 85.58% to 80.7%—and stays well above the open-weight models (50.4%). To catch words our list missed, we rank every n-gram by its chi-square association with the role, remove the top ones, and retrain (Table IV); removing the top $1{,}000$ features still leaves about 74% F_1. A feature decomposition (Table V) shows the remaining signal is lexical: the two structural features score near chance, while text alone nearly matches the full model. The surviving words differ in style: Byzantine agents cast suspicion on others, honest agents report what they saw.

Table III: Observer F_1 (%), mean and 95% CI, as role-linked words are removed cumulatively: all words; −action (*tag, teammate*); −strategy (*suspect, vote*); −entity (room/player placeholders). The *all* column is the unmodified-log observer of Table I. Despite removing two-thirds of tokens, F_1 drops only ∼5 points, staying above open-weight agents, indicating the observer tracks behavioral style rather than prompt-induced vocabulary.

Classifier	all	−action	−strat.	−entity
Logistic Reg.	85.25±2.1	84.3±2.3	82.7±2.5	80.7±2.7
SGD	85.58±2.1	83.8±2.3	82.3±2.4	80.1±2.7
SVM	85.00±2.2	83.8±2.4	82.2±2.5	80.1±2.7
MLP	84.42±2.1	83.8±2.5	82.4±2.6	80.3±2.8
XGBoost	83.83±2.5	82.3±2.9	80.6±3.1	78.2±3.5
Random Forest	79.89±4.7	78.4±4.4	74.4±6.0	75.7±4.9

Table IV: Observer F_1 (%) as the top-N most role-associated n-grams (chi-square) are removed. N=0 is the unmodified-log observer of Table I.

N removed	0	25	50	100	200	500	1000
Logistic Reg.	85.25	85.3	84.7	83.6	81.9	78.8	74.5
SGD	85.58	84.6	83.9	82.6	80.5	77.8	73.1
SVM	85.00	84.9	84.2	83.2	81.5	78.4	74.0
MLP	84.42	84.8	84.1	83.1	80.8	77.9	73.3
XGBoost	83.83	83.0	81.6	79.7	76.5	72.7	67.8
Random Forest	79.89	77.2	76.3	74.2	72.4	67.8	63.1

VI. Discussion

The classifiers serve as a baseline to verify that text features exist in multi-agent discourse. Initial inspection and LIME analysis (Figure 3) highlight role-associated vocabulary, but ablations confirm that classifier performance is not merely an artifact of prompt-induced keywords. Removing role-linked terms and top features only marginally impacts accuracy, showing observers track semantic patterns between deceptive and honest agents. The observer tells the two roles apart mostly by how agents talk. The words most tied to each role (Table V) are speculative for Byzantine agents (*could*, *odd*, *strange*) and observational for honest ones (*saw*, *location*). Any single word means little, so the pattern is only suggestive; one likely reason for it is that honest agents have real observations to describe while Byzantine agents do not. The pattern is spread across many words rather than a few, since it holds even after we remove role vocabulary and the top n-grams (Tables III and IV). A text classifier can therefore flag likely deceivers, but recognizing these word patterns is not the same as reasoning about who is lying. Comparing online and offline evaluations further clarifies how well models process game context. For open-weight models, evaluating isolated transcripts outside the game loop yields performance similar to online voting. This indicates that their limitations stem from reasoning failures across prior and ongoing game states rather than an absolute lack of textual information. However, top frontier models experience a noticeable performance drop in the offline setting compared to their live accuracy. Adding few-shot examples of correctly voted rounds did not improve performance as what is needed was personal context(Table IX). The drop in performance offline shows that advanced architectures better leverage the sequential context of live gameplay to track deceptive behavior. While performance trends upward with scale, matching the classification ceiling emerges sharply at the top rather than improving gradually.

Table V: Fully-masked classifier (the −entity setting of Table III). (a) Text vs. the two structural features (meeting report, statement number; F_1 %, mean). (b) Most role-associated surviving words, by decreasing chi-square.

(a) Feature decomposition

Features used	F_1 (%)
Structural	52.7±1.1
Text	80.6±2.8
Both	80.7±2.7

(b) Language used

Role	Role-associated words
Byzantine	*noticed, could, odd, strange, trying*
Honest	*saw, based, location, due, back*

In the system's implementation, agents are provided with a worldview during the voting phase, which includes prior round results and a window of the most recent discussion rounds from agents. Under these conditions, the evaluated open-weight models achieved a baseline voting accuracy of 50.39% F_1. Agents tend to be proactive when casting votes with an average voting aggression of 77%, but their ability to discern who is deceptive is only slightly better than random chance, at about 37% compared to the baseline 30%. In a live game, the agent must reconcile its internal goal-seeking behavior with its team, using dialogue logs, while also battling deceptive agents. The system is designed to help researchers isolate whether these failures stem from the volume of data or cascading social dynamics within the game loop. For example, the system's logging captures instances in which an individual agent's incorrect inference is immediately adopted and amplified by other models in subsequent turns, driving the crew toward a false consensus. Such examples of a model's behavioral mechanics can be analyzed downstream for a more systematic study [19].

VII. Conclusion

This work demonstrates that Agents Among Us provides a scalable environment to isolate and study reasoning failures in multi-agent settings. The system highlights the extraction and contextual bottlenecks hindering open-weight models in adversarial environments. This architecture gives the community a reproducible testbed for exposing the gap between passive classification and active deception detection, a distinction aggregate win rates cannot make.

Limitations and Future Work

The evaluation maintains a 1:1 data parity because both the LLM agents and the supervised observers process the exact same discussion rounds. However, the methods of inference differ. The observers were trained on balanced, labeled datasets of thousands of statements, whereas the agents operated in a largely zero-shot capacity. This comparison aims to explore the off-the-shelf capabilities of generative agents relative to a task-specific extraction baseline. Task-specific fine-tuning and reinforcement learning remain valuable directions for future work to help close this performance gap. Currently, the system enforces a turn-based discussion phase, which prevents the study of real-time interruptions that characterize human social deduction. Additionally, as a purely text-based platform, the framework cannot study multimodal deceptive signals. Relying entirely on text-to-text generation introduces inherent bottlenecks that can lead to the loss of semantic information. Future work could extend hybrid agents by exploring direct neural communication between models in the game [20]. Each model is trained with a system prompt that is sensitive to prompt phrasing and word choice. Including words like *kill* or *die* may alter game results and agent behavior and trigger encoded responses. The system does allow users to perform prompt engineering by directly modifying game prompts in the interface. We plan to study prompt-driven behavior with this feature. Researchers can also use the system's logging pipeline to study models' internal strategy by capturing chain-of-thought (CoT) processes alongside external actions and statements.

References

[1] S. Golechha and A. Garriga-Alonso, "Among us: A sandbox for measuring and detecting agentic deception," *arXiv preprint arXiv:2504.04072*, 2025.

[2] S. Bailis, J. Friedhoff, and F. Chen, "Werewolf arena: A case study in llm evaluation via social deduction," *arXiv preprint arXiv:2407.13943*, 2024.

[3] J. Light, M. Cai, S. Shen, and Z. Hu, "Avalonbench: Evaluating llms playing the game of avalon," *arXiv preprint arXiv:2310.05036*, 2023.

[4] Y. Chi, L. Mao, and Z. Tang, "Amongagents: Evaluating large language models in the interactive text-based social deduction game," *arXiv preprint arXiv:2407.16521*, 2024.

[5] X. Yuan, X. Zhang, K. Xu, Y. Xu, L. Yu, J. Wang, Y. Dong, and H. Wang, "Tracing llm reasoning processes with strategic games: A framework for planning, revision, and resource-constrained decision making," 2025. [Online]. Available: https://arxiv.org/abs/2506.12012

[6] Z. Song, Y. Huang, J. Liu, H. Luo, C. Wang, L. Gao, Z. Xu, M. Han, X. Chang, and X. Chen, "Beyond survival: Evaluating llms in social deduction games with human-aligned strategies," *arXiv preprint arXiv:2510.11389*, 2025.

[7] L. Hu, Q. Li, A. Xie, N. Jiang, I. Stoica, H. Jin, and H. Zhang, "Gamearena: Evaluating llm reasoning through live computer games," in *International Conference on Learning Representations*, vol. 2025, 2025, pp. 33 278–33 309.

[8] J. S. Park, J. O'Brien, C. J. Cai, M. R. Morris, P. Liang, and M. S. Bernstein, "Generative agents: Interactive simulacra of human behavior," in *Proceedings of the 36th annual acm symposium on user interface software and technology*, 2023, pp. 1–22.

[9] R. Gallotta, G. Todd, M. Zammit, S. Earle, A. Liapis, J. Togelius, and G. N. Yannakakis, "Large language models and games: A survey and roadmap," *IEEE Transactions on Games*, 2024.

[10] M. Agarwal, S. Rana, T. Sundoro, H. Berhe, S. Kim, V. Sharma, S. O'Brien, and K. Zhu, "Wolf: Werewolf-based observations for llm deception and falsehoods," *arXiv preprint arXiv:2512.09187*, 2025.

[11] F. Soldner, V. Pérez-Rosas, and R. Mihalcea, "Box of lies: Multimodal deception detection in dialogues," in *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, 2019, pp. 1768–1777.

[12] V. Pérez-Rosas, M. Abouelenien, R. Mihalcea, and M. Burzo, "Deception detection using real-life trial data," in *Proceedings of the 2015 ACM on international conference on multimodal interaction*, 2015, pp. 59–66.

[13] G. Chittaranjan and H. Hung, "Are you awerewolf? detecting deceptive roles and outcomes in a conversational role-playing game," in *2010 IEEE International Conference on Acoustics, Speech and Signal Processing*. IEEE, 2010, pp. 5334–5337.

[14] B. Lai, H. Zhang, M. Liu, A. Pariani, F. Ryan, W. Jia, S. A. Hayati, J. Rehg, and D. Yang, "Werewolf among us: Multimodal resources for modeling persuasion behaviors in social deduction games," in *Findings of the Association for Computational Linguistics: ACL 2023*, A. Rogers, J. Boyd-Graber, and N. Okazaki, Eds. Toronto, Canada: Association for Computational Linguistics, Jul. 2023, pp. 6570–6588. [Online]. Available: https://aclanthology.org/2023.findings-acl.411/

[15] A. O'Gara, "Hoodwinked: Deception and cooperation in a text-based game for language models," *arXiv preprint arXiv:2308.01404*, 2023.

[16] O. Vinyals, I. Babuschkin, W. M. Czarnecki, M. Mathieu, A. Dudzik, J. Chung, D. H. Choi, R. Powell, T. Ewalds, P. Georgiev *et al.*, "Grandmaster level in starcraft ii using multi-agent reinforcement learning," *nature*, vol. 575, no. 7782, pp. 350–354, 2019.

[17] N. Brown and T. Sandholm, "Superhuman ai for multiplayer poker," *Science*, vol. 365, no. 6456, pp. 885–890, 2019.

[18] B. Sarkar, W. Xia, C. K. Liu, and D. Sadigh, "Training language models for social deduction with multi-agent reinforcement learning," *arXiv preprint arXiv:2502.06060*, 2025.

[19] A. Author(s), "Evaluating llm social cognition through multi-agent strategic games," 2026, under review.

[20] T. Fu, Z. Min, H. Zhang, J. Yan, G. Dai, W. Ouyang, and Y. Wang, "Cache-to-cache: Direct semantic communication between large language models," *arXiv preprint arXiv:2510.03215*, 2025.

Appendix

Table VI: Crew metrics by discussion ablation and hybrid scale (2 Mixtral-8x7B imposters vs. 8 Qwen3-14B crewmates, N=100 games per tier). All cells show 95% CIs; win rate uses Wilson intervals, F1/Acu/Agr use percentile intervals.

		Hybrid Agents		
Metric	Ablation	0	4	8
Crew Win Rate	2.0%±3.2	27.0%±8.6	34.0%±9.1	**47.0%±9.6**
F_1 Score	36.6%±4.4	50.7%±6.7	59.7%±6.0	**64.5%±5.7**
Accusation Acu	24.4%±3.6	40.9%±6.7	54.0%±6.5	**69.8%±6.3**
Voting Agr.	**70.4%±6.3**	66.5%±6.8	66.8%±7.0	60.0%±6.7

Table VII: Frequency of discussion rounds per game.

Discussions per Game	**Frequency**
1	2,034
2	4,168
3	2,913
4	971
5	48

A. Role System Prompts

The following system prompts are injected once at the start of each game and remain fixed for the duration. Agent name placeholders (e.g., `Agent_A`) are filled at runtime.

Table VIII: Summary of four cross-environment evaluation splits to test observer generalization across crew composition and model scale.

Experiment	Training Data	Testing Data
Exp. 1	Homogeneous Crews	Heterogeneous Crews
Exp. 2	Heterogeneous Crews	Homogeneous Crews
Exp. 3	Lightweight Models (7–20B)	Middleweight Models (60–82B)
Exp. 4	Middleweight Models (60–82B)	Lightweight Models (7–20B)

Table IX: Effect of in-context learning (ICL) on offline judge F_1 (%). n=5 in-context examples of discussion and the correct suspect are added to the prompt. Neither model improves meaningfully: GPT-5.1 drops 0.9 points and Opus 4.8 drops 0.6 points.

Model	0-shot F_1 (%)	Few-shot F_1 (%)
OpenAI/GPT-5.1	60.9	59.0
Anthropic/Claude-Opus-4.8	63.0	62.4

Honest Agent System Prompt

```
You are [Agent Name], an Honest Agent in a
spaceship social deduction simulation. You are
NOT a chat assistant. You must output concise
commands during movement. During discussion,
be conversational. You do not use pleasantries
like "Great" or "Let's get started". You do
not include any internal thought processes
or analysis. You strictly follow formatting
instructions.
GAME RULES: 1. The Map: The ship consists of
connected rooms. You can only see occupants in
your current room and adjacent rooms. Here is
a map of the rooms and their connections: [Room
connectivity map]
2. Action Phase: You move between rooms to
complete tasks and observe others. Each round
you get 4 movement actions. - Movement: There
are (Byzantine agents) hiding among you who can
eliminate agents by tagging them. - Emergency
Button: In the Cafeteria, you can press the
Emergency Button to call a meeting, but only
once per game. - Reporting: Once you find an
eliminated body, a REPORT will be called to start
a discussion and voting.
3. Discussion Phase: When a meeting starts (via
Body Report or Emergency Button): - Ends ability
to be tagged or move for that round. - Agents
discuss who is suspicious. - Agents VOTE to EJECT
someone into space. Your goal is to identify and
eject Byzantine agents. - You can choose to skip
voting. However, voting is the only active path
to eject Byzantine agents.
4. Victory Condition: - WIN: Eject all Byzantine
agents or all rounds complete with agents
surviving. - LOSE: If Byzantine agents equal
or outnumber agents via tagging or ejections.
Additional Info: Use logic and deduction to
convince others and come to a consensus to vote
out the Byzantine agents.
```

Byzantine Agent System Prompt

```
You are [Agent Name], a Byzantine Agent in a
spaceship social deduction simulation. As a
Byzantine, you have the unique ability to Tag
honest agents. You are NOT a chat assistant. You
must output concise commands during movement.
During discussion, be conversational. You do
not use pleasantries like "Great" or "Let's
get started". You do not include any internal
thought processes or analysis. You strictly
follow formatting instructions.
GAME RULES: 1. The Map: The ship consists of
connected rooms. You can only see occupants in
your current room and adjacent rooms. Here is
a map of the rooms and their connections: [Room
connectivity map]
2. Action Phase: You move between rooms to tag
Honest agents. Each round you get 4 movement
actions. - Eliminating: You can TAG (eliminate)
an Honest agent if you are in the same room. You
cannot tag in consecutive actions in the same
round. - Reporting: If you find an eliminated
body, you may REPORT it to trigger a meeting. -
Emergency Button: Only if in the Cafeteria, you
can press the Emergency Button to call a meeting,
but only once per game.
3. Discussion Phase: When a meeting starts (via
Body Report or Emergency Button): - Ends ability
to tag players or move for that round. - Agents
discuss who is suspicious. - Agents VOTE to
EJECT someone into space. - Your goal is to
avoid ejection of you and your teammates while
eliminating Honest agents.
4. Victory Condition: - WIN: Eliminate Crewmates
until Byzantine Agents >= Crewmates via tagging
or ejections. - LOSE: If all Byzantine agents are
voted out or all rounds complete with more Honest
Agents than Byzantine Agents.
Additional Info: You know who your fellow
Byzantine Agents are. You cannot tag them. Work
with teammates to stack votes on honest agents.
```

B. LLM Specification

Table X details the individual F_1 performance for the 19 open-weight models evaluated in this study. We sample a diverse range of architectures (Llama-3.x, Qwen, Gemma, Mixtral) and post-training recipes, including some top-performing models sourced from the Hugging Face Open LLM Leaderboard. Some checkpoints feature nonstandard community naming that represent the broader ecosystem of fine-tunes; a few are upscaled merges whose parameter count exceeds that of the base model their name refers to, and we tier such models by their actual size. The framework remains model-agnostic, allowing users to modify any Hugging Face-compatible LM via backend configuration. Lightweight experiments were executed on a single compute node (1-2 minutes/game); Middleweight experiments (9-10 minutes/game) were distributed across three nodes to accommodate increased memory requirements. To assist researchers in resource management, the system provides available GPU memory during model initialization and batch scripts.

C. What Win Rates Miss

Win rate is an indirect measure of how well an agent detects deception, because a game can be won or lost for many reasons beyond any one agent's voting, such as crew members being eliminated before a meeting, a split vote failing to eject the imposter, or the round limit expiring. Accusation accuracy and voting aggressiveness instead describe voting

Table X: Individual open-weight model breakdown (F_1 Score %) across all games. Mixtral and Qwen3 are the top performers in their respective weight classes.

Model Name	Accusation Acu. (%)	Voting Agr. (%)	F_1 (%)
Aratako/Mixtral-8x7B-Instruct	43.3	82.4	**56.7**
Nexusflow/Athene-V2-Chat	41.7	81.5	55.2
arcee-ai/Arcee-Nova	39.6	90.2	55.0
Qwen/Qwen2.5-72B-Instruct	42.6	77.5	55.0
NousResearch/Hermes-4-70B	39.8	82.8	53.8
MultiverseComputingCAI/HyperNova	39.2	84.2	53.4
zerofata/L3.3-GeneticLemonade	39.9	78.0	52.8
OpenPipe/Qwen3-14B-Instruct	42.3	62.2	**50.4**
Qwen/Qwen3-Next-80B-A3B-Instruct	39.0	71.0	50.4
meta-llama/Llama-3.3-70B-Instr	36.8	79.1	50.2
openai/gpt-oss-20b	33.9	80.9	47.8
meta-llama/Llama-3.1-8B-Instruct	31.3	92.6	46.8
arcee-ai/Arcee-Agent	34.7	70.9	46.6
Qwen/Qwen2-7B-Instruct	35.7	65.0	46.1
Apertus-70B-Instruct-2509	32.4	76.1	45.5
Qwen/Qwen2.5-7B-Instruct	35.5	61.9	45.1
google/gemma-2-9b-it	33.2	69.6	45.0
meta-llama/Meta-Llama-3-8B-Instruct	29.5	87.0	44.1
swiss-ai/Apertus-8B-Instruct-2	32.1	64.5	42.9

Table XI: Crew win rate versus per-vote metrics, by tier. Win rate and Accusation Accuracy rise together across tiers, but win rate also includes game outcomes unrelated to voting.

Tier	Crew WR%	Acu. %	Agr. %	F_1 %
Open-weight, Lightweight (7–20B)	22.5	35.3	72.9	47.6
Open-weight, Middleweight (60–82B)	28.9	39.8	80.5	53.3
Frontier	48.9	51.7	86.3	**64.8**

behavior directly: how accurately an agent's vote identifies a deceiver, and how readily it votes rather than abstains. The two are distinct, and across every tier aggressiveness is higher than accuracy (Table XI). Agents cast a vote on 73–86% of opportunities but correctly identify an imposter only 35–52% of the time. This behavior is proactive yet frequently wrong, and it holds even for the strongest tier, despite high rate of participation. The evidence implies agents may commit to a suspect on possibly weak grounds, jumping to conclusions, forming false beliefs among the group. This overconfidence parallels hallucination, where a model emits a confident but unsupported answer rather than indicating uncertainty. A win rate cannot expose this behavior, because it reports a team-level outcome, and averages away what each agent did. The per-vote metrics operate on the individual agent's decision, which is what our analysis of deceptive behavior requires.