

# Program Verification in Elixir

Master's Degree in Formal Methods and Computer Engineering

---

Adrián Enríquez Ballester

Supervisor: Manuel Montenegro Montes

July 5, 2022

Complutense University of Madrid



# Table of Contents

Introduction

SMT Solver Integration in Elixir

Verification Intermediate Representation

Elixir Code Verification

Conclusions

# Introduction

---

# Motivation

- Light-weight program verification systems:

- Light-weight program verification systems:
  - Allow specifying and verifying code

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention

# Motivation

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention
- Dafny:



# Motivation

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention
- Dafny:
  - Specify code with pre/postconditions

# Motivation

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention
- Dafny:
  - Specify code with pre/postconditions
  - Help the system by providing ghost verification code

# Motivation

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention
- Dafny:
  - Specify code with pre/postconditions
  - Help the system by providing ghost verification code
- Dafny under the hood:

# Motivation

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention
- Dafny:
  - Specify code with pre/postconditions
  - Help the system by providing ghost verification code
- Dafny under the hood:
  - Compiled to Boogie, a verification IR

# Motivation

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention
- Dafny:
  - Specify code with pre/postconditions
  - Help the system by providing ghost verification code
- Dafny under the hood:
  - Compiled to Boogie, a verification IR
  - Verification conditions discharged by the Z3 theorem prover

# Motivation

- Light-weight program verification systems:
  - Allow specifying and verifying code
  - Reduce the required human intervention
- Dafny:
  - Specify code with pre/postconditions
  - Help the system by providing ghost verification code
- Dafny under the hood:
  - Compiled to Boogie, a verification IR
  - Verification conditions discharged by the Z3 theorem prover
  - Compiled also to other programming languages to be executed

# The Elixir programming language

# The Elixir programming language

- A functional programming language that runs on the Erlang Virtual Machine



# The Elixir programming language

- A functional programming language that runs on the Erlang Virtual Machine
- Dynamically typed

# The Elixir programming language

- A functional programming language that runs on the Erlang Virtual Machine
- Dynamically typed
- Suitable for developing DSLs through macros

# The Elixir programming language

- A functional programming language that runs on the Erlang Virtual Machine
- Dynamically typed
- Suitable for developing DSLs through macros
- Main current verification approaches:

# The Elixir programming language

- A functional programming language that runs on the Erlang Virtual Machine
- Dynamically typed
- Suitable for developing DSLs through macros
- Main current verification approaches:
  - Dialyzer (static)

# The Elixir programming language

- A functional programming language that runs on the Erlang Virtual Machine
- Dynamically typed
- Suitable for developing DSLs through macros
- Main current verification approaches:
  - Dialyzer (static)
  - Property-based testing (dynamic)

# The Elixir programming language


- A functional programming language that runs on the Erlang Virtual Machine
- Dynamically typed
- Suitable for developing DSLs through macros
- Main current verification approaches:
  - Dialyzer (static)
  - Property-based testing (dynamic)
  - Both of them show the presence of errors rather than their absence

## Our aim

Provide a system similar to that of Dafny but specialized for Elixir and implemented in Elixir itself

# Our aim

Provide a system similar to that of Dafny but specialized for Elixir and implemented in Elixir itself




<https://github.com/adrianen-ucm/verixir-project>



# Our aim

Provide a system similar to that of Dafny but specialized for Elixir and implemented in Elixir itself



<https://github.com/adrianen-ucm/verixir-project>

Scope: only a subset of sequential Elixir for the moment, and partial verification (i.e. not verifying termination)

# A valid Elixir program

```
result =  
  if selector === 1 do  
    1  
  else  
    false  
  end
```

```
result =  
  if selector === 1 do  
    result + 1  
  else  
    not result  
  end
```



1. SMT solver integration in Elixir

1. SMT solver integration in Elixir
2. L0, a low level language close to the SMT solver

1. SMT solver integration in Elixir
2. L0, a low level language close to the SMT solver
3. L1, a verification IR for dynamically typed Elixir expressions

1. SMT solver integration in Elixir
2. L0, a low level language close to the SMT solver
3. L1, a verification IR for dynamically typed Elixir expressions
4. L2, a high level language that models Elixir + verification code

# SMT Solver Integration in Elixir

---



We have developed an SMT-LIB (an SMT standard) binding for Elixir with the following features:

We have developed an SMT-LIB (an SMT standard) binding for Elixir with the following features:

- An SMT-LIB (subset) DSL

We have developed an SMT-LIB (an SMT standard) binding for Elixir with the following features:

- An SMT-LIB (subset) DSL
- Different SMT solvers that implement SMT-LIB can be easily integrated

We have developed an SMT-LIB (an SMT standard) binding for Elixir with the following features:

- An SMT-LIB (subset) DSL
- Different SMT solvers that implement SMT-LIB can be easily integrated
- Out-of-the-box support for Z3

## Elixir SMT-LIB binding example

```
import SmtLib

with_local_conn do
  declare_const x: Int,
               y: Int

  assert !(
    (:x + 3 <= :y + 3) ~> (:x <= :y)
  )

  check_sat
end
```

# The L0 language

# The L0 language

- The lowest level language of our verification stack

# The L0 language

- The lowest level language of our verification stack
- Close to the SMT solver



# The L0 language

- The lowest level language of our verification stack
- Close to the SMT solver
- Restricted SMT-LIB + control flow + failure

$$\text{Exp}^0 \ni \epsilon ::= \begin{array}{l} \text{skip} \\ | \\ \text{fail} \\ | \\ \epsilon_1; \epsilon_2 \\ | \\ \text{local } \epsilon \\ | \\ \text{add } \varphi \\ | \\ \text{declare } x \\ | \\ \text{when-unsat } \epsilon_1 \text{ do } \epsilon_2 \text{ else } \epsilon_3 \end{array}$$

$$\begin{array}{lcl} \mathbf{Exp}^0 \ni \epsilon & ::= & \mathbf{skip} \\ & | & \mathbf{fail} \\ & | & \epsilon_1; \epsilon_2 \\ & | & \mathbf{local} \ \epsilon \\ & | & \mathbf{add} \ \varphi \\ & | & \mathbf{declare} \ x \\ & | & \mathbf{when-unsat} \ \epsilon_1 \ \mathbf{do} \ \epsilon_2 \ \mathbf{else} \ \epsilon_3 \end{array}$$

where  $x \in V$  is a variable name and  $\varphi \in \mathbb{F}$  is a formula with many-sorted terms  $t \in \mathbb{T}$

Notation:

Notation:

- $X \subseteq V$  set of variable names

Notation:

- $X \subseteq V$  set of variable names
- $\Phi \subseteq \mathbb{F}$  set of formulas

Notation:

- $X \subseteq V$  set of variable names
- $\Phi \subseteq \mathbb{F}$  set of formulas
- $\mathbb{F}(X)$  subset of  $\mathbb{F}$  with free variables in  $X$

Notation:

- $X \subseteq V$  set of variable names
- $\Phi \subseteq \mathbb{F}$  set of formulas
- $\mathbb{F}(X)$  subset of  $\mathbb{F}$  with free variables in  $X$
- $(X, \Phi)$  SMT solver state



Notation:

- $X \subseteq V$  set of variable names
- $\Phi \subseteq \mathbb{F}$  set of formulas
- $\mathbb{F}(X)$  subset of  $\mathbb{F}$  with free variables in  $X$
- $(X, \Phi)$  SMT solver state
- $\langle \epsilon, X, \Phi \rangle \Downarrow (X', \Phi')$  judgement

$$\frac{}{\langle \text{skip}, X, \Phi \rangle \Downarrow (X, \Phi)}$$

$$\frac{}{\langle \mathbf{skip}, X, \Phi \rangle \Downarrow (X, \Phi)}$$

$$\frac{\varphi \in \mathbb{F}(X)}{\langle \mathbf{add} \ \varphi, X, \Phi \rangle \Downarrow (X, \Phi \cup \{\varphi\})}$$

# L0 big-step operational semantics

$$\frac{}{\langle \text{skip}, X, \Phi \rangle \Downarrow (X, \Phi)}$$

$$\frac{\varphi \in \mathbb{F}(X)}{\langle \text{add } \varphi, X, \Phi \rangle \Downarrow (X, \Phi \cup \{\varphi\})}$$

$$\frac{x \notin X}{\langle \text{declare } x, X, \Phi \rangle \Downarrow (X \cup \{x\}, \Phi)}$$

# L0 big-step operational semantics

$$\frac{}{\langle \text{skip}, X, \Phi \rangle \Downarrow (X, \Phi)}$$

$$\frac{\varphi \in \mathbb{F}(X)}{\langle \text{add } \varphi, X, \Phi \rangle \Downarrow (X, \Phi \cup \{\varphi\})}$$

$$\frac{x \notin X}{\langle \text{declare } x, X, \Phi \rangle \Downarrow (X \cup \{x\}, \Phi)}$$

$$\frac{\langle \epsilon_1, X, \Phi \rangle \Downarrow (X', \Phi') \quad \langle \epsilon_2, X', \Phi' \rangle \Downarrow (X'', \Phi'')}{\langle \epsilon_1; \epsilon_2, X, \Phi \rangle \Downarrow (X'', \Phi')}$$

$$\frac{\langle \epsilon, X, \Phi \rangle \Downarrow (X', \Phi')}{\langle \mathbf{local} \ \epsilon, X, \Phi \rangle \Downarrow (X, \Phi)}$$

$$\frac{\langle \epsilon, X, \Phi \rangle \Downarrow (X', \Phi')}{\langle \mathbf{local} \ \epsilon, X, \Phi \rangle \Downarrow (X, \Phi)}$$

$$\frac{\langle \epsilon_1, X, \Phi \rangle \Downarrow (X', \Phi') \quad \text{unsat}(\Phi') \quad \langle \epsilon_2, X, \Phi \rangle \Downarrow (X'', \Phi'')}{\langle \mathbf{when-unsat} \ \epsilon_1 \ \mathbf{do} \ \epsilon_2 \ \mathbf{else} \ \epsilon_3, X, \Phi \rangle \Downarrow (X'', \Phi')}$$

## L0 big-step operational semantics

$$\frac{\langle \epsilon, X, \Phi \rangle \Downarrow (X', \Phi')}{\langle \mathbf{local} \ \epsilon, X, \Phi \rangle \Downarrow (X, \Phi)}$$

$$\frac{\langle \epsilon_1, X, \Phi \rangle \Downarrow (X', \Phi') \quad \textit{unsat}(\Phi') \quad \langle \epsilon_2, X, \Phi \rangle \Downarrow (X'', \Phi'')}{\langle \mathbf{when-unsat} \ \epsilon_1 \ \mathbf{do} \ \epsilon_2 \ \mathbf{else} \ \epsilon_3, X, \Phi \rangle \Downarrow (X'', \Phi')}$$

$$\frac{\langle \epsilon_1, X, \Phi \rangle \Downarrow (X', \Phi') \quad \neg \textit{unsat}(\Phi') \quad \langle \epsilon_3, X, \Phi \rangle \Downarrow (X'', \Phi'')}{\langle \mathbf{when-unsat} \ \epsilon_1 \ \mathbf{do} \ \epsilon_2 \ \mathbf{else} \ \epsilon_3, X, \Phi \rangle \Downarrow (X'', \Phi')}$$



## L0 Elixir implementation

A simple implementation in Elixir is straightforward by using our SMT-LIB binding

## L0 Elixir implementation

A simple implementation in Elixir is straightforward by using our SMT-LIB binding

```
defmacro eval(conn, {:local, _, [e]}) do
  quote do
    conn = unquote(conn)
    :ok = push conn
    eval conn, unquote(e)
    :ok = pop conn
  end
end
```

## L0 Elixir example

```
eval conn do
  declare_const :x

  when_unsat add :x != :x do
    skip # Does not reach fail
  else
    fail
  end
end
```

## L0 Elixir example

```
eval conn do
  declare_const :x

  when_unsat add :x == :x do
    skip
  else
    fail # Reaches fail
  end
end
```

# **Verification Intermediate Representation**

---



- Verification IR

- Verification IR
- It models Elixir expressions dynamically typed



- Verification IR
- It models Elixir expressions dynamically typed
- Statements for writing verification code

$$\begin{array}{lcl} \mathbf{Exp}^1 \ni e & ::= & c \\ & | & x \\ & | & e_1 \mathbf{and} e_2 \\ & | & e_1 \mathbf{or} e_2 \\ & | & [] \\ & | & [e_1 \mid e_2] \\ & | & \{e_1, \dots, e_n\} \\ & | & f(e_1, \dots, e_n) \end{array}$$

$$\begin{array}{lcl} \mathbf{Exp}^1 \ni e & ::= & c \\ & | & x \\ & | & e_1 \mathbf{and} e_2 \\ & | & e_1 \mathbf{or} e_2 \\ & | & [] \\ & | & [e_1 \mid e_2] \\ & | & \{e_1, \dots, e_n\} \\ & | & f(e_1, \dots, e_n) \end{array}$$

where  $c$  is a constant literal of a simple type, currently integer or boolean, and  $f \in \Sigma^1$  a function name

**Stm**  $\ni S$  ::= **skip**  
                  | **block**  $S$   
                  | **havoc**  $x$   
                  |  $S_1; S_2$   
                  | **assume**  $e$   
                  | **assert**  $e$   
                  | **unfold**  $f(e_1, \dots, e_n)$

## Built-in SMT-LIB declarations

Foundation to represent L1 expressions in the underlying many-sorted logic (all of them have sort *Term* and can be associated to a *Type*):

## Built-in SMT-LIB declarations

Foundation to represent L1 expressions in the underlying many-sorted logic (all of them have sort *Term* and can be associated to a *Type*):

```
(declare-sort Term 0)
(declare-sort Type 0)
...
(declare-const int Type)
(declare-const bool Type)
(assert (distinct int bool))
...
(declare-fun type (Term) Type)
(define-fun is_integer ((x Term)) Bool
  (= (type x) int)
)
...
```

## Built-in L1 specifications

Built-in **sets** of pair/postconditions for functions to model their behavior in Elixir

## Built-in L1 specifications

Built-in **sets** of pair/postconditions for functions to model their behavior in Elixir

$$\{is\_integer(x) \wedge is\_integer(y)\}$$
$$x + y$$
$$\{$$
$$is\_integer(\hat{+}(x, y)) \wedge$$
$$integer\_value(\hat{+}(x, y)) = integer\_value(x) + integer\_value(y)$$
$$\}$$



## Built-in L1 specifications

Built-in **sets** of pair/postconditions for functions to model their behavior in Elixir

$$\{is\_integer(x) \wedge is\_integer(y)\}$$
$$x + y$$
$$\{$$
$$is\_integer(\hat{+}(x, y)) \wedge$$
$$integer\_value(\hat{+}(x, y)) = integer\_value(x) + integer\_value(y)$$
$$\}$$

There could be more for other types (e.g. float)

## Translation from L1 into L0

$$\begin{aligned} trExp \llbracket - \rrbracket &: \mathbf{Exp}^0 \times \mathbf{Exp}^1 \rightarrow \mathbf{Exp}^0 \times \mathbb{T} \\ trStm \llbracket - \rrbracket &: \mathbf{Stm} \rightarrow \mathbf{Exp}^0 \end{aligned}$$

$$\begin{aligned} trExp \llbracket \_ \rrbracket &: \mathbf{Exp}^0 \times \mathbf{Exp}^1 \rightarrow \mathbf{Exp}^0 \times \mathbb{T} \\ trStm \llbracket \_ \rrbracket &: \mathbf{Stm} \rightarrow \mathbf{Exp}^0 \end{aligned}$$

$trExp \gamma \llbracket e \rrbracket$  returns a tuple  $(\epsilon, t)$  where

$$\begin{aligned} trExp \llbracket \_ \rrbracket &: \mathbf{Exp}^0 \times \mathbf{Exp}^1 \rightarrow \mathbf{Exp}^0 \times \mathbb{T} \\ trStm \llbracket \_ \rrbracket &: \mathbf{Stm} \rightarrow \mathbf{Exp}^0 \end{aligned}$$

$trExp \gamma \llbracket e \rrbracket$  returns a tuple  $(\epsilon, t)$  where

- $\epsilon$  is an L0 expression that models the semantics of  $e$

$$\begin{aligned} trExp \llbracket \_ \rrbracket &: \mathbf{Exp}^0 \times \mathbf{Exp}^1 \rightarrow \mathbf{Exp}^0 \times \mathbb{T} \\ trStm \llbracket \_ \rrbracket &: \mathbf{Stm} \rightarrow \mathbf{Exp}^0 \end{aligned}$$

$trExp \gamma \llbracket e \rrbracket$  returns a tuple  $(\epsilon, t)$  where

- $\epsilon$  is an L0 expression that models the semantics of  $e$
- $t$  is a term in the underlying logic to refer to the result of  $e$

$$\begin{aligned} trExp \llbracket \_ \rrbracket &: \mathbf{Exp}^0 \times \mathbf{Exp}^1 \rightarrow \mathbf{Exp}^0 \times \mathbb{T} \\ trStm \llbracket \_ \rrbracket &: \mathbf{Stm} \rightarrow \mathbf{Exp}^0 \end{aligned}$$

$trExp \ \gamma \llbracket e \rrbracket$  returns a tuple  $(\epsilon, t)$  where

- $\epsilon$  is an L0 expression that models the semantics of  $e$
- $t$  is a term in the underlying logic to refer to the result of  $e$
- $\gamma$  models known facts by the time  $e$  is evaluated

## Translation of L1 lists

$$trExp \text{ - } \llbracket [] \rrbracket \equiv (\mathbf{skip}, nil)$$

$$trExp \gamma \llbracket [e_1 \mid e_2] \rrbracket \equiv (\epsilon_1; \epsilon_2; \epsilon, t)$$

$$\mathbf{where} \ (\epsilon_1, t_1) = trExp \gamma \llbracket e_1 \rrbracket$$

$$(\epsilon_2, t_2) = trExp \gamma \llbracket e_2 \rrbracket$$

$$t = cons(t_1, t_2)$$

$$\epsilon = \left[ \begin{array}{l} \mathbf{add} \ is\text{-}nonempty\text{-}list(t); \\ \mathbf{add} \ hd(t) = t_1; \\ \mathbf{add} \ tl(t) = t_2 \end{array} \right]$$

## Translation of L1 lists example

$trExp \ \gamma \ \llbracket [2, x] \rrbracket \equiv (\epsilon, cons(2, cons(\hat{x}, nil)))$

where  $\epsilon =$

**add** *is-integer*(*integer-lit*(2));  
**add** *integer-value*(*integer-lit*(2)) = 2;  
**add** *is-nonempty-list*(*cons*( $\hat{x}$ , *nil*));  
**add** *hd*(*cons*( $\hat{x}$ , *nil*)) =  $\hat{x}$ ;  
**add** *tl*(*cons*( $\hat{x}$ , *nil*)) = *nil*;  
**add** *is-nonempty-list*(*cons*(2, *cons*( $\hat{x}$ , *nil*)));  
**add** *hd*(*cons*(2, *cons*( $\hat{x}$ , *nil*))) = 2;  
**add** *tl*(*cons*(2, *cons*( $\hat{x}$ , *nil*))) = *cons*( $\hat{x}$ , *nil*);



# L1 Elixir implementation

Our implementation is quite direct from the formalization

# L1 Elixir implementation

Our implementation is quite direct from the formalization

```
def tr_exp(_, [{:|, _, [h, t]]]) do
  {h, h_sem} = tr_exp(_, h)
  {y, t_sem} = tr_exp(_, t)
  t =
    quote(do: :cons.(unquote(h), unquote(t)))

  { t, quote do
    unquote(h_sem)
    unquote(t_sem)
    add :is_nonempty_list.(unquote(t))
    add :hd.(unquote(t)) == unquote(h)
    add :tl.(unquote(t)) == unquote(t)
  end }
end
```

# L1 Elixir example

```
import Boogiex

with_local_env do
  assert (false or 2) === 2
  assert elem({1, 2, 3}, 0) === 1
  assert true or true + true

  havoc x
  assert x === x
  assert not (x !== x)
end
```

# Elixir Code Verification

---



- The highest level language of our verification stack

- The highest level language of our verification stack
- Elixir (subset) + ghost verification code

```
Exp2  $\ni$  E ::= e
      | P = E
      | empty
      | E1; E2
      | case E do
          P1 when f1 → E1
          ⋮
          Pn when fn → En
      | end
      | ghost do S end
```



$$\begin{array}{lcl} \mathbf{Exp}^2 \ni E & ::= & e \\ & | & P = E \\ & | & \mathbf{empty} \\ & | & E_1; E_2 \\ & | & \mathbf{case } E \mathbf{ do} \\ & & \quad P_1 \mathbf{ when } f_1 \rightarrow E_1 \\ & & \quad \vdots \\ & & \quad P_n \mathbf{ when } f_n \rightarrow E_n \\ & & \mathbf{end} \\ & | & \mathbf{ghost do } S \mathbf{ end} \end{array}$$

where  $P, P_1, \dots, P_n$  are patterns:

$$\mathbf{Pat} \ni P ::= c \mid x \mid [] \mid [P_1 \mid P_2] \mid \{P_1, \dots, P_n\}$$

$$\begin{aligned} trEXP \llbracket - \rrbracket &: \mathbf{Exp}^2 \rightarrow [\mathbf{Stm} \times \mathbf{Exp}^1] \\ trMatch \llbracket - \rrbracket \llbracket - \rrbracket &: \mathbf{Exp}^1 \times \mathbf{Pat} \rightarrow \mathbf{Exp}^1 \end{aligned}$$

$$trEXP \llbracket - \rrbracket : \mathbf{Exp}^2 \rightarrow [\mathbf{Stm} \times \mathbf{Exp}^1]$$

$$trMatch \llbracket - \rrbracket \llbracket - \rrbracket : \mathbf{Exp}^1 \times \mathbf{Pat} \rightarrow \mathbf{Exp}^1$$

$trEXP \llbracket E \rrbracket$  generates a sequence of pairs  $(S, e)$  where

$$\begin{aligned} trEXP \llbracket - \rrbracket &: \mathbf{Exp}^2 \rightarrow [\mathbf{Stm} \times \mathbf{Exp}^1] \\ trMatch \llbracket - \rrbracket \llbracket - \rrbracket &: \mathbf{Exp}^1 \times \mathbf{Pat} \rightarrow \mathbf{Exp}^1 \end{aligned}$$

$trEXP \llbracket E \rrbracket$  generates a sequence of pairs  $(S, e)$  where

- $S$  is an L1 statement that models the semantics of  $E$

$$\begin{aligned} trEXP \llbracket - \rrbracket &: \mathbf{Exp}^2 \rightarrow [\mathbf{Stm} \times \mathbf{Exp}^1] \\ trMatch \llbracket - \rrbracket \llbracket - \rrbracket &: \mathbf{Exp}^1 \times \mathbf{Pat} \rightarrow \mathbf{Exp}^1 \end{aligned}$$

$trEXP \llbracket E \rrbracket$  generates a sequence of pairs  $(S, e)$  where

- $S$  is an L1 statement that models the semantics of  $E$
- $e$  is an L1 expression that represents the result to which  $E$  is evaluated

$$\begin{aligned} trEXP \llbracket - \rrbracket &: \mathbf{Exp}^2 \rightarrow [\mathbf{Stm} \times \mathbf{Exp}^1] \\ trMatch \llbracket - \rrbracket \llbracket - \rrbracket &: \mathbf{Exp}^1 \times \mathbf{Pat} \rightarrow \mathbf{Exp}^1 \end{aligned}$$

$trEXP \llbracket E \rrbracket$  generates a sequence of pairs  $(S, e)$  where

- $S$  is an L1 statement that models the semantics of  $E$
- $e$  is an L1 expression that represents the result to which  $E$  is evaluated
- Each pair corresponds to an execution path

## Translation of L2 lists pattern matching

$trMatch \llbracket e \rrbracket \llbracket P \rrbracket$  returns an L1 expression that is a *boolean* term and is evaluated to *true* if and only if  $e$  matches  $P$

## Translation of L2 lists pattern matching

$trMatch \llbracket e \rrbracket \llbracket P \rrbracket$  returns an L1 expression that is a *boolean* term and is evaluated to *true* if and only if  $e$  matches  $P$

$$\begin{aligned} trMatch \llbracket e \rrbracket \llbracket [P_1 \mid P_2] \rrbracket = \\ is-nelist(e) \text{ and} \\ trMatch \llbracket hd(e) \rrbracket \llbracket P_1 \rrbracket \text{ and} \\ trMatch \llbracket tl(e) \rrbracket \llbracket P_2 \rrbracket \end{aligned}$$



## Translation of L2 pattern matching expressions

$trEXP \llbracket P = E \rrbracket = [(S_1; S'_1, e_1), \dots, (S_n; S'_n, e_n)]$

**where**  $[(S_1, e_1), \dots, (S_n, e_n)] = trEXP \llbracket E \rrbracket$

$\{y_1, \dots, y_m\} = vars(P)$

$\forall i \in \{1..n\} : S'_i = \left( \begin{array}{l} \mathbf{assert} \ trMatch \llbracket e_i \rrbracket \llbracket P \rrbracket; \\ \mathbf{havoc} \ y_1; \\ \vdots \\ \mathbf{havoc} \ y_m; \\ \mathbf{assume} \ e_i == P \end{array} \right)$

## Verifying user-defined functions

A single clause of a function with arity  $n$ :

$$def \equiv (\{p\} \quad (P_1, \dots, P_n) \ B \quad \{q\})$$

## Verifying user-defined functions

A single clause of a function with arity  $n$ :

$$def \equiv (\{p\} \quad (P_1, \dots, P_n) \ B \quad \{q\})$$

where  $p \in \mathbf{Exp}^1$  and  $q \in \mathbf{Exp}^1$  denote a specified precondition and a postcondition,  $P_1, \dots, P_n$  are the parameter patterns and  $B \in \mathbf{Exp}^2$  is its defined body

## Verifying user-defined functions

A single clause of a function with arity  $n$ :

$$def \equiv (\{p\} \quad (P_1, \dots, P_n) \ B \quad \{q\})$$

where  $p \in \mathbf{Exp}^1$  and  $q \in \mathbf{Exp}^1$  denote a specified precondition and a postcondition,  $P_1, \dots, P_n$  are the parameter patterns and  $B \in \mathbf{Exp}^2$  is its defined body

Clauses of a function  $f$  with arity  $n$ :

$$Defs(f/n) = (def_1, \dots, def_k)$$

## Verifying user-defined functions

## Verifying user-defined functions

1. Transform the function definition clauses into an L2 case expression with the parameter variables free and a trivial branch

## Verifying user-defined functions

1. Transform the function definition clauses into an L2 case expression with the parameter variables free and a trivial branch
2. Apply Static Single-Assignment to allow rebinding variables

## Verifying user-defined functions

1. Transform the function definition clauses into an L2 case expression with the parameter variables free and a trivial branch
2. Apply Static Single-Assignment to allow rebinding variables
3. Translate it into the corresponding execution paths in our IR



## Verifying user-defined functions

1. Transform the function definition clauses into an L2 case expression with the parameter variables free and a trivial branch
2. Apply Static Single-Assignment to allow rebinding variables
3. Translate it into the corresponding execution paths in our IR
4. Translate each path into an L0 statement

## Verifying user-defined functions

1. Transform the function definition clauses into an L2 case expression with the parameter variables free and a trivial branch
2. Apply Static Single-Assignment to allow rebinding variables
3. Translate it into the corresponding execution paths in our IR
4. Translate each path into an L0 statement
5. Verify them independently of each other

## Verifying user-defined functions

1. Transform the function definition clauses into an L2 case expression with the parameter variables free and a trivial branch
2. Apply Static Single-Assignment to allow rebinding variables
3. Translate it into the corresponding execution paths in our IR
4. Translate each path into an L0 statement
5. Verify them independently of each other

**Note:** our formalization does not address currently the verification of user-defined function invocations (i.e. their specifications and body unfolding), but our implementation does it by automatically generating ghost code

## L2 Elixir implementation

Again, our implementation is quite direct from the formalization

## L2 Elixir implementation

Again, our implementation is quite direct from the formalization

```
def tr_match({:|, _, [p1, p2]}, e) do
  tr_1 =
    tr_match(p1, quote(do: hd(unquote(e))))
  tr_2 =
    tr_match(p2, quote(do: tl(unquote(e))))

  quote(do:
    is_list(unquote(e)) and
    unquote(e) != [] and
    unquote(tr_1) and unquote(tr_2)
  )
end
```

Live demo

## Conclusions

---

# Conclusions



# Conclusions

- We have developed a framework for Elixir code verification across several areas (i.e. SMT solver integration, verification IR and code verification)

# Conclusions

- We have developed a framework for Elixir code verification across several areas (i.e. SMT solver integration, verification IR and code verification)
- Future work may address concurrent code and total verification

# Conclusions

- We have developed a framework for Elixir code verification across several areas (i.e. SMT solver integration, verification IR and code verification)
- Future work may address concurrent code and total verification
- Also, we have left several improvements on the way:

# Conclusions

- We have developed a framework for Elixir code verification across several areas (i.e. SMT solver integration, verification IR and code verification)
- Future work may address concurrent code and total verification
- Also, we have left several improvements on the way:
  - More of the SMT-LIB standard and SMT solvers support

# Conclusions

- We have developed a framework for Elixir code verification across several areas (i.e. SMT solver integration, verification IR and code verification)
- Future work may address concurrent code and total verification
- Also, we have left several improvements on the way:
  - More of the SMT-LIB standard and SMT solvers support
  - Extend our IR to model more Elixir value types and built-in functions

# Conclusions

- We have developed a framework for Elixir code verification across several areas (i.e. SMT solver integration, verification IR and code verification)
- Future work may address concurrent code and total verification
- Also, we have left several improvements on the way:
  - More of the SMT-LIB standard and SMT solvers support
  - Extend our IR to model more Elixir value types and built-in functions
  - Extend the Elixir subset to verify (e.g. pin operator and higher-order)

# Conclusions

- We have developed a framework for Elixir code verification across several areas (i.e. SMT solver integration, verification IR and code verification)
- Future work may address concurrent code and total verification
- Also, we have left several improvements on the way:
  - More of the SMT-LIB standard and SMT solvers support
  - Extend our IR to model more Elixir value types and built-in functions
  - Extend the Elixir subset to verify (e.g. pin operator and higher-order)
  - The current implementation is in an early proof of concept stage

# Program Verification in Elixir

Master's Degree in Formal Methods and Computer Engineering

---

Adrián Enríquez Ballester

Supervisor: Manuel Montenegro Montes

July 5, 2022

Complutense University of Madrid

