

TEST FOR ANYLOGISTIX API

The API info is here: <https://anylogistix.help/api/python/readme.html>

PHASE 1 CONNECTION AND SIMULATION WITH THE ANYLOGISTIX API

Install the dependencies

It assumes that the openapi_client is in the local directory ./openapi-python-client-3.3.1

```
In [2]: import sys
import os
# This is my personal directory
os.chdir(r"C:\Users\Luis\Downloads\TFG\API")
#!{sys.executable} -m pip install "pydantic>=2.10,<3"
!{sys.executable} -m pip install "pydantic<2,>=1.10.5"
!{sys.executable} -m pip install -e ./openapi-python-client-3.3.1
```

```

Requirement already satisfied: pydantic<2,>=1.10.5 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (1.10.26)
Requirement already satisfied: typing-extensions>=4.2.0 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from pydantic<2,>=1.10.5) (4.15.0)
Obtaining file:///C:/Users/Luis/Downloads/TFG/API/openapi-python-client-3.3.1
  Installing build dependencies: started
  Installing build dependencies: finished with status 'done'
  Checking if build backend supports build_editable: started
  Checking if build backend supports build_editable: finished with status 'done'
  Getting requirements to build editable: started
  Getting requirements to build editable: finished with status 'done'
  Preparing editable metadata (pyproject.toml): started
  Preparing editable metadata (pyproject.toml): finished with status 'done'
Requirement already satisfied: urllib3<2.1.0,>=1.25.3 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from openapi-client==1.0.0) (2.0.7)
Requirement already satisfied: python-dateutil in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from openapi-client==1.0.0) (2.9.0.post0)
Requirement already satisfied: pydantic<2,>=1.10.5 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from openapi-client==1.0.0) (1.10.26)
Requirement already satisfied: aenum in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from openapi-client==1.0.0) (3.1.17)
Requirement already satisfied: typing-extensions>=4.2.0 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from pydantic<2,>=1.10.5->openapi-client==1.0.0) (4.15.0)
Requirement already satisfied: six>=1.5 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from python-dateutil->openapi-client==1.0.0) (1.17.0)
Building wheels for collected packages: openapi-client
  Building editable for openapi-client (pyproject.toml): started
  Building editable for openapi-client (pyproject.toml): finished with status 'done'
  Created wheel for openapi-client: filename=openapi_client-1.0.0-0.editable-py3-none-any.whl size=3042 sha256=efbb24a5f79af471ee6e8fa2359b1ee8e053bcc0788e915cb30db8484484f7f0
  Stored in directory: C:\Users\Luis\AppData\Local\Temp\pip-ephem-wheel-cache-k4yep5ps\wheels\96\67\f9\218cef519d1de93e10ecbd2f12fb5f4d1d0e81b1c1d5296ba2
Successfully built openapi-client
Installing collected packages: openapi-client
  Attempting uninstall: openapi-client
    Found existing installation: openapi-client 1.0.0
    Uninstalling openapi-client-1.0.0:
      Successfully uninstalled openapi-client-1.0.0
Successfully installed openapi-client-1.0.0

```

```

In [3]: import openapi_client
        from openapi_client.rest import ApiException
        from pprint import pprint
        import urllib3

```

```

In [4]: # SERVER_IP="192.168.64.159"
        # SERVER_IP="192.168.67.110"
        SERVER_IP="alxserver.aut.uah.es"
        SERVER_URL=f"https://{SERVER_IP}:443/api/v1"

        # This is my personal APY KEY
        API_KEY="c184f1ab-9f13-484c-a1c1-3d543502da6e"

```

```
SERVER_URL
```

```
Out[4]: 'https://alxserver.aut.uah.es:443/api/v1'
```

PART I: CHECK CONNECTIVIY AND OPERATIONAL STATUS

```
In [5]: # Defining the host is optional and defaults to https://server_address:port/api/
# See configuration.py for a list of all supported configuration parameters.
configuration = openapi_client.Configuration(
    host = SERVER_URL
)
# The client must configure the authentication and authorization parameters
# in accordance with the API server security policy.
# Examples for each auth method are provided below, use the example that
# satisfies your auth use case.
# Configure API key authorization: ApiKey
configuration.api_key['ApiKey'] = API_KEY

# ALVARO: SUPER IMPORTANTE PARA PODER TRABAJAR CON CERTIFICADOS AUTO-FIRMADOS
configuration.verify_ssl = False
urllib3.disable_warnings(urllib3.exceptions.InsecureRequestWarning)
with openapi_client.ApiClient(configuration) as api_client:
    # Create an instance of the API class
    api_instance = openapi_client.OpenApiApi(api_client)
```

Obtain current user data

```
In [6]: try:
# Gets current user data.
api_response = api_instance.get_current_user()
print("The response of OpenApiApi->get_current_user:\n")
pprint(api_response)
except Exception as e:
print("Exception when calling OpenApiApi->get_current_user: %s\n" % e)
```

The response of OpenApiApi->get_current_user:

```
ApiUserData(email='adrian.encabo@edu.uah.es', first_name='adrian.encabo@edu.uah.e
s', id=403, last_name='', username='adrian.encabo@edu.uah.es')
```

PART II: OBTAIN PROJECTS, SCENARIOS, EXECUTIONS

Obtain the list of currently available projects

```
In [7]: try:
# Returns a List of projects that the user has access to.
api_response = api_instance.get_projects()
print("The response of OpenApiApi->get_projects:\n")
pprint(api_response)
except Exception as e:
print("Exception when calling OpenApiApi->get_projects: %s\n" % e)
```

The response of OpenApiApi->get_projects:

```
[ApiProjectResponse(accessible=True, creation_date='2026-03-10T16:19:55.145394Z',  
current_user_id=403, deleted=False, id=79020, name='TFG_ADRIAN_ENCABO', owner_use  
r_id=3)]
```

Open a project and get the list of scenarios available

```
In [8]: # My personal Project defined  
MY_PROJECT_NAME="TFG_ADRIAN_ENCABO"  
the_project_id=0  
try:  
    full_match = True # bool | Whether to match project name by complete match.  
    # Opens project with name projectName.  
    the_project = api_instance.find_and_open_project_by_name(full_match, MY_PROJ  
    print("The response of OpenApiApi->find_and_open_project_by_name:\n")  
    pprint(the_project)  
except Exception as e:  
    print("Exception when calling OpenApiApi->find_and_open_project_by_name: %s\  
try:  
    # Returns a List of scenarios for the project with identifier project_id.  
    the_scenarios = api_instance.get_scenarios(the_project.id)  
    print("The response of OpenApiApi->get_scenarios:\n")  
    pprint(the_scenarios)  
except Exception as e:  
    print("Exception when calling OpenApiApi->get_scenarios: %s\n" % e)
```

The response of OpenApiApi->find_and_open_project_by_name:

```
ApiProjectResponse(accessible=True, creation_date='2026-03-10T16:19:55.145394Z',
current_user_id=403, deleted=False, id=79020, name='TFG_ADRIAN_ENCABO', owner_user_id=3)
```

The response of OpenApiApi->get_scenarios:

```
[ApiScenarioData(id=82840, name='Budget Comparison (Estimated Demand)', type='SIM'),
 ApiScenarioData(id=87083, name='P3.3. GFA 1. Results 2_Different Locations', type='SIM'),
 ApiScenarioData(id=84191, name='Budget Comparison (Estimated Demand) 2', type='SIM'),
 ApiScenarioData(id=85538, name='Budget Comparison (Estimated Demand) 2', type='SIM'),
 ApiScenarioData(id=86671, name='P4.2.2 NO Distribution Network inside 4 Walls Models Capacity Restriction', type='NO'),
 ApiScenarioData(id=88185, name='P4.2.2 NO Distribution Network inside 4 Walls Models Capacity Restriction 2', type='NO'),
 ApiScenarioData(id=89212, name='P4.2.2 NO Distribution Network inside 4 Walls Models Capacity Restriction sim', type='SIM'),
 ApiScenarioData(id=92735, name='P4.2.6 SIM Distribution Network-4 Walls_New Inventory+New Transportation', type='SIM'),
 ApiScenarioData(id=95044, name='null', type='SIM'),
 ApiScenarioData(id=176431, name='Cold Chain (Risk Analysis)', type='SIM'),
 ApiScenarioData(id=177767, name='US Distribution Network', type='NO'),
 ApiScenarioData(id=178297, name='Lumber Production', type='NO'),
 ApiScenarioData(id=179567, name='Global Network Examination', type='SIM'),
 ApiScenarioData(id=181707, name='P3.1._Green_Field_Analysis_GFA_ALX3', type='GFA'),
 ApiScenarioData(id=180669, name='asset-v1_UAH+EUGLOH+EUG2_T2_1_0080+type@asset+block@P4.4_Demand_Variation_LoadingGates_2', type='SIM'),
 ApiScenarioData(id=192031, name='null 6', type='SIM'),
 ApiScenarioData(id=200223, name='P4.2.6 SIM Distribution Network-4 Walls_New Inventory+New Transportation 2', type='SIM'),
 ApiScenarioData(id=197360, name='null 8', type='SIM'),
 ApiScenarioData(id=184791, name='null 3', type='SIM'),
 ApiScenarioData(id=187186, name='null 4', type='SIM'),
 ApiScenarioData(id=182396, name='null 2', type='SIM'),
 ApiScenarioData(id=189602, name='null 5', type='SIM'),
 ApiScenarioData(id=194446, name='null 7', type='SIM'),
 ApiScenarioData(id=213266, name='null 13', type='SIM'),
 ApiScenarioData(id=202944, name='null 9', type='SIM'),
 ApiScenarioData(id=205644, name='null 10', type='SIM'),
 ApiScenarioData(id=222111, name='null 15', type='SIM'),
 ApiScenarioData(id=208189, name='null 11', type='SIM'),
 ApiScenarioData(id=218720, name='null 14', type='SIM'),
 ApiScenarioData(id=210209, name='null 12', type='SIM')]
```

Select the scenario by name

```
In [9]: #Add the name of the scenario
MY_SCENARIO_NAME="Global Network Examination"

# 1. Select the scenario
the_scenario = next(s for s in the_scenarios if s.name == MY_SCENARIO_NAME)
pprint(the_scenario)
```

```
ApiScenarioData(id=179567, name='Global Network Examination', type='SIM')
```

Get the list of experiment runs of a scenario

```
In [10]: try:
# Returns the results of experiment runs for scenario.
the_runs = api_instance.get_experiment_runs_for_scenario(the_scenario.id)
print("The response of OpenApiApi->get_experiment_runs_for_scenario:\n")
pprint(the_runs)
except Exception as e:
print("Exception when calling OpenApiApi->get_experiment_runs_for_scenario:
```

The response of OpenApiApi->get_experiment_runs_for_scenario:

```
[ApiBasicRun(has_options=False, id=201331, name='Statistics', rc_id=201332, removing=False, scenario_id=179567, type='SIMULATION'),
 ApiBasicRun(has_options=False, id=201578, name='Statistics 2', rc_id=201579, removing=False, scenario_id=179567, type='SIMULATION'),
 ApiBasicRun(has_options=False, id=201796, name='Statistics 3', rc_id=201797, removing=False, scenario_id=179567, type='SIMULATION'),
 ApiBasicRun(has_options=False, id=217384, name='Statistics 4', rc_id=217385, removing=False, scenario_id=179567, type='SIMULATION'),
 ApiBasicRun(has_options=False, id=217581, name='Statistics 5', rc_id=217582, removing=False, scenario_id=179567, type='SIMULATION'),
 ApiBasicRun(has_options=False, id=220765, name='Statistics 6', rc_id=220766, removing=False, scenario_id=179567, type='SIMULATION'),
 ApiBasicRun(has_options=False, id=220963, name='Statistics 7', rc_id=220964, removing=False, scenario_id=179567, type='SIMULATION')]
```

PART III. EXECUTE A SIMULATION

Get the list of RunConfigurations for the experiments of a given Scenario

Each type of experiment has a RunConfiguration. For example:

```
ApiBasicRunConfiguration(animation_model_id=None,
feasible_check_status='NOT_CONDUCTED', id=2439,
is_feasible_check_data_available=False, model_time=None,
name='i18n-Experiment_Simulation_text', progress=None,
project_id=63, routes_progress=None, run_status=None,
scenario_id=1752, speed=None, status='IDLE', step='IDLE',
type='SIMULATION', validation_status='VALID')
```

Types of available experiment runs are:

- SIMULATION
- VARIATION
- COMPARISON
- SAFETY_STOCK
- RISK_ANALYSIS

```
In [11]: MY_RUN_TYPE="SIMULATION"
try:
# Returns a List of experiments available for a given scenario.
```

```

the_run_configurations= api_instance.get_experiments(the_project.id, the_sce
print("The response of OpenApiApi->get_experiments:\n")
# Exception fixed for undefined variable
pprint(the_run_configurations)
except Exception as e:
    print("Exception when calling OpenApiApi->get_experiments: %s\n" % e)

# 2. Select the adequate RunConfiguration for the scenario
the_RC = next((r for r in the_run_configurations if r.type == MY_RUN_TYPE), None)
pprint(the_RC)

```

The response of OpenApiApi->get_experiments:

```

[ApiBasicRunConfiguration(animation_model_id=None, feasible_check_status='NOT_CON
DUCTED', id=180254, is_feasible_check_data_available=False, model_time=None, name
='i18n-Experiment_Simulation_text', progress=None, project_id=79020, routes_progr
ess=None, run_status=None, scenario_id=179567, speed=None, status='IDLE', step='I
DLE', type='SIMULATION', validation_status='VALID'),
 ApiBasicRunConfiguration(animation_model_id=None, feasible_check_status='NOT_CON
DUCTED', id=180429, is_feasible_check_data_available=False, model_time=None, name
='i18n-Experiment_VariationExperiment_text', progress=None, project_id=79020, rou
tes_progress=None, run_status=None, scenario_id=179567, speed=None, status='IDL
E', step='IDLE', type='VARIATION', validation_status='NOT_CONDUCTED'),
 ApiBasicRunConfiguration(animation_model_id=None, feasible_check_status='NOT_CON
DUCTED', id=179575, is_feasible_check_data_available=False, model_time=None, name
='i18n-Experiment_ComparisonExperiment_text', progress=None, project_id=79020, ro
utes_progress=None, run_status=None, scenario_id=179567, speed=None, status='IDL
E', step='IDLE', type='COMPARISON', validation_status='NOT_CONDUCTED'),
 ApiBasicRunConfiguration(animation_model_id=None, feasible_check_status='NOT_CON
DUCTED', id=180115, is_feasible_check_data_available=False, model_time=None, name
='i18n-Experiment_SafetyStockEstimation_text', progress=None, project_id=79020, r
outes_progress=None, run_status=None, scenario_id=179567, speed=None, status='IDL
E', step='IDLE', type='SAFETY_STOCK', validation_status='NOT_CONDUCTED'),
 ApiBasicRunConfiguration(animation_model_id=None, feasible_check_status='NOT_CON
DUCTED', id=179930, is_feasible_check_data_available=False, model_time=None, name
='i18n-Experiment_RiskAnalysisExperiment_text', progress=None, project_id=79020,
routes_progress=None, run_status=None, scenario_id=179567, speed=None, status='ID
LE', step='IDLE', type='RISK_ANALYSIS', validation_status='NOT_CONDUCTED')]
ApiBasicRunConfiguration(animation_model_id=None, feasible_check_status='NOT_COND
UCTED', id=180254, is_feasible_check_data_available=False, model_time=None, name
='i18n-Experiment_Simulation_text', progress=None, project_id=79020, routes_progr
ess=None, run_status=None, scenario_id=179567, speed=None, status='IDLE', step='I
DLE', type='SIMULATION', validation_status='VALID')

```

Run a new experiment over a scenario (synch)

Runs synchronously.

```

In [12]: try:
# Starts the experiment synchronously.
the_sync_result = api_instance.run_experiment_synchronously(the_RC.id)
print("The response of OpenApiApi->run_experiment_synchronously:\n")
pprint(the_sync_result)
except Exception as e:
    print("Exception when calling OpenApiApi->run_experiment_synchronously: %s\n")

```

The response of OpenApiApi->run_experiment_synchronously:

```
ApiExperimentResult(experiment_result_id=224701, validation_errors=None, validation_status='OK', validation_warnings=None)
```

Part IIIb. Asynch execution

Run a new experiment over a scenario (asynch)

Runs asynchronously. Periodic status check.

```
In [13]: skip_scenario_warnings = True # bool / Whether to skip scenario warnings. (optional)
try:
    # Starts the experiment asynchronously.
    the_execution = api_instance.run_experiment(the_RC.id, skip_scenario_warnings)
    print("The response of OpenApiApi->run_experiment:\n")
    pprint(the_execution)
except Exception as e:
    print("Exception when calling OpenApiApi->run_experiment: %s\n" % e)

import time
while True:
    try:
        # Returns the experiment status
        the_status = api_instance.get_experiment_status(the_RC.id)
        # pprint(api_response)

        # Check if execution finished
        if the_status.finished:
            print("Execution finished.")
            break

        # Optional: stop if failed
        # fixed exception of status check
        if the_status.failed:
            print("Execution failed.")
            break

    except Exception as e:
        print("Exception when calling OpenApiApi->get_experiment_status:", e)
        print("Not finished yet. Wait 1sec and check again")
        # wait before next check
        time.sleep(1)
```

The response of OpenApiApi->run_experiment:

```
ApiRunExperiment(animation_model_id=180254, experiment_type_id='SIMULATION', is3d_animation=False)
Execution finished.
```

Get the experiments results (pages)

You can ask for limited number of results (avoid overflow)

```
In [14]: skip = 0 # int / Number of records to skip. (default to 0)
take = 1000 # int / Number of records to be retrieved. (default to 1000)
```



```
try:
    # Returns all the results of the specific experiment run.
    the_run_results = api_instance.get_experiment_run_result(the_RC.id, skip, ta
    print("The response of OpenApiApi->get_experiment_run_result:\n")
    pprint(the_run_results)
except Exception as e:
    print("Exception when calling OpenApiApi->get_experiment_run_result: %s\n" %
```

The response of OpenApiApi->get_experiment_run_result:

```
ApiExperimentResultData(pages=[ApiExperimentResultPageWrapper(charts=[ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180257, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, start_row=0, width=2), name='Available Inventory', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180257, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180258, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, start_row=1, width=2), name='Available Inventory Including Backlog', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180258, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180259, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=4, start_row=0, width=2), name='Average Daily Available Inventory', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180259, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180260, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_row=1, width=2), name='Average Daily On-hand Inventory', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180260, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180261, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_row=0, width=2), name='On-hand Inventory', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180261, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE'))], page=ApiPage(id='180256', name='Available Inventory')), ApiExperimentResultPageWrapper(charts=[ApiExperimentResultTableChartWrapper(chart=ApiChartMetadataShort(id=180263, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, start_row=0, width=2), name='Demand Placed, Fulfillment Received (Accumulative)', rc_id=180254, type='TABLE'), class_name='ApiExperimentResultTableChartWrapper', data=ApiStrictTableChartData(entity_list=[], id=180263, total_entity_count=0, total_technical_row_count=0, type='TABLE')), ApiExperimentResultTableChartWrapper(chart=ApiChartMetadataShort(id=180264, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, start_row=1, width=2), name='Demand Placed, Fulfillment Received (Accumulative, Per Object)', rc_id=180254, type='TABLE'), class_name='ApiExperimentResultTableChartWrapper', data=ApiStrictTableChartData(entity_list=[], id=180264, total_entity_count=0, total_technical_row_count=0, type='TABLE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180265, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_row=0, width=2), name='Demand Placed, Fulfillment Received (Daily)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180265, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180266, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_row=1, width=2), name='Demand Placed, Fulfillment Received (Daily, Per Object)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180266, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultTableChartWrapper(chart=ApiChartMetadataShort(id=180267, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=4, start_row=0, width=2), name='Demand Received, Fulfillment Shipped (Accumulative)', rc_id=180254, type='TABLE'), class_name='ApiExperimentResultTableChartWrapper', data=ApiStrictTableChartData(entity_list=[], id=180267, total_entity_count=0, total_technical_row_count=0, type='TABLE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180268, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=4, start_row=1, width=2), name='Demand Received, Fulfillment Shipped (Daily)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180268, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE'))], page=ApiPage(id='180257', name='Demand Received, Fulfillment Shipped'))]
```

```

ent Shipped (Daily)', rc_id=180254, type='LINE')), class_name='ApiExperimentResult
GraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180268, show_x=Tru
e, total_entity_count=0, total_technical_row_count=0, type='LINE'))], page=ApiPag
e(id='180262', name='Fulfillment')), ApiExperimentResultPageWrapper(charts=[ApiEx
perimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180270, is_group_m
ode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, start_row=0,
width=2), name='Lead Time', rc_id=180254, type='LINE')), class_name='ApiExperim
entResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180270, show_
x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExpe
rimentResultTableChartWrapper(chart=ApiChartMetadataShort(id=180271, is_group_mod
e_enabled=False, layout=ApiChartLayoutData(height=1, start_col=4, start_row=0, wi
dth=2), name='Max Lead Time', rc_id=180254, type='TABLE')), class_name='ApiExperim
entResultTableChartWrapper', data=ApiStrictTableChartData(entity_list=[], id=1802
71, total_entity_count=0, total_technical_row_count=0, type='TABLE')), ApiExperim
entResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180272, is_group_mode_e
nabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_row=0, width
=2), name='Mean Lead Time (Best-Mean-Worst)', rc_id=180254, type='BMW-LINE')), cla
ss_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_lis
t=[], id=180272, show_x=True, total_entity_count=0, total_technical_row_count=0,
type='BMW-LINE'))], page=ApiPage(id='180269', name='Lead Time')), ApiExperimentRe
sultPageWrapper(charts=[ApiExperimentResultGraphChartWrapper(chart=ApiChartMetada
taShort(id=180274, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=
1, start_col=4, start_row=0, width=2), name='Available Inventory Including Backlo
g', rc_id=180254, type='LINE')), class_name='ApiExperimentResultGraphChartWraphe
r', data=ApiGraphChartData(entity_list=[], id=180274, show_x=True, total_entity_c
ount=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChart
Wrapper(chart=ApiChartMetadataShort(id=180277, is_group_mode_enabled=False, layou
t=ApiChartLayoutData(height=1, start_col=0, start_row=0, width=2), name='Products
Produced (Units) Factory Shenzhen', rc_id=180254, type='BAR')), class_name='ApiExp
erimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=18027
7, show_x=True, total_entity_count=0, total_technical_row_count=0, type='BAR')),
ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180280, is_gr
oup_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_ro
w=0, width=2), name='Products Produced (Units) Factory Xiamen', rc_id=180254, typ
e='BAR')), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartDa
ta(entity_list=[], id=180280, show_x=True, total_entity_count=0, total_technical_
row_count=0, type='BAR'))], page=ApiPage(id='180273', name='Production')), ApiExp
erimentResultPageWrapper(charts=[ApiExperimentResultTableChartWrapper(chart=ApiCh
artMetadataShort(id=180284, is_group_mode_enabled=False, layout=ApiChartLayoutDat
a(height=1, start_col=2, start_row=0, width=2), name='Profit and Loss Statement',
rc_id=180254, type='TABLE')), class_name='ApiExperimentResultTableChartWrapper', d
ata=ApiStrictTableChartData(entity_list=[], id=180284, total_entity_count=0, tota
l_technical_row_count=0, type='TABLE')), ApiExperimentResultGraphChartWrapper(ch
art=ApiChartMetadataShort(id=180285, is_group_mode_enabled=False, layout=ApiChartL
ayoutData(height=1, start_col=4, start_row=0, width=2), name='Profit, Revenue, To
tal Cost', rc_id=180254, type='BAR')), class_name='ApiExperimentResultGraphChartWr
apper', data=ApiGraphChartData(entity_list=[], id=180285, show_x=True, total_enti
ty_count=0, total_technical_row_count=0, type='BAR')), ApiExperimentResultGraphCh
artWrapper(chart=ApiChartMetadataShort(id=180286, is_group_mode_enabled=False, la
yout=ApiChartLayoutData(height=1, start_col=0, start_row=0, width=2), name='Reven
ue, Total Cost', rc_id=180254, type='LINE')), class_name='ApiExperimentResultGraph
ChartWrapper', data=ApiGraphChartData(entity_list=[], id=180286, show_x=True, tot
al_entity_count=0, total_technical_row_count=0, type='LINE'))], page=ApiPage(id
='180283', name='Profit and Loss Statement')), ApiExperimentResultPageWrapper(ch
arts=[ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180288,
is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, sta
rt_row=1, width=2), name='ELT Service Level by Products (Per Product)', rc_id=180
254, type='LINE')), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGra
phChartData(entity_list=[], id=180288, show_x=True, total_entity_count=0, total_t
echnical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=A

```

```

piChartMetadataShort(id=180289, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_row=1, width=2), name='ELT Service Level by Products (Per Source)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180289, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180290, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=4, start_row=1, width=2), name='ELT Service Level by Revenue (Per Object)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180290, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180291, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, start_row=0, width=2), name='Service Level by Products (Per Product)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180291, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180292, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=2, start_row=0, width=2), name='Service Level by Products (Per Source)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180292, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE')), ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180293, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=4, start_row=0, width=2), name='Service Level by Revenue (Per Object)', rc_id=180254, type='LINE'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180293, show_x=True, total_entity_count=0, total_technical_row_count=0, type='LINE'))], page=ApiPage(id='180287', name='Service Level')), ApiExperimentResultPageWrapper(charts=[ApiExperimentResultGraphChartWrapper(chart=ApiChartMetadataShort(id=180295, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=3, start_row=0, width=3), name='Customer Tariffs', rc_id=180254, type='BAR'), class_name='ApiExperimentResultGraphChartWrapper', data=ApiGraphChartData(entity_list=[], id=180295, show_x=True, total_entity_count=0, total_technical_row_count=0, type='BAR')), ApiExperimentResultTableChartWrapper(chart=ApiChartMetadataShort(id=180296, is_group_mode_enabled=False, layout=ApiChartLayoutData(height=1, start_col=0, start_row=0, width=3), name='Customer Tariffs, Profit, Total Cost, Revenue', rc_id=180254, type='TABLE'), class_name='ApiExperimentResultTableChartWrapper', data=ApiStrictTableChartData(entity_list=[], id=180296, total_entity_count=0, total_technical_row_count=0, type='TABLE'))], page=ApiPage(id='180294', name='Tariffs'))))

```

```

In [15]: for p in the_run_results.pages:
          print(f"\n{p.page.name} (id:{p.page.id})")
          for c in p.charts:
              print(f"    - {c.chart.name} (type: {c.chart.type}) (id: {c.chart.id})")

```

Available Inventory (id:180256)

- Available Inventory (type: LINE) (id: 180257)
- Available Inventory Including Backlog (type: LINE) (id: 180258)
- Average Daily Available Inventory (type: LINE) (id: 180259)
- Average Daily On-hand Inventory (type: LINE) (id: 180260)
- On-hand Inventory (type: LINE) (id: 180261)

Fulfillment (id:180262)

- Demand Placed, Fulfillment Received (Accumulative) (type: TABLE) (id: 180263)
- Demand Placed, Fulfillment Received (Accumulative, Per Object) (type: TABLE) (id: 180264)
- Demand Placed, Fulfillment Received (Daily) (type: LINE) (id: 180265)
- Demand Placed, Fulfillment Received (Daily, Per Object) (type: LINE) (id: 180266)
- Demand Received, Fulfillment Shipped (Accumulative) (type: TABLE) (id: 180267)
- Demand Received, Fulfillment Shipped (Daily) (type: LINE) (id: 180268)

Lead Time (id:180269)

- Lead Time (type: LINE) (id: 180270)
- Max Lead Time (type: TABLE) (id: 180271)
- Mean Lead Time (Best-Mean-Worst) (type: BMW-LINE) (id: 180272)

Production (id:180273)

- Available Inventory Including Backlog (type: LINE) (id: 180274)
- Products Produced (Units) Factory Shenzhen (type: BAR) (id: 180277)
- Products Produced (Units) Factory Xiamen (type: BAR) (id: 180280)

Profit and Loss Statement (id:180283)

- Profit and Loss Statement (type: TABLE) (id: 180284)
- Profit, Revenue, Total Cost (type: BAR) (id: 180285)
- Revenue, Total Cost (type: LINE) (id: 180286)

Service Level (id:180287)

- ELT Service Level by Products (Per Product) (type: LINE) (id: 180288)
- ELT Service Level by Products (Per Source) (type: LINE) (id: 180289)
- ELT Service Level by Revenue (Per Object) (type: LINE) (id: 180290)
- Service Level by Products (Per Product) (type: LINE) (id: 180291)
- Service Level by Products (Per Source) (type: LINE) (id: 180292)
- Service Level by Revenue (Per Object) (type: LINE) (id: 180293)

Tariffs (id:180294)

- Customer Tariffs (type: BAR) (id: 180295)
- Customer Tariffs, Profit, Total Cost, Revenue (type: TABLE) (id: 180296)

Obtain the pages in the experiment's result dashboard

```
In [16]: try:
# Returns statistics pages for the result of experiment run.
# Exception fixed for 'id' attribute
# We use the experiment_result_id from the previously executed synchronous r
result_id = the_sync_result.experiment_result_id
dashboard_pages = api_instance.get_experiment_dashboard_pages(result_id)
print("The response of OpenApiApi->get_experiment_dashboard_pages:\n")

# CHANGED Displaying the available pages and charts with their dynamic IDs
for page in dashboard_pages:
    print(f"Dashboard Page: {page.name} (ID: {page.id})")
    for chart in page.charts:
```

```
print(f" - Chart: {chart.name} (ID: {chart.id})")

except Exception as e:
    print("Exception when calling OpenApiApi->get_experiment_dashboard_pages: %s"
```

The response of OpenApiApi->get_experiment_dashboard_pages:

Dashboard Page: Available Inventory (ID: 224703)

- Chart: Available Inventory (ID: 224704)
- Chart: Available Inventory Including Backlog (ID: 224705)
- Chart: Average Daily Available Inventory (ID: 224706)
- Chart: Average Daily On-hand Inventory (ID: 224707)
- Chart: On-hand Inventory (ID: 224708)

Dashboard Page: Fulfillment (ID: 224709)

- Chart: Demand Placed, Fulfillment Received (Accumulative) (ID: 224710)
- Chart: Demand Placed, Fulfillment Received (Accumulative, Per Object) (ID: 224711)
- Chart: Demand Placed, Fulfillment Received (Daily) (ID: 224712)
- Chart: Demand Placed, Fulfillment Received (Daily, Per Object) (ID: 224713)
- Chart: Demand Received, Fulfillment Shipped (Accumulative) (ID: 224714)
- Chart: Demand Received, Fulfillment Shipped (Daily) (ID: 224715)

Dashboard Page: Lead Time (ID: 224716)

- Chart: Lead Time (ID: 224717)
- Chart: Max Lead Time (ID: 224718)
- Chart: Mean Lead Time (Best-Mean-Worst) (ID: 224719)

Dashboard Page: Production (ID: 224720)

- Chart: Available Inventory Including Backlog (ID: 224721)
- Chart: Products Produced (Units) Factory Shenzhen (ID: 224724)
- Chart: Products Produced (Units) Factory Xiamen (ID: 224727)

Dashboard Page: Profit and Loss Statement (ID: 224730)

- Chart: Profit and Loss Statement (ID: 224731)
- Chart: Profit, Revenue, Total Cost (ID: 224732)
- Chart: Revenue, Total Cost (ID: 224733)

Dashboard Page: Service Level (ID: 224734)

- Chart: ELT Service Level by Products (Per Product) (ID: 224735)
- Chart: ELT Service Level by Products (Per Source) (ID: 224736)
- Chart: ELT Service Level by Revenue (Per Object) (ID: 224737)
- Chart: Service Level by Products (Per Product) (ID: 224738)
- Chart: Service Level by Products (Per Source) (ID: 224739)
- Chart: Service Level by Revenue (Per Object) (ID: 224740)

Dashboard Page: Tariffs (ID: 224741)

- Chart: Customer Tariffs (ID: 224742)
- Chart: Customer Tariffs, Profit, Total Cost, Revenue (ID: 224743)

Export the results as an excel matrix

```
In [17]: # Exception fixed for wrong IDs
import shutil #For manipulating excel files
try:
    # Dynamically select the first dashboard page to export to avoid hardcoded ID
    if dashboard_pages and len(dashboard_pages) > 0:
        target_page_id = dashboard_pages[0].id
        target_result_id = the_sync_result.experiment_result_id

    print(f"Exporting dashboard page ID {target_page_id} from result ID {tar

    # Returns an Excel representation of the dashboard page
    excel_export = api_instance.export_dashboard_page(target_result_id, targ
```

```

# Save the exported Excel file locally
output_filename = "Simulation_Results.xlsx"

# Check if the API returns a temporary file path
if isinstance(excel_export, str) and os.path.exists(excel_export):
    shutil.move(excel_export, output_filename)
    print(f"Excel file saved successfully to: {os.path.abspath(output_filename)}")

# Check if the API returns binary data directly
elif isinstance(excel_export, bytes):
    with open(output_filename, "wb") as file:
        file.write(excel_export)
    print(f"Excel file saved successfully to: {os.path.abspath(output_filename)}")

else:
    print(f"Unexpected data format received. Type: {type(excel_export)}")
    pprint(excel_export)

print("\nData exported successfully.")
else:
    print("No dashboard pages available to export.")

except Exception as e:
    print("Exception when calling OpenApiApi->export_dashboard_page: %s\n" % e)

```

Exporting dashboard page ID 224703 from result ID 224701...

Excel file saved successfully to: C:\Users\Luis\Downloads\TFG\API\Simulation_Results.xlsx

Data exported successfully.

Close current project

In [18]: *#Error fixed of indentation*

```

try:
    # Closes the currently open project.
    api_response = api_instance.close_project()
    print("The response of OpenApiApi->close_project:\n")
    pprint(api_response)
    print("\nProject closed successfully.")
except ApiException as e:
    print("Exception when calling OpenApiApi->close_project: %s\n" % e)

```

The response of OpenApiApi->close_project:

```

ApiProjectResponse(accessible=True, creation_date='2026-03-10T16:19:55.145394Z',
current_user_id=None, deleted=False, id=79020, name='TFG_ADRIAN_ENCABO', owner_user_id=3)

```

Project closed successfully.

=====

PHASE 2



PART I Flat AI Decision & Scenario Cloning

Install the dependencies

In [19]: `!pip install pandas openpyxl`

```
Requirement already satisfied: pandas in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (2.3.3)
Requirement already satisfied: openpyxl in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (3.1.5)
Requirement already satisfied: numpy>=1.22.4 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from pandas) (2.2.6)
Requirement already satisfied: python-dateutil>=2.8.2 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from pandas) (2.9.0.post0)
Requirement already satisfied: pytz>=2020.1 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from pandas) (2026.1.post1)
Requirement already satisfied: tzdata>=2022.7 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from pandas) (2026.1)
Requirement already satisfied: et-xmlfile in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from openpyxl) (2.0.0)
Requirement already satisfied: six>=1.5 in c:\users\luis\downloads\tfg\anaconda\envs\tfg_anylogistix\lib\site-packages (from python-dateutil>=2.8.2->pandas) (1.17.0)
```

1. Define the Flat AI logic (3 predefined decisions)

```
In [20]: decision_options = [
    "DECISION 0: Increase Demand by 20% (Aggressive Growth)",
    "DECISION 1: Decrease Transport Costs by 15% (Cost Optimization)",
    "DECISION 2: Increase Safety Stock by 10% (Conservative Risk Management)"
]

print("--- FLAT AI: EVALUATING PREDEFINED DECISIONS ---")
for i, decision in enumerate(decision_options):
    print(f"[{i}] {decision}")

# For this 'flat AI' phase, we will simulate the AI choosing a decision automatically
# Let us assume the AI evaluates the current context and selects Decision 0.
selected_decision_index = 0
selected_decision_text = decision_options[selected_decision_index]

print(f"\nFLAT AI SELECTED: {selected_decision_text}")
```

```
--- FLAT AI: EVALUATING PREDEFINED DECISIONS ---
[0] DECISION 0: Increase Demand by 20% (Aggressive Growth)
[1] DECISION 1: Decrease Transport Costs by 15% (Cost Optimization)
[2] DECISION 2: Increase Safety Stock by 10% (Conservative Risk Management)

FLAT AI SELECTED: DECISION 0: Increase Demand by 20% (Aggressive Growth)
```

2. Flat AI Autonomous Data Modification

```
In [21]: # The AI reads the clean base Excel template, dynamically locates the 'Quantity'
# parameter across AnyLogistix 'Col X' format, applies +20%, and saves a new file
```



```

import pandas as pd
import os

# 1. Define the input and output paths
base_excel_path = r"C:\Users\Luis\Downloads\TFG\API\Global Network Examination.x
modified_excel_path = os.path.join(os.getcwd(), "AI_Modified_Scenario.xlsx")

print("--- PHASE 2 - BLOCK 2: AI APPLYING DECISION 0 (+20% DEMAND) ---")

try:
    if os.path.exists(base_excel_path):
        print(f"1. Loading base scenario from: {base_excel_path}")
        # Load all sheets into memory
        all_sheets = pd.read_excel(base_excel_path, sheet_name=None)

        demand_sheet_name = 'Demand'

        if demand_sheet_name in all_sheets:
            print(f"2. Found '{demand_sheet_name}' table. Searching for 'Quantity'")
            df_demand = all_sheets[demand_sheet_name]

            # Counter to track how many rows the AI modified
            modifications_made = 0

            # AnyLogistix stores parameter names in Col X, and their numerical v
            for i in range(1, 20):
                name_col = f'Col {i}'
                val_col = f'Col {i+3}'

                if name_col in df_demand.columns and val_col in df_demand.columns:
                    # Find all rows where this specific column contains the word
                    mask = df_demand[name_col] == 'Quantity'

                    if mask.any():
                        # We found quantities! Apply the 20% increase mathematic
                        # We force numeric conversion first to ensure safe multi
                        df_demand.loc[mask, val_col] = pd.to_numeric(df_demand.l

                        # Add the number of modified rows to our tracker
                        modifications_made += mask.sum()

            if modifications_made > 0:
                # Replace the original DataFrame with our modified one
                all_sheets[demand_sheet_name] = df_demand
                print(f"Success! Demand mathematically increased in {modification

                print(f"3. Saving the modified scenario to: {modified_excel_path}
                # Save all sheets back to a new Excel file
                with pd.ExcelWriter(modified_excel_path, engine='openpyxl') as w
                    for sheet_name, df in all_sheets.items():
                        df.to_excel(writer, sheet_name=sheet_name, index=False)

                print("\n[SYSTEM] Flat AI completely automated the data modifica
                print(f"The new file ready for AnyLogistix upload is: {modified_
            else:
                print("Error: Could not find any 'Quantity' parameter in the dyn

        else:
            print(f"Error: '{demand_sheet_name}' sheet not found in the Excel fi
    else:

```

```

        print(f"Error: Base Excel file not found at {base_excel_path}.")

except Exception as e:
    print("Exception during AI Excel modification: %s\n" % e)

--- PHASE 2 - BLOCK 2: AI APPLYING DECISION 0 (+20% DEMAND) ---
1. Loading base scenario from: C:\Users\Luis\Downloads\TFG\API\Global Network Examination.xlsx
C:\Users\Luis\Downloads\TFG\Anaconda\envs\tfg_anylogistix\lib\site-packages\openpyxl\styles\stylesheet.py:237: UserWarning: Workbook contains no default style, apply openpyxl's default
    warn("Workbook contains no default style, apply openpyxl's default")
2. Found 'Demand' table. Searching for 'Quantity' parameters...
Success! Demand mathematically increased in 153 rows.
3. Saving the modified scenario to: C:\Users\Luis\Downloads\TFG\API\AI_Modified_Scenario.xlsx
C:\Users\Luis\AppData\Local\Temp\ipykernel_17404\460417415.py:40: FutureWarning: Setting an item of incompatible dtype is deprecated and will raise an error in a future version of pandas. Value '[ 14.4  44.4  16.8  10.8   1.2  19.2  15.6 140.4 16.8  27.6   1.2  61.2   7.2  40.8  10.8  91.2   7.2  26.4  27.6  12.   43.2  12.   9.6  12.  51.6  32.4  12.   12.  13.2 267.6  25.2 156.   27.6  12.   3.6  40.8  10.8  10.8   9.6  20.4  30.   15.6 130.8   7.2  37.2   8.4   7.2   9.6   2.4 132.   20.4  40.8  42.   24.   16.8  10.8   8.4  32.4   9.6 123.6  14.4 132.   16.8  28.8  13.2   6.   13.2  26.4  31.2   9.6  21.6   9.6  32.4  33.6  92.4   2.4  90.   46.8   8.4  10.8  38.4  16.8   8.4  50.4  14.4   7.2  14.4  16.8  13.2 123.6 116.4  88.8  96.   55.2  28.8  18.  22.8  19.2 151.2  26.4  10.8  97.2   3.6   8.4  12.   12.   9.6  25.2  21.6  18.   18.   8.4  10.8  15.6  26.4  16.8  72.   1.2  27.6  12.  60.   8.4  88.8   8.4  85.2  31.2  19.2  34.8  13.2  32.4  13.2  15.6   9.6  12.   15.6  57.6  10.8 120.   7.2 123.6  19.2  33.6  55.2  15.6   1.2  31.2   9.6   9.6  19.2  20.4   2.4  15.6   8.4]' has dtype incompatible with int64, please explicitly cast to a compatible dtype first.
    df_demand.loc[mask, val_col] = pd.to_numeric(df_demand.loc[mask, val_col], errors='coerce') * 1.20
[SYSTEM] Flat AI completely automated the data modification!
The new file ready for AnyLogistix upload is: C:\Users\Luis\Downloads\TFG\API\AI_Modified_Scenario.xlsx

```

3. Modification by Excel

```

In [22]: # ROBUST SYNC INJECTION (CLONE + OVERWRITE)
# To bypass ALX server bugs when creating scenarios from scratch, the AI synchronously clones the base scenario, and then synchronously overwrites it with the modified scenario

import os
from pprint import pprint
import openapi_client

print("--- PHASE 2 - BLOCK 3: CLONE AND OVERWRITE WITH AI DATA ---")

try:
    if os.path.exists(modified_excel_path):
        print(f"1. Cloning base scenario '{the_scenario.name}' synchronously..."
              f"new_clone_name = f'{the_scenario.name} - AI Decision 0'")

        # Define the copy parameters with our custom name
        copy_parameters = openapi_client.ApiConvertAndCopyParameters(new_name=the_scenario.name)

```

```

        cloned_scenario = api_instance.copy_scenario_synchronously(
            new_type=the_scenario.type,
            scenario_id=the_scenario.id,
            body=copy_parameters
        )

    if cloned_scenario and cloned_scenario.id:
        print(f"    [SUCCESS] Scenario cloned! New ID: {cloned_scenario.id}")

        print(f"\n2. Injecting the modified Excel data into the clone synchronously...")
        print(f"    (This will safely overwrite the demand data with our +20% logic)")

        # We use the existing import function which is bulletproof
        updated_scenario = api_instance.import_scenario_existing(
            project_id=the_project.id,
            scenario_id=cloned_scenario.id,
            file=modified_excel_path
        )

        print(f"\n[SYSTEM] TOTAL SUCCESS! AI data injected perfectly.")
        print(f"Final AI Scenario ID: {updated_scenario.id}")
        print(f"Final AI Scenario Name: {updated_scenario.name}")

        # Save it globally for the final simulation block
        the_ai_scenario = updated_scenario

    else:
        print("Error: Failed to clone the scenario. Server returned empty data")
    else:
        print(f"Error: Could not find the file {modified_excel_path}")

except Exception as e:
    print(f"\n[SERVER ERROR] Exception during clone or upload:")
    print(e)

```

--- PHASE 2 - BLOCK 3: CLONE AND OVERWRITE WITH AI DATA ---

1. Cloning base scenario 'Global Network Examination' synchronously...
[SUCCESS] Scenario cloned! New ID: 226034
2. Injecting the modified Excel data into the clone synchronously...
(This will safely overwrite the demand data with our +20% logic)

[SYSTEM] TOTAL SUCCESS! AI data injected perfectly.
Final AI Scenario ID: 226034
Final AI Scenario Name: AI_Modified_Scenario

4. Run simulation on AI scenario and export results

In [23]:

```

# The AI automatically configures a SIMULATION experiment for its newly created
# runs it synchronously, and downloads the financial KPIs dashboard to evaluate

import os
import shutil
from pprint import pprint

print(f"--- PHASE 2 - BLOCK 4: RUNNING SIMULATION FOR AI SCENARIO ({the_ai_scenario.name})")

try:
    print("1. Fetching SIMULATION configuration for the new AI scenario...")

```

```

# Retrieve experiments explicitly for the AI scenario
ai_run_configurations = api_instance.get_experiments(the_project.id, the_ai_

# Select the 'SIMULATION' type
ai_simulation_RC = next((r for r in ai_run_configurations if r.type == 'SIMU

if ai_simulation_RC:
    print(f"Found SIMULATION experiment (ID: {ai_simulation_RC.id}). Launchi

# 2. Run the simulation
# Since the scenario was perfectly cloned and overwritten, it will simul
sim_result = api_instance.run_experiment_synchronously(ai_simulation_RC.

# Safely extract the result ID
sim_result_id = getattr(sim_result, 'experiment_result_id', None)

if sim_result_id:
    print(f"\n[SYSTEM] Simulation finished! Captured Result ID: {sim_res

# 3. Fetch the full, rich dashboard pages (KPIs)
print("\n3. Fetching dashboard pages to extract financial results...
pages = api_instance.get_experiment_dashboard_pages(sim_result_id)

if pages and len(pages) > 0:
    # Usually the first page has the main KPIs (Financial and Custom
    target_page = pages[0]
    print(f"Exporting the rich dashboard page '{target_page.name}' (

# Download the results
excel_data = api_instance.export_dashboard_page(sim_result_id, t

# UNIQUE FILE NAME FOR PHASE 2
output_filename = f"AI_Decision0_Final_Results_{sim_result_id}.x
output_path = os.path.join(os.getcwd(), output_filename)

# 4. Save the final report robustly
if isinstance(excel_data, str) and os.path.exists(excel_data):
    shutil.move(excel_data, output_path)
    print(f"\n[TOTAL SUCCESS] AI Simulation Results exported to:
elif isinstance(excel_data, bytes):
    with open(output_path, "wb") as file:
        file.write(excel_data)
    print(f"\n[TOTAL SUCCESS] AI Simulation Results exported to:
else:
    print(f"Unexpected data format received. Type: {type(excel_d

else:
    print("No dashboard pages found for this simulation result.")
else:
    print("Failed to capture 'experiment_result_id' from the synchronous
    print("Server response was:")
    pprint(sim_result)
else:
    print("No SIMULATION experiment found for the AI scenario.")

except Exception as e:
    print("Exception during Simulation Execution and Export: %s\n" % e)

```

--- PHASE 2 - BLOCK 4: RUNNING SIMULATION FOR AI SCENARIO (226034) ---

1. Fetching SIMULATION configuration for the new AI scenario...

Found SIMULATION experiment (ID: 226721). Launching synchronously...

[SYSTEM] Simulation finished! Captured Result ID: 228813

3. Fetching dashboard pages to extract financial results...

Exporting the rich dashboard page 'Available Inventory' (ID: 228815) to Excel...

[TOTAL SUCCESS] AI Simulation Results exported to: C:\Users\Luis\Downloads\TFG\API\AI_Decision0_Final_Results_228813.xlsx

=====

DEVELOPMENT TESTS - IGNORE THEM



```
In [ ]: #Avoid self-signed warnings
import os
import urllib3
```

For self-signed certificates it is necessary to download them and add to the certification path

```
In [ ]: import ssl
import socket

def download_self_signed_cert_no_validation(hostname, port, cert_file):
    context = ssl._create_unverified_context()
    conn = context.wrap_socket(socket.socket(socket.AF_INET), server_hostname=hostname)
    conn.connect((hostname, port))
    der_cert = conn.getpeercert(binary_form=True)
    pem_cert = ssl.DER_cert_to_PEM_cert(der_cert)

    with open(cert_file, 'w') as cert_file:
        cert_file.write(pem_cert)

    print(f"Certificate saved to {cert_file.name}")

# Example usage
download_self_signed_cert_no_validation(SERVER_IP, 443, MY_CERT_FILENAME)
```

```
In [ ]: # !/usr/bin/openssl s_client -showcerts -connect {SERVER_IP}:443 </dev/null 2>/dev/null
```

```
In [ ]: MY_CERT_FILE=os.path.abspath(MY_CERT_FILENAME)
if os.path.isfile(MY_CERT_FILE):
    print(f"Cert file OK: {MY_CERT_FILE} ")
else:
    print(f"Cert file ERROR: {MY_CERT_FILE} ")
MY_CERT_FILE
```

```
In [ ]: os.environ['REQUESTS_CA_BUNDLE'] = MY_CERT_FILE

# Create a PoolManager with a custom CA bundle
http = urllib3.PoolManager(
    cert_reqs='CERT_NONE',      # Enforce cert verification
```

```
    ca_certs=MY_CERT_FILE          # Path to your self-signed cert
)

urllib3.disable_warnings(urllib3.exceptions.InsecureRequestWarning)
http.request("GET", TEST_URL)
```

In []: **from** urllib3 **import** HTTPSConnectionPool

```
pool = HTTPSConnectionPool(
    SERVER_IP,
    port=443,
    cert_reqs='CERT_REQUIRED',
    ca_certs=MY_CERT_FILE
)
```

In []: **import** requests

```
# Any request you make now will use your certificate
response = requests.get(TEST_URL, verify=False)
print(response.text)
```

In []: