

Especificaciones



Eaton CHSPT2SURGE10

EATON SPD TYPE 2 CHSP SERVICE ENTRANCE SURGE PROTECTION, 120/240V LINE, 150V L-N, 300V L-L MCOV, 700V L-N, 1200V L-L, 900V N-G, 700V L-G VPR, 22 KA SCCR, NEMA 4, SINGLE-PHASE, 60 HZ, 10 KA NOMINAL CURRENT DISCHARGE, 60 KA SURGE CURRENT

Especificaciones generales

PRODUCT NAME	Eaton CHSPT2 surge protection device
CATALOG NUMBER	CHSPT2SURGE10
UPC	786689860523
PRODUCT LENGTH/DEPTH	7.5 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	5 in
PRODUCT WEIGHT	0.01 lb
CERTIFICATIONS	UL Recognized UL 1449 cUL Certified
CATALOG NOTES	10KA NOMINAL DISCHARGE CURRENT. HAS 60KA ONE TIME SURGE CURRENT RATING.

Especificaciones del producto

FREQUENCY RATING	60 Hz
INTERRUPT RATING	200 kAIC
NOMINAL DISCHARGE CURRENT	10 kA
OPERATING VOLTAGE	150V L-N, 300V L-L
PROTECTION	700V L-N, 1200V L-L, 900V N-G, 700V L-G
ENCLOSURE	NEMA 4
PHASE	Single-phase
SURGE CURRENT	60 kA
SHORT-CIRCUIT RATING	22000 kA
OPERATING TEMPERATURE	-40 to 50 °C
TYPE	SURGE PROTECTION DEVICE
SPECIAL FEATURES	MEETS OR EXCEEDS THE REQUIRMENTS SPECIFIED IN IBC ®2006, CBC2007, AND UBC®ZONE 4

Recursos

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2026 Eaton. Todos los derechos reservados.

Síganos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

