

# 16342-W

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.



Color :  White

UPC Code : 078477788264

Country Of Origin : Mexico

RoHS Compliant : Yes

NEMA :  5-20R

## Available Colors :



Black



Brown



Gray



Ivory



Light Almond

## Technical Information

AC Horsepower Ratings

**At Rated Voltage : 1 HP**

Electrical Specifications

**Amperage : 20 A**

**Current Limiting : Full Rated Current**

**Dielectric Voltage : Withstands 2000V per UL498**

**Grounding : Self-Grounding**

**Pole : 2-Pole**

**Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current**

**Voltage : 125 VAC**

**Wire : 3-Wire**

Environmental Specifications

**Flammability : Rated V-2 per UL94**

**Operating Temperature : -40C to 60C**

Material Specifications

**Body Material : Thermoplastic Nylon**

**Clamp Nuts : Zinc-Plated Steel**

**Color : White**

**Face Material : Thermoplastic Nylon**

**Ground Clips : Brass-Plated**

**Grounding Screw : Brass 8-32**

**Line Contacts : Brass Triple-Wipe .031 Thick**

**Strap Material : Zinc-Plated Steel**

**Terminal Screws : Brass 10-32**

Mechanical Specifications

**Product ID : Ratings are permanently marked on device**

**Screw Terminal Torque : 14-18 in-lbs**

**Terminal Accom. : 14-10 AWG**

**Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral**

**Termination : Side Wire**

Product Features

**Brand : Decora Plus**

**Color : White**

**Device Type : Duplex Receptacle Outlet**

**Feature 4 : Smooth Face**

**Grade : Commercial Specification Grade**

**Grounding : Self-Grounding**

**NEMA : 5-20R**

Standards and Certifications

**ANSI : C-73**

**CSA C22.2 No. 42 : File LR-406**

**NEMA : WD-1 & WD-6**

**NOM : 057**

**UL498 : File E13399**

**Warranty : 10-Year Limited**

## Patents\*

CA2483480

US6743029

MX257790

US8684771

MX321216

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

## SPECIFICATION SUBMITTAL

|                      |                      |                      |
|----------------------|----------------------|----------------------|
| JOB NAME:            | CATALOG NUMBERS:     |                      |
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| JOB NUMBER:          | <input type="text"/> | <input type="text"/> |

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

