

USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Olympia™ Micro™ Acoustical
Panels with ClimaPlus™ Performance/
USG Donn® Brand Finline® DXF™
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

Fine-Textured Panel

FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light-reflective finish (LR-0.86) reduces light fixtures and energy use.
- USDA Certified Biobased Product.⁷
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

APPLICATIONS

- Offices
- Classrooms
- Reception/lobby areas
- Hotels
- Conference areas
- Retail stores

SUBSTRATE

- Wet-formed mineral fiber

USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS
CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
phone: 866 528-7089 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818

30 YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection

10 YEAR
AVAILABILITY
4211, 4221, 4231,
4411, 4421, 4742,
4744

HRC HIGH RECYCLED
CONTENT



USG OLYMPIA™ MICRO™
PANELS UNPERFORATED⁹

USG OLYMPIA™ MICRO™
PANELS 50 NRC⁶

USG OLYMPIA™ MICRO™
PANELS 60 NRC⁶

USG OLYMPIA™
MICRO™ ILLUSION™
TWO/24 PANELS

PATTERNS

UL Classified												
Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost
SQ 	2'x2'x5/8"	Class A	4210	—	35	0.86	White	A,B,C	Low		42%	\$\$
	2'x4'x5/8"	Class A	4913	—	35	0.86	White	A,B	Low		42%	\$\$
SQ 	2'x2'x5/8"	Class A	4211	0.50	30	0.86	White	A,B,C	Low		43%	\$\$
	2'x4'x5/8"	Class A	4411	0.50	30	0.86	White	A,B	Low		43%	\$\$
SLT 	2'x2'x5/8"	Class A	4221	0.50	35	0.86	White	D	Low		43%	\$\$
	2'x4'x5/8"	Class A	4421	0.50	35	0.86	White	D	Low		43%	\$\$
FLB 	2'x2'x5/8"	Class A	4231	0.50	35	0.86	White	E,F,G,H	Low		43%	\$\$
	2'x4'x5/8"	Class A	4431	0.50	35	0.86	White	E,F,G,H	Low		43%	\$\$
SQ 	2'x2'x3/4"	Class A	4750	0.60	33	0.86	White	A,B,C	Low		60%	\$\$
	2'x4'x3/4"	Class A	4751	0.60	33	0.86	White	A,B	Low		60%	\$\$
SLT 	2'x2'x3/4"	Class A	4752	0.60	35	0.86	White	D	Low		60%	\$\$
	2'x4'x3/4"	Class A	4753	0.60	35	0.86	White	D	Low		60%	\$\$
FLB 	2'x2'x3/4"	Class A	4754	0.60	35	0.86	White	E,F,G,H	Low		60%	\$\$
	2'x4'x3/4"	Class A	4755	0.60	35	0.86	White	E,F,G,H	Low		60%	\$\$
SLT ⁴ 	2'x4'x3/4"	Class A	4742	0.50	35	0.86	White	D	Low		60%	\$\$
ILT ⁵ 	2'x4'x3/4"	Class A	4744	0.50	35	0.86	White	I,J	Low		60%	\$\$

USG Illusion™ Two/24



Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

HRC High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

GRID PROFILE OPTIONS

A USG DX®	B USG DXW™	C® USG Centricitee™ DXT™	D USG DX®	E USG Centricitee™ DXT™	F USG Identitee® DXI™	G USG Finline® DXF™	H USG Finline® 1/8 DXFF™	I USG Centricitee™ DXT™	J USG Identitee® DXI™

PHYSICAL DATA/
FOOTNOTES

Product literature
Data sheet: SC2180

ASTM E1264 classification
Type III, Form 2, Pattern CE

ASTM E84 and CAN/ULC S102
surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Weight
0.775–0.993 lb./sq. ft.

Thermal resistance
R-1.4 (5/8" panels)
R-1.7 (3/4" panels)

Maximum backloading
See USG 30-Year Limited System
Warranty Commercial Applications
(SC2102).

Maintenance
Can be cleaned easily with a soft
brush or vacuum.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- Panels have 15/16" routing.
- Panels have 9/16" routing.

- Mixing 0.50 and 0.60 NRC panels in the same ceiling plane is not recommended.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.
- Maximum 2'x2' with SQ edge panels.
- Item numbers 4210 and 4913 are not UL Classified for acoustics.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2180/rev. 8-21
© 2021 USG Corporation and/or its affiliates. All rights reserved.
Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, FINLINE, IDENTITEE, ILLUSION, MICRO, OLYMPIA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

