

MARKDOWN INPUT

That classic "Permission denied" error usually happens for one of two reasons: either the `**script file isn't executable**`, or the shell `**needs administrative root permissions**`.

Here is how to fix it based on what you are trying to do:

Scenario A: Executing a ``.sh`` or ``.py`` file directly

If you tried running ``../script.sh`` or ``../process.py`` and got ``Permission denied``, the file is missing execution permissions.

1. Make the file executable

Run ``chmod +x`` on the file to grant execute permissions:

```
```bash
chmod +x script.sh
```
```

Then try running it again:

```
```bash
pbpaste | ./script.sh
or
./script.sh "$(pbpaste)"
```
```

2. Bypass by calling the interpreter directly

Alternatively, you don't need execution permissions if you explicitly invoke the program handling it:

```
```bash
For bash scripts
pbpaste | bash script.sh

For python scripts
pbpaste | python3 process.py
```
---
```

LIVE PREVIEW

2. Bypass by calling the interpreter directly

Alternatively, you don't need execution permissions if you explicitly invoke the program handling it:

```
# For bash scripts
pbpaste | bash script.sh

# For python scripts
pbpaste | python3 process.py
```

Scenario B: System / Root protection

If the script is trying to modify system files, install packages, or access protected directories, standard user privileges won't be enough.

Prepend `sudo` to run the command with administrator rights:

```
# If piping clipboard content into bash:
pbpaste | sudo bash

# If passing clipboard content to a script requiring elevated privileges:
sudo ./script.sh "$(pbpaste)"
```

(You will be prompted to type your macOS password—characters won't show on screen as you type, which is normal).

Quick Reference Check

| Command | Cause | Solution |
|---|--|--|
| <code>./script.sh</code> → <code>Permission denied</code> | File mode bit missing <code>x</code> | <code>chmod +x script.sh</code> |
| Writing to <code>/usr/local</code> or <code>/etc</code> | Missing root privileges | Add <code>sudo</code> before the command |
| <code>`pbpaste</code>                                     | <code>python3</code> → <code>Permission denied`</code> | Destination file locked/protected |