

V2.0 Tables of Contents

AMS

Video

Product

get_category

get_attribute_tree

get_brand_list

get_item_limit

get_item_list

get_item_base_info

get_item_extra_info

add_item

update_item

delete_item

init_tier_variation

update_tier_variation

get_model_list

add_model

update_model

delete_model

unlist_item

update_price

update_stock

boost_item

get_boosted_list

get_item_promotion

update_sip_item_price

search_item

get_comment

reply_comment

category_recommend

register_brand

get_recommend_attribute

get_weight_recommendation

Product > v2.product.get_model_list

v2.product.get_model_list

GET /api/v2/product/get_model_list

API Description

Get model list of an item.

Collapse

Request

Request Address

Collapse

Environment	Location	HTTP Address
Live	Global	https://partner.shopeemobile.com/api/v2/product/get_model_list
	Chinese Mainland	https://openplatform.shopee.cn/api/v2/product/get_model_list
	Brazil	https://openplatform.shopee.com.br/api/v2/product/get_model_list
Sandbox	Global	https://openplatform.sandbox.test-stable.shopee.sg/api/v2/product/get_model_list
	Chinese Mainland	https://openplatform.sandbox.test-stable.shopee.cn/api/v2/product/get_model_list

Common Request Parameters

Collapse

Name	Type	Sample	Description
partner_id	int	1	Partner ID is assigned upon registration is successful. Required for all requests.
timestamp	timestamp	1610000000	This is to indicate the timestamp of the request. Required for all requests. Expires in 5 minutes.
access_token	string	c09222e3fc40ffb25fc947f738b1abf1	The token for API access, using to identify your permission to the api. Valid for multiple use and expires in 4 hours.
shop_id	int	600000	Shopee's unique identifier for a shop. Required param for most APIs.
sign	string	e318d3e932719916a9f9ebb57e2011961bd47abfa54a36e040d050d8931596e2	Signature generated by partner_id, api path, timestamp, access_token, shop_id and partner_key via HMAC-SHA256 hashing algorithm. More details: https://open.shopee.com/documents?module=87&type=2&id=58&version=2

Request Parameters

Collapse

Name	Type	Required	Sample	Description
item_id	int64	True	178312	The ID of the item

Request Example

```
HttpResponse<String> response = Unirest.get("https://partner.shopeemobile.com/api/v2/product/get_model_list?
access_token=access_token&item_id=178312&partner_id=partner_id&shop_id=shop_id&sign=sign&timestamp=ti
mestamp")
.asString();
```

Response

Response Parameters

^ Collapse

Name	Type	Sample	Description
message	string		Indicate error details if hit error. Empty if no error happened.
warning	string		Warning message.
request_id	string	75c2b01e50764cec8cfdc61e75c1f26d	The identifier for an API request for error tracking.
- response	object		
- tier_variation	object[]		Variation config of item.
- option_list	object[]		Option list.
option	string	testsku1	Option name.
- image	object		
image_id	string		Id of image
image_url	string		Url of image.
name	string		Variation name.
- model	object[]		Model list.
- price_info	object[]		Price info. For SG/MY/BR/MX/PL/ES/AR seller: Sellers can set the price with two decimal place, other regions can only set the price as an integer.
currency	string	TWD	Currency for the item price.
current_price	float	100.0	Current price of item.
original_price	float	100.0	Original price of item.
inflated_price_of_original_price	float	100.0	Original price of item after tax.
Name	Type	Sample	Description



	sip_item_price	float	100.0	SIP item price. If item is from SIP primary shop, this field will be returned.
	sip_item_price_source	string	manual	SIP item price source, could be manual or auto.If item is from SIP primary shop, this field will be returned.
	sip_item_price_currency	string	CNY	The currency of sip_item_price.If item is from SIP primary shop, this field will be returned.
	local_price	float	122.02	The original price multiplied by the local adjustment rate equals the local price. The local price is denominated in the local currency and is rounded to two decimal places. <path></path>
	local_promotion_price	float	122.02	During the promotion period, the CB price is multiplied by the local adjustment rate. Once the promotion starts, the price remains unchanged. During the promotion, the local_promotion_price= current_price, which is denominated in the local currency and retained to two decimal places. <path></path>
	model_id	int64	2000458802	Model ID.
	tier_index	int32[]	[0, 1]	Tier index of this model.
	promotion_id	uint64	0	Current promotion ID of this model.
	has_promotion	boolean	true	Indicates whether the model is currently under any ongoing promotion.
	model_sku	string	blue bag	SKU of this model. the length should be under 100.
	model_status	string	MODEL_NORMAL	The model status. Should be MODEL_NORMAL or MODEL_UNAVAILABLE. MODEL_NORMAL models can be sold on the buyer's side, and MODEL_UNAVAILABLE models cannot be sold on the buyer's side.
	pre_order	object		(Only whitelisted users can use)
	is_pre_order	boolean	false	Pre-order.
	days_to_ship	int32	3	The days to ship.
	stock_info_v2	object		new stock info. Please check this FAQ for more detail: https://open.shopee.com/faq?top=162&sub=166&page=1&faq=230
	summary_info	object		stock summary Info
	total_reserved_stock	int32		Stock reserved for promotion.
Name		Type	Sample	Description





total_available_stock	int32		Stock can be sold currently
[-] seller_stock	object[]		Seller-managed stock
location_id	string		location id
stock	int32		stock in the current warehouse
if_saleable	boolean	true	To return if the stock of the location id is saleable
[-] shopee_stock	object[]		Shopee warehouse stock
location_id	string		location id
stock	string		stock
[-] advance_stock	object		Only for PH/VN/ID/MY local selected shops.
sellable_advance_stock	int32		Refers to Advance Fulfillment stock that Seller has shipped out and is available to be used to fulfill an order.
in_transit_advance_stock	int32		Refers to Advance Fulfillment stock that seller has shipped out and is still in transit and unavailable to be used to fulfill an order.
gtin_code	string		(Only TW seller and BR local seller available) gtin code.
weight	string	"1.1"	The weight of this model, the unit is KG. If don't set the weight of this model, will use the weight of item by default.
[-] dimension	object		The dimension of this model. If don't set the dimension of this model, will use the dimension of item by default.
package_height	int32	11	The height of package for this model, the unit is CM.
package_length	int32	11	The length of package for this model, the unit is CM.
package_width	int32	11	The width of package for this model, the unit is CM.
is_fulfillment_by_shopee	boolean		whether model is fulfillment by shopee
[-] standardise_tier_variation	object[]		Standardise Variation config of item.
variation_id	int64		Standardise Variation ID
variation_name	string		Standardise Variation Name

Name

Type

Sample

Description





- variation_option_list	object[]	Standardise Variation Option List
variation_option_id	int64	Standardise Option ID
variation_option_name	string	Standardise Option Name
image_id	string	ID of image
image_url	string	URL of image
error	string	Indicate error type if hit error. Empty if no error happened.

Response Example

[^ Collapse](#)

JSON

Copy

```
{
  "message": "-",
  "warning": "-",
  "request_id": "75c2b01e50764cec8cfdc61e75c1f26d",
  "response": {
    "tier_variation": [
      {
        "option_list": [
          {
            "option": "testsku1",
            "image": {
              "image_id": "-",
              "image_url": "-"
            }
          }
        ]
      }
    ]
  }
}
```

Error Codes

[^ Collapse](#)

Business Error Codes

Error	Error Description	Details and Guidance
error_network	Inner http call failed	
error_data	parse data failed	
error_data	data not exist	
error_param	parameter invalid	
error_param	The information you queried is not found.	
error_param	Wrong parameters, detail: {msg}.	
error_server	Something wrong. Please try later.	
error_shop	shopid is invalid	
error_param	request not from gateway	
error_shop_not_found	Shop is not found.	
Error	Error Description	Details and Guidance





error_param_shop_id_not_found	Shop_id is not found.
error_data	error data
error_inner	Our system is taking some time to respond, please try later.
error_inner	System error, please try again later or contact the OpenAPI support team.
error_item_not_found	Product not found
error_inner	Update item failed {{.error_info}}
error_inner	Update item failed {{.error_info}}
error_inner	System error, please try again later or contact the OpenAPI support team.
error_inner	System error, please try again later or contact the OpenAPI support team.
error_auth	The location_id input is not matched the shop's location_id(more/wrong). Please double check.
error_auth	Lack of location_id, please double check.
error_auth	Please wait for the holiday mode set then to edit item. Please try later.
error_auth	Total stock must be more than reserved stock.
error_param	{{.error_info}}
error_auth	Your shop can not use model level dts
error_auth	You do not have right to use seller location_id, please only fill seller_stock filed.
error.param	Can not update item with stock less than reserved stock
error_param	Can not update item with different stock structure. Can only update seller stock with location id when existing seller stock have location id. Can only update seller stock without location id when existing seller stock without location id.





error_auth	Stock should be larger than reserved stock.
error_system_busy	Our system is taking some time to respond, please try later.
error_param	Can not update item with different stock structure. Can only update seller stock with location id when existing seller stock have location id. Can only update seller stock without location id when existing seller stock without location id.

Common Error Codes

Error Example

Collapse

JSONCopy

```
{
  "error": "product.error_param",
  "message": "invalid field ItemId: value must Not Null",
  "request_id": "a48d523f688e20f593446846638360d9"
}
```

API Permissions

Collapse

APP types that can call this API.

ERP System Seller In House System Product Management Accounting And Finance Customer Service Customized APP

Ads Service Swam ERP Livestream Management Ads Facil Affiliate Marketing Solution Management Shopee Video Management

API Tools

Collapse

API Test Tools

API Access Log

Update Log

Collapse

Date	Update Details
2026-07-31	promotion_id type change to uint64
2025-11-07	add new response field "has_promotion"
2025-09-05	add to new response field "local_promotion_price"and "local_price"
2025-02-17	Add is_fulfillment_by_shopee
2024-11-01	Update the description of total_reserved_stock to return the total reserved stock for P Item and all A Items under the P Item



User Guide

- Developer Guide
- API reference
- Push Mechanism
- Shopee Open Platform Data Protection Policy

Shopee Markets

- Service Market
- Seller Education Hub (Singapore)
- Seller Education Hub (Malaysia)
- Seller Education Hub (Thailand)
- Seller Education Hub (Vietnam)
- Seller Education Hub (Indonesia)
- Seller Education Hub (Philippines)
- Seller Education Hub (Brazil)
- Seller Education Hub (Japan)
- Seller Education Hub (Korea)
- Seller Education Hub (Hongkong)
- 虾皮卖家学习中心

Support

- Announcement
- FAQ
- Raise Ticket