



Sessions

[GET /sessions](#)

[Description](#)
[Authentication](#)
[Query parameters](#)
[Example response](#)

[GET /sessions/:sessionId](#)

[Description](#)
[Authentication](#)
[Example response](#)

[POST /sessions](#)

[Description](#)
[Authentication](#)
[Body parameters](#)
[Example response](#)

[POST /sessions/:sessionId](#)

[Description](#)
[Authentication](#)
[Body parameters](#)
[Example response](#)

[DELETE /sessions/:sessionId](#)

[Description](#)
[Authentication](#)
[Example response](#)

GET /sessions

Description

List the activated sessions opened by the current user.

Authentication

This route is accessible to connected users.

Query parameters

This route is paginated following the [before / after rules](#).

Example response

```
{
  "sessions": [
    {
      "id": "5a67007d95a4d30015fb27d2",
      "token": "0a109191800f3b28031b96bbbc41b451",
      "secured": false,
      "location": {
        "lng": 2.2003,
        "lat": 48.8914,
        "name": "Nanterre, France"
      },
      "userAgent": "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_13_2) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/63.0.3239.132",
      "lastAccessDate": "2018-04-04T09:29:33.209Z",
      "creation": "2018-01-23T09:29:33.000Z"
    },
    {
      "id": "5a8a963d9da75f00299bc0aa",
      "token": "28373cd7b2bc1e7a3c19f122b8e2cd90",
      "secured": false,
      "location": {
```

```

        "lng": 2.2067,
        "lat": 48.892,
        "name": "Nanterre, France"
    },
    "userAgent": "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_13_3) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/64.0.3282.186",
    "lastAccessDate": "2018-03-05T09:33:18.017Z",
    "creation": "2018-02-19T09:17:49.000Z"
  }
],
"remaining": 0
}

```

GET /sessions/:sessionId

Description

Get a single session.

The session is returned with the `user`, `user.business` embedded.

Authentication

This route is only accessible to the owner of the session.

Example response

```

{
  "session": {
    "id": "5a67007d95a4d30015fb27d2",
    "token": "0a109191800f3b28031b96bbbc41b451",
    "secured": false,
    "location": {
      "lng": 2.2003,
      "lat": 48.8914,
      "name": "Nanterre, France"
    }
  },
  "userAgent": "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_13_2) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/63.0.3239.132 Safari/601.6.1",
  "lastAccessDate": "2018-04-04T09:29:33.209Z",
  "creation": "2018-01-23T09:29:33.000Z",
  "user": {
    "id": "551e5181e4b040a27e5b6c8f",
    "name": "Julien Guepin",
    "picture": "58c83fdebff67e001386f218",
    "isFinsquare": false,
    "creation": "2015-04-03T08:38:25.000Z",
    "email": "guepin@lendix.com",
    "type": "admin",
    "phone": {
      "countryCode": "33",
      "number": "603239114"
    },
    "rights": [
      "export_requests",
      "edit_user_rights",
      "edit_project",
      "validate_project",
      "edit_online_project",
      "publish_project",
      "edit_user_email",
      "create_project",
      "edit_user_phone",
      "edit_project_health"
    ],
    "gender": "male",
    "taxResidency": "fr",
    "settings": {
      "language": "fr",
      "agreements": []
    },
    "intercomHash": "c32567a593a503d6cc5d4a347fe0658d08b31719fb06b3ef3113e5d9f2fffd0a7"
  }
}

```

POST /sessions

Description






Create a new session, allowing a user to connect on Lendix.

The user status can't be `closed`.

Authentication

This route allows authentication.

Body parameters

 Name	 Required	 Type	 Description
<u>email</u>		string	Email of the user
<u>password</u>		string	Password of the user

Example response

```
{
  "session": {
    "id": "5ac50205251554001ac4be9f",
    "token": "00b6e19e254dea67a68a1888ad9a6f",
    "secured": false,
    "location": {
      "lng": 2.2003,
      "lat": 48.8914,
      "name": "Nanterre, France"
    }
  },
  "userAgent": "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_13_3) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/65.0.3325.181 Safari/537.36",
  "lastAccessDate": "2018-04-04T16:49:09.801Z",
  "creation": "2018-04-04T16:49:09.000Z",
  "user": {
    "id": "587fb0c4ec9d800010838e52",
    "name": "Julien Test",
    "isFinsquare": false,
    "creation": "2017-01-18T18:15:32.000Z",
    "email": "julien+test@guepin.fr",
    "type": "admin",
    "phone": {
      "countryCode": "33",
      "number": "603239114"
    },
    "credit": 0,
    "status": "activated",
    "rights": [
      "create_user",
      "edit_user_rights",
      "create_project",
      "edit_project",
      "publish_project",
      "validate_project",
      "borrower_partner"
    ],
    "gender": "male",
    "slug": "jtest1",
    "tax": 0,
    "taxResidency": "fr",
    "settings": {
      "language": "fr",
      "agreements": [
        "lendix-fr"
      ]
    }
  },
  "intercomHash": "4e36827797f624b1e70ec1f4aa0c4ea09be0f36ea7b0bfff89611dbcd57e32cd8"
}
```

POST /sessions/:sessionId

Description

Update a session to securize it **during 1 hour**. The session has to be activated.

This is a 2 step process:

1. update `session.secured` to `true` to send a SMS code to the user
2. send the code in the body to verify it and update the session to secured

Authentication

This route is accessible to the owner of the session.

Body parameters

Name	Required	Type	Description
<code>code</code>	yes (if secured is not set)	string	Must match the code stored in session.code
<code>secured</code>	yes (if code is not set)	boolean	Must be true
<code>codeOrigin</code>	if not set, <code>sms</code> behavior is default	string	Mus be <code>sms</code> or <code>email</code> to know which 2FA method should be used (default <code>sms</code>)

Example response

```
{
  "session": {
    "id": "5a958a9b342f860019515778",
    "token": "edac5382f5c4fe95ab5c054e1a1d5791",
    "secured": true,
    "location": null,
    "userAgent": "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_13_3) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/64.0.3282.186 Safa",
    "lastAccessDate": "2018-04-04T17:56:50.017Z",
    "creation": "2018-02-27T16:43:07.000Z",
    "user": {
      "id": "551e5181e4b040a27e5b6c8f",
      "name": "Julien Guepin",
      "picture": "58c83fdebff67e001386f218",
      "isFinsquare": false,
      "creation": "2015-04-03T08:38:25.000Z",
      "email": "guepin@lendix.com",
      "type": "admin",
      "phone": {
        "countryCode": "33",
        "number": "603239114"
      },
      "rights": [
        "export_requests",
        "edit_user_rights",
        "edit_project",
        "validate_project",
        "edit_online_project",
        "publish_project",
        "edit_user_email",
        "create_project",
        "edit_user_phone",
        "edit_project_health"
      ],
      "gender": "male",
      "taxResidency": "fr",
      "settings": {
        "language": "fr",
        "agreements": []
      },
      "intercomHash": "c32567a593a503d6ff6d4b547fe0658d08b31719fb06b3ef3113e5d9f2ffd0a7"
    }
  }
}
```

DELETE /sessions/:sessionId

Description

Delete a session by setting `session.activated` to `false`. This allows to logout a user from Lendix.

Authentication

This route is accessible to the session owner.

Example response

```
{}
```