Priority Rank	Priority Group	Release	Tentative Cycle	Area	FEAT	FEAT Title	FEAT Scope	Requirement ID	Type	Requirement	FEAT Est Full Low (h)	FEAT Est Full High (h)	FEAT R1 Est Low (h)	FEAT R1 Est High (h)	Req Est Avg (h)	Dependencies	Risk Level	Risks	Recommendations	Edge Cases / Considerations	Notes & Concerns	Open Question / Decision Refs
1	R1-C1 Foundation & BLE spike	R1	C1	Cross-cutting (R1 work item)	—	Feature flag + feature-branch merge setup (R18)	—	R1-INFRA-FLAG	Work item	Feature flag + feature-branch merge setup (R18)	4.0	8.0	4.0	8.0	6.0	Greg team merge process; config delivery to Flex/Driver App.	L	Not in the original estimate (R18).	Single flag gating all #10082 entry points in Flex, Driver App and Form Builder.	Flag off must leave existing QR flows identical.		
1	R1-C1 Foundation & BLE spike	R1	C1	Cross-cutting (R1 work item)	—	BLE / Nearby transport spike (Android—Android): go/no-go Nov 3	—	R1-INFRA-SPIKE	Work item	BLE / Nearby transport spike (Android—Android): go/no-go Nov 3	16.0	24.0	8.0	14.0	11.0	Access to RecoveryTrac.UI source and Android devices; decision D2.	H	Driver App needs a BLE peripheral (advertising + GATT server) and common Capacitor plugins are central-only.	Timebox; evaluate BLE GATT vs Google Nearby Connections; decide D2 by Nov 3.	OEM Bluetooth stack differences; Android 12+ permission model.		D2, Q6
1	R1-C1 Foundation & BLE spike	R1	C1	Nearby Driver Transfer	FEATNDT-1	Driver App Nearby Discoverability	Full	10082-NDT-1-P01	Positive	When Driver App is open in the foreground and the runtime access required for Nearby is available, Driver App makes itself available for discovery by nearby Flex devices.	5.0	8.0	2.0	3.0	1.3	Transport (spike), DABA-1/3.	H	Android background/foreground advertising lifecycle; battery.	Start advertising on resume and stop on pause; no pairing (N02).	Returning from background re-advertises automatically (P03).		
1	R1-C1 Foundation & BLE spike	R1	C1	Nearby Driver Transfer	FEATNDT-1	Driver App Nearby Discoverability	Full	10082-NDT-1-P02	Positive	While Driver App remains open in the foreground and the runtime access required for Nearby remains available, Driver App remains available for Nearby discovery regardless of which Driver App page is displayed.	5.0	8.0	2.0	3.0	1.3	Transport (spike), DABA-1/3.	H	Android background/foreground advertising lifecycle; battery.	Start advertising on resume and stop on pause; no pairing (N02).	Returning from background re-advertises automatically (P03).		
1	R1-C1 Foundation & BLE spike	R1	C1	Nearby Driver Transfer	FEATNDT-1	Driver App Nearby Discoverability	Full	10082-NDT-1-P03	Positive	When Driver App returns to the foreground after being backgrounded and the runtime access required for Nearby is available, Driver App becomes available for Nearby discovery again without requiring the Driver App User to re-enable discoverability.	5.0	8.0	2.0	3.0	1.3	Transport (spike), DABA-1/3.	H	Android background/foreground advertising lifecycle; battery.	Start advertising on resume and stop on pause; no pairing (N02).	Returning from background re-advertises automatically (P03).		
1	R1-C1 Foundation & BLE spike	R1	C1	Nearby Driver Transfer	FEATNDT-1	Driver App Nearby Discoverability	Full	10082-NDT-1-N01	Negative	Driver App must not require the Driver App User to navigate to Home, Identity, or any other specific Driver App page before the foreground app can be discovered.	5.0	8.0	2.0	3.0	1.3	Transport (spike), DABA-1/3.	H	Android background/foreground advertising lifecycle; battery.	Start advertising on resume and stop on pause; no pairing (N02).	Returning from background re-advertises automatically (P03).		
1	R1-C1 Foundation & BLE spike	R1	C1	Nearby Driver Transfer	FEATNDT-1	Driver App Nearby Discoverability	Full	10082-NDT-1-N02	Negative	Driver App must not require the Driver App User to enter a pairing/receive mode or approve a discovery request before the foreground app can be discovered.	5.0	8.0	2.0	3.0	1.3	Transport (spike), DABA-1/3.	H	Android background/foreground advertising lifecycle; battery.	Start advertising on resume and stop on pause; no pairing (N02).	Returning from background re-advertises automatically (P03).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P01	Positive	When an applicable Flex workflow opens Nearby Driver discovery, Flex opens a standard Flex Action Menu and begins Nearby discovery immediately without requiring a separate Search action.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P02	Positive	While Nearby discovery is active, the discovery menu displays Searching for nearby Driver Apps... with an indeterminate spinner beside the message. The message and spinner are hidden when discovery stops so the Flex User can distinguish an active search from a stopped no-results state.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P03	Positive	When Flex finds a Driver App during active discovery, Flex displays a result card for that Driver App in the discovery result list while keeping the active-discovery status and spinner visible above the result list.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P04	Positive	While the discovery result list contains at least one Driver App, Flex continues Nearby discovery so additional Driver Apps can be found and the displayed result list can remain current while the menu is open. Flex does not apply the 10-second no-results timeout while at least one Driver App remains in the result list.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P05	Positive	When Flex finds an additional Driver App, Flex inserts the new card at the position required by the closest-first estimated-distance sort.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P07	Positive	When a displayed Driver App drops out of the discovery results while Nearby discovery remains active, Flex makes that Driver App card non-selectable before beginning its removal animation.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P10	Positive	While the Flex User has an active touch or pointer press on a discovery-result card, Flex defers result-list insertions, removals, and reordering that would move result cards until that interaction ends.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P11	Positive	When the active touch or pointer interaction ends, Flex applies any deferred discovery-result updates before processing subsequent user interactions with the result list.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P12	Positive	If the initiating workflow supplies an alternative action, Flex renders that action as a full-width secondary Action Menu action in a dedicated area below the discovery status/result region rather than as a Driver App result card.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P13	Positive	A supplied alternative action remains visible while Flex is searching, while Driver App results are displayed, and while the no-results state is displayed; result-list insertion, removal, or sorting does not reorder the alternative action with Driver App cards.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P14	Positive	When the Flex User selects a selectable Driver App result, Flex stops Nearby discovery before continuing to the next step for that selected Driver App.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P15	Positive	When the Flex User selects a supplied alternative action, Flex stops Nearby discovery, dismisses the discovery menu, and invokes that alternative action.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-P16	Positive	When the Flex User dismisses the discovery menu using the standard Flex Action Menu dismissal behavior, Flex stops Nearby discovery and leaves the initiating workflow unchanged.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-N01	Negative	Flex must not require the Flex User to manually refresh the discovery result list while Nearby discovery remains active.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-N02	Negative	Flex must not display No nearby Driver Apps found. while at least one Driver App remains in the discovery result list.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-N03	Negative	Flex must not allow a discovery-result list update to cause a touch or pointer interaction that began on one Driver App card to activate a different Driver App card after the list shifts.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-N04	Negative	Flex must not continue Nearby discovery after the discovery menu has been dismissed, an alternative action has been selected, a selectable Driver App has been selected, or the 10-second no-results interval has completed without finding a Driver App.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-E01	Edge case	If Flex finds no Driver App during the first 10 continuous seconds of a discovery attempt, Flex stops Nearby discovery and replaces the searching state with No nearby Driver Apps found.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-E02	Edge case	The No nearby Driver Apps found. state displays Make sure the Driver App is open and nearby.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-E03	Edge case	The No nearby Driver Apps found. state displays Try Again as the primary action for starting another discovery attempt.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-E04	Edge case	If the initiating workflow supplied an alternative action, that action remains available in the No nearby Driver Apps found. state.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-E05	Edge case	When the Flex User selects Try Again, Flex clears the no-results state, displays Searching for nearby Driver Apps... with the continuously rotating indeterminate spinner, and begins a new Nearby discovery attempt with a new 10-second no-results interval.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-E06	Edge case	If Flex finds at least one Driver App before the 10-second no-results interval expires, Flex does not display the no-results state and continues showing the discovered result list while discovery remains active.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-2	Flex Nearby Driver Discovery Menu	Full	10082-NDT-2-E10	Edge case	If the Driver App represented by a card under an active touch or pointer press drops out of the discovery results before that interaction ends, Flex does not select that Driver App when the interaction completes; Flex applies the pending removal after the interaction ends.	14.0	22.0	5.0	8.0	0.6	FAM-1...3, NDT-1, NDT-6, transport.	M	List instability causing mis-selection; the animation work is large.	R1: plain list with no-results timeout and Try Again. R2: insert/remove animations.	10-second no-results timer (E01); press-deferral so a list shift never selects a different card (P10/P11, N03, E10); device found again during removal (E09).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P01	Positive	For each Driver App in the Nearby discovery result list, Flex displays one identity card representing that Driver App.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P02	Positive	Driver App advertises its current Driver Session identity for Nearby discovery while that identity remains applicable to the current Driver App work context, including while the Driver Session is Active or Paused and while an Invalidated Driver Session is retained to complete an already-active load.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P03	Positive	When no current Driver Session identity is applicable, including after a Driver Session has Ended or after an Invalidated session's in-progress load has been completed, Driver App advertises the current Driver App Identity Code defined by FEATDAI-3.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P04	Positive	Starting, pausing, invalidating, ending, or replacing a Driver Session updates the Driver App's advertised discovery identity according to the currently applicable identity without changing the discoverability rules in FEATNDT-1.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P05	Positive	An existing Nearby Driver Link does not freeze or override what the Driver App advertises to new discovery attempts; linked-identity presentation for the already-linked Document is independently retained by FEATLID T-3.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P06	Positive	When a discovered Driver App provides Driver Session identity details, Flex displays the Truck Number as the card's primary identity in bold	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P07	Positive	When a discovered Driver App provides Driver Session identity details, Flex displays Capacity: <capacity> and Tag: <tag> as secondary labeled values below the primary identity.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P08	Positive	Flex renders secondary identity labels and values in regular-weight text so the bold primary identity remains the strongest visual element in the card.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P09	Positive	Flex displays Capacity and Tag in the same secondary-information row when both labeled values fit without wrapping; otherwise Flex does not fit, Flex moves a complete label/value pair to the next line rather than overlapping or clipping either pair.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P10	Positive	When a discovered Driver App provides Driver Session identity details, Flex displays Company Name: <company name> on a full-width secondary line below Capacity and Tag. Company Name may wrap onto additional lines when necessary to display the full value.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P11	Positive	When the Driver Session identity indicates that a trailer is present, Flex displays Trailer Number: <trailer number> on a full-width secondary line below Company Name. When no trailer is present, Flex does not reserve or display a Trailer Number line.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEATNDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P12	Positive	Flex does not truncate the Truck Number, Identity Code, Company Name, or other displayed identity value with an ellipsis. If the available card width is insufficient, the card increases its height and wraps applicable content so the full displayed identity remains readable.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3

Priority Rank	Priority Group	Release	Tentative Cycle	Area	FEAT	FEAT Title	FEAT Scope	Requirement ID	Type	Requirement	FEAT Est Full Low (h)	FEAT Est Full High (h)	FEAT R1 Est Low (h)	FEAT R1 Est High (h)	Req Est Avg (h)	Dependencies	Risk Level	Risks	Recommendations	Edge Cases / Considerations	Notes & Concerns	Open Question / Decision Refs
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P13	Positive	Flex displays the estimated distance as secondary text aligned opposite the primary identity when both fit on the card's first row. If the primary identity and distance cannot fit without overlap or truncation, Flex places the distance on its own line directly below the primary identity.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P21	Positive	When a discovered Driver App does not provide Driver Session identity details, Flex displays Driver App as the bold primary identity, displays Identity Code: <identity code> as a full-width secondary line, and displays the estimated distance using the same distance presentation used for Driver Apps with Driver Session identity details.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P22	Positive	When the same discovered Driver App begins providing different Driver Session identity details while the discovery menu remains open, Flex updates the identity content within that existing card rather than removing the result and adding a second card. The card changes position only when the distance-sorting requirements independently require a reorder.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-P23	Positive	When the same discovered Driver App changes between Driver Session identity and Identity Code identity while discovery remains open, Flex updates that existing card in place rather than creating a second result.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-N01	Negative	Flex must not display Trailer Capacity or Trailer Tag on a Driver App discovery identity card.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-E01	Edge case	If Capacity, Tag, or Company Name is unavailable for Driver Session identity details provided by a discovered Driver App, Flex keeps the applicable labeled field visible and displays Not available as its value.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-3	Driver App Discovery Identity Cards	Full	10082-NDT-3-E02	Edge case	If a trailer is present but Trailer Number is unavailable, Flex displays Trailer Number: Not available.	14.0	22.0	3.0	5.0	0.6	DAI-3, Driver Session identity, transport advertising payload.	M	BLE advertisement size limits for identity fields; RSSI distance is noisy. Nearby Connections gives no distance.	Keep the advertisement minimal (id + type) and fetch identity details over the connection or scan response. Distance sorting is deferred (D3).	Missing identity fields show "Not available" (E01/E02); no distance shows "Distance unavailable" (E03); identity changes in place (P22/P23).		D2, D3
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-5	Nearby Transfer Supported Clients	Full	10082-NDT-5-P01	Positive	Flex Android native supports Nearby Driver Transfer.	4.0	6.0	1.0	1.0	0.6	Capability detection in Flex.	M	Flex iOS (SCOPE-EXT-1) and Driver App iOS are deferred to R2 in A-Android.	Implement a "nearbySupported" capability flag; Flex iOS/Web fall back to QR with no Nearby UI.	Single entry point opens QR directly on unsupported clients (P07).	SCOPE-EXT-1: Flex iOS was also added as a Nearby client (user decision); deferred to R2 under A-Android.	D1, SCOPE-EXT-1
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-5	Nearby Transfer Supported Clients	Full	10082-NDT-5-P02	Positive	Driver App Android supports Nearby Driver Transfer.	4.0	6.0	1.0	1.0	0.6	Capability detection in Flex.	M	Flex iOS (SCOPE-EXT-1) and Driver App iOS are deferred to R2 in A-Android.	Implement a "nearbySupported" capability flag; Flex iOS/Web fall back to QR with no Nearby UI.	Single entry point opens QR directly on unsupported clients (P07).		D1, SCOPE-EXT-1
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-5	Nearby Transfer Supported Clients	Full	10082-NDT-5-P05	Positive	When the current Flex client does not provide Nearby Transfer capability and a workflow presents Nearby transfer as a distinct action alongside an applicable QR action, Flex omits the Nearby action and renders the remaining actions normally without leaving a disabled placeholder or empty gap.	4.0	6.0	1.0	1.0	0.6	Capability detection in Flex.	M	Flex iOS (SCOPE-EXT-1) and Driver App iOS are deferred to R2 in A-Android.	Implement a "nearbySupported" capability flag; Flex iOS/Web fall back to QR with no Nearby UI.	Single entry point opens QR directly on unsupported clients (P07).		D1, SCOPE-EXT-1
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-5	Nearby Transfer Supported Clients	Full	10082-NDT-5-P06	Positive	When the current Flex client does not provide Nearby Transfer capability, an applicable QR action that is presented separately from Nearby transfer remains enabled and continues to use its existing QR behavior.	4.0	6.0	1.0	1.0	0.6	Capability detection in Flex.	M	Flex iOS (SCOPE-EXT-1) and Driver App iOS are deferred to R2 in A-Android.	Implement a "nearbySupported" capability flag; Flex iOS/Web fall back to QR with no Nearby UI.	Single entry point opens QR directly on unsupported clients (P07).		D1, SCOPE-EXT-1
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-5	Nearby Transfer Supported Clients	Full	10082-NDT-5-P07	Positive	When the current Flex client does not provide Nearby Transfer capability and a workflow uses a single entry point that would otherwise open Nearby discovery with a QR alternative inside the discovery menu, activating that entry point opens the applicable QR interaction directly.	4.0	6.0	1.0	1.0	0.6	Capability detection in Flex.	M	Flex iOS (SCOPE-EXT-1) and Driver App iOS are deferred to R2 in A-Android.	Implement a "nearbySupported" capability flag; Flex iOS/Web fall back to QR with no Nearby UI.	Single entry point opens QR directly on unsupported clients (P07).		D1, SCOPE-EXT-1
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-5	Nearby Transfer Supported Clients	Full	10082-NDT-5-N01	Negative	When the current Flex client does not provide Nearby Transfer capability, Flex must not display a disabled Nearby action or other non-interactive Nearby placeholder solely to indicate that Nearby transfer is unavailable.	4.0	6.0	1.0	1.0	0.6	Capability detection in Flex.	M	Flex iOS (SCOPE-EXT-1) and Driver App iOS are deferred to R2 in A-Android.	Implement a "nearbySupported" capability flag; Flex iOS/Web fall back to QR with no Nearby UI.	Single entry point opens QR directly on unsupported clients (P07).		D1, SCOPE-EXT-1
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-5	Nearby Transfer Supported Clients	Full	10082-NDT-5-N02	Negative	When the current Flex client does not provide Nearby Transfer capability and an applicable QR path is available, Flex must not open Nearby discovery or show an intermediate Nearby-unavailable message before continuing to the QR interaction.	4.0	6.0	1.0	1.0	0.6	Capability detection in Flex.	M	Flex iOS (SCOPE-EXT-1) and Driver App iOS are deferred to R2 in A-Android.	Implement a "nearbySupported" capability flag; Flex iOS/Web fall back to QR with no Nearby UI.	Single entry point opens QR directly on unsupported clients (P07).		D1, SCOPE-EXT-1
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-P01	Positive	When a Flex User initiates Nearby transfer, Flex re-evaluates shared Flex Bluetooth Access and every location condition required by the current platform specifically for Nearby discovery before starting discovery.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-P02	Positive	When a Flex User initiates Nearby transfer and shared Flex Bluetooth Access is not ready, Flex shows the shared Flex Bluetooth Access flow defined in Flex Bluetooth Access before Nearby discovery begins.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-P03	Positive	When the shared Flex Bluetooth Access flow is shown for a Nearby transfer, it displays explanation Flex needs Bluetooth access to find and connect to nearby Driver Apps.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-P04	Positive	When the initiating workflow supplies an alternative action, the shared Flex Bluetooth Access flow displays that same alternative action as the modal's secondary action.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-P08	Positive	When the initiating workflow does not supply an alternative action, the applicable shared Bluetooth Access or Location Access modal displays its normal Cancel secondary action.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-P09	Positive	When shared Flex Bluetooth Access and every location condition required by the current platform for Nearby discovery are satisfied, Flex begins the Nearby discovery flow originally requested by the Flex User without requiring the original Nearby action to be selected again.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-N01	Negative	Flex must not begin Nearby discovery while shared Flex Bluetooth Access or a location condition required by the current platform specifically for Nearby discovery remains unsatisfied.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-E01	Edge case	If the Flex User selects the initiating workflow's alternative action from a shared Bluetooth Access or Location Access modal before discovery starts, Flex continues into that alternative workflow without starting Nearby discovery.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-E02	Edge case	If the Flex User selects Cancel from a shared Bluetooth Access or Location Access modal before discovery starts when no alternative action is supplied, Flex returns to the unchanged initiating surface without starting Nearby discovery.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-6	Flex Nearby Runtime Access	Full	10082-NDT-6-E03	Edge case	If a shared access flow returns without the required access becoming ready and without the Flex User selecting an alternative action, Flex does not start Nearby discovery.	8.0	12.0	1.0	2.0	0.4	FBA-1/3, (FLA-1/2/4 if DS), NDT-2.	M	Runtime access lost mid-discovery handling deferred.	R1: gate start of discovery; R2: mid-discovery loss/restart.	Access lost during discovery (P11–P14); restored mid-recovery (E07).		D5
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P01	Positive	After the Flex User selects a Driver App for a Nearby transfer, Flex stops discovery and keeps the same standard Action Menu open while replacing discovery content with the progress presentation for the selected Driver App.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P02	Positive	The progress Action Menu displays title Send Data for Producer Shared Data transfer, Receive Data for Consumer Shared Data receipt, and Send Receipt for Driver App Receipt Data transfer.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).	R1 implements only the "Send Data" title (Producer); the other titles come with R2 workflows.	
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P03	Positive	The progress presentation keeps the selected Driver App identity visible using the identity information defined by FEAT-NDT-3, but does not display or continue updating the discovery-distance value after selection.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P04	Positive	While Flex is attempting to establish the initial connection to the selected Driver App, the progress presentation displays Connecting... with an indeterminate spinner.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P06	Positive	After the connection required for the transfer is established and before the transfer reaches a terminal result, the progress presentation displays an indeterminate spinner and the applicable status: Sending data... for Producer Shared Data, Receiving data... for Consumer Shared Data, or Sending receipt data... for Driver App Receipt Data.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P07	Positive	Flex displays Cancel while the Nearby transfer is in the Connecting..., Reconnecting..., or transferring state.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P08	Positive	While a Nearby transfer is in one of those in-progress states, Flex prevents passive Action Menu dismissal. Tapping or clicking outside the Action Menu or pressing Escape does not dismiss it; cancellation requires the Flex User to select Cancel.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P09	Positive	When the Flex User selects Cancel, Flex requests termination of the current connection or transfer attempt.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-P10	Positive	When cancellation is confirmed before the receiving side has committed the workflow-specific transfer result, Flex dismisses the Action Menu and immediately returns control to the unchanged surface that initiated the Nearby action, whether that is an editable Form, the Standard Post-Submission Experience, a Kiosk Success presentation, or the persistent Form Summary Submitted context.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-N01	Negative	Flex must not display packet counts, byte counts, percentage-complete values, or determinate progress that does not represent a meaningful workflow-level completion state.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-N02	Negative	Flex must not treat an outside click/tap, backdrop tap, or Escape as a request to cancel an in-progress Nearby transfer.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-N03	Negative	A cancellation that completes before receiver commitment must not create a new Driver App active load, create Driver App receipt records, apply newly received Consumer values, establish or replace a Nearby Driver Link, or apply a new source-Document handoff lock from that canceled attempt.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-E01	Edge case	If the receiving side commits the workflow-specific transfer result before a cancellation request takes effect, the normal success outcome wins; Flex must not report that committed transfer as canceled.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-E02	Edge case	If an outbound Producer Shared Data or Receipt Data transfer ends after Driver App may have committed the transfer but before Flex can confirm that outcome, Flex does not report cancellation and instead uses the acknowledgement-uncertain recovery behavior in FEAT-NDT-13.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		
2	R1-C2 Transfer core	R1	C2	Nearby Driver Transfer	FEAT-NDT-10	Present Nearby Transfer Progress and Cancellation	Full	10082-NDT-10-E03	Edge case	Canceling a Consumer Shared Data transfer before Flex receives and applies a complete payload leaves the Receive Data control's prior presentation, the Consumer Document's existing values, and any existing Nearby Driver Link unchanged.	7.0	12.0	6.0	10.0	0.6	FAM-2 (passive-dismiss lock), transport.	M	Cancel vs commit race conditions.	Model transfer as a state machine (connecting → transferring → committed/cancelled) shared by all workflows.	Receiver commits before cancel takes effect: success wins (E01). Ack lost after commit → NDT-13 (E02).		