1. Complexity Table / Fast Lookup

Algorithm/Data Struct	Time	Space	Notes
Hash search/insert/delete	expected $O(1)$, worst $O(n)$	$O(n)$	α=n/m
BST ops	$O(h)$	$O(n)$	h $\log n$ balanced, n worst
Inorder BST	$\Theta(n)$	$O(h)$	sorted output
Insertion sort	best $\Theta(n)$, worst $\Theta(n^2)$	$O(1)$	stable
Merge sort	$\Theta(n \log n)$	$\Theta(n)$	stable
Quicksort randomized	expected $\Theta(n \log n)$	$O(\log n)$	worst $\Theta(n^2)$
Counting sort	$\Theta(n+k)$	$\Theta(n+k)$	integer keys
Heapify	$O(\log n)$	recursion	assumes children heaps
Build heap	$\Theta(n)$	$O(1)$	bottom-up
Heapsort	$\Theta(n \log n)$	$O(1)$	not stable
PQ insert/extract	$O(\log n)$	$O(n)$	heap
BFS	$\Theta(V+E)$	$\Theta(V)$	unweighted shortest paths
DFS	$\Theta(V+E)$	$\Theta(V)$	topo/cycles/SCC
Topological sort	$\Theta(V+E)$	$\Theta(V)$	DAG only
Kosaraju SCC	$\Theta(V+E)$	$\Theta(V+E)$	2 DFS
Union-Find op	$O(\alpha(n))$	$O(n)$	rank+compression
Kruskal	$O(E \log E)$	$O(V)$	sort + DSU
Prim	$O(E \log V)$	$O(V+E)$	PQ
Dijkstra	$O(E \log V)$	$O(V+E)$	no negative edges
Bellman-Ford	$\Theta(VE)$	$O(V)$	negative edges OK
DAG shortest path	$\Theta(V+E)$	$O(V)$	topo order
Ford-Fulkerson	$O(E\lvert f^*\rvert)$	$O(V^2+E)$	integer caps, residual
Edmonds-Karp	$O(VE^2)$	$O(V^2+E)$	BFS residual
Rod cutting	$\Theta(n^2)$	$\Theta(n)$	DP
Matrix chain	$\Theta(n^3)$	$\Theta(n^2)$	DP
LCS	$\Theta(nm)$	$\Theta(nm)$	DP
Knapsack 0/1	$\Theta(nW)$	$\Theta(nW)/\Theta(W)$	pseudo-poly
Coin change	$\Theta(W \cdot \#\text{coins})$	$\Theta(W)$	unbounded

Exam Pattern Matcher

new optimization + choices	DP: state/base/transition/order/answer/proof
local best + exchange	greedy: safe choice + induction
connect all min weight	MST: Kruskal/Prim + cut property
unweighted shortest path	BFS levels
weighted no negative	Dijkstra
negative weights / cycle	Bellman--Ford
dependencies / precedence	DAG + topological order
capacity / matching / disjoint paths	max-flow reduction
expected count	indicators + linearity
online unknown future	competitive ratio vs OPT
min max feasible value	binary search answer + monotone feasible
mutual reachability forbidden	SCC condensation / comp[u]=comp[v]
capacitated assignment	max-flow with integral capacities
tree path/subtree optimum	postorder DP: inside child / through root
tree traversals reconstruct	inorder+post/pre split at root
time-dependent edges	earliest-arrival Dijkstra/events
grid/assignment/paths	bipartite matching / max-flow

Exam Writeup Checklist

Algorithm: input/output, data structs, return value. Correctness: complete invariant/induction/exchange proof, not idea. DP: State, Base, Transition, Order, Answer, Runtime, Space. Bounds: define n, V, E, W; justify loops. Conventions: $<$ vs $\leq$, inclusive/exclusive, 0/1-index, reachable vs global negative cycle.

Proof Bank: Generic Templates

Loop inv. Init true before loop. Maint: one step preserves. Term: invariant + stop condition $\Rightarrow$ answer.

Induction/substitution. Claim upper/lower bound with constants. State IH for all smaller inputs. Substitute IH. Collect terms. Pick constants so inequality holds. Base cases: choose c large enough for all $n < n_0$.

Substitution trap. If $T(n) \leq c\sum_i (a_i n)^p + bn$ and $\sum_i a_i^p = 1$, then $cn^p + bn$ FAILS. No slack absorbs $+bn$. Strengthen: $T(n) \leq cn^p - dn^q$ with lower-order subtraction.

Midterm recurrence. $T(n) = T(4n/5) + T(3n/5) + an$. Guess $\Theta(n^2)$ because $(4/5)^2 + (3/5)^2 = 1$. Lower: $T(n) \geq T(4n/5)+T(3n/5) \geq c((4n/5)^2 + (3n/5)^2) = cn^2$. Upper must be strengthened: assume $T(m) \leq cm^2 - dm$ for all $m < n$. Then $T(n) \leq c(4n/5)^2 - d(4n/5) + c(3n/5)^2 - d(3n/5) + an = cn^2 - 7dn/5 + an \leq cn^2 - dn$ iff $d \geq 5a/2$. Choose d so, then choose c large for base cases.

D&C. Induct on size. Recursive calls solve smaller problems. Combine covers all optimum cases and constructs/chooses correct result.

DP. State meaning. Base correct. Induct in fill order. Transition enumerates all valid first/last choices; dependencies already optimal. Optimal solution uses one enumerated choice; every candidate feasible. Therefore $dp[s]$ optimum. Write answer $= dp[...]$.

Parametric search. Guess answer M. Build feasible(M). Prove monotone: if M works then any larger M works (minimization). Binary search smallest feasible M. Correctness = binary search invariant + feasible predicate exact.

Greedy. Safe choice: for optimum O containing current partial solution, if chosen $e \notin O$, exchange $f \in O$ with e without worsening. Then induct.

Proof Bank: Sorting / Hash / DS

BST inorder. Induct on subtree. Left keys $<$ root, right keys $\geq$ root. IH sorts left/right. Left,root,right sorted and complete.

Rank/interval. Store $size = 1 + size(L) + size(R)$. Rank follows one search path; when going right add $size(L)+1$. Thus $O(h)$. $[a,b] = rank_{\leq}(b) - rank_{<}(a)$.

Heapify. Children are heaps. Swap with larger child if violated; parent fixed. Only swapped child may violate; recurse to leaf. Cost height $O(\log n)$.

BuildHeap. Leaves are heaps. Bottom-up: children already heaps, so Heapify fixes subtree. Runtime: nodes height $h \leq n/2^{h+1}$, total $\sum_h O(h)n/2\hat{}h = O(n)$.

Sorting lower bound. Comparison sort decision tree needs $\geq n!$ leaves. Worst-case comparisons $\geq$ height $\geq \log_2(n!) = \Omega(n \log n)$.

Quicksort exp. Pair compared at most once. $X_{ij} = 1$ if ranks i, j compared. Compare iff first pivot among ranks $i..j$ is i or j, so $P(X_{ij}) = 2/(j-i+1)$. Sum $O(n \log n)$.

Hashing. Single key: for key x, $X_y = 1[h(y) = h(x)]$. Universal hashing gives $E[X_y] \leq 1/m$, so expected chain collisions $\leq (n-1)/m = \Theta(\alpha)$ and search $O(1+\alpha)$. Total collisions: $X = \sum_{i<j} X_{ij}$, $X_{ij} = 1[h(x_i) = h(x_j)]$, hence $E[X] \leq \binom{n}{2}/m = n(n-1)/(2m) = \Theta(n2/m)$. k-collision: $E[\#k\text{-collisions}] \leq \binom{n}{k}/m^{k-1}$. Markov: $P[X \geq 1] \leq E[X]$.

Hash mini. Length-ℓ keys: pair collision prob $1/m^\ell$, so $E[\#collisions] = \binom{n}{2}/m^\ell$; if $m^\ell \geq \binom{n}{2}$ then $P[\exists collision] \leq 1$. Random q-color vertices: edge mono prob $1/q$, so $E[\#mono] = |E|/q$.

DSU. Union by rank attaches smaller rank under larger. Rank increases only on equal-rank merge. Path compression preserves reps and shortens future paths. With both: m ops in $O(m\alpha(n))$.

Proof Bank: Graph Traversal

BFS. Queue processed in nondecreasing distance. Discover v from u: $d[v] = d[u] + 1$. Shorter path would come from smaller-distance vertex processed earlier, so v would already be discovered.

DFS/topo. Directed cycle iff DFS has back edge to GRAY ancestor. DAG has no back edges. For every edge $u \to v$, $f[u] > f[v]$; decreasing finish time is topo order.

DFS edge facts. Parenthesis theorem: finish intervals disjoint or nested; nested iff descendant. White-path theorem: v descendant of u iff when u discovered, there is a white path $u \rightsquigarrow v$.

SCC/Kosaraju. Condensation graph is DAG. First DFS finish order puts source SCCs late. In reversed graph, DFS from highest finish cannot leave its SCC to an unvisited SCC. Each second-pass DFS outputs one SCC.

SCC reachability pairs. $u \rightsquigarrow v$ and $v \rightsquigarrow u$ iff $comp[u] = comp[v]$. For forbidden pair (u, v) reject iff same component. Correct because SCC is maximal mutual reachability. Runtime $O(V+E)$.

DAG SP/LP. Topo order processes every predecessor before vertex. When processing u, $dist[u]$ already final over all paths ending at u; relaxing outgoing edges propagates optimum once. Runtime $\Theta(V+E)$.

Proof Bank: MST / Shortest Paths / Flow

Cut property. Let e be light edge crossing cut respecting A. Take MST $T \supseteq A$ not using e. Add e creates cycle with another crossing edge f. Since $w(e) \leq w(f)$, $T - f + e$ is MST containing $A \cup \{e\}$.

Cycle property. If MST T contains unique heaviest edge e on cycle, remove e; cycle has another edge f reconnecting cut with $w(f) < w(e)$. Then $T - e + f$ cheaper, contradiction.

Kruskal. DSU components define cut respecting chosen edges. Next accepted edge is lightest crossing some component cut. Cut property says safe. Induct until $|V| - 1$ edges.

Prim. $S =$ vertices in tree. Heap chooses lightest edge crossing $(S, V \setminus S)$. Cut property says safe. Add one vertex; repeat.

Dijkstra. $S =$ finalized. Pick outside x with min tentative dist. Any alternative path first crosses from S to outside at (u, v). Since $w \geq 0$, path length $\geq d[u] + w(u,v) \geq d[v] \geq d[x]$. So $d[x]$ final.

Bellman-Ford. After i passes, all shortest paths using $\leq i$ edges are correct. Induct by last edge relaxation. If no negative cycle, shortest simple path has $\leq V - 1$ edges. If pass V improves, reachable negative cycle.

Max-flow. If no augmenting path exists, let S be vertices reachable from s in residual graph. For every edge $u \in S, v \notin S$: $cf(u,v) = 0$, therefore $f(u,v) = c(u,v)$. For every edge $u \notin S, v \in S$: $cf(v,u) = 0$, therefore $f(u,v) = 0$.

Hence net flow crossing cut equals cut capacity: $|f| = c(S,T)$.

Since every flow $\leq$ every cut, flow and cut are both optimal.

Flow cert. Any flow value $\leq$ any cut capacity. Flow value F + cut capacity F proves both optimal.

Bipartite matching flow. Caps 1 force each left/right vertex used at most once. Integral capacities give integral max flow. Unit flow through $l \to r$ is matched pair; every matching gives same-size flow.

Cap assignment flow. Build $s \to$ people cap 1, person $\to$ acceptable item cap 1, item $\to t$ cap capacity. Feasible iff maxflow = #people. Integral flow = assignment; assignment = integral flow.

SP transform. Multiplying every edge weight by $a > 0$ preserves all shortest paths. Adding a to every edge does not: paths with different number of edges get different extra cost.

Resource SP. State graph (v, b) where $b =$ used budget / remaining battery. Add transition only if resource feasible. Run BFS/Dijkstra depending on edge costs. Size $O(VB + EB)$. Correct since every feasible walk corresponds to one state path and vice versa.

2D sorted matrix. Rows/cols sorted. Start top-right. If $A[i,j] > x$, move left; if $A[i,j] < x$, move down. Each step deletes one impossible row/col, so $O(n+m), O(1)$.

Proof Bank: Trees / Exam Reductions

Tree DP. Postorder. Return height/best info from children. Best at u is max(best in left, best in right, best crossing/using u). Induct on subtree: any optimal object either lies fully in one child or uses u.

Tree diameter. Let $h(u) = 1 + \max(h_L, h_R)$, empty height -1. $diam(u) = \max(diam_L, diam_R, h_L + h_R + 2)$. Path either inside one child or crosses through u.

Root path. Longest simple path forced to pass through root: $h(root.left) + h(root.right) + 2$ with empty height -1. Compute heights postorder in $O(n)$.

Tree rebuild. Inorder+postorder: root=last(post); split inorder at root; subtree sizes split postorder; recurse. Preorder+inorder: root=first(pre). Pre+post alone not unique.

Unicyclic spanning trees. Connected graph with $|E| = |V|$ has exactly one cycle C. Every spanning tree = delete exactly one edge of C. Deleting non-cycle edge disconnects; deleting cycle edge breaks only cycle. Hence #spanning trees $= |C|$.

Proof Bank: Online / Random

LRU paging. Cache size k. Phase has $\leq k$ distinct pages; new phase begins at request of $(k+1)$-st distinct. LRU: $\leq k$ misses/phase, because requested page survives until k other distinct pages requested. OPT: ≥ 1 miss/completed phase, because phase + first request of next phase contains $k+1$ distinct pages but cache holds k. Thus LRU $\leq k \cdot \text{OPT} + O(k)$; LRU is k-competitive.

Verbose Proof Micro-Stencils

Correctness opening: Start with a precise claim: after the algorithm terminates, the returned object is feasible and has objective value no worse than any feasible object. Then prove feasibility and optimality separately.

Induction base habit: Say exactly which subproblems are smallest and why their table/return value is correct. Do not write ``trivial'' unless the value is actually shown, e.g. dp[0]=0 or empty subtree height=-1.

Induction step habit: Assume all strict subproblems used by the transition are correct. Show every transition candidate is feasible, and the optimum's first/last choice appears among the candidates.

Exchange proof form: Let O be an optimum agreeing with greedy for as long as possible. If greedy choice g differs from O's next choice o, replace o by g; prove feasibility remains and weight/count is not worse. Contradiction to maximal agreement.

Greedy lower-bound proof: To prove greedy is optimal, also prove a matching lower bound: any solution needs at least X objects/cost. Then show greedy achieves X. Common in interval partitioning and stabbing.

Cut proof exactness: For MST safe edge proofs, the cut must respect already chosen edges A: no edge in A crosses it. Then swapping along the cycle cannot remove an edge of A.

Cycle proof exactness: For MST cycle proofs, removing the heavy edge disconnects T into a cut. The replacement edge on the cycle crosses the same cut, reconnects T, and has smaller/equal weight.

Reduction correctness: Prove both directions: any original solution maps to a feasible constructed solution of same value, and any constructed solution maps back to a valid original solution of same value. Then optimum values equal.

Flow reduction proof: Integral capacities imply an integral max flow. Unit flow through a gadget means the corresponding discrete choice is selected; capacity constraints exactly encode usage limits.

Matching proof: Flow->matching: cap 1 on s->L and R->t gives at most one matched edge per vertex. Matching->flow: send one unit along s-l-r-t for each matched pair.

Min-cut certificate: After max-flow, BFS in residual graph from s gives S. Edges S->T are saturated and T->S carry zero flow, so value crossing cut equals cut capacity.

Shortest path reduction: When adding state dimensions, prove bijection-ish: every feasible original walk corresponds to a path in the state graph, and every state path decodes to a feasible walk.

Dijkstra finality: The key sentence: when x is extracted, any alternative path to x must first leave the finalized set by some edge (u,v); nonnegative weights make that path at least dist[v] >= dist[x].

Bellman-Ford invariant: After i full passes, dist[v] is at most the length of the shortest s->v path using at most i edges, and no smaller value than any such path is needed. Last-edge relaxation proves it.

Negative-cycle proof: If pass V still relaxes an edge reachable from s, the improving walk has V edges, so some vertex repeats; the repeated cycle must have negative total weight.

BFS shortest proof: Use contradiction: let v be first vertex discovered with nonshortest distance. Its predecessor on a shortest path has smaller distance and was processed earlier, so it would have discovered v correctly.

DFS cycle proof: Directed cycle -> during DFS, take the first vertex on the cycle discovered; following the cycle reaches a gray ancestor edge before it finishes. Gray edge -> ancestor path plus edge forms a cycle.

Topo proof: In a DAG DFS has no back edge. For every edge u->v, v finishes before u whether discovered from u or already black. Therefore decreasing finish time respects every edge.

SCC proof: Condensation is a DAG. The second DFS in reverse graph starts from a source of remaining reverse condensation, equivalently a sink/source by finish order, so it cannot escape its SCC.

Binary search invariant: Maintain answer in [l,r]. Mid test discards only values impossible by monotonicity. Termination l=r gives the unique smallest feasible or largest feasible depending on direction.

Feasibility proof: For parametric search, prove feasible(M) is exact, not just sufficient. Usually: greedy uses the minimum possible resources for this M, so if greedy fails no valid solution exists.

Divide-farm proof: For fixed M, greedy makes each segment as long as possible. After t segments greedy covers at least as much prefix as any t-segment valid partition; hence greedy minimizes number of segments.

Interval scheduling proof: Let g be earliest finishing interval. For any optimum, replace its first interval by g. Since g finishes no later, all later intervals remain compatible; size unchanged. Induct on suffix.

Weighted interval DP proof: Optimal solution for first i intervals either skips i or takes i. If it takes i, all remaining chosen intervals lie among first p(i). These two cases are exhaustive and disjoint.

Travel-pass DP proof: In an optimum covering first uncovered day d[i], the bought pass has one of the allowed lengths L and covers exactly until d[i]+L-1. The remaining subproblem starts at next(i,L).

Knapsack proof: For item i, optimum either excludes it, giving dp[i-1][w], or includes it, forcing capacity w-weight[i] for previous items. No third possibility exists.

LCS proof: For prefixes i,j: if last chars match, some optimum can use them and reduce to i-1,j-1. If they differ, at least one last char is not used, giving max of the two smaller prefixes.

Matrix-chain proof: The final multiplication splits the product at some k. Costs before that split are independent subchains, so optimality follows by trying every k and using optimal subsolutions.

Rod-cutting proof: Look at the leftmost piece length i in an optimal cutting. The remainder length n-i must itself be cut optimally, else replace it and improve total revenue.

Optimal BST proof: Choosing root r increases depth of every key in left/right subtrees by 1, adding total interval probability w[i,j]. Subtrees are independent optimal BST subproblems.

Tree DP proof: Any optimal object in subtree u either lies completely in one child subtree or uses u / crosses between children. The recurrence takes the max over exactly these cases.

Tree reconstruction proof: Root position in inorder uniquely separates left and right key sets. Subtree sizes then uniquely split preorder/postorder blocks, so recursion reconstructs the only tree.

Heapify proof: Before heapify, both child subtrees are heaps. Swapping with the larger child fixes the parent; the only possible violation moves down one level. Eventually a leaf is reached.

Build-heap proof: Process internal nodes from bottom to top. When heapify(i) runs, both children already root heaps, so it makes subtree i a heap. At the root the whole array is a heap.

Insertion sort proof: Before iteration j, prefix A[0..j) is sorted and contains the original prefix elements. Inner loop shifts larger elements right; inserting key restores sorted prefix A[0..j+1).

Merge proof: Loop invariant: output contains the smallest consumed elements from both sorted halves, in sorted order. Taking the smaller head preserves sortedness; copying leftovers completes all elements.

Quicksort proof: Partition puts pivot in final rank: all left <= pivot, all right > pivot. Recursive calls sort the two sides; concatenating left,pivot,right is sorted and complete.

Counting-sort proof: Prefix count C[x] equals number of input keys <=x. Scanning input right-to-left places each key at the last free position of its value, giving sorted stable output.

Hash expectation proof: Define one indicator per bad pair/event. Compute probability for a fixed pair, then sum expectations. Independence between different pairs is not needed for the expectation.

Quicksort expectation proof: Elements of ranks i,j are compared iff the first pivot chosen among ranks i..j is one of them. That probability is 2/(j-i+1); summing pairs gives O(n log n).

Lower-bound proof: For comparison sorting, leaves of decision tree must distinguish all n! input orders. A binary tree of height h has at most 2^h leaves, so h>=log(n!).

Online upper proof: Partition the request sequence into phases. Prove ALG cost per phase <=A and OPT cost per phase >=B, then sum phases and absorb boundary phases into constant c.

Online lower proof: Adversary observes the deterministic algorithm's action and chooses when to stop/continue. Compare on the same final sequence against offline OPT.

Ski-rental proof: If T<=B, rent-then-buy pays T=OPT. If T>B, it pays at most B rent plus B buy, while OPT pays B; ratio <=2.

LRU phase proof: In one phase there are at most k distinct pages, so after a page is requested, LRU will not evict it before k other distinct pages appear, which would start a new phase.

Experts potential proof: Track total weight W. Algorithm mistake means wrong side has at least half W, so W shrinks by factor <=(1+beta)/2. Best expert gives lower bound beta^m*.

Prophet threshold proof: Separate value into threshold part tau*P[accept] and overshoot part. If all earlier variables miss threshold, each positive overshoot has chance to be captured; combine with tau=z/2.

Secretary proof: Condition on best arriving at position i>r. Success iff best among first i-1 positions is in sample. Probability sum over i: (1/n)*(r/(i-1)).

Runtime proof: Count objects actually processed: each vertex enqueued once, each edge scanned once, each DP state filled once, each heap operation O(log size). State dimensions after reductions.

Off-by-one proof: State intervals explicitly. Half-open [l,r) usually makes size r-l, empty when l=r, and split [l,m),[m,r). Closed [i,j] needs base i>j or i=j.

Final answer habit: After proof, write the exact returned value: dp[n], dp[1], dist[t], maxflow value, selected edges, or reconstructed choices. Missing this often loses points.

2. Complexity / Asymptotics

$\log n \ll \sqrt{n} \ll n \ll n \log n \ll n^2 \ll n^3 \ll 2^n \ll n! \ll n^n$

$O(g)$: $f \leq cg$ eventually. $\Omega(g)$: $f \geq cg$. $\Theta(g) = O \cap \Omega$. $o(g)$: $f/g \to 0$. $\omega(g)$: $f/g \to \infty$. Stirling: $n! \sim \sqrt{2\pi n}(n/e)^n$, so $\log(n!) = \Theta(n \log n)$.

Useful sums:

$\sum_{i=1}^n i = \frac{n(n+1)}{2} = \Theta(n^2)$, $\sum_{i=0}^{\log n} n = n \log n$, $\sum_{i\geq 0} 2^{-i} = 2$, $\sum_{h\geq 0} h2^{-h} = 2$

Master / recurrence solver:

Master: $T(n) = aT(n/b) + f(n)$. Let $d = \log_b(a)$. Compare $f(n)$ with n^d.

f smaller: $f = O(n^{d-\varepsilon})$ $T = \Theta(n^d)$

same: $f = \Theta(n^d \log^k n)$ $T = \Theta(n^d \log^{k+1} n)$

f bigger: $f = \Omega(n^{d+\varepsilon})$ $T = \Theta(f)$ if regularity

Fast mental version if $f = n^k$:

$k < d$	leaves win	$\Theta(n^d)$
$k = d$	tie/layers equal	$\Theta(n^d \log n)$
$k > d$	root/work wins	$\Theta(n^k)$

Non-equal splits: $T = \sum_i a_i T(b_i n) + \Theta(n^k)$. Find p s.t. $\sum_i a_i b_i^p = 1$.

$p > k$	leaves win	$\Theta(n^p)$
$p = k$	tie	$\Theta(n^p \log n)$
$p < k$	root/work wins	$\Theta(n^k)$

Trap: if $\sum_i a_i b_i^p = 1$, plain cn^p proof has no slack; use $cn^p - dn^q$.

Akra--Bazzi mini: $T(n) = \alpha T(an) + \beta T(bn) + \Theta(n^d)$. Find p: $\alpha a^p + \beta b^p = 1$. Then $p > d \Rightarrow \Theta(n^p)$, $p = d \Rightarrow \Theta(n^d \log n)$, $p < d \Rightarrow \Theta(n^d)$. Recurrences / runtimes:

```
BinSearch: T(n/2)+1 -> log n
Merge/MaxSub: 2T(n/2)+n -> n log n
Naive MM: 8T(n/2)+n^2 -> n^3
Strassen: 7T(n/2)+n^2 -> n^log2(7)
Heapify: T(2n/3)+1 -> log n
QSort(w): T(n-1)+n -> n^2
QSort(b): 2T(n/2)+n -> n log n
BF: (V-1)E relax -> VE
BFS/DFS: V+E

T(n/2)+1->log n     T(n/2)+n->n
2T(n/2)+1->n        2T(n/2)+n->n log n
3T(n/2)+n->n^log2(3)
7T(n/2)+n^2->Strassen
8T(n/2)+n^2->n^3
T(n-1)+n->n^2
```

3. Basic Data Structures

Stack / Queue / Linked List

Stack	push/pop/top	$O(1)$, array end, underflow if empty
Queue	enqueue/dequeue	$O(1)$ with circular array / deque
Linked list	search/insert/delete	search $O(n)$, known-node delete $O(1)$

Doubly linked list insert head: `x.next=head; if head!=NIL head.prev=x; head=x; x.prev=NIL`. Delete known node: reconnect `prev.next` and `next.prev`; finding node still $O(n)$.

Hash Tables

Idea: bucket $h(key) \bmod m$. Collisions: chaining / probing. Load factor $\alpha = n/m$.

Hash ops: insert/delete expected O(1), search expected O(1+alpha), all worst O(n); m=Theta(n) => alpha=Theta(1). Expected total collisions: $X = \sum_{i<j} X_{ij}$, where $X_{ij} = 1[h(x_i) = h(x_j)]$. Universal hashing gives P[Xij=1]<=1/m, so E[X]=sum E[Xij] <= C(n,2)/m = n(n-1)/(2m)=Theta(n2/m). For one key: $\mathbb{E}[\#\text{collisions}] \leq (n-1)/m = \Theta(\alpha)$, hence expected search $O(1+\alpha)$. Traps: HashMap/HashSet $O(1)$ is expected/amortized, not worst-case. Bad hashing / all collisions $\Rightarrow O(n)$.

k-collision stencil: $X_S = 1$ if fixed k-set collides. $P[X_S = 1] \leq 1/m^{k-1}$. $E[X] = \sum_{|S|=k} E[X_S] \leq \binom{n}{k}/m^{k-1}$. If need existence prob: $P[X \geq 1] \leq E[X]$.

Binary Search Trees

Binary search (sorted array):

```
fn binary_search(a: Vec<_>,x){
  l=0; r=a.len();
  while l<r {
    m=(l+r)/2;
    if a[m]==x { return Some(m); }
    if a[m]<x  { l=m+1; }
    else       { r=m; }
  }//lower_bound = first >= x:
  None//First position where the value is >= x.
} //upper_bound = first > x:
//First position where the value is > x.
```

BST property: BST property: all keys in L(x) < x.key; all keys in R(x) >= x.key.

BST ops search/insert/delete/min/max/succ/pred O(h); inorder Theta(n); balanced h=Theta(log n), degenerate h=Theta(n).

```
search(x,k):
  while x != NIL and x.key != k:
    if k < x.key: x = x.left
    else:         x = x.right
  return x

min(x): while x.left  != NIL: x = x.left; ret x
max(x): while x.right != NIL: x = x.right;ret x

successor(x):
  if x.right != NIL: return min(x.right)
  y = x.parent
  while y != NIL and x == y.right:
    x = y
    y = y.parent
  return y
insert(T,z):
  y=NIL; x=T.root
  while x!=NIL:
    y=x
    if z.key<x.key: x=x.left else: x=x.right
  z.parent=y
  if y==NIL: T.root=z
  else if z.key<y.key: y.left=z
  else: y.right=z
transplant(T,u,v):
  if u.parent==NIL: T.root=v
  else if u==u.parent.left: u.parent.left=v
  else: u.parent.right=v
  if v!=NIL: v.parent=u.parent

delete(T,z):
  if z.left==NIL: transplant(T,z,z.right)
  else if z.right==NIL: transplant(T,z,z.left)
  else:
    y=min(z.right)
    if y.parent!=z:
      transplant(T,y,y.right);
      y.right=z.right; y.right.parent=y
    transplant(T,z,y);
    y.left=z.left; y.left.parent=y
```

Delete cases: no left, no right, or replace by successor. All $O(h)$.

Traversals:

```
inorder(x):  if x!=NIL: inorder(x.left); visit(x); inorder(x.right)
preorder(x): if x!=NIL: visit(x); preorder(x.left); preorder(x.right)
postorder(x):if x!=NIL: postorder(x.left); postorder(x.right); visit(x)
```

inorder(BST)=sorted order.

Augmented BST / rank queries: sz=1+L+R, rank O(h). [a,b]=r<=b-r<a, (a,b]=r<=b-r<=a, [a,b)=r<b-r<a, (a,b)=r<b-r<=a.

4. Sorting Algorithms

Insertion Sort

In-place, stable. Invariant: before iteration j, prefix $A[0..j)$ sorted.

```
fn insertion_sort(a: &mut Vec<i32>) {
  for j in 1..a.len() {
    let key = a[j];
    let mut i = j;
    while i > 0 && a[i-1] > key {
      a[i] = a[i-1]; i -= 1;
    }
    a[i] = key;
  } // Best Theta(n), worst/avg Theta(n^2), space O(1)
}
```

Merge Sort

Stable, simple version uses Theta(n) temp.

```
fn merge_sort(a,l,r){
  if r-l <= 1 { return; }
  let m=(l+r)/2;
  merge_sort(a,l,m);
  merge_sort(a,m,r);
  merge(a,l,m,r);
}
fn merge(a,l,m,r){
  let (mut i,mut j)=(l,m); let mut t=Vec::new();
  while i<m && j<r {
    if a[i] <= a[j] { t.push(a[i]); i+=1; }
    else { t.push(a[j]); j+=1; }
  }
  while i<m { t.push(a[i]); i+=1; }
  while j<r { t.push(a[j]); j+=1; }
  for k in 0..t.len(){ a[l+k]=t[k]; }
}
```

T(n)=2T(n/2) + Theta(n) = Theta(n log n)

Quicksort

In-place. Partition invariant: A[l..i]<= p, A[i+1..j]>p, unknown after j, pivot at r.

```
fn partition(a,l,r)->usize{
  let p=a[r]; let mut i=l;
  for j in l..r {
    if a[j] <= p { a.swap(i,j); i+=1; }
  }
  a.swap(i,r); i
}
fn quicksort(a,l,r){
  if l>=r { return; }
  let q=partition(a,l,r);
  if q>0 { quicksort(a,l,q-1); }
  quicksort(a,q+1,r);
}
```

Balanced/expected randomized Theta(n log n), worst Theta(n^2), stack expected O(log n) worst O(n).

Counting Sort / Linear Sorting

Integer keys $0..k$, stable with prefix sums, not comparison-based.

```
fn counting_sort(a:&Vec<usize>, k:usize)->Vec<usize>{
  let mut c=vec![0;k+1]; let mut out=vec![0;a.len()];
  for &x in a { c[x]+=1; }
  for i in 1..=k { c[i]+=c[i-1]; }
  for idx in (0..a.len()).rev(){
    let x=a[idx]; c[x]-=1; out[c[x]]=x;
  }
  out
}
```

$\Theta(n+k)$ time/space. Stable with prefix sums. Needs bounded integer keys.

5. Heaps / Priority Queues / Heapsort

Max-Heapify

Assume children subtrees are heaps; only $A[i]$ may violate. 0-index:

```
fn max_heapify(a:&mut Vec<i32>, i:usize, heap_size:usize){
  let (l,r)=(2*i,2*i+1); let mut largest=i;
  if l<heap_size && a[l]>a[largest] { largest=l; }
  if r<heap_size && a[r]>a[largest] { largest=r; }
  if largest!=i { a.swap(i,largest); max_heapify(a,largest,heap_size); }
}
```

$O(height(i)) \leq O(\log n)$. Trap: during heapsort, heap_size $\neq$ a.len().

Build Max Heap

```
fn build_max_heap(a:&mut Vec<i32>){
  let n=a.len();
  for i in (0..(n/2)).rev(){ max_heapify(a,i,n); }
}
```

Tight: nodes height $h \leq n/2^{h+1}$, cost $O(h)$, so $\sum_h nh/2\hat{}h = O(n)$; hence BuildHeap $\Theta(n)$, not $\Theta(n \log n)$.

Heapsort

```
fn heapsort(a:&mut Vec<i32>){
  build_max_heap(a); let mut h=a.len();
  while h>1 { a.swap(0,h-1); h-=1; max_heapify(a,0,h); }
}
```

Build $\Theta(n)$ + n extracts $O(\log n)$ = $\Theta(n \log n)$, space $O(1)$, not stable.

Priority Queue

```
fn heap_extract_max(a:&mut Vec<i32>)->Option<i32>{
  if a.is_empty(){return None;}
  let ans=a[0]; let last=a.pop().unwrap();
  if !a.is_empty(){ a[0]=last; max_heapify(a,0,a.len()); }
  Some(ans)
}
fn heap_increase_key(a:&mut Vec<i32>, mut i:usize, key:i32){
  if key<a[i]{return;} a[i]=key;
  while i>0 { let p=(i-1)/2; if a[p]>=a[i]{break;} a.swap(i,p); i=p; }
}
fn max_heap_insert(a:&mut Vec<i32>, key:i32){
  a.push(i32::MIN); heap_increase_key(a,a.len()-1,key);
}//Ops insert/extract/increase-key O(log n)
```

6. Divide & Conquer Algorithms

Karatsuba Multiplication

$$x = x_h B^m + x_l, \quad y = y_h B^m + y_l$$
$$a = x_h y_h, \quad b = x_l y_l, \quad c = (x_h + x_l)(y_h + y_l)$$
$$xy = aB^{2m} + (c - a - b)B^m + b$$

3 recursive multiplications.

3 recursive multiplications: $T(n) = 3T(n/2) + \Theta(n) = \Theta(n^{\log_2 3}) \approx \Theta(n^{1.585})$.

Maximum Sum Subarray

Problem:
Input A[0..n) Output max sum contiguous nonempty subarray
D&C idea:
best subarray is:

- entirely left
- entirely right
- crosses middle

```
fn max_crossing(a,l,m,r){
  // left suffix [l,m)
  left_sum=-INF;
  sum=0;
  for i in (l..m).rev(){
    sum+=a[i];
    left_sum=max(left_sum,sum);
  }
  // right prefix [m,r)
  right_sum=-INF;
  sum=0;
  for j in m..r {
    sum+=a[j];
    right_sum=max(right_sum,sum);
  }
  left_sum+right_sum
}
fn max_subarray(a,l,r){
  if r-l==1 {return a[l]}
  m=(l+r)/2;
  left=max_subarray(a,l,m);
  right=max_subarray(a,m,r);
  cross=max_crossing(a,l,m,r);
  max(left,max(right,cross))
}
```

Complexity: T(n)=2T(n/2)+Theta(n)=Theta(nlog n)

Linear Kadane:

```
fn kadane(a: &Vec<i32>) -> i32 {
    let mut best: i32 = a[0];
    let mut cur: i32 = a[0];
    for i in 1..a.len() {
        cur = a[i].max(cur + a[i]);
        best = best.max(cur);
    }
    best
}
```

Kadane invariant: cur[i] = max(A[i], cur[i-1]+A[i]), best[i]=max(best[i-1],cur[i])

Matrix Multiplication

Naive:

```
for i in 0..n {for j in 0..n {for k in 0..n {c[i][j] += a[i][k] * b[k][j];}}}
```

Complexity: Theta(n^3), Space: Theta(n^2)

D&C block formula (8 mults): C11=A11B11+A12B21, C12=A11B12+A12B22, C21=A21B11+A22B21, C22=A21B12+A22B22. Hence T(n)=8T(n/2)+Theta(n^2)=Theta(n^3).

Strassen (7 mults): M1=(A11+A22)(B11+B22), M2=(A21+A22)B11, M3=A11(B12-B22), M4=A22(B21-B11), M5=(A11+A12)B22, M6=(A21-A11)(B11+B12), M7=(A12-A22)(B21+B22). C11=M1+M4-M5+M7, C12=M3+M5, C21=M2+M4, C22=M1-M2+M3+M6.

```
fn strassen(A,B,n){
  if n==1 { return A*B }
  split A,B into A11..A22,B11..B22;
  M1..M7 = strassen(formulas above);
  C11=M1+M4-M5+M7; C12=M3+M5;
  C21=M2+M4;       C22=M1-M2+M3+M6;
  combine(C11,C12,C21,C22)
}
```

T(n)=7T(n/2)+Theta(n^2)=Theta(n^log2 7) $\approx$ Theta(n^2.807).

7. Dynamic Programming

Rod Cutting

revenue$[\ell]$ = best revenue length ℓ, first$[\ell]$ = first cut. Rod cutting: revenue[0]=0; revenue[l]=max over 1<=c<=l of price[c]+revenue[l-c].

```
fn rod_cut(price:Vec<i32>, n:usize){
  revenue=vec![0;n+1]; first=vec![0;n+1];
  for length in 1..=n {revenue[length]=-INF;
    for cut in 1..=length {
      candidate=price[cut]+revenue[length-cut];
      if candidate>revenue[length] {
        revenue[length]=candidate; first[length]=cut
      }
    }
  }
  (revenue,first)
}
```

Reconstruct: output `first[length]`, set `length-=first[length]`. Runtime $\Theta(n^2)$.

Matrix Chain Multiplication

Matrix i: $p_i \times p_{i+1}$. $dp[i][j]$ = min cost for $A_i \cdots A_j$. MCM recurrence: dp[i][i]=0; dp[i][j]=min over i<=k<j of dp[i][k]+dp[k+1][j]+p[i]*p[k+1]*p[j+1].

```
fn matrix_chain(p:Vec<usize>){     // optimal parenthesization
  n=p.len()-1; dp=vec![vec![0;n];n]; split=vec![vec![0;n];n];
  for len in 2..=n {for i in 0..=n-len {
    j=i+len-1; dp[i][j]=INF;
    for k in i..j {
      cost=dp[i][k]+dp[k+1][j]+p[i]*p[k+1]*p[j+1];
      if cost<dp[i][j] {dp[i][j]=cost; split[i][j]=k}
    }
  }}
  (dp,split)
}
```

Increasing chain length. $\Theta(n^2)$ states $\times \Theta(n)$ splits $= \Theta(n^3)$.

Optimal BST

Sorted keys K_i with successful probs p_i; optional unsuccessful q_i. $e[i][j] =$ min expected cost for subtree $i..j$, $w[i][j] =$ prob mass, $root[i][j] =$ best root. OBST: e[i][i-1]=0, w[i][i-1]=q[i-1]; e[i][j]=min over root r in [i,j] of e[i][r-1]+e[r+1][j]+w[i][j].

```
fn optimal_bst(p,q,n){
  for i in 1..=n+1 {e[i][i-1]=0; w[i][i-1]=q[i-1]}
  for len in 1..=n {for i in 1..=n-len+1 {
    j=i+len-1; e[i][j]=INF; w[i][j]=w[i][j-1]+p[j]+q[j];
    for r in i..=j {
      cost=e[i][r-1]+e[r+1][j]+w[i][j];
      if cost<e[i][j] {e[i][j]=cost; root[i][j]=r}
    }
  }}
  (e,root)
}
```

Runtime Theta(n^3), space Theta(n^2).

Longest Common Subsequence

$dp[i][j]$ = LCS length of $A[0..i)$, $B[0..j)$. LCS: dp[0][*]=dp[*][0]=0. If A[i-1]==B[j-1]: dp[i][j]=1+dp[i-1][j-1]; else max(up,left).

```
fn lcs(a:Vec<char>, b:Vec<char>){
  n=a.len(); m=b.len();
  dp=vec![vec![0;m+1];n+1];
  for i in 1..=n {for j in 1..=m {
    dp[i][j]=if a[i-1]==b[j-1]
      {1+dp[i-1][j-1]}
      else {dp[i-1][j].max(dp[i][j-1])}
  }}
  dp[n][m]
}
fn lcs_reconstruct(a,b,dp){
  i=a.len(); j=b.len(); ans=vec![];
  while i>0 && j>0 {
    if a[i-1]==b[j-1] {
      ans.push(a[i-1]); i-=1; j-=1
    }
    else if dp[i-1][j]>=dp[i][j-1] {i-=1}
    else {j-=1}
  }
  ans.reverse(); ans
}
```

$\Theta(nm)$ time, $\Theta(nm)$ or rolling $\Theta(m)$ space. Equal $\to$ diagonal+1; unequal $\to$ max(up,left).

Knapsack 0/1

$dp[i][c]$ = best value using first i items, capacity c. 0/1 knapsack: dp[i][c]=max(skip dp[i-1][c], take v[i-1]+dp[i-1][c-w[i-1]]) if w[i-1]<=c.

```
fn knapsack(w:Vec<usize>, v:Vec<i32>, cap:usize){ // choose item at most once
  n=w.len(); dp=vec![vec![0;cap+1];n+1];
  for i in 1..=n {for c in 0..=cap {
    dp[i][c]=dp[i-1][c];
    if w[i-1]<=c {
      dp[i][c]=dp[i][c].max(v[i-1]+dp[i-1][c-w[i-1]])
    }
  }}
  dp[n][cap]
}
// 1D 0/1: capacity descending. Unbounded: capacity ascending.
```

$\Theta(nW)$ pseudo-polynomial.

Coin Change / Change-Making

Coin change: mincoins[0]=0; mincoins[x]=min over coin<=x of 1+mincoins[x-coin].

```
fn coin_change(coins:Vec<usize>, target:usize){ // unlimited coins
  mincoins=vec![INF;target+1]; mincoins[0]=0;   // min number of coins
  for amount in 1..=target {for coin in coins {
    if coin<=amount {
      mincoins[amount]=mincoins[amount].min(1+mincoins[amount-coin])
    }
  }}
  mincoins[target]
}
```

Runtime $\Theta(target \cdot \#coins)$.

Longest Increasing Subsequence

Quadratic: LIS $O(n^2)$: $dp[i] = 1 + \max\{dp[j] : j < i, a[j] < a[i]\}$; answer=$\max dp$.

```
fn lis_n2(a:Vec<i32>){
  dp=vec![1;a.len()];
  for i in 0..a.len(){for j in 0..i{
    if a[j]<a[i]{dp[i]=dp[i].max(1+dp[j])}
  }}
  max(dp)
}
fn lis_nlogn(a:Vec<i32>){
  tails=vec![]; // min tail of length len
  for x in a {
    l=0; r=tails.len();
    while l<r {m=(l+r)/2;
      if tails[m]<x {l=m+1}else{r=m}}
    if l==tails.len(){tails.push(x)}
    else{tails[l]=x}
  }
  tails.len()
}
```

DAG Longest Path

Input `adj: WGraph`. Topological order; max-relaxation; negative weights OK because no cycles.

```
fn dag_longest(adj:WGraph, source:usize){
  n=adj.len(); dist=vec![-INF;n]; parent=vec![None;n]; dist[source]=0;
  for u in topo(adj) {if dist[u]!=-INF {for (v,w) in adj[u] {
    if dist[u]+w>dist[v] {dist[v]=dist[u]+w; parent[v]=Some(u)}
  }}}
  dist
}
```

Runtime $\Theta(V+E)$.

8. Graph Representation / Types

Use these names everywhere:

```
type Graph  = Vec<Vec<usize>>;        // adj[u] = neighbors v
type WGraph = Vec<Vec<(usize,i32)>>;  // adj[u] = (v,weight)
struct Edge { u:usize, v:usize, w:i32 }
type EdgeList = Vec<Edge>;
```

adj list	space $\Theta(V+E)$	scan neighbors $\Theta(\deg u)$
adj matrix	space $\Theta(V^2)$	edge lookup $\Theta(1)$, scan $\Theta(V)$
edge list	space $\Theta(E)$	Bellman-Ford/Kruskal scans all edges

9. BFS

Input `adj: Graph`. Unweighted shortest paths / levels / components / bipartite. Runtime $\Theta(V+E)$.

```
fn bfs(adj:Graph, source:usize){
  n=adj.len(); // shortest path
  dist=vec![INF;n]; //in unweighted graph
  parent=vec![None;n];// levels, components
  queue=VecDeque::new();
  dist[source]=0;
  queue.push\_back(source);

  while let Some(u)=queue.pop_front(){
    for v in adj[u] {
      if dist[v]==INF {
        dist[v]=dist[u]+1;
        parent[v]=Some(u);
        queue.push\_back(v);
      }
    }
  }
  (dist,parent)
}
fn bipartite(adj:Graph){ // 2-coloring
  n=adj.len(); color=vec![-1;n];
  queue=VecDeque::new();
  for s in 0..n {  // false iff odd cycle
    if color[s]!=-1 {continue}
    color[s]=0; queue.push\_back(s);
    while let Some(u)=queue.pop_front(){
      for v in adj[u] {
        if color[v]==-1 {
          color[v]=1-color[u];
          queue.push\_back(v);
        }
        else if color[v]==color[u] {ret false}
      }
    }
  }
  true
}
```

Invariant: queue processed in nondecreasing distance. First discovery gives shortest unweighted distance. If a shorter path to v existed, its predecessor would have been processed earlier, so v would already be discovered.

Uses: unweighted shortest path, levels, connected components, bipartite test.

Path reconstruction: follow parent$[t]$ backward until source, then reverse.

10. DFS / Topological Sort / SCC

Input `adj: Graph`. Colors: WHITE/GRAY/BLACK. Runtime $\Theta(V+E)$.

```
fn dfs(adj:Graph){  // topo, cycle detection, SCC
  n=adj.len(); color=vec![WHITE;n]; parent=vec![None;n]; time=0;
  fn visit(u:usize){
    time+=1; discover[u]=time; color[u]=GRAY;
    for v in adj[u] {
      if color[v]==WHITE {parent[v]=Some(u); visit(v)}
    }
    color[u]=BLACK; time+=1; finish[u]=time;
  }
  for u in 0..n {if color[u]==WHITE {visit(u)}}
}
```

Directed edges: tree = white target; back = gray ancestor; forward/cross = black. Undirected: only tree/back; cycle test = visited neighbor $\neq$ parent. DFS times: d[u]<d[v]<f[v]<f[u] => descendant/tree/forward; d[v]<d[u]<f[u]<f[v] => back to ancestor/cycle; disjoint intervals => cross. Directed cycle detection: edge to GRAY vertex $\Leftrightarrow$ back edge $\Leftrightarrow$ directed cycle. Edge to BLACK does not prove a cycle.

Topological Sort

DAG order: every edge $u \to v$ has u before v. DFS = decreasing finish times.

```
fn topo_dfs(adj:Graph){
  n=adj.len(); seen=vec![false;n]; order=vec![];
  fn visit(u:usize){
    seen[u]=true;
    for v in adj[u]{if !seen[v]{visit(v)}}
    order.push(u)
  }
  for u in 0..n {if !seen[u]{visit(u)}}
  order.reverse(); order
}
fn topo_kahn(adj:Graph){
  n=adj.len(); indeg=vec![0;n];
  queue=VecDeque::new(); order=vec![];
  for u in 0..n {for v in adj[u]{indeg[v]+=1}}
  for u in 0..n {if indeg[u]==0 {
    queue.push\_back(u)}}
  while let Some(u)=queue.pop_front(){
    order.push(u);
    for v in adj[u]{
      indeg[v]-=1;
      if indeg[v]==0{queue.push\_back(v)}
    }
  }
  if order.len()==n {Some(order)} else {None}
}//Kahn returns `None` iff
 //not all vertices are output.
```

Strongly Connected Components

SCC: $u \leftrightsquigarrow v$. Kosaraju = DFS finish order, reverse graph, DFS in decreasing finish order.

```
fn kosaraju(adj:Graph){   // SCC. DFS order ->
  order=dfs_finish_order(adj); rev=reverse_graph(adj);
  seen=vec![false;n]; comps=[]; //-> reverse graph
  for source in order.rev() {
    if seen[source]{continue}
    comp=[]; stack=[source]; seen[source]=true;
    while let Some(u)=stack.pop(){
      comp.push(u);
      for v in rev[u]{
        if !seen[v]{seen[v]=true; stack.push(v)}
      }
    }
    comps.push(comp)
  }
  comps
}
```

Runtime: Theta(V+E).

11. Union-Find / Disjoint Sets

Forest of trees. parent$[x]$ points upward. Root is representative. rank$[x]$ upper-bounds height.

```
struct DSU {
  parent: Vec<usize>,
  rank: Vec<usize>,
}
impl DSU{
  fn new(n){DSU{parent:(0..n).collect(),
    rank:vec![0;n]}}

  fn find(&mut self,x){
    if self.parent[x]!=x {
      self.parent[x]=self.find(self.parent[x])
    }
    self.parent[x]
  }
  fn union(&mut self,x,y){
    let (mut rx,mut ry)=(self.find(x),
      self.find(y));
    if rx==ry {return false}
    if self.rank[rx] < self.rank[ry]
      { swap(rx,ry) }
    self.parent[ry]=rx;
    if self.rank[rx]==self.rank[ry] {
      self.rank[rx]+=1;
    }
    true
  }
}
```

Complexities: LL weighted union O(m + n log n), forest + union by rank + path compression O(m alpha(n)). alpha(n)<= 5 in practice

```
//Connected components:
let mut dsu: DSU = DSU::new(n);
for (u, v) in edges {
    dsu.union(u, v);
}
if dsu.find(a) == dsu.find(b) {
    // same component
}
//Cycle detection (undirected):
let mut dsu: DSU = DSU::new(n);
for (u, v) in edges {
    if !dsu.union(u, v) {
        // cycle
    }
}
```

12. Minimum Spanning Trees

Chooser

sparse graph — Kruskal often easiest
dense graph — Prim often easier
disconnected graph — forest, no MST
<= |E|=|V|-1

tree: connected + acyclic connected graph: tree

MST: spanning tree with min total edge weight

Cut / Cycle Properties

Cut $(S, V-S)$: edge crosses cut iff one endpoint in S, one outside. Light edge = minimum-weight crossing edge.

Cut property: if cut respects chosen edge set A, then a light crossing edge is safe.

Cycle property: for any cycle, a heaviest edge on that cycle is excluded from some MST. If weights distinct, the heaviest edge is in no MST.

Kruskal

```
struct Edge {u,v,w; i32,}
fn mst_edges(n: Vec<Edge> -> ...;
let mut dsu: DSU = DSU::new(n);
let mut mst: Vec<Edge> = Vec::new();
let mut total: i32 = 0;
fn kruskal(n,edges: Vec<Edge>) // MST
  sort_by_weight(edges); dsu=DSU::new(n);
  total=0; mst=[]                    (total,mst)
}
```

Complexity: sort: O(E log E) DSU: O(E alpha(V)) total: O(E log E)

Output condition: if `mst.len()==n-1`, it is an MST; otherwise graph disconnected and result is a forest.

Traps:

- If graph disconnected ⟶ MST does not exist; returns forest.
- Need sort by weight increasing.
- Skip edge if endpoints already connected.

Prim

```
let mut adj: Vec<Vec<(usize, i32)>>
  = vec![Vec::new(); n];
let mut used: Vec<bool> = vec![false; n];
let mut heap: BinaryHeap<Reverse<(i32, usize)>>
  usize, usize)>> = BinaryHeap::new();
// (weight, vertex, parent)          // MST
fn prim(adj,s){ // min crossing edge  // cnt==n if disconnected */
  heap.push((0,s)); total=0; cnt=0;  total
  while let Some((w,u))=heap.pop_min(){ }
```

Complexity:

- Binary heap lazy: $O(E \log E)$; for dense graphs $E \leq V^2$, so $O(E \log V)$.

Output condition: if `cnt==n`, `total` is MST weight; otherwise graph disconnected.

MST Reduction Stencils

Roads+airports: add supernode s; edge s–city cost=airport; old road edges unchanged; MST in augmented graph. Add one new vertex given old MST T; run MST on T plus new incident edges; old non-tree edges still unnecessary by cut/cycle property. Points/routes: complete graph on points, edge cost=squared distance; run Kruskal/Prim. E=Theta(n^2), time O(n^2 log n).

13. Shortest Paths

Chooser

unweighted	BFS
DAG	topo DP
weights ≥ 0	Dijkstra
negative edges	Bellman-Ford

Relaxation

Relax edge (u,v,w): if dist[u]!=INF and dist[v] > dist[u]+w, set dist[v]=dist[u]+w and parent[v]=u.

Dijkstra

```
fn dijkstra(adj:&Graph, source:usize){
  // all weights >= 0
  n=adj.len(); dist=vec![INF;n];
  parent=vec![None;n];
  heap=MinHeap::<(i32,usize)>::new();
  dist[source]=0;
  heap.push((0,source));
  while let Some((du,u))=heap.pop(){
    if du!=dist[u] {continue} // stale
  }
}
```

Runs $O((V+E)\log V)$. Requires all weights ≥ 0; negative edges break it.

Bellman-Ford

Input `edges`: EdgeList`. Negative edges OK; detects reachable negative cycles.

```
fn bellman_ford(n,edges,source){
  dist=vec![INF;n]; parent=vec![None;n];
  dist[source]=0;
  for _ in 0..n-1 { changed=false;
    for e in &edges {
      if dist[e.u]!=INF &&
         dist[e.v]>dist[e.u]+e.w {
        dist[e.v]=dist[e.u]+e.w;
        parent[e.v]=Some(e.u);
        changed=true;
      }
    }
    if !changed {break}
  }
  for e in &edges {
    if dist[e.u]!=INF &&
       dist[e.v]>dist[e.u]+e.w {
      return None; // negative cycle
    }
  }
  Some(dist)
}
```

Runtime $\Theta(VE)$. Returns `None` if a reachable negative cycle is detected. Negative cycle not reachable from source: Bellman-Ford still returns shortest paths. Only improvements after pass V reachable from source matter.

Weight transform trap: $w'(e) = a\,w(e)$ with $a > 0$ preserves shortest paths. $w'(e) = w(e) + a$ does not preserve shortest paths unless all shortest numbers of edges.

Shortest Paths in DAG

```
fn dag_shortest_path(adj:&Graph, source:usize){
  let n=adj.len();
  let mut dist=vec![INF;n];
  let mut parent=vec![None;n];
  dist[source]=0;

  for u in topo_order() {
    if dist[u]==INF {continue}

    for (v,w) in adj[u] {
      if dist[v]>dist[u]+w {
        dist[v]=dist[u]+w;
        parent[v]=Some(u);
        }// topological order.
      }// one relaxation per edge
    }// negative weights ok
    dist
  }//Runtime Theta(V+E)
```

Time-Dependent / Ferry Shortest Path

$dist[u] = $ earliest arrival. Road relax: $dist[v] = \min(dist[v], dist[u] + w)$. Ferry/event (u, v, dep, arr) usable iff $dist[u] \leq dep$, then relax $dist[v] = \min(dist[v], arr)$. Use PQ by earliest arrival if time is FIFO/nonnegative; otherwise expand state/event graph.

14. Flow Networks

Directed $G = (V, E)$, source s, sink t, capacities $c(u, v) \geq 0$. Flow constraints: 0<=f(u,v)<=c(u,v); conservation for u!=s,t: inflow=outflow; |f|=out(s)-in(s). Augmenting path: $s \rightarrow t$ path in residual graph; bottleneck $= \min c_f(e)$ on path. Flow reduction recipe: selected object = unit flow; capacities = usage limits; source/sink = constraints; value = objective; integral caps => integral solution.

Ford-Fulkerson / Edmonds-Karp

Types: `cap[u][v]` residual capacity matrix; `adj: Graph` stores forward+reverse residual neighbors.

```
fn add_edge(c:usize,v:usize,c:i32){
adj[u].push(v);adj[v].push(u);cap[u][v]+=c
}
fn bfs_path(source:usize, sink:usize){
  parent.fill(None); parent[source]=Some(source);
  queue.push_back(source);
  while let Some((u,flow))=queue.pop_front(){
    for v in adj[u]{
      if parent[v].is_none() && cap[u][v]>0 {
        parent[v]=Some(u);
        pushed=flow.min(cap[u][v]);
        if v==sink {return pushed}
        queue.push_back((v,pushed))
      }
    }
  }
  0
}
fn max_flow(source:usize, sink:usize){
  flow=0;     // augment while path exists
  loop {
    pushed=bfs_path(source,sink);
    if pushed==0 {break}
    flow+=pushed;
    v=sink;
    while v!=source {
      u=parent[v].unwrap();
      cap[u][v]-=pushed; cap[v][u]+=pushed;
      v=u
    }
  }
  flow
} // f* is the highest flow
```

Ford-Fulkerson integer caps: $O(E|f^*|)$. Edmonds-Karp BFS: $O(VE^2)$. Final residual graph gives min cut by residual reachability from s.

Max-Flow Min-Cut / Reductions

Max-flow min-cut: $\max |f| = \min c(S, V \setminus S), s \in S, t \notin S$.

Optimality certificate: flow value f and cut capacity F.

Bipartite matching: source ⟶ L cap 1; L ⟶ R cap 1 for original edges; R ⟶ sink cap 1. Flow-1 L ⟶ R edges are matched pairs.

Capacitated assignments: S ⟶ person cap 1; person ⟶ acceptable activity cap 1; activity ⟶ t cap capacity. Feasible iff maxflow = #people. Integral capacities give integral assignment.

```
source=0; left0=1; right0=1+n_left; sink=1+n_left+n_right;
for i in 0..n_left {add_edge(source,left0+i,1)}
for (i,r) in bip_edges {add_edge(left0+i,right0+r,1)}
for r in 0..n_right {add_edge(right0+r,sink,1)}
// flow=1 edge left0+l -> right0+r = matched pair
```

Edge-disjoint paths: all edges cap 1. Vertex-disjoint: split v into $v_{in} \rightarrow v_{out}$ cap 1; original $u \rightarrow v$ becomes $u_{out} \rightarrow v_{in}$ cap INF. Grid domino: checkerboard cells L/R, edge for adjacency, max dominoes = max bipartite matching. Path $x \rightarrow y$ through z: one internally vertex-disjoint paths $z \rightsquigarrow x$ and $z \rightsquigarrow y$; split vertices cap 1, add x, $y \rightarrow t$ cap 1, ask maxflow $z \rightarrow t$ value 2. Special edge $e = a\,b$ used: try orientations $\cdots a - b \cdots$ and $\cdots b - a \cdots$; remove e, enforce disjoint prefix/suffix with unit capacities.

15. Randomized / Probabilistic Analysis

Indicator: $X_A = \mathbb{1}[A]$, $\mathbb{E}[X_A] = \Pr(A)$. Linearity: $E[\Sigma_i X_i] = \Sigma_i E[X_i]$. No independence needed.

Hiring: $P(i \text{ new best}) = 1/i$, so $E[\#hires] = \Sigma_i 1/i = H_n = \Theta(\log n)$. Hat-check: $P(i \text{ own hat}) = 1/n$, so $E[\#fixed] = 1$.

Randomized quicksort: random pivot avoids input-dependent bad order; expected $\Theta(n \log n)$, worst still $\Theta(n^2)$.

Birthday: $\Pr[\text{all different among } q \text{ into } m] = \Pi_{i=0}^{q-1}(1 - i/m) \approx e^{-q(q-1)/(2m)}$; for 365 days, $q = 23$ gives match prob $> 1/2$. Integral bound for decreasing f: $\Sigma_{k=a+1}^{b} f(k) \leq \int_a^b f(x)\,dx$.

16. Online Algorithms / Competitive Analysis / Experts

Online: decide before future inputs arrive. Competitive ratio: $ALG(I) \leq r\,OPT(I) + c$. Ski rental: rent 1/day, buy B. Rent until paid B, then buy. If $T \leq B$: ALG=T=OPT. If $T > B$: ALG<=B+B=2B=2OPT. Lower bound: adversary stops just before/after purchase; deterministic CR=2.

Caching MC traps

LRU evicts least-recently requested page. LFU evicts smallest request count; tie usually LRU. Neither has pointwise fewer misses than the other on every sequence. LRU is k-competitive for cache size k; no deterministic paging algorithm beats k in worst-case competitive ratio.

Experts / Weighted Majority

n experts, rounds $t = 1..T$. Expert i predicts; loss $\ell_{i,t} \in \{0, 1\}$.

Weights $w_i = 1$ initially. Let $W = \Sigma_i\, w_i$.

```
for t in 1..=T {
  predict weighted majority of experts;
  observe true outcome;
  for expert i wrong this round {
    w[i] *= beta;          // 0 < beta < 1, often beta=1/2
  }
}
```

Weighted prediction: choose label with larger total weight. Potential: $W_t = \Sigma_i\, w_i^{(t)}$. If ALG makes mistake, wrong-weight $\geq W_t/2$, so $W_{t+1} \leq W_t/2 \cdot \beta + W_t/2 = W_t(1+\beta)/2$. If best expert has m^* mistakes, its weight is β^{m^*}, hence $\beta^{m^*} \leq W_T \leq n((1+\beta)/2)^M$. For $\beta = 1/2$: $M \leq 2.41(m^* + \log_2 n)$.

General randomized Hedge: choose expert with prob w_i/W; update $w_i \leftarrow w_i e^{-\eta \ell_{i,t}}$; regret $O(\sqrt{T \log n})$.

Prophet Inequality

Independent nonnegative X_i, known distributions. $M = \max_i X_i$; $z = E[M]$, threshold $\tau = z/2$. Accept first $X_i \geq \tau$. Guarantee $E[ALG] \geq z/2$. Proof stencil: $q = P[\forall i : X_i < \tau]$, $b_i = E[(X_i - \tau)^+]$. Value from threshold part $\geq \tau(1-q)$; overshoot part $\geq q\,\Sigma_i\, b_i$; combine to get $\geq z/2$.

Secretary: random order; observe first n/e candidates, remember best rank seen, then hire first later candidate better than all observed.

$P(\text{success}) \approx 1/e$

17. WORKED EXAM PROBLEMS

P01. Loop invariant proof: linear search returns matching index or NIL.
Inv.: before iteration i, no earlier position contains v: A[j] != v for all j<i. Init: i=1: empty set. Maint: if A[i] != v, then the statement extends to all j<i+1. Term: if equality found, returned first index; if not found, loop terminates because i > n, so no position contains v.

P02. Asymptotic proof with constants: show (n+a)^ b = Theta(n^ b) for fixed constants.
For n>=2|a|: n/2 <= n+a <= 2n. Raise to fixed b>0: 2^ (b) n^ b <= (n+a)^ b <= 2^ b n^ b. Choose constants c1=2^ (-b), c2=2^ b, n0=2|a|.

P03. Recursion tree: T(n)=8T(n/2)+Theta(n^2), leaves dominate.
Level k: 8^ k nodes, size n/2^ i, work 8^ k (n/2^ k)^2 = c*n^2*2^ i. Sum until lg n: c*n^2*sum_i=0..lg n 2^ i = Theta(n^3). Leaves: 8^ (lg n)=n^3. Hence Theta(n^3).

P04. Recursive insertion sort: remove last element, sort prefix, insert last.
Recurrence T(n)=T(n-1)+Theta(n). Unroll: T(n)=Theta(sum_i=1..n i)=Theta(n^2). Correctness by induction: sorted prefix by IH; insertion puts last element in unique sorted position.

P05. Strengthened recurrence proof: split sizes 3n/5, 4n/5 plus linear work.
T(n)=T(3n/5)+T(4n/5)+a*n. Guess T(n)<=c*n^2 since (3/5)^2+(4/5)^2=1. Upper needs slack: IH T(m)<=c*m^2-d*m. Then T(n)<=c*n^2-d*(7n/5)+a*n <= c*n^2-d*n iff d>=5a/2. Pick d, then pick c for bases. Lower: T(n)>=c*((3n/5)^2+(4n/5)^2)=c*n^2.

P06. Master theorem pattern: fastest among several recurrence-defined algorithms.
Compute exponent. aT(n/b)+n^ k: compare k to log base b of a. Examples: 2T(n/2)+n^3 -> Theta(n^3); 30T(n/4)+n -> Theta(n^ (log_4 30)); 8T(n/2)+1 -> Theta(n^3). T(n/2)+n^4 -> Theta(n^4); 2T(n-1)+1 -> Theta(2^ n). Pick smallest asymptotic.

P07. Restaurant spacing DP: choose subset of line positions at mutual distance at least k.
Sort by position. dp[i] = max profit using restaurants 1..n. next[i] = first j with M[j] > M[i]+k. dp[n+1]=0, dp[i]=max(dp[i+1], p[i]+dp[next(i)]). Ans: dp[1] Proof: optimum skips i or takes i, then all remaining choices start at next(i). Runtime O(n log n) with binary search.

P08. Restaurant variant: force the current restaurant to be the leftmost open one.
c[i] = best profit among solutions whose leftmost chosen restaurant is i. Then c[i]=p[i]+max{c[j]: j>i and M[j]>M[i]+k}, with empty max 0. Ans: max_i c[i]. Use suffix maxima plus binary search for O(n log n), or scan for O(n^2).

P09. Binary search proof: sorted array membership in O(log n).
Maintain half-open interval [l,r) with invariant: if x is present then it lies in A[l..r). Compare with A[m]. If A[m]<x, discard [l,m]; if A[m]>x, discard [m,r). Sortedness preserves invariant. Termination gives found index or empty candidate set. Runtime T(n)=T(n/2)+O(1).

P10. 2D sorted matrix: rows and columns increasing, find x in O(n).
Start at upper right (i=1,j=n). If A[i,j]=x return. If A[i,j]>x, move left: everything below in column j is also >x. If A[i,j]<x, move down: everything left in row i is also <x. Each step removes one row/column, so at most 2n-1 steps.

P11. Augmented BST invariant counting: count keys in [a,b] with subtree sizes.
Store size(x)=1+size(L)+size(R) at each node and preserve it under rotations/parts. rankLT(x) follows search path; when moving right add size(left)+1. rankLE(x) similarly includes equals. Count [a,b]=rankLE(b)-rankLT(a). Runtime O(h).

P12. MinStack: stack with Push, Pop, GetMin all worst-case O(1).
Use two stacks: data stack S, minimum stack M. Push x: push to S; if M empty or x<=top(M) push x to M. Pop: y=pop(S); if y=top(M) pop M. GetMin returns top(M). Duplicates need <= on push, not just <.

P13. Heap / priority queue trace: Build-Max-Heap and Heapify correctness.
BuildHeap calls Heapify from floor(n/2) down to 1. Invariant: before processing i, all nodes >i root heaps. Heapify assumes children heaps and pushes violation downward. Runtime sum over heights h of (n/2^ (h+1))*O(h)=O(n), not O(n log n).

P14. Comparison sorting lower bound: prove Omega(n log n) comparisons.
Any deterministic comparison sort is a decision tree. Each permutation of n distinct keys must end in a different leaf, so at least n! leaves. Height h satisfies 2^ h >= n!, so h>=log2(n!)=Omega(n log n).

P15. Randomized Quicksort comparison probability relative to a fixed element.
For ranks i<j, they are compared iff the first pivot chosen among ranks i..j is either i or j. Thus $P(i,j) = 2/(j-i+1)$. For element of rank r, probability with rank q is $2/(|q-r|+1)$; sort options by distance from r.

P16. All-equal Lomuto partition: bad split and robust duplicate fix.
If partition condition is <= pivot, all equal elements move left, pivot index returns r. Recurrence T(n)=T(n-1)+Theta(n)=Theta(n^2). Fix with 3-way partition into <,=,> pivot or choose middle of equal block.

P17. Simple uniform hashing: expected number of pair collisions.
X=sum over pairs i<j of X[i,j], where X[i,j]=1[h(i)=h(j)]. E[X[i,j]]=1/m. Thus E[X]=C(n,2)/m=Theta(n^2/m). For collisions with first slot only: pair probability $1/m^2$, so expectation C(n,2)/m^2=Theta(n^2/m^2).

P18. Hash table with values: expected O(1) search, insert, delete.
For fixed distinct x,y, collision requires equality in all eight coordinates, so P[x,y collide]=(1/m)^ eight. Let X=sum over pairs x<y of X[x,y]. Then E[X]=C(n,2)/m^ eight <= n^2/(2m^ eight) <= 1 if m^ eight >= n^2.

P19. Hash chains high-probability bound: on bucket longer than eH.
A k-collision is a k-set in one bucket. E[# k-collisions] <= C(n,k)/m^(k-1) <= n^k/m^(k-1). Chain length >eH iff an (eH+1)-collision exists. If m>=100n^(1+1/eH), then E[#(eH+1)-collisions] <= n^(eH+1)/m^ eH <= 1/100^ eH <=0.01. Markov: bad prob <=0.01.

P20. Expected hires with random arrival, skip first 10 percent.
For position i>n/10, indicator X[i]=1 if candidate i is best among first i. P[X[i]=1]=1/i. Expected hires = sum_i=n/10+1..n 1/i <= integral from n/10 to n of dx/x = ln 10 < 10.

P21. Random edge/color expectation: count bad local events by indicators.
If each edge/vertex color is independent uniform among q colors, define X[e]=1 if event e is bad. Usually P[X[e]=1] is 1/q or 1/q^ r. Then E[#bad]=sum_e P[X[e]=1]. Use Markov P[#bad>=1] <= E[#bad] for existence/probability bounds.

P22. Bipartite matching as unit-capacity flow: source, sink, cap 1.
Build s->L cap 1; original edges L->R cap 1; R->t cap 1. Integral capacities give integral max flow. Capacity 1 forces each vertex used once. Flow edge l->r is a matched pair; every matching gives same-size flow. Hence max flow = max matching.

P23. Cascaded activity/cheese assignment: each person gets one acceptable item, bins have capacities.
Network: s->each person/type cap demand; person/type->item if acceptable cap INF or demand; item->t cap supply/spots. Feasible iff maxflow equals total people/students. Integral flow gives integer assignment; assignment gives flow.

P24. Domino tiling / maximum non-overlapping adjacent grid pairs.
Checkerboard color cells. Black cells L, white cells R. For every adjacent allowed pair add edge L->R. Max domino placement = maximum bipartite matching: each domino is one matched edge and matching prevents cell reuse.

P25. Edge-disjoint paths: route multiple requests, avoid wasteful reusing edges.
Give every edge capacity 1 and run maxflow. Value k iff there are k edge-disjoint paths (integrality). For undirected edges, either replace by two directed arcs sharing one unit-capacity gadget, or orient both ways carefully with a single capacity-1 edge gadget.

P26. Vertex-disjoint paths / simple path through required vertex z.
To find simple path x->z->y, need internally vertex-disjoint paths from z to x and z to y. Split every vertex v into v.in->v.out cap 1 (INF for terminals if allowed). Original edge u-v becomes arcs u.out->v.in and v.out->u.in. Add x,y->t cap 1, source z, ask maxflow value 2.

P27. Special required edge e*=(a,b) in an edge-simple u-v trail.
Try both orientations. For orientation a->b, remove e* and require edge-disjoint prefix/suffix paths u->a and b->v using unit edge capacities; similarly orientation b->a. If flow construction returns both paths, concatenate prefix + e* + suffix. If both orientations fail, no valid trail.

P28. Haunted-house escape: k agents, grid over times, ghosts, no two agents same cell.
Build time-expanded flow. For every safe cell (c,t) create cell(c,t).in->cell(c,t).out cap 1. For each legal step/move c->c' add cell(c,t).out->cell(c',t+1).in cap 1 if target safe. Source to start cells at time 1 cap 1. Boundary cells at times <=T connect to sink cap 1. Maxflow=k iff all escape. Size O(Tn^2) nodes/edges up to constants.

P29. Shortest path with battery/resource budget: minimize time, spend at most B.
State graph has vertices (v,b) = at v after spending b battery, 0<=b<=B. For edge e=(u,v) add (u,b)->(v,b+cost(e)) when b+cost(e)<=B. Ans: min_b dist(t,b) (both directions if undirected). Run Dijkstra from (s,0). Ans: min_b dist(t,b). Runtime O(n^2 B log(BV)).

P30. Road network mutual reachability forbidden for listed directed pairs.
Compute SCCs with Kosaraju/Tarjan in O(V+E). For each forbidden pair (u,v), reject iff comp[u]=comp[v]. Same SCC => both directions have cycle. Different SCC => at most one direction reachable. If all pairs pass, accept. Given el<=E, total runtime O(V+E).

P31. Topological-sort / Course Schedule: can all prerequisites be satisfied?
Directed graph prerequisite u->v. Run DFS colors or Kahn indegrees. If cycle/back edge exists, impossible. Otherwise topological order exists and gives valid schedule. Runtime O(V+E). Proof: DAG iff topo order iff no DFS back edge.

P32. DAG maximum-weight path with vertex weights from s to t.
Topologically sort. Initialize dp[s]=w(s), others -INF. In topo order, relax u->v: dp[v]=max(dp[v], dp[u]+w(v)). Ans: dp[t]. Correct because all predecessors of v processed before v. Runtime O(V+E).

P33. Verify claimed shortest-path distances in graph with negative edges but no negative cycles.
Check d[s]=0. For every edge (u,v) check triangle inequality d[v]<=d[u]+w(u,v); if vi-olated reject. Build tight-edge graph E'={(u,v): d[v]=d[u]+w(u,v)}. DFS/BFS from s in E'. Accept iff all vertices reached. Inequality gives d[v] <= every path length; tight paths give actual paths of length d[v], so equality.

P34. Bellman-Ford negative-cycle / altitude consistency with signed edge changes.
A bad closed tour is a directed cycle with nonzero total weight. Run Bellman-Ford on w and on -w from a super-source connected to all vertices by 0 edges. A negative cycle in w or in -w means some cycle has nonzero sum. If neither run detects, all cycles have sum 0. Runtime O(VE).

P35. Shortest-path weight transition DP: count vertices vs multiply by positive constant.
Multiplying all edge weights by a>0 preserves every path ordering, so shortest paths unchanged. Adding a to every edge changes w(P) to w(P)+a*|P|, so paths with different numbers of edges can change order.

P36. Dijkstra choice proof: nonnegative weights only.
Maintain finalized set S. Pick outside vertex v with minimum tentative distance. Any s->v path must exit S at some first edge (u,v); length to v is at least d[u]+w(u,v)>=d[v]>=d[x] because w>=0. Thus d[x] is final. Negative edges break this step.

P37. Bellman-Ford exact invariant and negative-cycle certificate.
After i full passes, d[v] is shortest path length among paths using at most i edges. Induct by last edge. Without negative cycles, shortest paths can be simple, so use at most V-1 edges. If a V-th pass still relaxes, there is a reachable negative cycle.

P38. MST over complete graph of points: connect all islands with n-1 routes.
Build complete undirected graph on the n points with edge weight squared Euclidean distance. Need connected graph with n-1 routes minimizing total cost = MST. Run Kruskal/Prim on O(n^2) edges. Runtime O(n^2 log n); output MST edges.

P39. MST cut/cycle proof: min crossing edge safe, max cycle edge unsafe.
Cut: add lightest edge crossing any cut; otherwise exchange another crossing edge f with w(f)>=w(e); swap f->e. Cycle: if unique heaviest edge e of a cycle is in MST, remove it; another cycle edge reconnects the cut cheaper, contradiction.

P40. Minimum-weight feedback edge set in undirected weighted graph.
Need remove edges so remaining graph is acyclic. Equivalent: keep an acyclic subset of maximum total weight. In connected graph, this means keep a spanning tree. Run Kruskal in descending weights, keep tree edges, remove all others. Correct because any acyclic connected kept set has at most V-1 edges and maximum spanning tree weight.

P41. Airport + roads connectivity: cities can connect by roads or both having airports.
Add super-node s. For every city v, add edge (s,v) of cost airport cost c[v]. Keep original road edges with costs w[e]. Run MST on augmented graph. Chosen original edges = roads; chosen s-edges = airports. Super-node models free travel between airports. Runtime O((E+V)log(E+V)).

P42. Edge belongs to at least one MST: linear-time query for edge e=(a,b).
Let W=w(e). Run DFS/BFS from a using only edges with weight <W. If b reached, then e is heaviest on a strictly lighter cycle, so no MST contains it. If not reached, take component S of a in subgraph w<W; every edge crossing (S,V-S) has weight >=W, and e crosses, so e is lightest for this cut. Thus some MST contains e. Runtime O(V+E).

P43. Unique MST vs many MSTs: detect swappable equal-weight non-tree edge.
Compute one MST T. For every non-tree edge e=(u,v), find maximum edge weight M on the unique path u->v in T. If w(e)=M, swap e with a max edge on that path to get another MST: MANY. If all w(e)>M, no equal swap exists: ONE. Naive runtime O(EV); faster with LCA + heavy-light.

P44. Connected graph with n vertices and n edges: count spanning trees in O(n).
Connected with |E|=|V| has exactly one cycle. Find cycle length c by DFS back edge or repeatedly delete degree-1 leaves until the cycle remains. Every spanning tree is obtained by deleting exactly one cycle edge; deleting non-cycle edge disconnects. Ans: number of spanning trees = c, because between 3 and 5 or for simple graph.

P45. Tree diameter: output farthest pair of nodes in binary tree.
Postorder returns (height, deepest, bestLen, bestPair). At node u, candidate crossing pair is deepest node in left subtree to deepest node in right subtree with length hL+hR+2 (handle empty child). Best is max of left best, right best, crossing. Runtime O(n).

P46. Longest simple path constrained to pass through the root.
Compute heights of left and right subtrees. If height counts edges and empty height is -1, answer is h(root.left)+h(root.right)+2. The path through root is maximized by independently choosing deepest descendant on each side. Runtime O(n).

P47. Reconstruct binary tree from inorder and postorder traversals.
Root is last element of postorder. Find root in inorder; left/right inorder blocks determine subtree sizes. Split postorder into corresponding left/right blocks, recurse. Base empty list. Runtime O(n) with value-to-inorder-index map. Preorder+inorder similar; preorder+postorder alone is not unique.

P48. Travel passes DP: cover sorted travel days with 1/7/30-day passes.
Days d[1]<...<d[n], costs c[1],c[7],c[30]. dp[i] = min cost to cover days i..n. next(i,L)=first j with d[j]>=d[i]+L. dp[n+1]=0, dp[i]=min over L of c[L]+dp[next(i,L)]. Fill decreasing i. Ans: dp[1]. Trap: pass bought on day d[i] covers days <d[i]+L.

P49. Weighted interval scheduling: choose non-overlapping intervals of max weight.
Sort by finish. p(j)=last interval ending <=start[j]. dp[j]=best using first i intervals. dp[0]=0, dp[i]=max(dp[i-1], w[i]+dp[p(i)]). Ans: dp[n]. Runtime O(n log n) with binary search for p.

P50. Cardinality-constrained weighted intervals: choose at most k disjoint intervals.
Sort by finish and compute p(i). dp[i][j]=best value using first i intervals and at most j intervals. Base dp[0][j]=dp[i][0]=0. dp[i][j]=max(dp[i-1][j], w[i]+dp[p(i)][j-1]). Ans: dp[n][k]. Runtime O(nk+n log n).

P51. Interval scheduling greedy: max number of mutually disjoint intervals.
Sort by increasing finish time. Repeatedly take first interval compatible with current last finish. Exchange proof: earliest-finishing interval e can replace first interval of any optimum solution without reducing feasibility. Then recurse on intervals starting after e.

P52. Divide farm into exactly 3 contiguous nonempty parts minimizing largest sum.
Input A[1..n], A[i] positive and A[i]<=1000. Need cuts i<j minimizing max(sum 1..i, sum i+1..j, sum j+1..n). Binary-search answer M = allowed max child area. Bounds: L=max A[i] (cannot put A[i] anywhere if M<A[i]), R=sum A[i] (one part contains all). Feasible(M): scan left->right with cur=0, parts=1; if cur+i<=M then cur+=i, else parts++, cur=x. Reject if parts>3. Why greedy works: for fixed M, greedy makes each part as long as possible, so after t parts it has covered at least as much prefix as any valid t-part partition; hence greedy uses the minimum possible #parts. Therefore parts>3 <=> impossible. If parts<=3 => possible for exactly 3 by splitting a long part or a single existing nonempty parts until there are 3; splitting only decreases part sums. Predicate monotone: bigger M cannot need more parts. Binary search smallest feasible M. Runtime Feasible=O(n), K<=1000n => > O(n log(1000n))=O(n log n). No direct sum(a,b) needed; cur is computed during scan. Recover cuts: rerun greedy at M*, then split if fewer than 3 parts, output the two cut indices.

P53. Split array into k contiguous parts minimizing maximum load.
Same as P52 with k instead of 3. L=max a[i], R=sum a[i]. Feasible(M) greedily computes the minimum number q of parts needed with each part sum<=M. Feasible iff q<=k; if exact k required and n>=k, split parts until k. Binary search smallest feasible M. Runtime O(n log R); if a[i] polynomially bounded, O(n log n).

P54. Short grid walk with value and move limit: moves right/up/diag, at most 3n/2 moves.
dp[i][j][ell] = max value reaching cell (i,j) in exactly ell moves. Base dp[0][0][0]=v(0,0). Transition from predecessors (i-1,j), (i,j-1), (i-1,j-1) with ell-1, add v(i,j). Ans: max over ell<=3n/2 at (n-1,n-1). Time O(n^3). Space O(n^3).

P55. Rod cutting / unbounded segmentation: maximize revenue over cuts summing to n.
r[0]=0. For length j=1..n: r[j]=max over 1<=i<=j of p[i]+r[j-i]. This chooses leftmost piece length i and solves remainder optimally. Runtime O(n^2), space O(n). Store argmax to reconstruct cuts.

P56. Matrix-chain multiplication: choose parenthesization minimizing scalar multiplications.
Matrices A[i] have dimensions p[i-1] x p[i]. m[i,j]=0. For length ell=2..n: m[i,j]=min over i<=k<j of m[i,k]+m[k+1,j]+p[i-1]*p[k]*p[j]. Ans: m[1,n]. Runtime O(n^3), space O(n^2).

P57. LCS of two strings: subsequence, not substring.
dp[i][j] = LCS length of prefixes X[1..i], Y[1..j]. Base row/col 0. If X[i]=Y[j], dp[i][j]=1+dp[i-1][j-1]; else max(dp[i-1][j], dp[i][j-1]). Runtime O(mn). Reconstruct by walking backward.

P58. Longest increasing subsequence: standard DP and faster tails version.
dp[i] = 1+max{L[i]: i<j and A[i]<A[j]}, empty max 0; answer max_j L[j], O(n^2). Tails: maintain smallest possible tail for each length; for x, lower_bound first tail >= x and replace. Length of tails = LIS length. O(n log n).

P59. Longest modular increasing subsequence: increasing values and sum divisible by 3.
If W mod 3 != 0, NO. Let target S=W/3. dp[i][x][y] = possible after first i items with subset1 sum x, subset2 sum y; subset3 implicit. Transition: put item i in subset1 if x>=w[i], subset2 if y>=w[i], or subset3. Ans: dp[n][S][S]. Runtime O(ns^2).

P60. 0/1 knapsack: each item used at most once, capacity W.
dp[i][w] = best value using first i items with capacity w. dp[0][w]=0. If weight[i]>w, skip; else dp[i][w]=max(dp[i-1][w], value[i]+dp[i-1][w-weight[i]]). Runtime O(nW) pseudo-polynomial. 1D update w decreasing.

P61. 3-way equal partition: split positive integers into 3 subsets each sum W/3.
If W mod 3 != 0, NO. Let target S=W/3. dp[i][x][y] = possible after first i items with subset1 sum x, subset2 sum y; subset3 implicit. Transition: put item i in subset1 if x>=w[i], subset2 if y>=w[i], or subset3. Ans: dp[n][S][S]. Runtime O(ns^2).

P62. Coin-row two-player game: optimal play, take leftmost or rightmost coin.
dp[i][j] = max value current player can guarantee from interval i..j. dp[i][i]=a[i]. Recurrence dp[i][j]=max(a[i]+min(dp[i+2][j],dp[i+1][j-1]), a[j]+min(dp[i+1][j-1],dp[i][j-2])). Opponent chooses branch minimizing our future. Fill by increasing interval length. Runtime O(n^2).

P63. Coin change / minimum number of coins, unlimited copies.
dp[0]=0, dp[x]=INF initially. For amount x=1..W, dp[x] = 1+min over c<=x of dp[x-c]. Ans: dp[W] or impossible if INF. Runtime O(nW) pseudo-polynomial. For number of ways, loop coins outside and amounts increasing.

P64. Optimal BST DP with key probabilities / search frequencies.
e[i,j] = min expected cost for keys i..j, w[i,j] = total probability/frequency in interval. Choose root r: e[i,j]=min over r=i..j of e[i,r-1]+e[r+1,j]+w[i,j]. Empty interval cost 0. Fill by increasing length. Runtime O(n^3).

P65. DP answer skeleton when the problem statement is unfamiliar.
State meaning with units and exact interval/index convention. Base cases. Transition: enumerate the first/last decision and consider both sensible values of forced states. Order: dependencies first. Answer: exact table cell. Correctness: induction in fill order; optimum uses one enumerated choice and every candidate is feasible. Runtime = states * transition cost.

P66. Ski rental competitive analysis: rent price 1, buy price B.
Algorithm: rent until total rent reaches B, then buy. If T<=B, ALG=T=OPT. If T>B, ALG<=B+B=2B=2OPT. Lower bound for deterministic algorithms: adversary stops just before algorithm buys or continues just after; no deterministic ratio <2.

P67. Paging/caching LRU: cache size k, prove k-competitive.
Partition requests into phases with at most k distinct pages; new phase starts when (k+1)st distinct page appears. LRU has at most k misses per phase. OPT has at least 1 miss per completed phase because phase plus next first request contains k+1 distinct pages. Hence LRU <= k*OPT + O(k).

P68. Weighted majority: mistake bound, bound mistakes against best expert.
Weights start 1; after wrong prediction multiply expert weight by beta. If algorithm makes a mistake, wrong side has weight >= W/2, so W'<=W(1+beta)/2. Best expert with m* mistakes has weight beta^(m*) <= W[T] <= n((1+beta)/2)^ M. Solve for M.

P69. Secretary problem: maximize chance of choosing overall best candidate online.
Reject first r=floor(n/e), remember best sample. Then accept first candidate better than all seen. Success if global best appears at position i>r and best among first i-1 was in sample. Probability sum_i=r+1..n (1/n)*(r/(i-1)) approx (r/n)ln(n/r) approx 1/e.

P70. Online bipartite matching: greedy and ranking algorithms.
Greedy matches each arriving vertex to any free neighbor. Each ALG edge can be charged by at most two OPT edges, so ALG >= OPT/2. Ranking: pick random priority order on offline left vertices; each arrival chooses highest-priority free neighbor; expected value (1-1/e)OPT.

P71. Prophet inequality: threshold at half expected maximum.
Independent nonnegative X[i], known distributions. Let M=max_i X[i], z=E[M], threshold tau=z/2. Accept first X[i]>=tau. Guarantee E[ALG]>=z/2. Proof uses q=P[all i: X[i]<tau] and overshoots (X[i]-tau)^ +; threshold contribution tau(1-q) plus overshoot contribution q*sum_i E[(X[i]-tau)^ +].

Standard Recurrences / Tricks

Two Sum: scan i left->right; map has earlier values j<i. If target-a[i] exists return; else insert. Inv: when second endpoint appears, first is stored. Exp O(n).

Valid parentheses: stack unmatched opens; closing bracket must match top; accept iff stack empty. Inv: stack = opens not yet closed, in order. O(n).

Grid islands: for each unvisited land cell: count++, BFS/DFS 4-neighbors. Each cell/edge checked O(1) times. O(rc).

Redundant connection: DSU scan edges in input order; if find(u)==find(v), current edge closes first cycle; else union. O(E alpha V).

Top-k frequent: count HashMap. Heap: O(n+m log m), pop k. Bucket by freq 0..n: append bucket[f], scan downward. O(n+m).

Distinct sliding window