



Sequential Modelling of the Evolution of Word Representations for Semantic Change Detection

Adam Tsakalidis & Maria Liakata

EMNLP 2020



Queen Mary
University of London

The
Alan Turing
Institute



Lexical Semantic Change



Ah, look at those *blackberries*, aren't they beautiful?

Where? I can't see them...



There! Where this little guy is *tweeting*!

Huh...?



Task: Identify words that change their meaning over time ([Tahmasebi et al., 2018](#))

Applications: historical linguistics, evolution of communities, cultural shifts...



Related Work

Diachronic representations:

topics ([Frermann & Lapata, 2016](#); [Perrone et al., 2019](#))

graphs ([Mitra et al., 2014](#))

neural ([Hamilton et al., 2016](#); [Shoemark et al., 2019](#); [Schlechtweg et al., 2019](#))

Common practice ([Hamilton et al., 2016](#)):

- Learn word representations in two distinct time periods
- Align them via Orthogonal Procrustes ([Schönemann, 1966](#))
- Measure cosine similarity

+Pros: Highly effective, fast

-Cons: Temporality? Non-linear?



Related Work & Contributions

Approaches taking time into consideration:

- Rely on linear transformations ([Kulkarni et al., 2015](#); [Shoemark et al., 2019](#))
- Focus on *word representation* ([Kim et al., 2014](#); [Dubossarsky et al., 2019](#))

Our contributions:

- Work with “*any*” pre-trained word representations over time
- Non-linear, sequential models for semantic change
- Evaluate models in a sequential dataset; compare against strong baselines



Proposed Method

Input: Pre-trained word vectors
in T time periods:

$[W_0, W_1, \dots, W_{i-1}, W_i, W_{i+1}, \dots, W_{T-1}]$

Goal: Learn how the vectors
evolve over time.

Semantic change: Words whose sequence
is hard to predict


Proposed Method

Input: Pre-trained word vectors
in T time periods:

$[W_0, W_1, \dots, W_{i-1}, W_i, W_{i+1}, \dots, W_{T-1}]$

Goal: Learn how the vectors
evolve over time.

How: (a) autoencoder
(b) future prediction
(c) multi-task



Proposed Method

Input: Pre-trained word vectors
in T time periods:


$[W_0, W_1, \dots, W_{i-1}, W_i, W_{i+1}, \dots, W_{T-1}]$

Goal: Learn how the vectors
evolve over time.

How: (a) autoencoder *seq2seq_r*
(b) future prediction
(c) multi-task

Reconstruct input sequence
of word vectors through time

$$L_r = \frac{1}{i} \sum_{j=0}^{i-1} MSE(W_j, W_j^r)$$



Proposed Method

Input: Pre-trained word vectors
in T time periods:


$[W_0, W_1, \dots, W_{i-1}, W_i, W_{i+1}, \dots, W_{T-1}]$

Goal: Learn how the vectors
evolve over time.

How: (a) autoencoder *seq2seq_r*
(b) future prediction *seq2seq_f*
(c) multi-task

Predict future sequence of
word vectors through time

$$L_f = \frac{1}{T-i} \sum_{j=i}^{T-1} MSE(W_j, W_j^f)$$



Proposed Method

Input: Pre-trained word vectors
in T time periods:

$[W_0, W_1, \dots, W_{i-1} \mid W_i, W_{i+1}, \dots, W_{T-1}]$


Goal: Learn how the vectors
evolve over time.

How: (a) autoencoder $seq2seq_r$
(b) future prediction $seq2seq_f$
(c) multi-task $seq2seq_{rf}$

Reconstruct past & predict
future sequences

$$L_r = \frac{1}{i} \sum_{j=0}^{i-1} MSE(W_j, W_j^r)$$

$$L_f = \frac{1}{T-i} \sum_{j=i}^{T-1} MSE(W_j, W_j^f)$$





Dataset

UK Web Archive ([Tsakalidis et al., 2019](#))

Size: 47.8K words

Time period: 2000-2013 - each year corresponds to a timestep in our modelling

Vectors: 100-dim ([Mikolov et al., 2013](#)), trained on each year independently


Split: 80/20 (train/test)

Proof of Concept (Experiments)

Synthetic Semantic Shift: force 5% of word vectors in the test set ($w^{(\alpha)}$) to shift their meaning towards $w^{(\beta)}$ over time:

$$w_t^{*(\alpha)} = \lambda_t w_t^{(\alpha)} + (1 - \lambda_t) w_t^{(\beta)}$$

Setting λ :



Selecting $w^{(\beta)}$:

Condition: $c - 0.1 < \cos(w_0^{(\alpha)}, w_0^{(\beta)}) \leq c$

Note: high c value => challenging!
 $w^{(\alpha)}$ moves towards a more similar $w^{(\beta)}$ - lower level of change


Proof of Concept (Results)

Evaluation: Rank words in test set based on their average *cosDist*

High *cosDist* => model failure => semantic change

Metric: average rank of the semantically shifted words (μ_r)

Full



Note: high *c* value => challenging!


$w^{(\alpha)}$ moves towards a more
similar $w^{(\beta)}$ - lower level of change

Proof of Concept (Results)

Evaluation: Rank words in test set based on their average *cosDist*

High *cosDist* => model failure => semantic change

Metric: average rank of the semantically shifted words (μ_r)





Experiments & Comparisons

Data: 47.8K words - 65 words with altered meaning ([Oxford English Dictionary](#))

Goal: Better rank for the 65 words with altered lexical semantics

Metrics: μ_r (lower is better)

$rec@k$ (higher is better)

Baselines: Models from prior work & alterations of our models


Results

		μ_r	rec@5	rec@10	rec@50
Prior Work	PROCR	30.63	18.46	27.69	78.46
	PROCR_k	31.01	<u>21.54</u>	27.69	75.38
	PROCR_kt	31.91	20.00	27.69	70.77
	RF	30.01	10.77	21.54	78.46
	LSTM_r	27.87	12.31	29.23	80.00
	LSTM_f	28.62	16.92	32.31	76.92
	GT_c	47.87	7.69	16.92	52.31
	GT $_{\beta}$	38.09	13.85	24.62	66.15
	PROCR_*	25.01	<u>21.54</u>	32.31	81.54
Ours	seq2seq_r	<u>24.75</u>	<u>21.54</u>	<u>38.46</u>	<u>84.62</u>
	seq2seq_f	<u>23.86</u>	<u>26.15</u>	<u>46.15</u>	<u>84.62</u>
	seq2seq_rf	<u>24.28</u>	<u>29.23</u>	<u>36.92</u>	<u>84.62</u>

Results

		μ_r	rec@5	rec@10	rec@50
Prior Work	PROCR	30.63	18.46	27.69	78.46
	PROCR_k	31.01	<u>21.54</u>	27.69	75.38
	PROCR_kt	31.91	20.00	27.69	70.77
	RF	30.01	10.77	21.54	78.46
	LSTM_r	27.87	12.31	29.23	80.00
	LSTM_f	28.62	16.92	32.31	76.92
	GT_c	47.87	7.69	16.92	52.31
	GT_ β	38.09	13.85	24.62	66.15
	PROCR_*	25.01	<u>21.54</u>	32.31	81.54
Ours	seq2seq_r	<u>24.75</u>	<u>21.54</u>	<u>38.46</u>	<u>84.62</u>
	seq2seq_f	<u>23.86</u>	<u>26.15</u>	<u>46.15</u>	<u>84.62</u>
	seq2seq_rf	<u>24.28</u>	<u>29.23</u>	<u>36.92</u>	<u>84.62</u>

Results



tweet, eta,
friend...

parmesan,
even, unlike

Future:
Contextual
word vectors
(Giulianelli et
al., 2020)

Prior Work

Ours

	μ_r	rec@5	rec@10	rec@50
PROCR	30.63	18.46	27.69	78.46
PROCR_k	31.01	<u>21.54</u>	27.69	75.38
PROCR_kt	31.91	20.00	27.69	70.77
RF	30.01	10.77	21.54	78.46
LSTM_r	27.87	12.31	29.23	80.00
LSTM_f	28.62	16.92	32.31	76.92
GT_c	47.87	7.69	16.92	52.31
GT_β	38.09	13.85	24.62	66.15
PROCR_*	25.01	<u>21.54</u>	32.31	81.54
seq2seq_r	<u>24.75</u>	<u>21.54</u>	<u>38.46</u>	<u>84.62</u>
seq2seq_f	<u>23.86</u>	<u>26.15</u>	<u>46.15</u>	<u>84.62</u>
seq2seq_rf	<u>24.28</u>	<u>29.23</u>	<u>36.92</u>	<u>84.62</u>



Conclusion

3 variants of non-linear, sequential models for Semantic Change Detection

Experiments with synthetic/real data; comparison against strong baselines

Future Work:

- Contextual word representations ([Devlin et al., 2018](#))
- Different languages/durations
- Anomaly detection approaches
- Different model architectures


References



- [1] Devlin et al., 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *NAACL*.
- [2] Dubossarsky et al., 2019. Time-Out: Temporal Referencing for Robust Modeling of Lexical Semantic Change. In *ACL*.
- [3] Frermann & Lapata, 2016. A Bayesian Model of Diachronic Meaning Change. In *Computational Linguistics*.
- [4] Giulianelli et al., 2020. Analysing Lexical Semantic Change with Contextualised Word Representations. In *ACL*.
- [5] Hamilton et al., 2016. Diachronic Word Embeddings Reveal Statistical Laws of Semantic Change. In *ACL*.
- [6] Kim et al., 2014. Temporal Analysis of Language through Neural Language Models. In *Workshop on Language Technologies and Computational Social Science*.
- [7] Kulkarni et al., 2015. Statistically Significant Detection of Linguistic Change. In *WWW*.
- [8] Mikolov et al., 2013. Distributed Representations of Words and Phrases and their Compositionality. In *NIPS*.
- [9] Mitra et al., 2014. That's Sick Dude!: Automatic Identification of Word Sense Change across Different Timescales. In *ACL*.
- [10] Perrone et al., 2019. GASC: Genre-aware Semantic Change for Ancient Greek. In *International Workshop on Computational Approaches to Historical Language Change*.
- [11] Schlechtweg et al., 2019. A Wind of Change: Detecting and Evaluating Lexical Semantic Change across Times and Domains. In *ACL*.
- [12] Schönemann, 1966. A Generalized Solution of the Orthogonal Procrustes Problem. In *Psychometrika*.
- [13] Shoemark et al., 2019. Room to Glo: A Systematic Comparison of Semantic Change Detection Approaches with Word Embeddings. In *EMNLP*.
- [14] Tahmasebi et al., 2018. Survey of Computational Approaches to Lexical Semantic Change. In *ArXiv*.
- [15] Tsakalidis et al., 2019. Mining the UK Web Archive for Semantic Change Detection. In *RANLP*.



Thank you!



atsakalidis@turing.ac.uk
mliakata@turing.ac.uk



@adtsakal
@xrysoflhs

Acknowledgements: This work was supported by The Alan Turing Institute (grant EP/N510129/1) and by a Turing AI Fellowship to M. Liakata, funded by the Department of Business, Energy & Industrial Strategy.