

# The Alan Turing Institute



UNIVERSITY OF  
CAMBRIDGE



[A. Tsakalidis](#), M. Bazzi, M. Cucuringu, P. Basile, B. McGillivray

---

## Mining the UK Web Archive for Semantic Change Detection

# INTRODUCTION

- ▶ **Semantic Change:** Identify words whose lexical semantics have changed over time (tweet, follow, blackberry, etc.)
- ▶ **Importance:** historical/social studies, NLP tasks

# INTRODUCTION

- ▶ **Semantic Change:** Identify words whose lexical semantics have changed over time (tweet, follow, blackberry, etc.)
- ▶ **Importance:** historical/social studies, NLP tasks
- ▶ **Challenges:** (a) lack of labelled datasets  
(b) short-term Semantic Change Detection  
(c) evaluation

# CONTRIBUTIONS

- ▶ **Data:** Labelled dataset of word vectors during 2000–2013
- ▶ **Approach:** Variant of Procrustes Alignment trained on an extremely small number of “stable” words
- ▶ **Evaluation:** Rank-based approach

# BACKGROUND

## ▶ Early work:

- ▶ comparison of frequency & co-occurrence patterns between words across time [Sagi et al., 2009; Cook & Stevenson, 2010; Gulordava & Baroni, 2011]

## ▶ Current approaches:

- ▶ Learn word representations over different time intervals & compute shift [Kim et al., 2014; Hamilton et al., 2016; Del Tredici et al., 2018]
- ▶ Diachronic word embeddings [Bamler and Mandt, 2017; Rosenfeld and Erk, 2018; Yao et al., 2018; Rudolph and Blei, 2018]

# BACKGROUND

## ▶ Early work:

- ▶ comparison of frequency & co-occurrence patterns between words across time [Sagi et al., 2009; Cook & Stevenson, 2010; Gulordava & Baroni, 2011]

## ▶ Current approaches:

- ▶ Learn word representations over different time intervals & compute shift [Kim et al., 2014; Hamilton et al., 2016; Del Tredici et al., 2018]
- ▶ Diachronic word embeddings [Bamler and Mandt, 2017; Rosenfeld and Erk, 2018; Yao et al., 2018; Rudolph and Blei, 2018]

# MAIN ISSUE

- ▶ **Current approaches:** learn word representations over different time intervals & compute shift [[Kim et al., 2014](#); [Hamilton et al., 2016](#); [Del Tredici et al., 2018](#)]

**Issue:** comparison of word vectors is impossible

# MAIN ISSUE

- ▶ **Current approaches:** learn word representations over different time intervals & compute shift [Kim et al., 2014; Hamilton et al., 2016; Del Tredici et al., 2018]

**Issue:** comparison of word vectors is impossible


## Solutions:

- ▶ initialise word vectors at  $t+1$  based on the word vectors at  $t$  [Kim et al., 2014]
- ▶ Orthogonal Procrustes [Schonemann, 1966]: map the word vectors of *the whole vocabulary* at  $t$  to their corresponding ones at  $t+1$  [Hamilton et al., 2016]

**Problem:** trying to align *all* words can be noisy (those that have changed meaning?)



# APPROACH: OVERVIEW



## APPROACH: DETAILS

- ▶ We want to find:

$$R = \operatorname{argmin}_{\Omega; \Omega^T \Omega = I} \left\| W^{(t)} \Omega - W^{(t+1)} \right\|_F$$

- ▶ Solved as:

$$R = UV^T, \text{ where}$$
$$U \Sigma V^T = \text{SVD}(W^{(t+1)} W^{(t)T})$$

## APPROACH: DETAILS

- ▶ We want to find:

$$R = \operatorname{argmin}_{\Omega; \Omega^T \Omega = I} \left\| W^{(t)} \Omega - W^{(t+1)} \right\|_F$$

- ▶ Solved as:

$$R = UV^T, \text{ where}$$
$$U \Sigma V^T = \operatorname{SVD}(W^{(t+1)} W^{(t)T})$$

- ▶ Align vectors as:

$$W_*^{(t+1)} = W^{(t+1)} R^T s$$

- ▶ Displacement Error:

$$D^{(t,t+1)}: \operatorname{dist} \{W^{(t)}, W_*^{(t+1)}\}$$

## APPROACH: DETAILS

- ▶ We want to find:

$$R = \operatorname{argmin}_{\Omega; \Omega^T \Omega = I} \left\| W^{(t)} \Omega - W^{(t+1)} \right\|_F$$

- ▶ Solved as:

$$R = UV^T, \text{ where} \\ U \Sigma V^T = \operatorname{SVD}(W^{(t+1)} W^{(t)T})$$

- ▶ Align vectors as:

$$W_*^{(t+1)} = W^{(t+1)} R^T s$$

- ▶ Displacement Error:

$$D^{(t,t+1)}: \operatorname{dist} \{W^{(t)}, W_*^{(t+1)}\}$$

- ▶ **anchors:**  $k$  words with lowest displacement error between  $[t, t+1]$

## APPROACH: DETAILS

- ▶ We want to find:

$$R = \operatorname{argmin}_{\Omega; \Omega^T \Omega = I} \left\| W^{(t)} \Omega - W^{(t+1)} \right\|_F$$

- ▶ Solved as:

$$R = UV^T, \text{ where} \\ U \Sigma V^T = \operatorname{SVD}(W^{(t+1)} W^{(t)T})$$

- ▶ Align vectors as:

$$W_*^{(t+1)} = W^{(t+1)} R^T s$$

- ▶ Displacement Error:

$$D^{(t,t+1)}: \operatorname{dist} \{W^{(t)}, W_*^{(t+1)}\}$$

- ▶ **anchors:**  $k$  words with lowest displacement error between  $[t, t+1]$
- ▶ **Diachronic Anchors:**  $k$  words with lowest avg displacement error across time

## APPROACH: DETAILS

- ▶ We want to find:

$$R = \operatorname{argmin}_{\Omega; \Omega^T \Omega = I} \left\| W^{(t)} \Omega - W^{(t+1)} \right\|_F$$

- ▶ Solved as:

$$R = UV^T, \text{ where}$$
$$U \Sigma V^T = \operatorname{SVD}(W^{(t+1)} W^{(t)T})$$

- ▶ Align vectors as:

$$W_*^{(t+1)} = W^{(t+1)} R^T s$$

- ▶ Displacement Error:

$$D^{(t,t+1)}: \operatorname{dist} \{ W^{(t)}, W_*^{(t+1)} \}$$

- ▶ **anchors:**  $k$  words with lowest displacement error between  $[t, t+1]$
- ▶ **Diachronic Anchors:**  $k$  words with lowest avg displacement error across time
- ▶ **Core idea:** learn a new alignment based *strictly* on (diachronic) anchors

# DATASET

## ▶ Word Vectors:

- ▶ *UK Web Domain Dataset 1996-2013* (>20TB) [[Basile & McGillivray, 2018](#)]
- ▶ Annual word2vec representations [[Mikolov et al., 2013](#)] during 2000-2013

# DATASET

## ▶ Word Vectors:

- ▶ *UK Web Domain Dataset 1996-2013* (>20TB) [[Basile & McGillivray, 2018](#)]
- ▶ Annual word2vec representations [[Mikolov et al., 2013](#)] during 2000-2013

## ▶ Ground Truth:

- ▶ *Oxford English Dictionary* (>250K lemmata)
- ▶ Gold standard: 208 words with a new meaning after the year 2000



# DATASET

## ▶ Word Vectors:

- ▶ *UK Web Domain Dataset 1996-2013* (>20TB) [Basile & McGillivray, 2018]
- ▶ Annual word2vec representations [Mikolov et al., 2013] during 2000-2013


## ▶ Ground Truth:

- ▶ *Oxford English Dictionary* (>250K lemmata)
- ▶ Gold standard: 208 words with a new meaning after the year 2000



## ▶ Intersected Dataset:

- ▶ 47,886 word vectors per year (2000-13)
- ▶ 65 words with known semantic shift

# EMPIRICAL INSIGHTS







# EMPIRICAL INSIGHTS




# EXPERIMENTS

- ▶ **Experiment 1:** train/eval split | eval set size: {10%, ..., 50%} | 40 runs
- ▶ **Experiment 2:** single run (whole dataset)
- ▶ **Models:**
  - ▶ PROCR\_90: alignment based on train set (Experiment 1)
  - ▶ PROCR\_100: alignment using all words
  - ▶ PROCR\_k: alignment based on anchor words
  - ▶ PROCR\_kt: alignment based on diachronic anchor words
- ▶ **Evaluation:** rank (%) of a semantically shifted word based on displacement error ( $\mu$ -rank)

## RESULTS: EXPERIMENT 1



# RESULTS: EXPERIMENT 2




**PROCR\_100:**  $35.08 \pm 4.71$

**PROCR\_k:**  $32.68 \pm 4.93$

**PROCR\_kt:**  $29.48 \pm 3.67$

# RESULTS: EXPERIMENT 2



**PROCR\_100:**  $35.08 \pm 4.71$

**PROCR\_k:**  $32.68 \pm 4.93$

**PROCR\_kt:**  $29.48 \pm 3.67$

## *Anchor vs Diachronic Anchor words:*

- ▶ #Diachronic Anchor words: 48 (i.e., top-0.1%)
- ▶ #Anchor words: 434 (from an overall possible of 631)
- ▶ Only 16% of anchor are diachronic anchor words (noise)

**Diachronic Anchor words:  
more robust short-term alignments**

# CONCLUSION & FUTURE WORK

## ▶ **Summary:**

- ▶ New labelled dataset for Semantic Change Detection
- ▶ Rank-based task & evaluation
- ▶ Procrustes Alignment based on a few diachronically stable words

## ▶ **Future Work:**

- ▶ Generalised Procrustes Alignment [[Gower, 1975](#)]
- ▶ Temporal Modelling (Temporal Clustering, Change point Detection)



# REFERENCES

- [1] Robert Bamler and Stephan Mandt. 2017. Dynamic word embeddings via skip-gram filtering. *stat* 1050:27.
- [2] Pierpaolo Basile and Barbara McGillivray. 2018. Exploiting the Web for Semantic Change Detection. In *International Conference on Discovery Science*. Springer, pages 194–208.
- [3] Paul Cook and Suzanne Stevenson. 2010. Automatically Identifying Changes in the Semantic Orientation of Words. In *Proceedings of the Seventh conference on International Language Resources and Evaluation (LREC'10)*.
- [4] Marco Del Tredici, Raquel Fern´andez, and Gemma Boleda. 2018. Short-term meaning shift: an exploratory distributional analysis. *arXiv preprint arXiv:1809.03169* .
- [5] John C Gower. 1975. Generalized procrustes analysis. *Psychometrika* 40(1):33–51.
- [6] Kristina Gulordava and Marco Baroni. 2011. A distributional similarity approach to the detection of semantic change in the Google Books Ngram corpus. In *Proceedings of the GEMS 2011 Workshop on Geometrical Models of Natural Language Semantics*. pages 67–71.
- [7] William L Hamilton, Jure Leskovec, and Dan Jurafsky. 2016. Diachronic Word Embeddings Reveal Statistical Laws of Semantic Change. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. volume 1, pages 1489–1501.
- [8] Yoon Kim, Yi-I Chiu, Kentaro Hanaki, Darshan Hegde, and Slav Petrov. 2014. Temporal Analysis of Language through Neural Language Models. In *Proceedings of the ACL 2014 Workshop on Language Technologies and Computational Social Science*. pages 61–65.
- [9] Vivek Kulkarni, Rami Al-Rfou, Bryan Perozzi, and Steven Skiena. 2015. Statistically significant detection of linguistic change. In *Proceedings of the 24th International Conference on World Wide Web*. International World Wide Web Conferences Steering Committee, pages 625–635.
- [10] Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems*. pages 3111–3119.
- [11] Alex Rosenfeld and Katrin Erk. 2018. Deep neural models of semantic shift. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*. pages 474–484.
- [12] Maja Rudolph and David Blei. 2018. Dynamic embeddings for language evolution. In *Proceedings of the 2018 World Wide Web Conference on World Wide Web*. International World Wide Web Conferences Steering Committee, pages 1003–1011.
- [13] Eyal Sagi, Stefan Kaufmann, and Brady Clark. 2009. Semantic density analysis: Comparing word meaning across time and phonetic space. In *Proceedings of the Workshop on Geometrical Models of Natural Language Semantics*. Association for Computational Linguistics, pages 104–111.
- [14] Peter H Schönemann. 1966. A generalized solution of the orthogonal procrustes problem. *Psychometrika* 31(1):1–10.
- [15] Zijun Yao, Yifan Sun, Weicong Ding, Nikhil Rao, and Hui Xiong. 2018. Dynamic word embeddings for evolving semantic discovery. In *Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining*. ACM, pages 673–681.

# THANK YOU!

Any  
Questions?

Dataset: [https://github.com/adtsakal/Semantic\\_Change](https://github.com/adtsakal/Semantic_Change)



@adtsakal  
@BarbaraMcGilli  
@basilepp

atsakalidis@turing.ac.uk