1. Make a class called Thing with no contents and print it. Then, create an object called example from this class and also print it. Are the printed values the same or different?

Answer:

2. Create a new class called Thing2 and add the value 'abc' to the letters class attribute. Letters should be printed.

Answer:

3. Make yet another class called, of course, Thing3. This time, assign the value 'xyz' to an instance (object) attribute called letters. Print letters. Do you need to make an object from the class to do this?

```
In [38]:
          1 class thing3:
                 def __init__ (self):
                      self.latter='xyz'
In [39]:
          1 print(thing3.latter)
         AttributeError
                                                    Traceback (most recent call last)
         ~\AppData\Local\Temp/ipykernel_27644/2748932243.py in <module>
         ----> 1 print(thing3.latter)
         AttributeError: type object 'thing3' has no attribute 'latter'
In [40]:
            obj=thing3()
In [41]:
           1 print(obj.latter)
         xyz
```

4. Create an Element class with the instance attributes name, symbol, and number. Create a class object with the values 'Hydrogen,' 'H,' and 1.

Answer:

```
In [42]: 1 class Element:
    def __init__(self,name,symbol, number):
        self.name=name
        self.symbol=symbol
        self.number=number

In [43]: 1 hydrogen=Element('Hydrogen','H',1)
```

5. Make a dictionary with these keys and values: 'name': 'Hydrogen', 'symbol': 'H', 'number': 1. Then, create an object called hydrogen from class Element using this dictionary.

```
In [2]: 1 hydrogen=Element('Hydrogen','H',1)
In [3]: 1 dic={'name':'Hydrogen','symbol':'H','number':1}
In [4]: 1 v=Element(**dic)
In [5]: 1 print(v.name)
Hydrogen
```

6. For the Element class, define a method called dump() that prints the values of the object's attributes (name, symbol, and number). Create the hydrogen object from this new definition and use dump() to print its attributes.

Answer:

7. Call print(hydrogen). In the definition of Element, change the name of method dump to __str__, create a new hydrogen object, and call print(hydrogen) again.

8. Modify Element to make the attributes name, symbol, and number private. Define a getter property for each to return its value.

```
In [56]:
          1 class Element:
                  def __init__(self,name,symbol,number):
           3
                      self. name=name
           4
                      self.__symbol=symbol
           5
                      self. number=number
           6
                  @property
           7
                  def name(self):
           8
                     return self.__name
           9
                 @property
          10
                  def symbol(self):
          11
                      return self.__symbol
          12
                  @property
          13
                  def number (self):
          14
                      return self. number
In [57]:
             hydrogen = Element('Hydrogen', 'H', 1)
In [58]:
           1 hydrogen.name
Out[58]: 'Hydrogen'
In [59]:
             hydrogen.symbol
Out[59]: 'H'
In [60]:
              hydrogen.number
Out[60]: 1
```

9. Define three classes: Bear, Rabbit, and Octothorpe. For each, define only one method: eats(). This should return 'berries' (Bear), 'clover' (Rabbit), or 'campers' (Octothorpe). Create one object from each and print what it eats.

```
In [61]:
              class Bear:
                  def eats(self):
           2
                      return 'berries'
           3
             class Rabbit:
           4
           5
                  def eats(self):
           6
                      return "clover"
           7
              class campers:
           8
                  def eats(self):
                      return 'Octothorpe'
           9
In [62]:
              a=Bear()
             b=Rabbit()
           2
              c=campers()
In [63]:
           1
             print(a.eats())
             print(b.eats())
           3 print(c.eats())
         berries
         clover
         Octothorpe
```

10. Define these classes: Laser, Claw, and SmartPhone. Each has only one method: does(). This returns 'disintegrate' (Laser), 'crush' (Claw), or 'ring' (SmartPhone). Then, define the class Robot that has one instance (object) of each of these. Define a does() method for the Robot that prints what its component objects do.

```
In [64]: 1 class Laser:
                def does(self):
                      return 'disintegrate'
           5 class Claw:
                def does(self):
                      return 'cursh'
           8
           9 class Smartphone:
                def does(self):
          10
          11
                      return 'ring'
          12
In [65]: 1 class Robot:
                def __init__(self):
                       self.laser = Laser()
self.claw = Claw()
                          self.Smartphone = Smartphone()
                def does(self):
    return '''My laser, to %s. \nMy claw, to %s.\nMy smartphone, to %s.''' % (
    self.laser.does(),
                          self.claw.does(),
          10
                          self.Smartphone.does() )
In [66]: 1 robbie = Robot()
In [67]: 1 print(robbie.does())
         My laser, to disintegrate. My claw, to cursh.
         My smartphone, to ring.
```