



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Danske Bank Guideline to payments in ISO 20022 XML format (pain.001.001.03)

This document describes how to distinguish between the variety of payments supported by Danske Bank using ISO 20022 XML CustomerCreditTransfer Initiation (pain.001.001.03) based on Common Global Implementation (CGI) recommendations and country specific recommendations in Denmark, Norway and Finland.
Please note that Swedish payment types are implemented based on Danske Bank interpretation due to the fact that no country specific recommendations have been published yet.

The tabel below only serves to distinguish between the several types of payments supported by Danske Bank. In addition to the tags mentioned other required tags must be filled in too.

For a full list of supported tags please see the document "Danske Bank MIG - ISO 20022 XML CustomerCreditTransferInitiation (pain.001.001.03)"



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Contents

Change log	3
Danish payment types	4
Norwegian payment types	8
Swedish payment types	9
Finnish payment types	12
German payment types	14
English payment types	15
Irish payment types	16
Polish payment types	17
Foreign payment types	19
Notes	23
Denmark – sample files	26
Norway – sample files	60
Sweden – sample files	70
Finland – sample files	92
Germany – sample files	119
Great Britain – sample files	129
Ireland – sample files	135
Poland – sample files	145
Foreign payment types – sample files	155

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Change log

Version	Date	Change
1.0	05.10.2012	Document created

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Danish payment types						
Danish cheque		2.2 2.61 / 2.79 2.99	<PmtMtd> <DlvrTo> or <Cdtr> <Ustrd>	'CHK' Name and address (PstCd and TwnNm in structured form) Unstructured advice for creditor (Max. 1435 char)	link	Domestic cheques are always crossed and sent to creditor
Danish account transfer	Short-form advice, entry text on account statement	2.2 2.88	<PmtMtd> <Prtry>	'TRF' Short message for creditor (Max. 20 char)	link	
	Immediate advice, letter to beneficiary	2.2 2.7 / 2.32 2.99	<PmtMtd> <InstrPrty> <Ustrd>	'TRF' 'HIGH' Unstructured advice for creditor (Max. 1435 char)	link	
	Long-form advice, enclosed with next account statement	2.2 2.88 2.99	<PmtMtd> <Prtry> <Ustrd>	'TRF' Short message for creditor (Max. 20 char) Unstructured advice for creditor (Max. 1435 char)	link	
Danish inpayment form	Type 01	2.2 2.80:1.1.3 2.80:1.1.6 2.99 2.123 2.126	<PmtMtd> <Id> <Prtry> <Ustrd> <Cd> <Ref>	'TRF' Danish GIRO Number 7-8 digits 'OCR' Unstructured advice for creditor (Max. 945 char) 'SCOR' '01/'	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Danish inpayment form	Type 04	2.2 2.80:1.1.3 2.80:1.1.6 2.123 2.126	<PmtMtd> <Id> <Prtry> <Cd> <Ref>	'TRF' Danish GIRO Number 7-8 digits 'OCR' 'SCOR' '04/NNNNNNNNN' (NNNNNNNNNN is max. 16 char)	link	
	Type 15	2.2 2.80:1.1.3 2.80:1.1.6 2.123 2.126	<PmtMtd> <Id> <Prtry> <Cd> <Ref>	'TRF' Danish GIRO Number 7-8 digits 'OCR' 'SCOR' '15/NNNNNNNNNN' (NNNNNNNNNN is max. 16 char)	link	
	Type 41	2.2 2.80:1.1.3 2.80:1.1.6 2.99 2.123 2.126	PmtMtd> <Id> <Prtry> <Ustrd> <Cd> <Ref>	'TRF' Danish GIRO Number 7-8 digits 'OCR' Unstructured advice for creditor (Max. 945 char) 'SCOR' '41/NNNNNNNNNN' (NNNNNNNNNN is max. 10 char)	link	
	Type 71	2.2 2.80:1.1.3 2.80:1.1.6 2.123 2.126	<PmtMtd> <Id> <Prtry> <Cd> <Ref>	'TRF' Creditor Number 7-8 digits 'OCR' 'SCOR' '71/NNNNNNNNNN' (NNNNNNNNNN is max. 15 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Danish inpayment form	Type 73	2.2 2.80:1.1.3 2.80:1.1.6 2.99	<PmtMtd> <Id> <Prtry> <Ustrd>	'TRF' Creditor Number 7-8 digits 'OCR' Unstructured advice for creditor (Max. 14 35 char) 2.123 = 'SCOR' 2.126 = '73/'	link	
	Type 75	2.2 2.80:1.1.3 2.80:1.1.6 2.99	<PmtMtd> <Id> <Prtry> <Ustrd>	'TRF' Creditor Number 7-8 digits 'OCR' Unstructured advice for creditor (Max. 14 35 char) 'SCOR' '75/NNNNNNNNNN' (NNNNNNNNNN is max. 16 char)	link	
Danish salary		2.2 2.15 / 2.40	<PmtMtd> <Cd>	'TRF' 'SALA'	link	Danish account transfer with restricted advice "Lønoverførsel" (=Salary) to the creditor. Transfer to accounts within Danske Bank is for disposal the next banking day (neutral disposal).

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Easy account payments (NemKonto)	EasyAccount payment (CPR)	2.2 2.80:1.1.3 2.80:1.1.6	<PmtMtd> <Id> <Prtry>	2.2 = 'TRF' Social security number (CPR) 'NNNNNNNNNN' 'NKC'	link	Danish account transfer using a private or business ID as beneficiary's "account number"
	EasyAccount payment (CVR)	2.2 2.80:1.1.3 2.80:1.1.6	<PmtMtd> <Id> <Prtry>	'TRF' Central business registration number (CVR) 'NNNNNNNN' 'NKV'	link	See Danish account transfers for supported advice.
	EasyAccount payment (CVR with P-unit number)	2.2 2.80:1.1.3 2.80:1.1.6	<PmtMtd> <Id> <Prtry>	'TRF' Central business registration number (CVR with P-unit number) 'NNNNNNNN/NNNNNNNNNN' 'NKP'	link	For more information about Easy account transfers please see information on Danske Bank's website .
	EasyAccount payment (CVR with SE number)	2.2 2.80:1.1.3 2.80:1.1.6	<PmtMtd> <Id> <Prtry>	'TRF' Central business registration number (CVR with SE number) 'NNNNNNNN/NNNNNNNN' 'NKR'	link	
	EasyAccount payment (SE number)	2.2 2.80:1.1.3 2.80:1.1.6	<PmtMtd> <Id> <Prtry>	'TRF' SE number 'NNNNNNNN' 'NKS'	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Norwegian payment types						
Norwegian salary		2.2 2.15 / 2.40	<PmtMtd> <Cd>	'TRF' 'SALA'	link	
Norwegian account transfer	Short-form advice	2.2 2.88	<PmtMtd> <Prtry>	'TRF' Short message for creditor (Max. 27 char)	link	
	Long-form advice	2.2 2.88 2.99	<PmtMtd> <Prtry> <Ustrd>	'TRF' Short message for creditor (Max. 27 char) Unstructured advice for creditor (Max. 1750 char)	link	
	KID (OCR) reference	2.2 2.80:1.1.6 2.123 2.126	<PmtMtd> <Prtry> <Cd> <Ref>	'TRF' 'OCR' 'SCOR' KID (OCR) reference (Max. 25 char)	link	
Norwegian cash payment		2.2 2.61 / 2.79 2.99	<PmtMtd> <DlvrTo> or <Cdtr> <Ustrd>	'CHK' Name and address (PstCd and TwnNm in structured form) Unstructured advice for creditor (Max. 1750 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Swedish payment types Please note that Swedish payments are implemented based on Danske Bank interpretation due to the fact that no country specific recommendations have been published yet.						
Swedish salary		2.2 2.15 / 2.40 2.20:1.1.3 2.20:1.1.6	<PmtMtd> <Cd> <Id> <Prtry>	'TRF' 'SALA' If debtor account is BANKGIRO BANKGIRO number 'BGNR'	link	Danish account transfer with restricted advice "Lønoverførsel" (=Salary) to the creditor. Transfer to accounts within Danske Bank is for disposal the next banking day (neutral disposal).
Swedish account transfer	Short-form advice	2.2 2.88	<PmtMtd> <Prtry>	'TRF' Short message for creditor (Max. 12 char)	link	For transfers between own or intra-group accounts in the bank, 20 characters are available.
	Long-form advice	2.2 2.88 2.79 2.99	<PmtMtd> <Prtry> <Cdtr> <Ustrd>	'TRF' Short message for creditor (Max. 20 char) or Name and address (PstCd and TwnNm in structured form) and Unstructured advice for creditor (Max. 525 char)	link	If both 2.88 <Prtry> and 2.99 <Ustrd> are filled in then 2.88 <Prtry> is ignored

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Swedish cash payment		2.2 2.61 / 2.79 2.99	<PmtMtd> <DlvrTo>or <Cdtr> <Ustrd>	'CHK' Name and address (PstCd and TwnNm in structured form) Unstructured advice for creditor (Max. 525 char)	link	
	Text reference	2.2 2.80:1.1.3 2.80:1.1.6 2.88	<PmtMtd> <Id> <Prtry> <Prtry>	'TRF' BankGiro number 7-8 digits 'BGNR' Short message for creditor (Max. 25 char)	link	
	Long-form advice	2.2 2.80:1.1.3 2.80:1.1.6 2.99	<PmtMtd> <Id> <Prtry> <Ustrd>	'TRF' BankGiro number 7-8 digits 'BGNR' Unstructured advice for creditor (Max. 525 char)	link	
	OCR reference	2.2 2.80:1.1.3 2.80:1.1.6 2.123 2.126	<PmtMtd> <Id> <Prtry> <Cd> <Ref>	'TRF' BankGiro number 7-8 digits 'BGNR' 'SCOR' OCR reference (25 char)	link	
Swedish PlusGiro transfer	Text reference	2.2 2.80:1.1.3 2.80:1.1.5 2.88	<PmtMtd> <Id> <Cd> <Prtry>	'TRF' PlusGiro number 2-8 digits 'BBAN' Short message for creditor (Max. 25 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Swedish PlusGiro transfer	Long-form advice	2.2 2.80:1.1.3 2.80:1.1.5 2.99	<PmtMtd> <Id> <Cd> <Ustrd>	'TRF' PlusGiro number 2-8 digits 'BBAN' Unstructured advice for creditor (Max. 10 x 35 char)	link	
	OCR reference	2.2 2.80:1.1.3 2.80:1.1.5 2.123 2.126	<PmtMtd> <Id> <Cd> <Cd> <Ref>	'TRF' PlusGiro number 2-8 digits 'BBAN' 'SCOR' OCR reference (25 char)	link	
Swedish PlusGiro sweeping transfer		2.2 2.20:1.1.3 2.20:1.1.5 2.80	<PmtMtd> <Id> <Cd> <CdtrAcct>	'TRF' PlusGiro number 2-8 digits 'BBAN' Creditor account must be stated as IBAN or BBAN	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Finnish payment types						
Finnish salary		2.2 2.15 / 2.40 2.87	<PmtMtd> <Cd> <Cd>	'TRF' 'SALA' Salary code	link	
Finnish account transfer	Structured message	2.2 2.106 2.107 2.108	<PmtMtd> <Issr> <Nb> <RltdDt>	'TRF' Customer number Invoice number Invoice date	link	Danske Bank support 2-9 occurrences of structured message. Please see note concerning KATESIIRTO
	Unstructured message	2.2 2.99	<PmtMtd> <Ustrd>	'TRF' Unstructured advice for creditor (Max. 140 char)	link	
	OCR reference	2.2 2.123 2.126	<PmtMtd> <Cd> <Ref>	'TRF' 'SCOR' OCR reference (max. 20 char or ISO reference max. 21 char)	link	
	Tax message	2.2 2.15 / 2.40 2.123 2.126 2.129	<PmtMtd> <Cd> <Cd> <Ref> <AddtlRmtInf>	'TRF' 'TAXS' 'SCOR' OCR reference Text message (Max. 140 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Finnish account transfer	Money order	2.2 2.79 2.80:1.1.3 2.80:1.1.5 2.99	<PmtMtd> <Cdtr> <Id> <Cd> <Ustrd>	'TRF' Name and address (PstCd and TwnNm in structured form) '899999999999999' 'BBAN' Unstructured advice for creditor (Max. 140 char)	link	
	Repetitive payment	2.2 2.80:1.1.3 2.80:1.1.5	<PmtMtd> <Id> <Cd> <Ustrd>	'TRF' '811111xxxxxxx' 'BBAN' Unstructured advice for creditor (Max. 140 char)	link	'xxxxxxx' constitutes a code that will be mapped internally to an account number. The value must be agreed with the Bank beforehand.
Finnish express account transfer	Unstructured message	2.2 2.9 / 2.34 2.99	<PmtMtd> <Cd> <Ustrd>	'TRF' 'URGP' Unstructured advice for creditor (Max. 140 char)	link	
	OCR reference	2.2 2.9 / 2.34 2.123 2.126	<PmtMtd> <Cd> <Cd> <Ref>	'TRF' 'URGP' 'SCOR' OCR reference (max. 20 char or ISO reference max. 21 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
German payment types						
German account transfer	Ordinary payment	2.2 2.99	<PmtMtd> <Ustrd>	'TRF' Unstructured advice for creditor (Max. 140 char)	link	
	Express payment	2.2 2.9 / 2.34 2.99	<PmtMtd> <Cd> <Ustrd>	'TRF' 'URGP' Unstructured advice for creditor (Max. 140 char)	link	
	Internal payment	2.2 2.15 / 2.40 2.99	<PmtMtd> <Cd> <Ustrd>	'TRF' 'INTC' Unstructured advice for creditor (Max. 140 char)	link	Intracompany payment
German cheque		2.2 2.59 2.99	<PmtMtd> <Cd> <Ustrd>	'CHK' 'MLCD' Unstructured advice for creditor (Max. 140 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
English payment types						
English account transfer	Faster payment	2.2 2.88	<PmtMtd> <Prtry>	'TRF' Short message for creditor (Max. 18 char)	link	
	CHAPS payment	2.2 2.9 / 2.34 2.99	<PmtMtd> <Cd> <Ustrd>	'TRF' 'URGP' Unstructured advice for creditor (Max. 140 char)	link	For transfers between own or intra-group accounts in the bank, only 18 characters are available.
	Internal payment	2.2 2.15 / 2.40 2.88	<PmtMtd> <Cd> <Prtry>	'TRF' 'INTC' Short message for creditor (Max. 18 char)	link	Intracompany payment
	Indirect BACS	2.2 2.19:9.1.16 2.88	<PmtMtd> <Id> <Prtry>	'TRF' BACS ID - 6 digits Short message for creditor (Max. 18 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Irish payment types						
Irish account transfer	External payment	2.2 2.88	<PmtMtd> <Prtry>	'TRF' Short message for creditor (Max. 18 char)	link	
	Same day domestic payment	2.2 2.9 / 2.34 2.99	<PmtMtd> <Cd> <Ustrd>	'TRF' 'URGP' Unstructured advice for creditor (Max. 140 char)	link	For transfers between own or intra-group accounts in the bank, only 18 characters are available.
	Internal payment	2.2 2.15 / 2.40 2.88	<PmtMtd> <Cd> <Prtry>	'TRF' 'INTC' Short message for creditor (Max. 18 char)	link	Intracompany payment
	EFTS payment	2.2 2.19:9.1.16 2.88	<PmtMtd> <Id> <Prtry>	'TRF' EFTS ID - 6 digits Short message for creditor (Max. 18 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Polish payment types						
Polish account transfer	Payment with details	2.2 2.77:6.1.4 2.77:6.1.6 2.99	<PmtMtd> <Cd> <Mmbld> <Ustrd>	'TRF' 'PLKNR' BankIdentifier - 8 digits Unstructured advice for creditor (Max. 140 char)	link	
Polish account transfer	Payment without details	2.2 2.77:6.1.4 2.77:6.1.6	<PmtMtd> <Cd> <Mmbld>	'TRF' 'PLKNR' BankIdentifier - 8 digits	link	
	ZUS - insurance	2.2 2.15 / 2.40 2.77:6.1.4 2.77:6.1.6 2.99	<PmtMtd> <Cd> <Cd> <Mmbld> <Ustrd>	'TRF' 'SECU' 'PLKNR' BankIdentifier - 8 digits See note	link	
	US - tax	2.2 2.15 / 2.40 2.77:6.1.4 2.77:6.1.6 2.99	<PmtMtd> <Cd> <Cd> <Mmbld> <Ustrd>	'TRF' 'TAXS' 'PLKNR' BankIdentifier - 8 digits See note	link	
Polish express account transfer	Payment with details	2.2 2.9 / 2.34 2.77:6.1.4 2.77:6.1.6 2.99	<PmtMtd> <Cd> <Cd> <Mmbld> <Ustrd>	'TRF' 'URGP' 'PLKNR' BankIdentifier - 8 digits Unstructured advice for creditor (Max. 140 char)	link	



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Polish express account transfer	Payment without details	2.2	<PmtMtd>	'TRF'	link	
		2.9 / 2.34	<Cd>	'URGP'		
		2.77:6.1.4	<Cd>	'PLKNR'		
		2.77:6.1.6	<Mmbld>	BankIdentifier - 8 digits		

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Foreign payment types						
Foreign cheque	Cheque to be sent to account holder	2.2 2.59 2.61/ 2.79	<PmtMtd> <Cd> <DlvrTo>or/ <Cdtr>	'CHK' 'MLDB' Name and country code of receiver must be specified.	link	For instructing a crossed cheque, state 'CROSSED' in 2.66 <FrmsCd>
	Cheque to be collected in branch	2.2 2.59 2.61 / 2.79 2.69	<PmtMtd> <Cd> <DlvrTo> or <Cdtr> <PrtLctn>	'CHK' 'PUDB' Name and country code of receiver must be specified. Sort code of branch	link	
	Cheque to be sent to beneficiary	2.2 2.59 2.61/ 2.79	<PmtMtd> <Cd> <DlvrTo> or <Cdtr>	'CHK' 'MLCD' Name and country code of receiver must be specified.	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Transfer from account abroad (MT101)	Transfer to own account	2.2 2.15 / 2.40 2.21:6.1.1 2.99	<PmtMtd> <Cd> <BIC> <Ustrd>	'TRF' 'INTC' BIC of debtor agent Unstructured advice for creditor (Max. 1x140 char)	link	These payment types can be used for initiating transfers from accounts held
	Regular transfer	2.2 2.21:6.1.1 2.99	<PmtMtd> <BIC> <Ustrd>	'TRF' BIC of debtor agent Unstructured advice for creditor (Max. 1x140 char)	link	with Danske Bank in the Baltic countries, Danske Bank, Russia and from accounts held with foreign banks.
	Urgent transfer	2.2 2.9 / 2.34 2.21:6.1.1 2.99	<PmtMtd> <Cd> <BIC> <Ustrd>	'TRF' 'URGP' BIC of debtor agent Unstructured advice for creditor (Max. 1x140 char)	link	The following tags under <Strd> can be used too: 2.107<Nb> 2.108<RltdDt> 2.126<Ref>
	Domestic salary transfer	2.2 2.15 / 2.40 2.21:6.1.1 2.99	<PmtMtd> <Cd> <BIC> <Ustrd>	'TRF' 'SALA' BIC of debtor agent Unstructured advice for creditor (Max. 1x140 char)	link	<Ustrd> will overwrite <Strd> if both tags are used
	Domestic cheque	2.2 2.21:6.1.1 2.99	<PmtMtd> <BIC> <Ustrd>	'CHK' BIC of debtor agent Unstructured advice for creditor (Max. 1x140 char)	link	

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Transfer from account abroad (MT101)	Foreign cheque	2.2	<PmtMtd>	‘CHK’	link	
		2.21:6.1.1	<BIC>	BIC of debtor agent		
		2.59	<Cd>	‘MLCD’		
		2.99	<Ustrd>	Unstructured advice for creditor (Max. 1x140 char)		
Foreign account transfer	Ordinary transfer	2.2	<PmtMtd>	‘TRF’	link	
		2.99	<Ustrd>	Unstructured advice for creditor (Max 140 char)		
	Express transfer	2.2	<PmtMtd>	‘TRF’	link	
		2.9 / 2.34	<Cd>	‘URGP’		
		2.99	<Ustrd>	Unstructured advice for creditor (Max 140 char)		
	Group transfer	2.2	<PmtMtd>	‘TRF’	link	
2.15 / 2.40		<Cd>	‘INTC’			
	2.99	<Ustrd>	Unstructured advice for creditor (Max 140 char)			
Financial/treasury transfers	Nationalbank transfer (only Denmark)	2.2	<PmtMtd>	‘TRF’	link	Special rules apply to this payment type. Please contact Support Direct.
		2.9 / 2.34	<Cd>	‘URGP’		
		2.85	<InstrForDbtrAgt>	‘NATIONALBANK OVERFØRSEL’		
		2.99	<Ustrd>	Unstructured advice for creditor (Max 140 char)		
	Riksbank transfer (only Sweden)	2.2	<PmtMtd>	‘TRF’	link	Special rules apply to this payment type. Please contact Support Direct.
		2.9 / 2.34	<Cd>	‘URGP’		
2.85		<InstrForDbtrAgt>	‘RIKSBANK BETALING’			
2.99		<Ustrd>	Unstructured advice for creditor (Max 140 char)			



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Payment type		Special usage of tags			Example file	Additional Info
Financial/treasury transfers	Capital payment (only Finland)	2.2 2.9 / 2.34 2.99	<PmtMtd> <Cd> <Ustrd>	'TRF' 'SDVA' Unstructured advice for creditor (Max 140 char)	link	Special rules apply to this payment type. Please contact Support Direct.
	Financial payment (all countries)	2.15 / 2.40 2.43 2.71 2.77 2.78 2.79 2.99	<Cd> <InstdAmt Ccy> <IntrmyAgt1> <CdtrAgt> <CdtrAgtAcct> <Cdtr> <Ustrd>	'CORT' or 'TREA' Currency of instructed amount Name and BIC of correspondent bank Name and BIC of creditor agent Creditor agent account in correspondent bank Name of creditor Unstructured advice for creditor (Max. 140 char)	link	Special rules apply to this payment type. Please contact Support Direct.

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Notes

CategoryPurpose	<p>These CategoryPurpose code are supported in 2.15 / 2.40 <Cd>:</p> <p>CORT - Transaction is related to settlement of a trade, eg a foreign exchange deal or a securities transaction</p> <p>INTC - Transaction is an intra-company payment, ie, a payment between two companies belonging to the same group</p> <p>PENS- Transaction is the payment of pension</p> <p>SALA - Transaction is the payment of salaries</p> <p>SECU - Transaction is the payment of securities</p> <p>SSBE - Transaction is a social security benefit, ie payment made by a government to support individuals</p> <p>SUPP - Transaction is related to a payment to a supplier</p> <p>TAXS - Transaction is the payment of taxes</p> <p>TREA - Transaction is related to treasury operations. E.g. financial contract settlement</p>																		
Polish ZUS insurance payment	<p>Unstructured Remittance Information must be formatted this way (3 occurrences of 2.99 Ustrd)</p> <table border="1"> <thead> <tr> <th>Field</th><th>Status</th><th>Format</th><th>Data</th><th>Occurrence no. (Ustrd)</th></tr> </thead> <tbody> <tr> <td>NIP -company no.</td><td>M</td><td>10 n</td><td>NIP</td><td>1</td></tr> <tr> <td>Type of supplementary identity document</td><td>M</td><td>1 a</td><td> P-Pesel R - Regon 1 - Identity card 2 - Passport </td><td>2</td></tr> </tbody> </table>				Field	Status	Format	Data	Occurrence no. (Ustrd)	NIP -company no.	M	10 n	NIP	1	Type of supplementary identity document	M	1 a	P-Pesel R - Regon 1 - Identity card 2 - Passport	2
Field	Status	Format	Data	Occurrence no. (Ustrd)															
NIP -company no.	M	10 n	NIP	1															
Type of supplementary identity document	M	1 a	P-Pesel R - Regon 1 - Identity card 2 - Passport	2															

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

	Supplementary identity doc.	M	14 a	Supplementary identity document. Right-adjusted and filled with blanks up to 14 characters	2
	Type of payment	M	1 a	S - payment for 1 month period only D - additional fee E - execution K - payment after control M - payment for period longer than 1 month T - postponing the deadline U - partial payment	3
	Period	M	6 n	Type of payment = D:000000 Type of payment = E: numeric Other types: Month covered by the payment YYYYMM	3
		M	2 n	Type of payment = E: 00 Type of payment = K: 99 Other types: Number of declaration.	3
Polish US tax payment	Unstructured Remittance Information must be formatted this way [4 occurrences of 2.99 Ustrd] :				
	Field	Status	Format	Code	Data
	Type of supplementary identity document	M	1 a	/TI/	Type of supplementary identity document can have one of following values: N - NIP P - Pesel R - Regon

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

					1 - Identity card 2 - Passport.	
	Supplementary identity doc.	M	14 a		Supplementary identity document. Right-adjusted filled with blanks up to 14 characters	1
	Period covered by the payment	M	7 a	/OKR/	Format: YYQXXXXX Where Q is a qualifier, that gives meaning to the next four characters (X) M = Month (01 - 12), e.g. 95M09 P = Half year (01 - 02), e.g. 96P01 R = [empty] e.g. 97R K = Quarter (01 - 04) e.g. 98K03 D = Decade and month (01 - 03 and 01 - 12) e.g. 99D0211 (Decade is a period of 10 days in a month)	2
	Symbol of the form or reason of payment	M	6 a	/SFP/	Code supplied by public authority	3
		O	21 a	/TXT/	Additional details in free format	4
KATESIIRTO (only Finland)	A "Speed-up" agreement on a Finnish account can be avoided by entering the word KATESIIRTO in 2.99 Ustrd.					

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

File Examples

Denmark – sample files

Danish cheque

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <LclInstrm>
          <Prtry>CII</Prtry>
        </LclInstrm>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>DK cheque</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="DKK">1.00</InstdAmt>
  </Amt>
  <ChqInstr>
    <ChqTp>BCHQ</ChqTp>
  </ChqInstr>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABADKKK</BIC>
      <PstlAdr>
        <Ctry>DK</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Danske Bank</Nm>
    <PstlAdr>
      <StrtNm>Holmens Kanal</StrtNm>
      <BldgNb>2-12</BldgNb>
      <PstCd>1092</PstCd>
      <TwnNm>København K</TwnNm>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </Cdtr>
  <RmtInf>
    <Ustrd>CHK LIN 1.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitt>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish account transfer - short-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK acc. trf. with short form advice</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>3258186214</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>20 char short advice</Prtry>
</Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish account transfer - immediate advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <InstrPrty>HIGH</InstrPrty>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK acc. trf. with immediate advice</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstdAmt Ccy="DKK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABADKKK</BIC>
      <PstlAdr>
        <Ctry>DK</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>3258186214</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Ustrd>LIN 1.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish account transfer - long-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK acc. trf. with long-form advice</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```




Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>3258186214</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>20 char short advice</Prtry>
</Purp>
<RmtInf>
  <Ustrd>LIN 1.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish inpayment form - Type 01

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK inpayment form IK01</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>1234567</Id>
      <SchmeNm>
        <Prtry>OCR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>IK01 LIN 1.....END</Ustrd>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>01</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish inpayment form - Type 04

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK inpayment form IK04</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>1234567</Id>
      <SchmeNm>
        <Prtry>OCR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>04/1234567890123456</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish inpayment form - Type 15

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK inpayment form IK15</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>1234567</Id>
      <SchmeNm>
        <Prtry>OCR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>15/1234567890123456</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish inpayment form - Type 41

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK inpayment form IK41</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```




Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>1234567</Id>
      <SchmeNm>
        <Prtry>OCR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>IK41 LIN 1.....END</Ustrd>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>41/1234567890</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish inpayment form - Type 71

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK inpayment form IK71</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678</Id>
      <SchmeNm>
        <Prtry>OCR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>71/123456789012345</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish inpayment form - Type 73

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK inpayment form IK73</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678</Id>
      <SchmeNm>
        <Prtry>OCR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>IK73 LIN 1.....END</Ustrd>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>73</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish inpayment form - Type 75

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK inpayment form IK75</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678</Id>
      <SchmeNm>
        <Prtry>OCR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>IK75 LIN 1.....END</Ustrd>
  <Strd>
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>75/1234567890123456</Ref>
    </CdtrRefInf>
  </Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Danish salary

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>SALA</Cd>
        </CtgyPurp>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK salary payment</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```




Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="DKK">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>3258186214</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

NemKonto (Easy Account) - CPR

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Business Online 1</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK NemKonto payment for CPR number</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>1234567890</Id>
      <SchmeNm>
        <Prtry>NKC</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>20 char short advice</Prtry>
</Purp>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

NemKonto (Easy Account) - CVR

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Business Online 1</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK NemKonto payment for CVR number</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678</Id>
      <SchmeNm>
        <Prtry>NKV</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>20 char short advice</Prtry>
</Purp>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

NemKonto (Easy Account) - CVR with P-unit number

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Business Online 1</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK NemKonto pmt. CVR/P-unit number</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678/1234567890</Id>
      <SchmeNm>
        <Prtry>NKP</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>20 char short advice</Prtry>
</Purp>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

NemKonto (Easy Account) - CVR with SE number

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Business Online 1</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK NemKonto pmt. for CVR/SE number</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```




Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678/12345678</Id>
      <SchmeNm>
        <Prtry>NKR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>20 char short advice</Prtry>
</Purp>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

NemKonto (Easy Account) - SE number

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2009-02-17T12:49:35</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Business Online 1</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DK NemKonto payment for SE number</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678</Id>
      <SchmeNm>
        <Prtry>NKS</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>20 char short advice</Prtry>
</Purp>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Norway - sample files

Norwegian salary

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Nm>Initiating party name</Nm>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>SALA</Cd>
        </CtgyPurp>
      </PmtTplInf>
      <ReqdExctnDt>2012-09-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>NO</Ctry>
        </PstlAdr>
        <Id>
          <OrgId>
            <Othr>
              <Id>12345678</Id>
            </Othr>
          </OrgId>
        </Id>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>N061976000000105</IBAN>
        </Id>
        <Ccy>NOK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<FinInstnId>
  <BIC>DABANO22</BIC>
  <PstlAdr>
    <PstCd>7012</PstCd>
    <TwnNm>Trondheim</TwnNm>
    <Ctry>NO</Ctry>
    <AdrLine>Søndregate 13-15</AdrLine>
  </PstlAdr>
</FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>NO salary</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="NOK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABANO22</BIC>
      <PstlAdr>
        <TwnNm>Trondheim</TwnNm>
        <Ctry>NO</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>NO</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>N051976000000091</IBAN>
    </Id>
  </CdtrAcct>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Norwegian account transfer – short-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Nm>Initiating party name</Nm>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfId>PmtInfId</PmtInfId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-26</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>NO</Ctry>
        </PstlAdr>
        <Id>
          <OrgId>
            <Othr>
              <Id>12345678</Id>
            </Othr>
          </OrgId>
        </Id>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>N06197600000105</IBAN>
        </Id>
        <Ccy>NOK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABANO22</BIC>
          <PstlAdr>
            <Ctry>NO</Ctry>
          </PstlAdr>
        </FinInstnId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>NO account trf. with short advice</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="NOK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABANO22</BIC>
      <PstlAdr>
        <TwnNm>Trondheim</TwnNm>
        <Ctry>NO</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>7012</PstCd>
      <TwnNm>Trondheim</TwnNm>
      <Ctry>NO</Ctry>
      <AdrLine>Søndregate 13-15</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>N051976000000091</IBAN>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>27 char beneficiary ref END</Prtry>
  </Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Norwegian account transfer – long-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Nm>Initiating party name</Nm>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfId>PmtInfId</PmtInfId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>NO</Ctry>
        </PstlAdr>
        <Id>
          <OrgId>
            <Othr>
              <Id>12345678</Id>
            </Othr>
          </OrgId>
        </Id>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>N06197600000105</IBAN>
        </Id>
        <Ccy>NOK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABANO22</BIC>
          <PstlAdr>
            <Ctry>NO</Ctry>
          </PstlAdr>
        </FinInstnId>
```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>NO account trf. with long advice</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="NOK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABANO22</BIC>
      <PstlAdr>
        <TwnNm>Trondheim</TwnNm>
        <Ctry>NO</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>7012</PstCd>
      <TwnNm>Trondheim</TwnNm>
      <Ctry>NO</Ctry>
      <AdrLine>Søndregate 13-15</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>976000000091</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>27 char beneficiary ref END</Prtry>
  </Purp>
  <RmtInf>
    <Ustrd>Ustrd .....line 1</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Norwegian account transfer - KID reference

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Nm>Initiating party name</Nm>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfId>PmtInfId</PmtInfId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>NO</Ctry>
        </PstlAdr>
        <Id>
          <OrgId>
            <Othr>
              <Id>12345678</Id>
            </Othr>
          </OrgId>
        </Id>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>N061976000000105</IBAN>
        </Id>
        <Ccy>NOK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABANO22</BIC>
          <PstlAdr>
            <Ctry>NO</Ctry>
          </PstlAdr>
        </FinInstnId>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>NO account trf. with KID reference</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="NOK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABANO22</BIC>
      <PstlAdr>
        <TwnNm>Trondheim</TwnNm>
        <Ctry>NO</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>7012</PstCd>
      <TwnNm>Trondheim</TwnNm>
      <Ctry>NO</Ctry>
      <AdrLine>Søndregate 13-15</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>NO51976000000091</IBAN>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Strd>
      <CdtrRefInf>
        <Tp>
          <CdOrPrtry>
            <Cd>SCOR</Cd>
          </CdOrPrtry>
        </Tp>
        <Ref>1234567890123456789012345</Ref>
      </CdtrRefInf>
    </Strd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Norwegian cash payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Nm>Initiating party name</Nm>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfId>PmtInfId</PmtInfId>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>NO</Ctry>
        </PstlAdr>
        <Id>
          <OrgId>
            <Othr>
              <Id>12345678</Id>
            </Othr>
          </OrgId>
        </Id>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>N06197600000105</IBAN>
        </Id>
        <Ccy>NOK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABANO22</BIC>
          <PstlAdr>
            <Ctry>NO</Ctry>
          </PstlAdr>
        </FinInstnId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>NO cash payment</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="NOK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABANO22</BIC>
      <PstlAdr>
        <TwnNm>Trondheim</TwnNm>
        <Ctry>NO</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>7012</PstCd>
      <TwnNm>Trondheim</TwnNm>
      <Ctry>NO</Ctry>
      <AdrLine>Søndregate 13-15</AdrLine>
    </PstlAdr>
  </Cdtr>
  <RmtInf>
    <Ustrd>Ustrd .....line 1</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Sweden - sample files

Swedish salary

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplnf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>SALA</Cd>
        </CtgyPurp>
      </PmtTplnf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
        <PstlAdr>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <Ctry>SE</Ctry>
  </PstlAdr>
</FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>SE salary transfer</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>10392</PstCd>
      <TwnNm>Stockholm</TwnNm>
      <Ctry>SE</Ctry>
      <AdrLine>Norrmlalmstorg 1</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678901</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish account transfer – short-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initiating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-26</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```




Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>SE account trf. with short advice</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
      <PstlAdr>
        <Ctry>SE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678901</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>Short advice</Prtry>
  </Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish account transfer – long-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initiating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfd>PmtInfd</PmtInfd>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-26</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>SE account trf. with long advice</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
      <PstlAdr>
        <Ctry>SE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>10392</PstCd>
      <TwnNm>Stockholm</TwnNm>
      <Ctry>SE</Ctry>
      <AdrLine>Norrmalmstorg 1</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678901</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Ustrd>Ustrd .....line 1</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish cash payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initiating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<InstrId>SE cash payment</InstrId>
<EndToEndId>EndToEndId</EndToEndId>
</PmtId>
<Amt>
  <InstdAmt Ccy="SEK">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABASESX</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <PstCd>10392</PstCd>
    <TwnNm>Stockholm</TwnNm>
    <Ctry>SE</Ctry>
    <AdrLine>Norrmalmstorg 1</AdrLine>
  </PstlAdr>
</Cdtr>
<RmtInf>
  <Ustrd>Ustrd .....line 1</Ustrd>
  <Ustrd>Ustrd .....line 2</Ustrd>
  <Ustrd>Ustrd .....line 3</Ustrd>
  <Ustrd>Ustrd .....line 4</Ustrd>
  <Ustrd>Ustrd .....line 5</Ustrd>
  <Ustrd>Ustrd .....line 6</Ustrd>
  <Ustrd>Ustrd .....line 7</Ustrd>
  <Ustrd>Ustrd .....line 8</Ustrd>
  <Ustrd>Ustrd .....line 9</Ustrd>
  <Ustrd>Ustrd .....line 10</Ustrd>
  <Ustrd>Ustrd .....line 11</Ustrd>
  <Ustrd>Ustrd .....line 12</Ustrd>
  <Ustrd>Ustrd .....line 13</Ustrd>
  <Ustrd>Ustrd .....line 14</Ustrd>
  <Ustrd>Ustrd .....END.....line 15</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish Bankgiro payment - text reference

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>SE BankGiro text reference</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
      <PstlAdr>
        <Ctry>SE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>10392</PstCd>
      <TwnNm>Stockholm</TwnNm>
      <Ctry>SE</Ctry>
      <AdrLine>Norrmalmstorg 1</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678</Id>
        <SchmeNm>
          <Prtry>BGNR</Prtry>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>Short message</Prtry>
  </Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish Bankgiro payment - long-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initiating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<InstrId>SE BankGiro long advice</InstrId>
<EndToEndId>EndToEndId</EndToEndId>
</PmtId>
<Amt>
  <InstdAmt Ccy="SEK">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABASESX</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <PstCd>10392</PstCd>
    <TwnNm>Stockholm</TwnNm>
    <Ctry>SE</Ctry>
    <AdrLine>Norrmalmstorg 1</AdrLine>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678</Id>
      <SchmeNm>
        <Prtry>BGNR</Prtry>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Ustrd .....line 1</Ustrd>
  <Ustrd>Ustrd .....line 2</Ustrd>
  <Ustrd>Ustrd .....line 3</Ustrd>
  <Ustrd>Ustrd .....line 4</Ustrd>
  <Ustrd>Ustrd .....line 5</Ustrd>
  <Ustrd>Ustrd .....line 6</Ustrd>
  <Ustrd>Ustrd .....line 7</Ustrd>
  <Ustrd>Ustrd .....line 8</Ustrd>
  <Ustrd>Ustrd .....line 9</Ustrd>
  <Ustrd>Ustrd .....line 10</Ustrd>
  <Ustrd>Ustrd .....line 11</Ustrd>
  <Ustrd>Ustrd .....line 12</Ustrd>
  <Ustrd>Ustrd .....line 13</Ustrd>
  <Ustrd>Ustrd .....line 14</Ustrd>
  <Ustrd>Ustrd .....END.....line 15</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish Bankgiro payment - OCR reference

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>SE BankGiro OCR reference</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
      <PstlAdr>
        <Ctry>SE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>10392</PstCd>
      <TwnNm>Stockholm</TwnNm>
      <Ctry>SE</Ctry>
      <AdrLine>Norrmalmstorg 1</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678</Id>
        <SchmeNm>
          <Prtry>BGNR</Prtry>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Strd>
      <CdtrRefInf>
        <Tp>
          <CdOrPrtry>
            <Cd>SCOR</Cd>
          </CdOrPrtry>
        </Tp>
        <Ref>123456789</Ref>
      </CdtrRefInf>
    </Strd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish Plusgiro payment - text reference

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>SE PlusGiro text reference</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
      <PstlAdr>
        <Ctry>SE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>10392</PstCd>
      <TwnNm>Stockholm</TwnNm>
      <Ctry>SE</Ctry>
      <AdrLine>Norrmalmstorg 1</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>Short message</Prtry>
  </Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish Plusgiro payment - long-form advice

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initiating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<InstrId>SE PlusGiro long form</InstrId>
<EndToEndId>EndToEndId</EndToEndId>
</PmtId>
<Amt>
  <InstdAmt Ccy="SEK">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABASESX</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <PstCd>10392</PstCd>
    <TwnNm>Stockholm</TwnNm>
    <Ctry>SE</Ctry>
    <AdrLine>Norrmalmstorg 1</AdrLine>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345678</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Ustrd .....line 1</Ustrd>
  <Ustrd>Ustrd .....line 2</Ustrd>
  <Ustrd>Ustrd .....line 3</Ustrd>
  <Ustrd>Ustrd .....line 4</Ustrd>
  <Ustrd>Ustrd .....line 5</Ustrd>
  <Ustrd>Ustrd .....line 6</Ustrd>
  <Ustrd>Ustrd .....line 7</Ustrd>
  <Ustrd>Ustrd .....line 8</Ustrd>
  <Ustrd>Ustrd .....line 9</Ustrd>
  <Ustrd>Ustrd .....END.....line 10</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish Plusgiro payment - OCR reference

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12200115199</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>SE PlusGiro OCR reference</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
      <PstlAdr>
        <Ctry>SE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>10392</PstCd>
      <TwnNm>Stockholm</TwnNm>
      <Ctry>SE</Ctry>
      <AdrLine>Norrmalmstorg 1</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Strd>
      <CdtrRefInf>
        <Tp>
          <CdOrPrtry>
            <Cd>SCOR</Cd>
          </CdOrPrtry>
        </Tp>
        <Ref>1234567</Ref>
      </CdtrRefInf>
    </Strd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Swedish Plusgiro sweeping transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-05-11T10:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfd>PmtInfd</PmtInfd>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-09-17</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>12345678</Id>
            <SchmeNm>
              <Cd>BBAN</Cd>
            </SchmeNm>
          </Othr>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>SE PlusGiro sweeping transfer</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="SEK">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABASESX</BIC>
      <PstlAdr>
        <Ctry>SE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>10392</PstCd>
      <TwnNm>Stockholm</TwnNm>
      <Ctry>SE</Ctry>
      <AdrLine>Norrnormalstorg 1</AdrLine>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345678901</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finland – sample files

Finnish salary

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </Id>
      <OrgId>
        <Othr>
          <Id>Initating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </Id>
  </InitgPty>
</GrpHdr>
  <PmtInf>
    <PmtInflId>PmtInflId</PmtInflId>
    <PmtMtd>TRF</PmtMtd>
    <PmtTpInf>
      <SvcLvl>
        <Cd>SEPA</Cd>
      </SvcLvl>
      <CtgyPurp>
        <Cd>SALA</Cd>
      </CtgyPurp>
    </PmtTpInf>
    <ReqdExctnDt>2012-06-19</ReqdExctnDt>
    <Dbtr>
      <Nm>Debtor Name</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </Dbtr>
    <DbtrAcct>
      <Id>
        <IBAN>FI5934499400001396</IBAN>
      </Id>
    </DbtrAcct>
  </PmtInf>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Id>
<Ccy>EUR</Ccy>
</DbtrAcct>
<DbtrAgt>
  <FinInstnId>
    <BIC>DABAFIHH</BIC>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </FinInstnId>
</DbtrAgt>
<ChrgBr>SLEV</ChrgBr>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>Finnish salary payment</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
      <Nm>CdtrAgt</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>FI6934499400001701</IBAN>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
  <Id>
    <PrvtId>
      <Othr>
        <Id>000000-000T</Id>
        <SchmeNm>
          <Cd>SOSE</Cd>
        </SchmeNm>
      </Othr>
    </PrvtId>
  </Id>
</UltmtCdtr>
<Purp>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```
<Cd>STDY</Cd>
</Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish account transfer - structured message

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>SEPA</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<PstlAdr>
  <Ctry>FI</Ctry>
</PstlAdr>
</FinInstnId>
</DbtrAgt>
<ChrgBr>SLEV</ChrgBr>
<CdtTrfTxInf>
  <PmtId>
    <InstId>FI acc. trf. - structured message</InstId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
      <Nm>CdtrAgt</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>FI6934499400001701</IBAN>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
    <Id>
      <PrvtId>
        <Othr>
          <Id>000000-000T</Id>
          <SchmeNm>
            <Cd>SOSE</Cd>
          </SchmeNm>
        </Othr>
      </PrvtId>
    </Id>
  </UltmtCdtr>
  <RmtInf>
    <Strd>
      <RfrdDocInf>
        <Tp>
          <CdOrPrtry>
            <Cd>CINV</Cd>
          </CdOrPrtry>

```




Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```
<Issr>12345678</Issr>
</Tp>
<Nb>123456789012345</Nb>
<RltdDt>2012-03-29</RltdDt>
</RfrdDocInf>
</Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish account transfer - unstructured message

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>SEPA</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </FinInstnId>
</DbtrAgt>
<ChrgBr>SLEV</ChrgBr>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>FI acc. trf. - unstructured message</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
      <Nm>CdtrAgt</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>FI6934499400001701</IBAN>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
    <Id>
      <PrvtId>
        <Othr>
          <Id>000000-000T</Id>
          <SchmeNm>
            <Cd>SOSE</Cd>
          </SchmeNm>
        </Othr>
      </PrvtId>
    </Id>
  </UltmtCdtr>
  <RmtInf>
    <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

</Document>

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish account transfer - OCR reference

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInfd>PmtInfd</PmtInfd>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>SEPA</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<PstlAdr>
  <Ctry>FI</Ctry>
</PstlAdr>
</FinInstnId>
</DbtrAgt>
<ChrgBr>SLEV</ChrgBr>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>FI acc. trf. - OCR reference</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.01</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
      <Nm>CdtrAgt</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>FI6934499400001701</IBAN>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
    <Id>
      <PrvtId>
        <Othr>
          <Id>000000-000T</Id>
          <SchmeNm>
            <Cd>SOSE</Cd>
          </SchmeNm>
        </Othr>
      </PrvtId>
    </Id>
  </UltmtCdtr>
  <RmtInf>
    <Strd>
      <CdtrRefInf>
        <Tp>
          <CdOrPrtry>
            <Cd>SCOR</Cd>
          </CdOrPrtry>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    </Tp>
    <Ref>RF01234567890123456789012</Ref>
  </CdtrRefInf>
</Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish account transfer - tax message

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>SEPA</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>TAXS</Cd>
        </CtgyPurp>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<DbtrAgt>
  <FinInstnId>
    <BIC>DABAFIHH</BIC>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </FinInstnId>
</DbtrAgt>
<ChrgBr>SLEV</ChrgBr>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>FI acc. trf. - OCR ref. and text</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
      <Nm>CdtrAgt</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>FI6934499400001701</IBAN>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
    <Id>
      <PrvtId>
        <Othr>
          <Id>000000-000T</Id>
          <SchmeNm>
            <Cd>SOSE</Cd>
          </SchmeNm>
        </Othr>
      </PrvtId>
    </Id>
  </UltmtCdtr>
  <RmtInf>
    <Strd>
      <CdtrRefInf>
        <Tp>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <CdOrPrtry>
      <Cd>SCOR</Cd>
    </CdOrPrtry>
  </Tp>
  <Ref>RF01234567890123456789012</Ref>
</CdtrRefInf>
<AddtlRmtInf>Text message</AddtlRmtInf>
</Strd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish account transfer - money order

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<PstlAdr>
  <Ctry>FI</Ctry>
</PstlAdr>
</FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>FI money order</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
      <Nm>CdtrAgt</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <PstCd>00</PstCd>
      <TwnNm>Helsinki</TwnNm>
      <AdrLine>AdrLine 1</AdrLine>
      <AdrLine>AdrLine 2</AdrLine>
    </PstlAdr>
    <CtryOfRes>FI</CtryOfRes>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>8999999999999999</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
    <Id>
      <PrvtId>
        <Othr>
          <Id>000000-000T</Id>
          <SchmeNm>
            <Cd>SOSE</Cd>
          </SchmeNm>
        </Othr>
      </PrvtId>
    </Id>
  </UltmtCdtr>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    </UltmtCdtr>
    <RmtInf>
      <Ustrd> 140 char unstructured remittance
information.....END</Ustrd>
    </RmtInf>
  </CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntr>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish account transfer - repetitive payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<PstlAdr>
  <Ctry>FI</Ctry>
</PstlAdr>
</FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>FI repetitive payment</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.01</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
      <Nm>CdtrAgt</Nm>
      <PstlAdr>
        <Ctry>FI</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>811111XXXXXXX</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
  <Id>
    <PrvtId>
      <Othr>
        <Id>000000-000T</Id>
        <SchmeNm>
          <Cd>SOSE</Cd>
        </SchmeNm>
      </Othr>
    </PrvtId>
  </Id>
  </UltmtCdtr>
  <RmtInf>
    <Ustrd>Unstructured remittance information</Ustrd>
  </RmtInf>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```
</CdtTrfTxInf>  
</PmtInf>  
</CstmrCdtTrfIntrn>  
</Document>
```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish express account transfer - unstructured message

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>FI urg. acc. trf. - unstruct. msg.</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
    </FinInstnId>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>FI6934499400001701</IBAN>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
  <Id>
    <PrvtId>
      <Othr>
        <Id>000000-000T</Id>
        <SchmeNm>
          <Cd>SOSE</Cd>
        </SchmeNm>
      </Othr>
    </PrvtId>
  </Id>
  </UltmtCdtr>
  <RmtInf>
    <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)
Supported payment types and examples

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Finnish express account transfer - OCR reference

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2011-04-12T08:30:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <PstlAdr>
          <AdrTp>ADDR</AdrTp>
          <Dept>Department</Dept>
          <SubDept>Subdepartment</SubDept>
          <StrtNm>Street name</StrtNm>
          <BldgNb>1</BldgNb>
          <PstCd>00075</PstCd>
          <TwnNm>Town name</TwnNm>
          <CtrySubDvsn>Country subdivision</CtrySubDvsn>
          <Ctry>FI</Ctry>
          <AdrLine>AdrLine</AdrLine>
        </PstlAdr>
      </InitgPty>
      <OrgId>
        <Othr>
          <Id>Initiating Party Id</Id>
          <SchmeNm>
            <Cd>BANK</Cd>
          </SchmeNm>
        </Othr>
      </OrgId>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>FI</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<PstlAdr>
  <Ctry>FI</Ctry>
</PstlAdr>
</FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>FI urg. acc. trf. - OCR reference</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAFIHH</BIC>
    </FinInstnId>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>FI6934499400001701</IBAN>
    </Id>
  </CdtrAcct>
  <UltmtCdtr>
    <Nm>UltmtCdtr</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
      <AdrLine>AdrLine1</AdrLine>
      <AdrLine>AdrLine2</AdrLine>
    </PstlAdr>
  <Id>
    <PrvtId>
      <Othr>
        <Id>000000-000T</Id>
        <SchmeNm>
          <Cd>SOSE</Cd>
        </SchmeNm>
      </Othr>
    </PrvtId>
  </Id>
  </UltmtCdtr>
  <RmtInf>
    <Strd>
      <CdtrRefInf>
        <Tp>
          <CdOrPrtry>
            <Cd>SCOR</Cd>
          </CdOrPrtry>
        </Tp>
        <Ref>RF01234567890123456789012</Ref>
      </CdtrRefInf>
    </Strd>
  </RmtInf>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```
</CdtrRefInf>  
</Strd>  
</RmtInf>  
</CdtTrfTxInf>  
</PmtInf>  
</CstmrCdtTrfInitn>  
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Germany - sample files

German account transfer - Ordinary payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>SEPA</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DE01234567890123456789</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADEHH</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <ChrgBr>SLEV</ChrgBr>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>DE transf. (regular)</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>COBADEFF</BIC>
      <Nm>Creditor Agent</Nm>
      <PstlAdr>
        <Ctry>DE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>DE</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>DE12345678901234567890</IBAN>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

German account transfer - Express payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor Name</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DE01234567890123456789</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADEHH</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DE transfer {urgent}</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="EUR">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>COBADEFF</BIC>
    <PstlAdr>
      <Ctry>DE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>DE12345678901234567890</IBAN>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

German account transfer - Internal payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplnf>
        <SvcLvl>
          <Cd>SEPA</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>INTC</Cd>
        </CtgyPurp>
      </PmtTplnf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DE01234567890123456789</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADEHH</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <ChrgBr>SLEV</ChrgBr>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DE group transfer</InstrId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABADEHH</BIC>
      <Nm>Creditor Agent</Nm>
      <PstlAdr>
        <Ctry>DE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>DE</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>DE12345678901234567890</IBAN>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

German cheque

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <LclInstrm>
          <Prtry>CII</Prtry>
        </LclInstrm>
      </PmtTpInf>
      <ReqdExctnDt>2012-05-23</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor Name</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DE01234567890123456789</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADEHH</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>DE domestic cheque</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="EUR">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChqInstr>
  <ChqTp>BCHQ</ChqTp>
  <DlvryMtd>
    <Cd>MLCD</Cd>
  </DlvryMtd>
</ChqInstr>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
    <AdrLine>AdrLine1</AdrLine>
    <AdrLine>AdrLine2</AdrLine>
  </PstlAdr>
</Cdtr>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

English account transfer - Faster payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>GB</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>GB89DABA95012141352105</IBAN>
        </Id>
        <Ccy>GBP</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAGB2L</BIC>
          <PstlAdr>
            <Ctry>GB</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>GB faster payment</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="GBP">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>BARCGB2102A</BIC>
    <PstlAdr>
      <Ctry>GB</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>GB</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>20337012345678</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>18 char benef. ref</Prtry>
</Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Great Britain – sample files

English account transfer - CHAPS payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>GB</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>GB89DABA95012141352105</IBAN>
        </Id>
        <Ccy>GBP</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAGB2L</BIC>
          <PstlAdr>
            <Ctry>GB</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>GB transfer (urgent)</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="GBP">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>BARCGB2102A</BIC>
    <PstlAdr>
      <Ctry>GB</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>GB</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>20337012345678</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

English account transfer - Internal payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>INTC</Cd>
        </CtgyPurp>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>GB</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>GB89DABA95012141352105</IBAN>
        </Id>
        <Ccy>GBP</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAGB2L</BIC>
          <PstlAdr>
            <Ctry>GB</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>GB trf. [internal]</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfIntrn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="GBP">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABAGB2L</BIC>
    <PstlAdr>
      <Ctry>GB</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>GB</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>95012112345678</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>18 char benef. ref</Prtry>
</Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

English account transfer - Indirect BACS

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfIntrn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>GB</Ctry>
        </PstlAdr>
        <Id>
          <OrgId>
            <Othr>
              <Id>999999</Id>
            </Othr>
          </OrgId>
        </Id>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>GB72DABA30128193018476</IBAN>
        </Id>
        <Ccy>GBP</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAGB2L</BIC>
          <PstlAdr>
            <Ctry>GB</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```
<CdtTrfTxInf>
  <PmtId>
    <InstrId>GB trf. (BACS)</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="GBP">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAGB2L</BIC>
      <PstlAdr>
        <Ctry>GB</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>GB</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>95012112345678</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>18 char benef. ref</Prtry>
  </Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Ireland - sample files

Irish account transfer - External payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>IE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>IE07DABA12345612345678</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAIE2D</BIC>
          <PstlAdr>
            <Ctry>IE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>IE trf. (external)</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="EUR">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>AIBKIE2D</BIC>
    <PstlAdr>
      <Ctry>IE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>IE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345612345678</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<Purp>
  <Prtry>18 char benef. ref</Prtry>
</Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Irish account transfer - Same day domestic payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>IE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>IE07DABA12345612345678</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAIE2D</BIC>
          <PstlAdr>
            <Ctry>IE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>IE trf. {urgent}</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="EUR">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <BIC>AIBKIE2D</BIC>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>IE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>12345612345678</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Irish account transfer - Internal payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplnf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>INTC</Cd>
        </CtgyPurp>
      </PmtTplnf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>IE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>IE07DABA12345612345678</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAIE2D</BIC>
          <PstlAdr>
            <Ctry>IE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>IE trf. [internal]</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAIE2D</BIC>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>IE</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>IE82DABA12345612345678</IBAN>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>18 char benef. ref</Prtry>
  </Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInittn>
</Document>

```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Irish account transfer - EFTS payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>IE</Ctry>
        </PstlAdr>
        <Id>
          <OrgId>
            <Othr>
              <Id>999999</Id>
            </Othr>
          </OrgId>
        </Id>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>IE07DABA12345612345678</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAIE2D</BIC>
          <PstlAdr>
            <Ctry>IE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>IE trf. [EFTS]</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="EUR">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <BIC>DABAIE2D</BIC>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>IE</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>12345612345678</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <Purp>
    <Prtry>18 char benef. ref</Prtry>
  </Purp>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInIt>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Polish account transfer - with details

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>PL</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>PL01234567890123456789012345</IBAN>
        </Id>
        <Ccy>PLN</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAPLPW</BIC>
          <PstlAdr>
            <Ctry>PL</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>PL acc. trf. with text {regular}</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="PLN">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <ClrSysMmbld>
      <ClrSysId>
        <Cd>PLKNR</Cd>
      </ClrSysId>
      <Mmbld>12345678</Mmbld>
    </ClrSysMmbld>
    <PstlAdr>
      <Ctry>PL</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>PL</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>PL12345678901234567890123456</IBAN>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>This holds a 140 char Unstructured advice.....The 140 char advice
ends here</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Poland – sample files

Polish account transfer - without details

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>PL</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>PL01234567890123456789012345</IBAN>
        </Id>
        <Ccy>PLN</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAPLPW</BIC>
          <PstlAdr>
            <Ctry>PL</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>PL acc. trf. without text (regular)</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="PLN">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <ClrSysMmbld>
      <ClrSysId>
        <Cd>PLKNR</Cd>
      </ClrSysId>
      <Mmbld>12345678</Mmbld>
    </ClrSysMmbld>
    <PstlAdr>
      <Ctry>PL</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>PL</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>PL12345678901234567890123456</IBAN>
  </Id>
</CdtrAcct>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Polish account transfer - ZUS insurance

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplnf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>SECU</Cd>
        </CtgyPurp>
      </PmtTplnf>
      <ReqdExctnDt>2012-06-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>PL</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>PL01234567890123456789012345</IBAN>
        </Id>
        <Ccy>PLN</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAPLPW</BIC>
          <PstlAdr>
            <Ctry>PL</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>PL acc. trf. ZUS (regular)</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="PLN">1.00</InstdAmt>
</Amt>
<CdtrAgt>
  <FinInstnId>
    <ClrSysMmbld>
      <ClrSysId>
        <Cd>PLKNR</Cd>
      </ClrSysId>
      <Mmbld>12345678</Mmbld>
    </ClrSysMmbld>
    <PstlAdr>
      <Ctry>PL</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>PL</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>01234567890123456789012345</Id>
      <SchmeNm>
        <Cd>BBAN</Cd>
      </SchmeNm>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>0123456789</Ustrd>
  <Ustrd>R123456789</Ustrd>
  <Ustrd>S20120619</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Polish account transfer - US tax

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplnf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>TAXS</Cd>
        </CtgyPurp>
      </PmtTplnf>
      <ReqdExctnDt>2012-06-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>PL</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>PL01234567890123456789012345</IBAN>
        </Id>
        <Ccy>PLN</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAPLPW</BIC>
          <PstlAdr>
            <Ctry>PL</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <UltmtDbtr>
        <Nm>Ultimate Debtor</Nm>
        <PstlAdr>
          <AdrLine>AdrLine1</AdrLine>
        </PstlAdr>
      </UltmtDbtr>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <AdrLine>AdrLine1</AdrLine>
  </PstlAdr>
</UltmtDbtr>
<CdtTrfTxInf>
  <PmtId>
    <InstrId>PL acc. trf. TAX</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="PLN">1.00</InstdAmt>
  </Amt>
  <CdtrAgt>
    <FinInstnId>
      <ClrSysMmbld>
        <ClrSysId>
          <Cd>PLKNR</Cd>
        </ClrSysId>
        <Mmbld>12345678</Mmbld>
      </ClrSysMmbld>
      <PstlAdr>
        <Ctry>PL</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>PL</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>01234567890123456789012345</Id>
        <SchmeNm>
          <Cd>BBAN</Cd>
        </SchmeNm>
      </Othr>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Ustrd>/TI/N5471027863</Ustrd>
    <Ustrd>/OKR/03D0312</Ustrd>
    <Ustrd>/SFP/PIT-5</Ustrd>
    <Ustrd>/TXT/FREETEXT</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Polish express account transfer - with details

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>PL</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>PL01234567890123456789012345</IBAN>
        </Id>
        <Ccy>PLN</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAPLPW</BIC>
          <PstlAdr>
            <Ctry>PL</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>PL acc. trf. with text [urgent]</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="PLN">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <ClrSysMmbld>
      <ClrSysId>
        <Cd>PLKNR</Cd>
      </ClrSysId>
      <Mmbld>12345678</Mmbld>
    </ClrSysMmbld>
    <PstlAdr>
      <Ctry>PL</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>PL</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>PL12345678901234567890123456</IBAN>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>This holds a 140 char Unstructured advice.....The 140 char advice
ends here</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Polish express account transfer - without details

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-20</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>PL</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>PL01234567890123456789012345</IBAN>
        </Id>
        <Ccy>PLN</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAPLPW</BIC>
          <PstlAdr>
            <Ctry>PL</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>PL acc. trf. without text [urgent]</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="PLN">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<CdtrAgt>
  <FinInstnId>
    <ClrSysMmbld>
      <ClrSysId>
        <Cd>PLKNR</Cd>
      </ClrSysId>
      <Mmbld>12345678</Mmbld>
    </ClrSysMmbld>
    <PstlAdr>
      <Ctry>PL</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>PL</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>PL12345678901234567890123456</IBAN>
  </Id>
</CdtrAcct>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInittn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign payment types – sample files

Foreign cheque - to be sent to account holder

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <LclInstrm>
          <Prtry>CII</Prtry>
        </LclInstrm>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Crossed cross border cheque</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="EUR">1.00</InstdAmt>
</Amt>
<ChrgBr>CRED</ChrgBr>
<ChqInstr>
  <ChqTp>BCHQ</ChqTp>
  <DlvryMtd>
    <Cd>MLDB</Cd>
  </DlvryMtd>
  <FrmsCd>CROSSED</FrmsCd>
</ChqInstr>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
    <AdrLine>AdrLine1</AdrLine>
    <AdrLine>AdrLine2</AdrLine>
  </PstlAdr>
</Cdtr>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntr>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign cheque - to be collected in branch

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <LclInstrm>
          <Prtry>CII</Prtry>
        </LclInstrm>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Cross border chq - pickup in branch</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="EUR">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChrgBr>CRED</ChrgBr>
<ChqInstr>
  <ChqTp>BCHQ</ChqTp>
  <DlvryMtd>
    <Cd>PUDB</Cd>
  </DlvryMtd>
  <PrtLctn>3627</PrtLctn>
</ChqInstr>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
    <AdrLine>AdrLine1</AdrLine>
    <AdrLine>AdrLine2</AdrLine>
  </PstlAdr>
</Cdtr>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign cheque - to be sent to beneficiary

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxes>1</NbOfTxes>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <LclInstrm>
          <Prtry>CII</Prtry>
        </LclInstrm>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Cross border chq - sent to creditor</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="EUR">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChrgBr>CRED</ChrgBr>
<ChqInstr>
  <ChqTp>BCHQ</ChqTp>
  <DlvryMtd>
    <Cd>MLCD</Cd>
  </DlvryMtd>
</ChqInstr>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
    <AdrLine>AdrLine1</AdrLine>
    <AdrLine>AdrLine2</AdrLine>
  </PstlAdr>
</Cdtr>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInittn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Transfer from account abroad - transfer to own account

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplnf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>INTC</Cd>
        </CtgyPurp>
      </PmtTplnf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>1234567890</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>COBADEFF</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>MTA Domestic group transfer</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="USD">1.00</InstdAmt>
  </Amt>
  <ChrgBr>CRED</ChrgBr>
  <CdtrAgt>
    <FinInstnId>
      <BIC>COBADEFF</BIC>
      <PstlAdr>
        <Ctry>DE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>DE</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>0123456789</Id>
      </Othr>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Transfer from account abroad - regular transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>1234567890</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>COBADEFF</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>MTA Domestic acc. trf. [regular]</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<Amt>
  <InstdAmt Ccy="USD">1.00</InstdAmt>
</Amt>
<ChrgBr>CRED</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <BIC>COBADEFF</BIC>
    <PstlAdr>
      <Ctry>DE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>0123456789</Id>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Transfer from account abroad - urgent transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor Name</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>1234567890</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>COBADEFF</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>MTA Domestic acc. trf. [urgent]</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<Amt>
  <InstdAmt Ccy="USD">1.00</InstdAmt>
</Amt>
<ChrgBr>CRED</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <BIC>COBADEFF</BIC>
    <PstlAdr>
      <Ctry>DE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <Othr>
      <Id>0123456789</Id>
    </Othr>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Transfer from account abroad - domestic salary transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTplnf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>SALA</Cd>
        </CtgyPurp>
      </PmtTplnf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>1234567890</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>COBADEFF</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

    <InstrId>MTA Domestic salary transfer</InstrId>
    <EndToEndId>EndToEndId</EndToEndId>
  </PmtId>
  <Amt>
    <InstdAmt Ccy="USD">1.00</InstdAmt>
  </Amt>
  <ChrgBr>CRED</ChrgBr>
  <CdtrAgt>
    <FinInstnId>
      <BIC>COBADEFF</BIC>
      <PstlAdr>
        <Ctry>DE</Ctry>
      </PstlAdr>
    </FinInstnId>
  </CdtrAgt>
  <Cdtr>
    <Nm>Creditor</Nm>
    <PstlAdr>
      <Ctry>DE</Ctry>
    </PstlAdr>
  </Cdtr>
  <CdtrAcct>
    <Id>
      <Othr>
        <Id>0123456789</Id>
      </Othr>
    </Id>
  </CdtrAcct>
  <RmtInf>
    <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
  </RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Transfer from account abroad - domestic cheque

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <LclInstrm>
          <Prtry>CII</Prtry>
        </LclInstrm>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>1234567890</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>COBADEFF</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>MTA Domestic cheque</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<Amt>
  <InstdAmt Ccy="EUR">1.00</InstdAmt>
</Amt>
<ChrgBr>CRED</ChrgBr>
<ChqInstr>
  <ChqTp>BCHQ</ChqTp>
  <DlvryMtd>
    <Cd>MLCD</Cd>
  </DlvryMtd>
</ChqInstr>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DE</Ctry>
    <AdrLine>AdrLine1</AdrLine>
    <AdrLine>AdrLine2</AdrLine>
  </PstlAdr>
</Cdtr>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Transfer from account abroad - foreign cheque

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>CHK</PmtMtd>
      <PmtTpInf>
        <LclInstrm>
          <Prtry>CII</Prtry>
        </LclInstrm>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-25</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <Othr>
            <Id>1234567890</Id>
          </Othr>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>COBADEFF</BIC>
          <PstlAdr>
            <Ctry>DE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>MTA Cross border cheque</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<Amt>
  <InstdAmt Ccy="USD">1.00</InstdAmt>
</Amt>
<ChrgBr>CRED</ChrgBr>
<ChqInstr>
  <ChqTp>BCHQ</ChqTp>
  <DlvryMtd>
    <Cd>MLCD</Cd>
  </DlvryMtd>
</ChqInstr>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
    <AdrLine>AdrLine1</AdrLine>
    <AdrLine>AdrLine2</AdrLine>
  </PstlAdr>
</Cdtr>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign account transfer - ordinary transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor Name</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Ordinary cross border transfer</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="SEK">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChrgBr>SHAR</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABASESX</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>SE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>SE1234567890123456789012</IBAN>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign account transfer - express transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor Name</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Express cross border transfer</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChrgBr>SHAR</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABASESX</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>SE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>SE1234567890123456789012</IBAN>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInittn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign account transfer - group transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>NURG</Cd>
        </SvcLvl>
        <CtgyPurp>
          <Cd>INTC</Cd>
        </CtgyPurp>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Cross border group transfer</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</PmtId>
<Amt>
  <InstdAmt Ccy="DKK">1.00</InstdAmt>
</Amt>
<ChrgBr>SHAR</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <BIC>DABASESX</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>SE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>SE1234567890123456789012</IBAN>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInitn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign account transfer - Nationalbank transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Danish National Bank transfer</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="DKK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChrgBr>SHAR</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <BIC>NDEADKKK</BIC>
    <PstlAdr>
      <Ctry>DK</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>DK</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>DK1234567890123456</IBAN>
  </Id>
</CdtrAcct>
<InstrForDbtrAgt>NATIONALBANK OVERFØRSEL</InstrForDbtrAgt>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfInittn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign account transfer - Riksbank transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>URGP</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>SE</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>SE3312000000012200115199</IBAN>
        </Id>
        <Ccy>SEK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABASESX</BIC>
          <PstlAdr>
            <Ctry>SE</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Swedish Riksbank transfer</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="SEK">1.00</InstdAmt>
        </Amt>
      </CdtTrfTxInf>
    </PmtInf>
  </CstmrCdtTrfInitn>
</Document>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChrgBr>SHAR</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <BIC>ESSESESS</BIC>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>SE</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>SE1234567890123456789012</IBAN>
  </Id>
</CdtrAcct>
<InstrForDbtrAgt>RIKSBANK BETALING</InstrForDbtrAgt>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```

Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign account transfer - capital payment

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTxs>1</NbOfTxs>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInflId>PmtInflId</PmtInflId>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <SvcLvl>
          <Cd>SDVA</Cd>
        </SvcLvl>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>FI5934499400001396</IBAN>
        </Id>
        <Ccy>EUR</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABAFIHH</BIC>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Finnish capital payment</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="EUR">1.00</InstdAmt>
        </Amt>
        <ChrgBr>SHAR</ChrgBr>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

<CdtrAgt>
  <FinInstnId>
    <BIC>DABAFIHH</BIC>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Creditor</Nm>
  <PstlAdr>
    <Ctry>FI</Ctry>
  </PstlAdr>
</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>FI6934499400001701</IBAN>
  </Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Unstructured remittance information of 140 char
length.....END</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```


Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

Foreign account transfer - financial transfer

```
<?xml version="1.0" encoding="utf-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03 pain.001.001.03.xsd">
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MsgId</MsgId>
      <CreDtTm>2012-03-01T09:30:47+01:00</CreDtTm>
      <NbOfTx>1</NbOfTx>
      <InitgPty>
        <Id>
          <OrgId>
            <Othr>
              <Id>Initating Party Id</Id>
              <SchmeNm>
                <Cd>BANK</Cd>
              </SchmeNm>
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfl>PmtInfl</PmtInfl>
      <PmtMtd>TRF</PmtMtd>
      <PmtTpInf>
        <CtgyPurp>
          <Cd>CORT</Cd>
        </CtgyPurp>
      </PmtTpInf>
      <ReqdExctnDt>2012-06-19</ReqdExctnDt>
      <Dbtr>
        <Nm>Debtor</Nm>
        <PstlAdr>
          <Ctry>DK</Ctry>
        </PstlAdr>
      </Dbtr>
      <DbtrAcct>
        <Id>
          <IBAN>DK0630003258186230</IBAN>
        </Id>
        <Ccy>DKK</Ccy>
      </DbtrAcct>
      <DbtrAgt>
        <FinInstnId>
          <BIC>DABADKKK</BIC>
          <PstlAdr>
            <Ctry>DK</Ctry>
          </PstlAdr>
        </FinInstnId>
      </DbtrAgt>
      <CdtTrfTxInf>
        <PmtId>
          <InstrId>Financial payment</InstrId>
          <EndToEndId>EndToEndId</EndToEndId>
        </PmtId>
        <Amt>
          <InstdAmt Ccy="SEK">1.00</InstdAmt>
```



Danske Bank Message Implementation Guide

Common Global Implementation (CGI)

Supported payment types and examples

```

</Amt>
<ChrgBr>SHAR</ChrgBr>
<IntrmyAgt1>
  <FinInstnId>
    <BIC>NDEASESS</BIC>
    <Nm>Nordea Bank AB Stockholm</Nm>
    <PstlAdr>
      <Ctry>SE</Ctry>
    </PstlAdr>
  </FinInstnId>
</IntrmyAgt1>
<CdtrAgt>
  <FinInstnId>
    <BIC>NDEAFIHH</BIC>
    <Nm>Nordea Bank Finland Plc, Helsinki</Nm>
    <PstlAdr>
      <Ctry>FI</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<CdtrAgtAcct>
  <Id>
    <IBAN>SE1234567890123456789012</IBAN>
  </Id>
</CdtrAgtAcct>
<Cdtr>
  <Nm>Nordea Bank Finland Plc, Helsinki</Nm>
  <PstlAdr>
    <Ctry>FI</Ctry>
  </PstlAdr>
</Cdtr>
<RmtInf>
  <Ustrd>Unstructured remittance information</Ustrd>
</RmtInf>
</CdtTrfTxInf>
</PmtInf>
</CstmrCdtTrfIntrn>
</Document>

```