

1.	Document Overview	3
	1.1 Background	3
	1.2 Document Purpose	3
2.	The Character Set	4
3.	Fields Types	5
4.	Usage Rules	5
5.	Unused Optional Tags	5
6.	Tag Depth Structure	6
7.	File Name	6
8.	File Format Table	7
9.	PAIN.008.001.02 Sample File	24
10.	Appendix	28



1. Document Overview

This document details the PAIN.008.001.02 file format that will be accepted by Bank of Ireland for SEPA Direct Debit Collections.

Bank of Ireland is implementing the industry PAIN formats as outlined by the Irish Payments Service Organisation (IPSO). This document adheres to the following file specification available on the IPSO website:

IPSO Customer File Formats V10

1.1 Background

SEPA aims to create a single, integrated and standardised payments market across the current 32 SEPA countries in Europe.

Direct debit originators must be SEPA compliant by 1st February 2014 in order to continue making electronic non-urgent euro payments (SEPA payments) in Ireland. Further background information is available on our website: http://bankofireland.com/SEPA

Bank of Ireland has also published a Direct Debit Readiness Checklist for direct debit originators on the Bank of Ireland website. To ensure you are aware of the changes required within your business please visit: http://bankofireland.com/SEPA

1.2 Document Purpose

The purpose of this document is to outline the PAIN008.001.02 XML file format that will be accepted by Bank of Ireland.

Knowledge of XML is recommended to interpret this document.



2. The Character Set

The PAIN.008.001.02 message format can support a range of characters; the following are the supported characters which are the basic Latin character set:

abcdefghijklmnopqrstuvwxyz

ABCDEFGHIJKLMNOPQRSTUVWXYZ

0123456789

/-?:().,'+

Space

If required, the following characters can also be used in text or information fields only, but must be provided using the XML representation shown.

Special XML Character	XML Representation
& (ampersand)	&
< (left brace)	<
> (right brace)	>
" (double quotation)	"
' (single quotation)	'

e.g. AB & C Transport would populate their name in a PAIN.008, appearing as:

<Cdtr>

<Nm>AB & amp; C TRANSPORT </Nm>

</Cdtr>

Note: Senders must ensure that the content of Identifiers/reference data elements is restricted to the restricted basic Latin character set (across). If non supported characters are used in these fields they may lead to rejection of files or transactions in the payment chain.

Exceptionally, the content of Identifiers/reference data elements

- Must not start or end with a '/'
- ► Must not contain two consecutive '/'s anywhere in the data element

These identifier fields include the following:

Mandatory Fields

- ▶ End-to-End Identification (NB: This must be unique within the Batch).
- Mandate Identification
- Message Identification
- Payment Information Identification (NB: This must be unique within the File).


Optional Fields


- Instruction Identification
- Creditor and Debtor Identification
- ► Ultimate Debtor/Creditor Identification
- Original mandate identification
- ► Remittance Information
- Proprietary Codes



3. Field Types

The following section details the type of fields that are contained in the specification document.









Note: There are a number of fields that may be populated at payment information level or at transaction level.

The Creditor Scheme Identification must be populated, and Bank of Ireland recommends populating at payment information (batch) level.

The following fields are optional and if used may be populated at payment information (batch) or transaction level;

- Ultimate Creditor
- Charge Bearer

4. Usage Rules

For a number of fields usage rules must be followed. There are outlined throughout the specification and failure to adhere to these usage rules will result in failed payments/batches/files.

5. Unused Optional Tags

Where optional tags have not been populated, the tag should be omitted from the file along with its parent tag.



6. Tag Depth Structure

In the 'TAG DEPTH' column within the file format table below, each of the 'field name' tags are represented by a '+'.

These '+' icons represent the depth of the field name tag within the document.

For example:

'+' would represent a Parent Element

'++' would represent the Child Element of the previous Parent Element

TAG DEPTH	TAG STRUCTURE
+	<>
++	
+++	

7. File Name

The following rules apply to the file name:

- 1. The file name must contain the following reference 'PAIN008'. This may appear at the beginning or within the filename.
- 2. The file extension must be '.xml'
- 3. Filename must not exceed 50 characters.
- 4. Only alphanumeric characters must be used in the filename (preceding the file extension '.xml').
- 5. Filename must contain no spaces

Example: 20130628001PAIN008.xml

It is recommended that a unique file name is used for each file. For example, this can be achieved by incorporating a date or sequence number of your own choosing.



8. File Format Table

Field Index - Field Name - Tag (Field Index as referenced in EPC Implementation Guide)	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	Data
<pre><?xml version="1.0" encoding="UTF-8"?> <document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.008.001.02" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"></document></pre>		Empty Tag	Mandatory	This tag must always be placed before the group header tag	
<cstmrdrctdbtinitn></cstmrdrctdbtinitn>		Empty Tag	Mandatory	This tag must always be placed before the group header tag	

Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	
1.0 Group Header <grphdr></grphdr>	+	Empty Tag	Mandatory		
1.1 Message Identification <msgid></msgid>	++	Yes	Mandatory	Originator's unique identifier of the submitted file/bulk. Note: This ID cannot be reused on future files	Data Type: Text Format: Max length: 35 Min length: 1
1.2 Creation Date Time <credttm></credttm>	++	Yes	Mandatory	Date and time that the file was created	Data Type: ISODateTime Format: YYYY-MM-DDTHH:MM:SS e.g. 2012-02-06T08:35:30
1.6 Number Of Transactions <nboftxs></nboftxs>	++	Yes	Mandatory	Number of individual transactions contained in the file	Data Type: Max15NumericText Format: [0-9] {1,15}

Mandatory	Field	sk
	Mandatory	√andatory Field

Optional Fields

Conditional Fields

Payment Information (Batch)/Transaction Level



Group Header Block – this can only occur once per file							
Field Index - Field Name – Tag	Tag Depth Content Mandatory/ Description Optional/ Conditional						
1.7 Control Sum <ctrlsum></ctrlsum>	++	Yes	Mandatory	Total of all individual amounts included in the file	Data Type: Decimal Number Format: Fraction Digits: 2 Total Digits: 18		
Initiating Party Usage Rule: For Group Header BOI originators must populate Private ID field							
1.8 Initiating Party <initgpty></initgpty>	++	Empty Tag	Mandatory				
1.8 Identification <id></id>	+++	Empty Tag	Mandatory				
1.8 Private Identification <prvtid></prvtid>	++++	Empty Tag	Mandatory				
1.8 Other <othr></othr>	+++++	Empty Tag	Mandatory				
1.8 Identification <id></id>	+++++	Yes	Mandatory	Populate with Creditor Scheme Identification - SEPA equivalent of OIN Number	Data Type: Text Format: Max length: 35 Min length: 1		

Optional Fields

Conditional Fields

Payment Information (Batch)/Transaction Level



Payments Information (Batch) Block – this can occur m	ultiple times withii	n a file			
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	
2.0 Payment Information <pmtinf></pmtinf>	+	Empty Tag	Mandatory		
2.1 Payment Information Identification < PmtInfld>	++	Yes	Mandatory	Originator's unique identifier of this batch of transactions within this file. PLEASE NOTE – THIS MUST BE UNIQUE WITHIN THE FILE	Data Type: Text Format: Max length: 35 Min length: 1
2.2 Payment Method <pmtmtd></pmtmtd>	++	Yes	Mandatory	Specifies the means of payment that will be used to move the amount of money.	Only 'DD' is allowed
Batch Booking Usage Rule: May be populated with true or fa	alse however payme	ents will always be l	oatch. Originators are	permitted to omit field	
2.3 Batch Booking <btchbookg></btchbookg>	++	Yes	Optional	Payments will always be batched regardless of what originator populates here	Data Type: Indicator Format: True, false
2.4 Number Of Transactions <nboftxs></nboftxs>	++	Yes	Mandatory	Populate with number of transactions in batch	Data Type: Numeric Text Format: [0-9] {1,15}
2.5 Control Sum <ctrlsum></ctrlsum>	++	Yes	Mandatory	Total of all individual amounts included in the batch	Data Type: Decimal Number Format: Fraction Digits: 2 Total Digits: 18
2.6 Payment Type Information < PmtTpInf>	++	Empty Tag	Mandatory		
2.8 Service Level <svclvl></svclvl>	+++	Empty Tag	Mandatory		
2.9 Code <cd></cd>	++++	Yes	Mandatory	Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list	Only 'SEPA' is allowed
2.11 Local Instrument <lclinstrm></lclinstrm>	+++	Empty Tag	Mandatory		
2.12 Code <cd></cd>	++++	Yes	Mandatory	Specifies the local instrument	Only 'CORE' is allowed

Optional Fields

Conditional Fields

Payment Information (Batch)/Transaction Level



Payments Information (Batch) Block – this can occur multiple times within a file							
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description			
2.14 Sequence Type <seqtp></seqtp>	+++	Yes	Mandatory	Identifies the direct debit sequence, such as first, recurrent, final or one-off	Code: FRST, RCUR, OOFF, FNAL		
2.15 Category Purpose <ctgypurp></ctgypurp>	+++	Empty Tag	Optional				
2.16 Code <cd></cd>	++++	Yes	Optional	This is used by the initiating party to provide information concerning the processing of the payment – code form	Format: Max length: 4 Min length: 1 see code list in appendix		
2.17 Proprietary <prtry></prtry>	++++	Yes	Optional	This is used by the initiating party to provide information concerning the processing of the payment – proprietary form	Data Type: Text Format: Max length: 35 Min length: 1		
2.18 Requested Collection Date < ReqdColltnDt>	++	Yes	Mandatory	Date on which the creditor requests that the amount of money is to be collected from the debtor. File must be submitted at least 6 days in advance of this date for first collections and at least 3 days in advance of this data for subsequent collections. Cut off times also apply.	Data Type: ISODate Format: YYYY-MM-DD e.g. 1998-03-30		
2.19 Creditor <cdtr></cdtr>	++	Empty Tag	Mandatory				
2.19 Name <nm></nm>	+++	Yes	Mandatory	Name by which a creditor party is known and which is usually used to identify that party	Data Type: Text Format: Max length: 70 Min length: 1		
2.19 Postal Address <pstladr></pstladr>	+++	Empty Tag	Mandatory				
2.19 Country <ctry></ctry>	++++	Yes	Optional	Country Code of creditor	Format: [A-Z]{2,2} ISO 3166, Alpha-2 code		

Optional Fields

Conditional Fields

Payment Information (Batch)/Transaction Level



Payments Information (Batch) Block – this can occur multipl	Payments Information (Batch) Block – this can occur multiple times within a file							
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description				
2.19 Address Line (2) <adrline></adrline>	++++	Yes	Optional	Creditor Postal address in free format text. Note: Two occurrences of this tag are allowed	Data Type: Text Format: Max length: 70 Min length: 1			
2.20 Creditor Account <cdtracct></cdtracct>	++	Empty Tag	Mandatory					
2.20 Identification <id></id>	+++	Empty Tag	Mandatory					
2.20 IBAN <iban></iban>	++++	Yes	Mandatory	International Bank Account Number (IBAN) of the creditor to which a credit entry will be posted as a result of the payment transaction.	Data Type: IBAN2007Identifier Format: [A-Z]{2,2}[0-9]{2,2} [a-zA-Z0-9]{1,30}			
2.20 Currency <ccy></ccy>	+++	Yes	Optional	Identification of the currency in which the account is held. Note: No processing or validation is completed on this field – for information purpose only	Currency Code Format: [A-Z]{3,3} Valid active or historic currency codes are registered with the ISO 4217			
2.21 Creditor Agent <cdtragt></cdtragt>	++	Empty Tag	Mandatory					
2.21 Financial Institution Identification < FinInstnId>	+++	Empty Tag	Mandatory					
2.21 BIC <bic></bic>	++++	Yes	Mandatory	Bank Identifier Code of the creditor.	Data Type: BIC Identifier Format: [A-Z]{6,6}[A-Z2-9] [A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}. THIS MUST BE 'BOFIIE2D'.			
Ultimate Creditor Usage Rule – Ultimate Creditor is an optional field	d, if used the N	lame and Identific	ation can be populated	at either batch or transaction level				
2.23 Ultimate Creditor <ultmtcdtr></ultmtcdtr>	++	Empty Tag	Optional					
2.23 Name <nm></nm>	+++	Yes	Optional	Ultimate party to which an amount of money is due	Data Type: Text Format: Max length: 70 Min length: 1			



Conditional Fields

Payment Information (Batch)/Transaction Level



Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/	Description					
			Optional/ Conditional						
Identification Usage Rule – Either Organisation Identification or Private Identification to be populated									
2.23 Identification <id></id>	+++	Empty Tag	Optional						
Organisation Identification Usage Rule: Either 'BIC or BEI' or one occurrence of 'Other' is allowed.									
2.23 Organisation Identification <orgid></orgid>	++++	Empty Tag	Optional						
2.23 BICOrBEI <bicorbei></bicorbei>	+++++	Yes	Optional	BIC Identifier	Data Type: Any BIC Identifier Format: [A-Z]{6,6}[A-Z2-9] [A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}				
2.23 Other <othr></othr>	++++	Empty Tag	Optional						
2.23 Identification <id></id>	+++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1				
2.23 Scheme Name <schmenm></schmenm>	+++++	No	Optional						
2.23 Code <cd></cd>	++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max Length: 4 Min length: 1				
2.23 Proprietary <prtry></prtry>	++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1				
2.23 Issuer <issr></issr>	+++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1				
Private Identification Usage Rule: Either 'Date and Pla	ace of Birth' or one occurr	ence of 'Other' is	allowed						
2.23 Private Identification < PrvtId>	++++	Empty Tag	Optional						



For small steps, for big steps, for life

Optional Fields

Conditional Fields

Payments Information (Batch) Block – this can occur multipl	e times within	n a file			
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	
2.23 Date And Place Of Birth < DtAndPlcOfBirth>	+++++	Empty Tag	Optional		
2.23 Birth Date <birthdt></birthdt>	+++++	Yes	Optional	Date on which a person is born	Data Type: ISODate Format: YYYY-MM-DD e.g. 1998-03-30
2.23 Province Of Birth <prvcofbirth></prvcofbirth>	+++++	Yes	Optional	Province where a person was born	Data Type: Text Format: Max length: 35 Min length: 1
2.23 City Of Birth <cityofbirth></cityofbirth>	+++++	Yes	Optional	City where a person was born	Data Type: Text Format: Max length: 35 Min length: 1
2.23 Country Of Birth <ctryofbirth></ctryofbirth>	+++++	Yes	Optional	Country where a person was born	Data Type: Country Code Format: [A-Z]{2,2}
2.23 Other <othr></othr>	+++++	Empty Tag	Optional		
2.23 Identification <id></id>	+++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1
2.23 Scheme Name <schmenm></schmenm>	+++++	No	Optional		
2.23 Code <cd></cd>	++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max length: 4 Min length: 1
2.23 Proprietary <prtry></prtry>	++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1



Conditional Fields



Field Index - Field Name - Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description			
2.23 Issuer <issr></issr>	+++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1		
Charge Bearer Usage Rule: Charge Bearer is optional and ma	ay be populated at p	oayment informatio	on or transaction level. B	OI recommend to populate at payment	t information level		
2.24 Charge Bearer <chrgbr></chrgbr>	++	Yes	Optional	Specifies which party/parties will bear the charges associated with the processing of the payment transaction	Only 'SLEV' is allowed		
Creditor Scheme Identification Usage Rule: CID must be populated at either payment information or transaction level. BOI recommend to populate at payment information level							
2.27 Creditor Scheme Identification <cdtrschmeld></cdtrschmeld>	++	Empty Tag	Advise to populate at Payment information (batch) level				
2.27 Identification <id></id>	+++	Empty Tag	Advise to populate at pymt info (batch) level				
2.27 Private Identification <prvtid></prvtid>	++++	Empty Tag	Advise to populate at pymt info (batch) level				
2.27 Other <othr></othr>	+++++	Empty Tag	Advise to populate at pymt info (batch) level				
2.27 Identification <id></id>	+++++	Yes	Advise to populate at pymt info (batch) level	This contains the Creditor Scheme identifier (CID) - formerly OIN	Data: Text Format: Max length: 35 Min length: 1		
2.27 Scheme Name <schmenm></schmenm>	+++++	Empty Tag	Advise to populate at pymt info (batch) level				
2.27 Proprietary <prtry></prtry>	++++++	Yes	Advise to populate at pymt info (batch) level	Name of the identification scheme, in a free text form.	Must contain 'SEPA'		

Mandatan	Fields
Mandatory	rieius

Conditional Fields



Transaction Information Block – this can occur multiple times within a Payment Information Block							
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description			
2.28 Direct Debit Transaction Information < DrctDbtTxInf>	++	Empty Tag	Mandatory				
2.29 Payment Identification <pmtid></pmtid>	+++	Empty Tag	Mandatory				
2.30 Payment Identification/Instruction Identification < InstrId>	++++	Yes	Optional	Secondary identification that the originator may place on the payment Note: Many originators will choose not to use this field unless there is a business reason to do so	Data Type: Text Format: Max length: 35 Min length: 1		
2.31 Payment Identification/End to End Identification < EndToEndId>	++++	Yes	Mandatory	Originator's unique reference on the transaction – THIS MUST BE UNIQUE WITHIN THE BATCH.	Data Type: Text Format: Max length: 35 Min length: 1		
2.44 Instructed Amount <instdamt></instdamt>	+++	Yes	Mandatory	Amount of money to be moved between the debtor and creditor	Usage Rule: Only 'EUR' is allowed. Usage Rule: Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits. e.g. <instdamt ccy="EUR">3421.00</instdamt>		
Charge Bearer Usage Rule: Charge Bearer is optional and may be	populated at p	payment information	n or transaction level. B (OI recommend to populate at payment	information level		
2.45 Charge Bearer <chrgbr></chrgbr>	+++	Yes	Advise to populate at pymt info level	Specifies which party/parties will bear the charges associated with the processing of the payment transaction	Only 'SLEV' is allowed		
2.46 Direct Debit Transaction < DrctDbtTx>	+++	Empty Tag	Mandatory				
2.47 Mandate Related Information < MndtRltdInf>	++++	Empty Tag	Mandatory				
2.48 Mandate Identification <mndtld></mndtld>	++++	Yes	Mandatory	Unique Mandate Reference	Data Type: Text Format: Max length: 35 Min length: 1		



Conditional Fields

Payment Information (Batch)/Transaction Level



Transaction Information Block – this can occur multiple times within a Payment Information Block							
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description			
2.49 Date of Signature <dtofsgntr></dtofsgntr>	++++	Yes	Mandatory	Date on which the direct debit mandate has been signed by the debtor.	Data Type: ISODate Format: YYYY-MM-DD e.g. 1998-03-30		
Amendment Indicator Usage Rule: Amendment indicator must b	e set to true wh	nen an amendment	has been made and the	e relevant details added to the amended fi	eld		
2.50 Amendment Indicator <amdmntind></amdmntind>	+++++	Yes	Optional	Indicator notifying whether the underlying mandate is amended or not.	true when an amendment has been made; otherwise do not put this tag in the file		
2.51 Amendment Information Details < AmdmntInfDtls>	+++++	Empty Tag	Conditional				
2.52 Original Mandate Identification <orgnlmndtid></orgnlmndtid>	+++++	Yes	Conditional	Previous UMR is included here if an amendment has been made to the UMR (see2.48)	Data Type: Text Format: Max length: 35 Min length: 1		
2.53 Original Creditor Scheme ID < OrgnlCdtrSchmeld>	+++++	Empty Tag	Conditional				
2.53 Name <nm></nm>	++++++	Yes	Conditional	Previous creditor name. If present the new 'Name' must be specified under Creditor – 2.19	Data Type: Text Format: Max length: 70 Min length: 1		
2.53 Identification <id></id>	++++++	Empty Tag	Conditional				
2.53 Private Identification < PrvtId>	+++++++	Empty Tag	Conditional				
2.53 Other <othr></othr>	++++++	Empty Tag	Conditional				
2.53 Identification <id></id>	++++++	Yes	Conditional	Previous creditor scheme identification	Data Type: Text Format: Max length: 35 Min length: 1		

Optional Fields

Conditional Fields



Transaction Information Block – this can occur multiple time	Transaction Information Block – this can occur multiple times within a Payment Information Block							
Field Index - Field Name - Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description				
2.53 Scheme Name <schmenm></schmenm>	++++++	Empty Tag	Conditional					
2.53 Proprietary <prtry></prtry>	++++++	Yes	Conditional	Name of the identification scheme, in a free text form.	Must contain SEPA			
2.57 Original Debtor Account <orgnidbtracct></orgnidbtracct>	+++++	Empty Tag	Conditional					
2.57 Identification <id></id>	++++++	Empty Tag	Conditional					
2.57 IBAN <iban></iban>	+++++++++++++++++++++++++++++++++++++++	Yes	Conditional	Original debtor account that has been modified. Used only if originator still with same bank but using a different account on the mandate	Data Type: IBAN2007Identifier Format: [A-Z]{2,2}[0-9]{2,2} [a-zA-Z0-9]{1,30}			
Original Debtor Agent Usage Rule: To be used with the 'FRST' inc	licator in the 'S	equence Type' Fiel	d Index 2.14 in the Payr	ment Information Block				
2.58 Original Debtor Agent <orgnidbtragt></orgnidbtragt>	+++++	Empty Tag	Conditional					
2.58 Financial Institution Identification < FinInstnId>	++++++	Empty Tag	Conditional					
2.58 Other <othr></othr>	++++++	Empty Tag	Conditional					
2.58 Identification <id></id>	++++++	Yes	Conditional	Must be populated with 'SMNDA' to indicate same mandate with new debtor agent Note: To be used with the 'FRST' indicator in the 'Sequence Type' Field Index 2.14	SMNDA			
Electronic Signature Usage Rule: This data element is not to be us	sed if the manc	late is a paper man	date					
2.62 Electronic Signature <elctrncsgntr></elctrncsgntr>	+++++	Yes	Optional	Additional security provisions, such as a digital signature, as provided by the debtor.	Data Type: Text Format: Max length: 1025 Min length: 1			



For small steps, for big steps, for life

Mandatory Fields

Optional Fields

Conditional Fields

Transaction Information Block – this can occur multiple times within a Payment Information Block								
Field Index - Field Name - Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description				
Creditor Scheme Identification Usage Rule: CID must be populated at either payment information or transaction level. BOI recommend to populate at payment information level								
2.66 Creditor Scheme Identification <cdtrschmeid></cdtrschmeid>	++++	Empty Tag	Advise to populate at pymt info level					
2.66 Identification <id></id>	+++++	Empty Tag	Advise to populate at pymt info level					
2.66 Private Identification <prvtid></prvtid>	+++++	Empty Tag	Advise to populate at pymt info level					
2.66 Other <othr></othr>	++++++	Empty Tag	Advise to populate at pymt info level					
2.66 Identification <id></id>	++++++	Yes	Advise to populate at pymt info level	This contains the Creditor Scheme identifier (CID) - formerly OIN	Data: Text Format: Max length: 35 Min length: 1			
2.66 Scheme Name <schmenm></schmenm>	++++++	Empty Tag	Advise to populate at pymt info level					
2.66 Proprietary <prtry></prtry>	++++++	Yes	Advise to populate at pymt info level	Name of the identification scheme, in a free text form.	Must contain 'SEPA'			
Ultimate Creditor Usage Rule – Ultimate Creditor is optional, if use	d Name and I	dentification can b	e populated at batch or	transaction level				
2.69 Ultimate Creditor <ultmtcdtr></ultmtcdtr>	+++	Empty Tag	Optional					
2.69 Name <nm></nm>	++++	Yes	Optional	Ultimate party to which an amount of money is due	Data Type: Text Format: Max length: 70 Min length: 1			
Identification Usage Rule – Either Organisation Identification or Pr	ivate Identifica	tion to be populate	d					
2.69 Identification <id></id>	++++	Empty Tag	Optional					

Mandatory	Fields

Conditional Fields

Payment Information (Batch)/Transaction Level



Field Index - Field Name - Tag Tag Depth Content Mandatory/ Description									
Field Index - Field Name – Tag	lag Depth	Content	Optional/ Conditional	Description					
Organisation Identification Usage Rule: Either 'BIC or BEI' or one occurrence of 'Other' is allowed.									
2.69 Organisation Identification <orgid></orgid>	+++++	Empty Tag	Optional						
2.69 BICOrBEI <bicorbei></bicorbei>	+++++	Yes	Optional	BIC Identifier	Data Type: Any BIC Identifier Format: [A-Z]{6,6}[A-Z2-9] [A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}				
2.69 Other <othr></othr>	+++++	Empty Tag	Optional						
2.69 Identification <id></id>	++++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1				
2.69 Scheme Name <schmenm></schmenm>	++++++	No	Optional						
2.69 Code <cd></cd>	+++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max Length: 4 Min length: 1				
2.69 Proprietary <prtry></prtry>	++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1				
2.69 Issuer <issr></issr>	++++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1				
Private Identification Usage Rule: Either 'Date and Place	of Birth' or one occurr	ence of 'Other' is	allowed						
2.69 Private Identification < PrvtId>	++++	Empty Tag	Optional						
2.69 Date And Place Of Birth < DtAndPlcOfBirth>	+++++	Empty Tag	Optional						



Conditional Fields



Transaction Information Block – this can occur multiple time	s within a Pay	ment Information	n Block		
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	
2.69 Birth Date <birthdt></birthdt>	++++++	Yes	Optional	Date on which a person is born	Data Type: ISODate Format: YYYY-MM-DD e.g. 1998-03-30
2.69 Province Of Birth < PrvcOfBirth>	++++++	Yes	Optional	Province where a person was born	Data Type: Text Format: Max length: 35 Min length: 1
2.69 City Of Birth <cityofbirth></cityofbirth>	++++++	Yes	Optional	City where a person was born	Data Type: Text Format: Max length: 35 Min length: 1
2.69 Country Of Birth <ctryofbirth></ctryofbirth>	++++++	Yes	Optional	Country where a person was born	Data Type: Country Code Format: [A-Z]{2,2}
2.69 Other <othr></othr>	+++++	Empty Tag	Optional		
2.69 Identification <id></id>	++++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1
2.69 Scheme Name <schmenm></schmenm>	++++++	No	Optional		
2.69 Code <cd></cd>	+++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max length: 4 Min length: 1
2.69 Proprietary < Prtry>	+++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1
2.69 Issuer <issr></issr>	++++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1

Optional Fields

Conditional Fields

Payment Information (Batch)/Transaction Level



Transaction Information Block – this can occur multiple times within a Payment Information Block							
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description			
2.70 Debtor Agent <dbtragt></dbtragt>	+++	Empty Tag	Mandatory				
2.70 Financial Institution Identification < FinInstnId>	++++	Empty Tag	Mandatory				
2.70 BIC <bic></bic>	+++++	Yes	Mandatory	Bank Identifier Code	Data Type: BIC Identifier Format: [A-Z]{6,6}[A-Z2-9] [A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		
2.72 Debtor <dbtr></dbtr>	+++	Empty Tag	Mandatory				
2.72 Name <nm></nm>	++++	Yes	Mandatory	Debtor name	Data Type: Max70Text Format: Max length: 70 Min length: 1		
2.72 Postal Address <pstladr></pstladr>	++++	Empty Tag	Optional				
2.72 Country <ctry></ctry>	+++++	Yes	Optional	Country code	Data Type: Country Code Format: [A-Z]{2,2} SO 3166, Alpha-2 code		
2.72 Address Line (2) <adrline></adrline>	+++++	Yes	Optional	Debtor address in free format text. Note: Two occurrences of this tag are allowed	Data Type: Text Format: Max length: 70 Min length: 1		
Identification Usage Rule – Optional field, if used Either Organisat	ion Identificatic	on or Private Identifi	cation to be populated				
2.72 Identification <id></id>	++++	Empty Tag	Optional				
Organisation Identification Usage Rule: Either 'BIC or BEI' or one	e occurrence c	of 'Other' is allowed.					
2.72 Organisation Identification <orgid></orgid>	+++++	Empty Tag	Optional				
2.72 BICOrBEI <bicorbei></bicorbei>	+++++	Yes	Optional	BIC Identifier	Data Type: Any BIC Identifier Format: [A-Z]{6,6}[A-Z2-9] [A-NP-Z0-9]{(A-Z0-9]{3,3}){0,1}		



For small steps, for big steps, for life

Conditional Fields

Mandatory Fields

Field Index - Field Name - Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	
2.72 Other <othr></othr>	+++++	Empty Tag	Optional		
2.72 Identification <id></id>	++++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1
2.72 Scheme Name <schmenm></schmenm>	++++++	No	Optional		
2.72 Code <cd></cd>	+++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max Length: 4 Min length: 1
2.72 Proprietary <prtry></prtry>	+++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1
2.72 Issuer <issr></issr>	++++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1
Private Identification Usage Rule: Either 'Date and Place of Bin	h' or one occurr	rence of 'Other' is a	allowed		
2.72 Private Identification < PrvtId>	+++++	Empty Tag	Optional		
2.72 Date And Place Of Birth < DtAndPlcOfBirth>	+++++	Empty Tag	Optional		
2.72 Birth Date <birthdt></birthdt>	++++++	Yes	Optional	Date on which a person is born	Data Type: ISO Date Format: YYYY-MM-DD e.g. 1998-03-30
2.72 Province Of Birth < PrvcOfBirth>	+++++	Yes	Optional	Province where a person was born	Data Type: Text Format: Max length: 35 Min length: 1



Conditional Fields



Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	
2.72 City Of Birth <cityofbirth></cityofbirth>	++++++	Yes	Optional	City where a person was born	Data Type: Text Format: Max length: 35 Min length: 1
2.72 Country Of Birth <ctryofbirth></ctryofbirth>	++++++	Yes	Optional	Country where a person was born	Data Type: Country Code Format: [A-Z]{2,2}
2.72 Other <othr></othr>	+++++	Empty Tag	Optional		
2.72 Identification <id></id>	++++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1
2.72 Scheme Name <schmenm></schmenm>	++++++	No	Optional		
2.72 Code <cd></cd>	+++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max length: 4 Min length: 1
2.72 Proprietary <prtry></prtry>	+++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1
2.72 Issuer <issr></issr>	++++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1
2.73 Debtor Account <dbtracct></dbtracct>	+++	Empty Tag	Mandatory		
2.73 Identification <id></id>	++++	Empty Tag	Mandatory		
2.73 IBAN <iban></iban>	++++	Yes	Mandatory	International Bank Account Number (IBAN)	Data Type: IBAN2007Identifier Format: [A-Z]{2,2}[0-9]{2,2} [a-zA-Z0-9]{1,30}



Conditional Fields

Payment Information (Batch)/Transaction Level



Field Index - Field Name - Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description			
Ultimate Debtor Usage Rule - Optional field however must be populated if provided by the Debtor in the Mandate							
2.74 Ultimate Debtor <ultmtdbtr></ultmtdbtr>	+++	Empty Tag	Optional				
2.74 Name <nm></nm>	++++	Yes	Optional	Debtor must be the party who signed the mandate. Ultimate debtor is a third party to the mandate who may ultimately hold the debt Note: This is for information purposes only	Data Type: Text Format: Max length: 70 Min length: 1		
Identification Usage Rule – Either Organisation Identification or R	Private Identifica	tion to be popula	ted				
2.74 Identification <id></id>	++++	Empty Tag	Optional				
Organisation Identification Usage Rule: Either 'BIC or BEI' or one occurrence of 'Other' is allowed.							
2.74 Organisation Identification <orgid></orgid>	+++++	Empty Tag	Optional				
2.74 BICOrBEI <bicorbei></bicorbei>	+++++	Yes	Optional	BIC Identifier	Data Type: Any BIC Identifier Format: [A-Z]{6,6}[A-Z2-9] [A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		
2.74 Other <othr></othr>	+++++	Empty Tag	Optional				
2.74 Identification <id></id>	++++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1		
2.74 Scheme Name <schmenm></schmenm>	++++++	No	Optional				
2.74 Code <cd></cd>	+++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max Length: 4 Min length: 1		



Conditional Fields



Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description	
2.74 Proprietary <prtry></prtry>	++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1
2.74 Issuer <issr></issr>	++++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1
Private Identification Usage Rule: Either 'Date and Place o	f Birth' or one occurr	ence of 'Other' is a	allowed		
2.74 Private Identification <prvtid></prvtid>	++++	Empty Tag	Optional		
2.74 Date And Place Of Birth <dtandplcofbirth></dtandplcofbirth>	+++++	Empty Tag	Optional		
2.74 Birth Date <birthdt></birthdt>	++++++	Yes	Optional	Date on which a person is born	Data Type: ISODate Format: YYYY-MM-DD e.g. 1998-03-30
2.74 Province Of Birth <prvcofbirth></prvcofbirth>	++++++	Yes	Optional	Province where a person was born	Data Type: Text Format: Max length: 35 Min length: 1
2.74 City Of Birth <cityofbirth></cityofbirth>	++++++	Yes	Optional	City where a person was born	Data Type: Text Format: Max length: 35 Min length: 1
2.74 Country Of Birth <ctryofbirth></ctryofbirth>	++++++	Yes	Optional	Country where a person was born	Data Type: Country Code Format: [A-Z]{2,2}
2.74 Other <othr></othr>	+++++	Empty Tag	Optional		
2.74 Identification <id></id>	++++++	Yes	Optional	Identification assigned by an institution	Data Type: Text Format: Max length: 35 Min length: 1



Conditional Fields



Transaction Information Block – this can occur multiple times within a Payment Information Block						
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description		
2.74 Scheme Name <schmenm></schmenm>	++++++	No	Optional			
2.74 Code <cd></cd>	+++++++	Yes	Optional	Name of the identification scheme, in a coded form as published in an external list	Data Type: ExternalOrganisation Identification1Code Format: Max length: 4 Min length: 1	
2.74 Proprietary < Prtry>	+++++++	Yes	Optional	Name of the identification scheme, in a free text form	Data Type: Text Format: Max length: 35 Min length: 1	
2.74 Issuer <issr></issr>	++++++	Yes	Optional	Entity that assigns the identification	Data Type: Text Format: Max length: 35 Min length: 1	
2.77 Purpose <purp></purp>	+++	Empty Tag	Optional			
2.77 Code <cd></cd>	++++	Yes	Optional	Underlying reason for the payment transaction	Format: Max length: 4 Min length: 1 see code list in appendix	
Remittance Information Usage Rule: Optional field, either 1 instance of 'Structured' or 1 instance of 'Unstructured', may be present						
2.88 Remittance Information < RmtInf>	+++	Empty Tag	Optional			
2.89 Unstructured <ustrd></ustrd>	++++	Yes	Optional	Free text provided for matching reconciliation	Data Type: Text Format: Max length: 140 Min length: 1	
2.90 Structured <strd></strd>	++++	Empty Tag	Optional			
Creditor Reference Information Usage Rule: When used, both 'Type' and 'Reference' must be present.						
2.110 Creditor Reference Information <cdtrrefinf></cdtrrefinf>	+++++	Empty Tag	Optional			
2.111 Type <tp></tp>	+++++	Empty Tag	Optional			



For small steps, for big steps, for life

Mandatory Fields

Conditional Fields

Transaction Information Block – this can occur multiple times within a Payment Information Block						
Field Index - Field Name – Tag	Tag Depth	Content	Mandatory/ Optional/ Conditional	Description		
2.112 Code or Proprietary <cdorprtry></cdorprtry>	++++++	Empty Tag	Optional			
2.113 Code <cd></cd>	+++++++	Yes	Optional	Type of creditor reference, in a coded form.	Usage Rule Only 'SCOR' is allowed	
2.115 Issuer <issr></issr>	++++++	Yes	Optional	Entity that assigns the credit reference type.	Data Type: Text Format: Max length: 35 Min length: 1	
2.116 Reference <ref></ref>	+++++	Yes	Optional	Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.	Data Type: Text Format: Max length: 35 Min length: 1	



Conditional Fields



SEPA Direct Debit PAIN.008.001.02 XML File Structure – PAIN.008.001.02 Sample File

```
<?xml version="1.0" encoding="UTF-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.008.001.02" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
       <CstmrDrctDbtInitn>
              <GrpHdr>
                     <Msgld>MSGID12345678912</msgld>
                      <CreDtTm>2013-10-01T09:30:48</CreDtTm>
                      <NbOfTxs>4</NbOfTxs>
                     <CtrlSum>400.4</CtrlSum>
                     <InitgPty>
                             < |d>
                               <PrvtId>
                                        <Othr>
                                                     <ld>|E97ZZZ123456</ld>
                                                   </Othr>
                                    </Prvtld>
                             </Id>
                     </GrpHdr>
              <PmtInf>
```



```
<PmtInfld>PMTINFID1</PmtInfld>
                <PmtMtd>DD</PmtMtd>
<NbOfTxs>2</NbOfTxs>
                <CtrlSum>200.2</CtrlSum>
                <PmtTpInf>
                       <SvcLvl>
                              <Cd>SEPA</Cd>
                       </SvcLvl>
                       <Lcllnstrm>
                              <Cd>CORE</Cd>
                       </Lclinstrm>
                       <SeqTp>FRST</SeqTp>
                </PmtTpInf>
                <ReqdColltnDt>2013-10-09</ReqdColltnDt>
                <Cdtr>
                       <Nm>CREDITOR</Nm>
                </Cdtr>
                <CdtrAcct>
                       < ld >
                              <IBAN>IE98B0FI90393912345678</IBAN>
                       </Id>
                </CdtrAcct>
                <CdtrAgt>
```



```
<FinInstnId>
              <BIC>BOFIIE2D</BIC>
       </FinInstnId>
</CdtrAgt>
<CdtrSchmeld>
       < ld >
              <PrvtId>
                      <Othr>
                             <ld>IE97ZZZ123456</ld>
                             <SchmeNm>
                                    <Prtry>SEPA</Prtry>
                             </SchmeNm>
                      </Othr>
              </Prvtld>
       </Id>
</CdtrSchmeld>
<DrctDbtTxInf>
       <Pmtld>
              <EndToEndId>E2EID1</EndToEndId>
       </Pmtld>
       <InstdAmt Ccy="EUR">100.1/InstdAmt>
       <DrctDbtTx>
              <MndtRltdInf>
```



```
<Mndtld>MANDATEID1</Mndtld>
                     <DtOfSgntr>2013-09-01</DtOfSgntr>
              </MndtRltdInf>
       </DrctDbtTx>
       <DbtrAgt>
              <FinInstnId>
                     <BIC>BOFIIE2D</BIC>
              </FinInstnId>
       </DbtrAgt>
       <Dbtr>
              <Nm>DEBTOR1</Nm>
       </Dbtr>
       <DbtrAcct>
              < Id >
                     <IBAN>IE98BOFI90393912121212</IBAN>
              </ld>
       </DbtrAcct>
</DrctDbtTxInf>
<DrctDbtTxInf>
       <Pmtld>
              <EndToEndId>E2EID2</EndToEndId>
       </Pmtld>
       <InstdAmt Ccy="EUR">100.1</InstdAmt>
```



```
<DrctDbtTx>
       <MndtRltdlnf>
              <Mndtld>MANDATEID2</Mndtld>
              <DtOfSgntr>2013-09-01</DtOfSgntr>
              <AmdmntInd>true</AmdmntInd>
              <AmdmntInfDtls>
                <OrgnIDbtrAgt>
                       <FinInstnId>
                          <Othr>
                            <ld>SMNDA</ld>
                         </Othr>
                       </FinInstnId>
                      </OrgnIDbtrAgt>
              </AmdmntInfDtls>
       </MndtRltdInf>
</DrctDbtTx>
<DbtrAgt>
       <FinInstnId>
              <BIC>AIBKIE2D</BIC>
       </FinInstnId>
</DbtrAgt>
<Dbtr>
       <Nm>DEBTOR2</Nm>
```



```
</Dbtr>
                       <DbtrAcct>
                              < ld >
                                      <IBAN>IE16AIBK93110187654321</IBAN>
                              </Id>
                       </DbtrAcct>
                </DrctDbtTxInf>
         </PmtInf>
         <PmtInf>
                <PmtInfld>PMTINFID2</PmtInfld>
                <PmtMtd>DD</PmtMtd>
<NbOfTxs>2</NbOfTxs>
                <CtrlSum>200.2</CtrlSum>
                <PmtTpInf>
                       <SvcLvl>
                              <Cd>SEPA</Cd>
                       </SvcLvl>
                       <Lcllnstrm>
                              <Cd>CORE</Cd>
                       </LclInstrm>
                       <SeqTp>RCUR</SeqTp>
                </PmtTpInf>
                <ReqdColltnDt>2013-10-04</ReqdColltnDt>
```



```
<Cdtr>
       <Nm>CREDITOR</Nm>
</Cdtr>
<CdtrAcct>
       < ld >
              <IBAN>IE98B0FI90393987654321</IBAN>
       </Id>
</CdtrAcct>
<CdtrAgt>
       <FinInstnId>
              <BIC>BOFIIE2D</BIC>
       </FinInstnId>
</CdtrAgt>
<CdtrSchmeld>
       < ld >
              <Prvtld>
                     <Othr>
                             <ld>IE97ZZZ123456</ld>
                             <SchmeNm>
                                    <Prtry>SEPA</Prtry>
                             </SchmeNm>
                     </Othr>
              </Prvtld>
```



```
</Id>
</CdtrSchmeld>
<DrctDbtTxInf>
       <Pmtld>
              <EndToEndId>E2EID3</EndToEndId>
       </Pmtld>
       <InstdAmt Ccy="EUR">100.1</InstdAmt>
       <DrctDbtTx>
              <MndtRltdInf>
                     <Mndtld>MANDATEID3</Mndtld>
                     <DtOfSgntr>2013-09-01/DtOfSgntr>
              </MndtRltdInf>
       </DrctDbtTx>
       <DbtrAgt>
              <FinInstnId>
                     <BIC>AIBKIE2D</BIC>
              </FinInstnId>
       </DbtrAgt>
       <Dbtr>
              <Nm>DEBTOR3</Nm>
       </Dbtr>
       <DbtrAcct>
              < ld >
```



<IBAN>IE16AIBK93110112345678</IBAN>

```
</Id>
       </DbtrAcct>
</DrctDbtTxInf>
<DrctDbtTxInf>
       <Pmtld>
              <EndToEndId>E2EID4</EndToEndId>
       </Pmtld>
       <InstdAmt Ccy="EUR">100.1/InstdAmt>
       <DrctDbtTx>
              <MndtRltdInf>
                      <Mndtld>MANDATEID4</Mndtld>
                      <DtOfSgntr>2013-09-01</DtOfSgntr>
                      <AmdmntInd>true</AmdmntInd>
                      <AmdmntInfDtls>
                       <OrgnIDbtrAcct>
                             < ld >
                         <IBAN>IE98B0FI90393956785678</IBAN>
                  </Id>
                             </OrgnIDbtrAcct>
                      </AmdmntInfDtls>
              </MndtRltdInf>
       </DrctDbtTx>
```



```
<DbtrAgt>
                             <FinInstnId>
                                    <BIC>BOFIIE2D</BIC>
                             </FinInstnId>
                     </DbtrAgt>
                     <Dbtr>
                             <Nm>DEBTOR4</Nm>
                     </Dbtr>
                     <DbtrAcct>
                             < |d>
                                    <IBAN>IE98B0FI90393912341234</IBAN>
                             </ld>
                     </DbtrAcct>
              </DrctDbtTxInf>
       </PmtInf>
      </CstmrDrctDbtInitn>
</Document>
```



10. Appendix

1. ISO Country Codes:

The ISO Country Code list available on the ISO website: http://www.iso.org/iso/home/standards/country_codes/iso-3166-1_decoding_table.htm

2. Category Purpose Code List

ISO publish lists of codes allowed within ISO 20022 XML message schemes. Please see the Inventory of External Code Lists on the ISO website www.ISO20022.org

