RA2126120

1st Assessment - CSIR11 Introduction to Computer Programming (C)

Section: ICE-B
Venue: LH214
Date: 12-10-2026
Time: 11–12 pm

Instructions: Answer all the following questions. Each question carries 0.5 marks. Modified answers will be given ZERO marks, even though it is correct.

30 * 0.5 = 15 Marks

1. Which type of programming language is generally closest to the hardware?
   A) High-level language
   B) Assembly language
   C) Scripting language
   D) Query language
2. Which of the following is the most appropriate first step when developing a program?
   A) Identify and understand the problem
   B) Develop an algorithm first
   C) Draw a flow chart before coding
   D) Analyse debugging scenarios before writing program
3. Which characteristic of an algorithm means that every step must be precisely defined?
   A) Finiteness
   B) Effectiveness
   C) Definiteness
   D) Input
4. In a flowchart, a parallelogram is generally used for:
   A) Decision making
   B) Processing
   C) Input/output
   D) Program termination
5. Which of the following represents a sequential structure?
   A) Statements executed one after another
   B) Statements executed based on a condition
   C) Statements repeatedly executed
   D) Statements executed randomly
6. Which of the following is a principle of structured programming?
   A) Extensive use of unconditional jumps
   B) Program using sequence, selection and iteration
   C) Programs using structures and unions
   D) Using only global variables and functions
7. Which of the following is a valid C identifier?
   A) 2value B) total-marks C) total_marks D) float
8. Which of the following is not a C keyword?
   A) int B) return C) main D) if
9. printf("%d", 17 / 5);
   A) 3 B) 3.4 C) 2 D) Error
10. Which operator is known as the conditional operator?
    A) :: B) ?: C) :? D) None
11. printf("%d", 5 | 3);
    A) 1 B) 5 C) 3 D) 7
12. What is the main limitation of scanf("%s", name) for reading a string?
    A) It cannot read all characters
    B) It cannot store strings
    C) It stops reading at whitespace
    D) It always reads only one character
13. Which statement is used to execute a block only when a condition is true?
    A) switch B) for C) goto D) if
14. What happens if a matching case in a switch statement does not contain a break?
    A) The switch terminates automatically
    B) The next case may also execute
    C) The program terminates
    D) Compilation Error
15.
```
int i = 10;
    do{printf("%d", i);}while (i < 5);
```
    A) 1 B) 10 C) False D) Infinite loop
16. for (int i = 1; i <= 5; i++){if (i == 3) continue; printf("%d ", i);}
    A) 1 2 4 5 B) 1 2 3 4 5 C) 1 5 D) 3
17. int x = 10;
    printf("%d", x > 5 && x < 15);
    A) 0 B) 1 C) Compilation Error D) 10
18. printf("%d ", 2 & 5);
    printf("%d ", 2 && 5);
    A) 1 0 B) 0 1 C) 0 0 D) 1 1
19. printf("%d ", 3 | 5);
    printf("%d ", 3 || 5);
    A) 1 7 B) 7 1 C) 8 0 D) 0 8

20. int a = 2, b = 3, c;
c = (a += 2, b *= 2, a + b);
printf("%d %d %d", a, b, c);
A) 4 6 10 B) 6 5 11 C) 6 4 10 D) 2 3 5

21. if (10 < 5)
printf("Compiler Error");
return 0;
A) 0 B) Compiler Error C) No output D) Logical Error

22. switch (3){
default: printf("D");
case 3: printf("C");}
A) D B) C C) Syntax Error D) 0

23. int x = 4;
printf("%d", x == 4 ? x > 5 ? 10 : 20 : 30);
A) 10 B) 20 C) 30 D) 4

24. for (int i = 1; i <= 5; i++){
if (i % 2 == 0)
printf("%d ", i);}
A) 1 2 4 B) 2 4 C) 1 2 3 4 5 D) None

25. for (int i = 1; i <= 3; i++){
for (int j = 1; j <= i; j++)
printf("%d", j);
printf(" ");}
A) 1 11 111 B) 1 12 123 C) 123 123 123 D) 1 2 3

26. for (int i = 5; i > 0; i -= 2)
printf("%d ", i);
A) 5 3 2 B) 5 3 1 C) 5 4 3 2 1 D) 4 2

27. int i = 1;
for (; i < 3;)
{
printf("%d ", i);
i++;
}
A) 1 2 B) 2 C) No output D) Infinite loop

28. int i = 1;
for (;;)
{
printf("%d ", i);
if (i == 3)
break;
i++;
}
A) 1 2 3 B) 1 2 C) Infinite loop D) Error

29. int a = 1, b = 2, c = 3;
printf("%d", a > b > c);
A) 1 B) 0 C) 3 D) Syntax Error

30. int i = 1, x = 0;
while (i <= 10)
{
x += i;
i += 2;
}
printf("%d \n", x);
A) 20 B) 0 C) 25 D) 2