



## A friendly user guide to ELF micropatching with Shiva (alpha v1)

### Shiva Manual

1 Introduction to Shiva.....	2
ELF program interpreters.....	2
Shiva is an ELF program interpreter.....	3
Systems and arch's that Shiva supports.....	3
2 Installing Shiva-AArch64.....	4
Download Source code.....	4
Build source code.....	4
Build and install libelfmaster.....	4
Build and install Shiva.....	4
Build and install example patches.....	5
3 Writing patches with Shiva.....	5
The Shiva workflow.....	6
ELF Program compilation and linking example.....	6
Static linking of objects.....	6
Dynamically linked executable.....	7
Dynamically patched executable.....	7
ELF Symbol interposition.....	8
Patching an .rodata string (Simple first patch).....	8
Building the patch.....	9

Testing our patch: ro_patch.o.....	9
Using shiva-ld to prelink the patch.....	10
Before we run ./test_rodata, let's take a quick look to see what modifications shiva-ld made to the executable:.....	10
Final outcome of patching test_rodata.....	12
Current limitations of patching const data.....	13
Patching global .data variables and .bss variables.....	14
Patching STB_LOCAL variables.....	14
Using the extern keyword in your patch code.....	14

# 1 Introduction to Shiva

## ELF program interpreters

Shiva is an ELF microcode-patching technology that works similarly to the well known (*but little understood*) ELF dynamic linker “/lib/ld-linux.so”. Every ELF program that is dynamically linked has a program header segment type called PT\_INTERP that describes the path to the *program interpreter*. The program interpreter is a separate ELF program loaded by the kernel that is responsible for helping to build the process runtime image by loading and linking extra modules containing code and data. Traditionally these modules are called shared libraries, and the program interpreter is “/lib/ld-linux.so”. On aarch64 it is “/lib/ld-linux-aarch64.so.1”

### Image 1.0: Requesting program interpreter

```
Elf file type is DYN (Shared object file)
Entry point 0x7e0
There are 8 program headers, starting at offset 64

Program Headers:
  Type           Offset             VirtAddr           PhysAddr
                 FileSiz             MemSiz             Flags   Align
  PHDR           0x0000000000000040 0x0000000000000040 0x0000000000000040
                 0x00000000000001c0 0x00000000000001c0  R       0x8
  INTERP         0x0000000000000200 0x0000000000000200 0x0000000000000200
                 0x000000000000001b 0x000000000000001b  R       0x1
    [Requesting program interpreter: /lib/ld-linux-aarch64.so.1]
  LOAD           0x0000000000000000 0x0000000000000000 0x0000000000000000
                 0x0000000000000a98 0x0000000000000a98  R E     0x10000
  LOAD           0x0000000000000d40 0x00000000000010d40 0x00000000000010d40
                 0x00000000000002d0 0x000000000000042e0  RW      0x10000
  DYNAMIC        0x0000000000000d50 0x00000000000010d50 0x00000000000010d50
                 0x0000000000000200 0x0000000000000200  RW      0x8
  NOTE           0x000000000000021c 0x000000000000021c 0x000000000000021c
                 0x0000000000000044 0x0000000000000044  R       0x4
  GNU_STACK      0x0000000000000000 0x0000000000000000 0x0000000000000000
                 0x0000000000000000 0x0000000000000000  RW      0x10
  GNU_RELRO      0x0000000000000d40 0x00000000000010d40 0x00000000000010d40
                 0x00000000000002c0 0x00000000000002c0  R       0x1
```

Just like any other interpreter, such as Python, or Java, the ELF program interpreter is responsible for performing various types of loading, patching and transformation.

## Shiva is an ELF program interpreter

Shiva is a newly designed program interpreter who's sole purpose is to load ELF microcode patches that are written in C and compiled into Shiva modules (ELF relocatable objects). Shiva modules are relocatable objects and by nature already contain the ELF meta-data (*sections, symbols relocations*) necessary to re-build much of the process image. Additionally Shiva has introduced some new concepts such as *Transformations* which are an extension to traditional ELF relocations, allowing for complex patching operations such as function splicing.

The core purpose of Shiva is to create a microcode patching system that seamlessly fits into the existing ELF ABI toolchain of compilers, linkers, and loaders. Shiva aims to load and link patches that are written 100% in C, in a way that is natural for developers who may not be reverse engineers but are experts in C. Shiva is in-itself a linker and a loader that works alongside and in conjunction with the existing Dynamic linker "ld-linux.so". To understand more technical details see "shiva\_final\_desing.pdf" within the documentation directory.

## Systems and arch's that Shiva supports

Currently Shiva's AMP tailored-microcode patching system runs on **Linux AArch64**, and supports **AArch64 Linux ELF PIE binaries**. Future support for ARM32, x86\_64/x86\_32 and other requested architectures. At the present moment Shiva doesn't support ET\_EXEC ELF binaries (non-pie) due to time constraints, but it's on the road map.

## 2 Installing Shiva-AArch64

### Download Source code

```
git clone git@github.com:advanced-microcode-patching/shiva
git clone github.com/elfmaster/libelfmaster
```

### Build source code

## Build and install libelfmaster

Shiva requires a custom libelfmaster branch that has not been merged into main yet. Specifically make sure to use the *aarch64\_support* branch.

```
cd libelfmaster
git checkout aarch64_support
cd ./src
sudo ./make.sh
```

## Build and install Shiva

### Commands:

```
cd shiva
make
make shiva-ld
make patches
sudo make install
```

### Build results:

Shiva is a static ELF executable and installed to “/lib/shiva”. The Shiva modules are typically stored in “/opt/shiva/modules”. The example patches all live within “/git/shiva/modules/aarch64\_patches”.

## Build and install example patches

Please see the “shiva/modules/aarch64\_patches/” directory. All of the example patches live here. Let us illustrate an example of building and testing one such patch on a program called ‘test\_rodata’.

### Commands:

```
cd shiva/modules/aarch64_patches/rodata_interposing
make
sudo make install
```

Test the patch by setting the patch path and running “/lib/shiva” manually.

```
$ SHIVA_MODULE_PATH=./ro_patch.o /lib/shiva ./test_rodata
```

Notice that the software prints the new string “The great arcanum”, per the patch. Yet when the program is executed without Shiva it executes with its old behavior.

```
$ ./test_rodata
```

Install the patch permanently

You may also install the patch permanently with the Shiva prelinking tool. This tool updates the PT\_INTERP segment from “/lib/ld-linux.so” to “/lib/shiva”, and updates the dynamic segment with several new tags describing the path to the patch that should be loaded and linked at runtime: “/opt/shiva/modules/ro\_patch.o”.

```
$ /bin/shiva-ld -e test_rodata -p ro_patch.o -i /lib/shiva -s /opt/shiva/modules -o test_rodata.patched
```

Shiva now installs the patch in memory everytime it's executed

```
$ ./test_rodata.patched
```

The only discernible difference between test\_rodata.patched and test\_rodata are the PT\_INTERP segment modification and the PT\_DYNAMIC addition of two new entries describing the patch path. No actual code or data has changed within the ELF binary. Shiva performs all of the patching at runtime.

### 3 Writing patches with Shiva

#### The Shiva workflow


Before delving in to the use of Shiva, let us first explain the workflow of what the ELF compilation and linking process looks like before and after Shiva.

#### ELF Program compilation and linking example

Standard program compilation begins with a compiler like gcc; the source code files (i.e. main.o and foo.o) are compiled and then get linked (By “/bin/ld”) into a final output ELF executable my\_program.

#### *Static linking of objects*


Image 3.0: static linking of two ELF relocatable objects with “/bin/ld”



Additionally these ELF relocatable object files contain calls to functions that live within ELF shared libraries. Once the object files (foo.o and main.o) are linked into an ELF executable (my\_program), additional Dynamic linking meta-data is created and stored into what is known as the PT\_DYNAMIC segment of the program header table. The PT\_DYNAMIC segment contains additional meta-data that is to be passed along to the Program interpreter at runtime. The program interpreter (aka: dynamic linker) is specified as a file path in the PT\_INTERP segment: “/lib/ld-linux.so”. When the executable is run, the kernel loads and executes the interpreter program first: “/lib/ld-linux.so”. The interpreter loads and links the needed shared libraries (i.e. libc.so). The program has now been compiled, and linked twice: once statically, and again dynamically.

### ***Dynamically linked executable***


Image 3.1: Dynamically link libc.so in at runtime



A Shiva patch can be written in C and compiled as an ELF relocatable object file. In the same sense that “ld-linux.so” loads and links shared libraries (ELF ET\_DYN files), Shiva will load and link patch objects (ELF ET\_REL files) to re-write the program in memory just before execution.

## Dynamically patched executable

Image 3.2: Chained linking with Shiva



## ELF Symbol interposition

The ELF format uses symbols to denote code and data. Program functions generally live in the `.text` section, and global variables live within the `.data`, `.rodata`, and `.bss` sections. Shiva makes use of the ELF relocation, section, and symbol data to allow patch developers to *interpose* existing symbols; in other words re-link functions and data that have symbols associated with them. As patch developers we will find this as a natural and beautifully convenient way to patch code and data.

### Citation 3.0: From “Oracle linkers and libraries guide”

“Interposition can occur when multiple instances of a symbol, having the same name, exist in different dynamic objects that have been loaded into a process. Under the default search model, symbol references are bound to the first definition that is found in the series of dependencies that have been loaded. This first symbol is said to interpose on the other symbols of the same name.”

## Patching an `.rodata` string (Simple first patch)

This patching exercise lives in “`modules/aarch64_patches/rodata_interposing`”. In the following example we are going to look at a simple program that prints a constant string “Arcana Technologies”. Constant data is read-only and is usually stored in the `.rodata` section of a program. The `.rodata` section is generally put into text segment, or

a read-only segment that is adjacent to the text segment. A shiva module has it's own .rodata section within it's mapped text segment at runtime. Our goal with the following patch is to replace a read-only string with another by simply re-defining it in C.

### Image 2.0: Source code of program rodata\_test.c

```
#include <stdio.h>

const char rodata_string[] = "Arcana Technologies";

int main(void)
{
    printf("rodata_string: %s\n", rodata_string);
    exit(0);
}
```

NOTE: The source code to rodata\_test.c is only being shown for the sake of illustrating what the program does that we are patching. In may workflows the source code wouldn't even exist, and Shiva doesn't depend on or use the source in any way.

### Image 3.3: Source code of patch object: ro\_patch.c

```
elfmaster@esoteric-aarch64:~/amp/shiva/modules/aarch64_patches/rodata_interposing$ cat ro_patch.c
const char rodata_string[] = "The Great Arcanum";
```

#### ***Building the patch***

The patch source code “modules/aarch64\_patches/rodata\_interposing/ro\_patch.c” is a single line patch, redefining the symbol “rodata\_string[]”. To build this patch we can simply run the following gcc command to build the patch:

```
$ gcc -mmodel=large -fno-pic -fno-stack-protector -c ro_patch.c -o ro_patch.o
```

The ELF ET\_REL object: ro\_patch.o describes a symbol with the same exact name as the symbol **rodata\_string** in the target executable. Shiva will see this when linking and it will link in the version of the symbol from our patch. This perfectly demonstrates the concept of symbol interposition in Shiva.



## ***Testing our patch: ro\_patch.o***

In this example we are patching the AArch64 ELF PIE executable: “modules/aarch64\_patches/rodata\_interposing/test\_rodata” Let’s first run the program un-patched.

```
$ ./test_rodata
rodata_string: Arcana Technologies
$
```

The program simply prints the string “rodata\_string: Arcana technologies”. To see if our patch worked we can invoke Shiva directly to load and link the executable with the patch at runtime. We must specify the path to our patch object with the SHIVA\_MODULE\_PATH environment variable.

```
$ SHIVA_MODULE_PATH=./ro_patch.o /lib/shiva ./test_rodata
rodata_string: The Great Arcanum
$
```

When executing ./test\_rodata with “/lib/shiva” as the primary loader it installs the specified patch, and the new rodata\_string[] value “The Great Arcanum” is printed to stdout. When we run ./test\_rodata without “/lib/shiva” it does not install the patch and the original string “Arcana Technologies” is printed.

## ***Using shiva-ld to prelink the patch***

The reality is that a user doesn’t want to invoke “/lib/shiva” every single time they want to run a program that needs a patch. This is why “/lib/shiva” is designed to be an ELF interpreter like “ld-linux.so”. We can use the Shiva prelinker “/bin/shiva-ld” to install the appropriate meta-data into the program we are patching:

- Update PT\_INTERP with the path to “/lib/shiva” (Replacing “/lib/ld-linux.so”).
- Add several custom entries to PT\_DYNAMIC describing the patch basename: “ro\_patch.o” and the module search path “/opt/shiva/modules”.

The following command will install the Shiva interpreter path and patch information into the ./test\_rodata binary.


```
$ shiva-ld -e test_rodata -p ro_patch.o -i /lib/shiva -s /opt/shiva/modules
```

This next command copies the patch file into the correct search path: “/opt/shiva/modules”

```
$ sudo cp ro_patch.o /opt/shiva/modules
```

Before we run `./test_rodata`, let's take a quick look to see what modifications shiva-ld made to the executable:

Image 3.4: Requesting program interpreter is “/lib/shiva”



```
Program Headers:
Type           Offset          VirtAddr          PhysAddr
              FileSiz          MemSiz              Flags  Align
PHDR           0x0000000000000040 0x0000000000000040 0x0000000000000040
              0x00000000000001c0 0x00000000000001c0  R      0x8
INTERP         0x0000000000000200 0x0000000000000200 0x0000000000000200
              0x000000000000001b 0x000000000000001b  R      0x1
  [Requesting program interpreter: /lib/shiva]
LOAD           0x0000000000000000 0x0000000000000000 0x0000000000000000
              0x0000000000000868 0x0000000000000868  R E    0x10000
LOAD           0x0000000000000d78 0x0000000000001d78 0x0000000000001d78
              0x0000000000000298 0x00000000000002a0  RW     0x10000
DYNAMIC        0x0000000000000300 0x0000000000001200 0x0000000000001200
              0x00000000000001d0 0x00000000000001d0  RW      0x8
LOAD           0x0000000000000300 0x0000000000001200 0x0000000000001200
              0x0000000000000259 0x0000000000000259  RW E   0x1000
GNU_STACK      0x0000000000000000 0x0000000000000000 0x0000000000000000
              0x0000000000000000 0x0000000000000000  RW     0x10
GNU_RELRO     0x0000000000000d78 0x0000000000001d78 0x0000000000001d78
              0x0000000000000288 0x0000000000000288  R       0x1
```

In image 2.2 we can see that “/lib/shiva” is set as the new Interpreter path. The astute reader will also notice that there is a third PT\_LOAD segment marked RWE. The shiva-ld tool creates a new dynamic segment (As shown below in Image 2.3). In order to make room for this new and larger dynamic segment shiva-ld creates a new PT\_LOAD segment and updates the PT\_DYNAMIC segment program header so that it points into the new PT\_LOAD segment at 0x3000. The updated PT\_DYNAMIC segment is moved and stored in this new segment

Image 3.5: New dynamic segment contains 3 custom entries

```

Dynamic section at offset 0x3000 contains 29 entries:
Tag          Type          Name/Value
0x0000000000000001 (NEEDED)      Shared library: [libc.so.6]
0x000000000000000c (INIT)        0x5d0
0x000000000000000d (FINI)        0x81c
0x0000000000000019 (INIT_ARRAY)  0x10d78
0x000000000000001b (INIT_ARRAYSZ) 8 (bytes)
0x000000000000001a (FINI_ARRAY)  0x10d80
0x000000000000001c (FINI_ARRAYSZ) 8 (bytes)
0x000000006ffffef5 (GNU_HASH)    0x260
0x0000000000000005 (STRTAB)    0x388
0x0000000000000006 (SYMTAB)    0x280
0x000000000000000a (STRSZ)     142 (bytes)
0x000000000000000b (SYMENT)    24 (bytes)
0x0000000000000015 (DEBUG)     0x0
0x0000000000000003 (PLTGOT)    0x10f78
0x0000000000000002 (PLTRELSZ)  144 (bytes)
0x0000000000000014 (PLTREL)    RELA
0x0000000000000017 (JMPREL)    0x540
0x0000000000000007 (RELA)     0x450
0x0000000000000008 (RELASZ)    240 (bytes)
0x0000000000000009 (RELAENT)   24 (bytes)
0x000000000000001e (FLAGS)     BIND_NOW
0x000000006fffffb (FLAGS_1)    Flags: NOW PIE
0x000000006fffffe (VERNEED)    0x430
0x000000006ffffff (VERNEEDNUM) 1
0x000000006fffff0 (VERSYM)     0x416
0x0000000060000018 (Operating System specific: 60000018) 0x121d0
0x0000000060000017 (Operating System specific: 60000017) 0x121e3
0x0000000060000019 (Operating System specific: 60000019) 0x121ee
0x0000000000000000 (NULL)      0x0

```

The above image 2.3 shows the dynamic segment of the ELF binary: `test_rodata`, after we ran the `shiva-ld` tool on it. Notice the three *Operating System specific* entries at the tail end. The `readelf` utility doesn't know how to parse these custom entries. Here is what the actual entry types and values are:

```

(SHIVA_NEEDED)      Patch object: [ro_patch.o]
(SHIVA_SEARCH)      Search path: [/opt/shiva/modules]
(SHIVA_ORIG_INTERP) Original RTLD: [/lib/ld-linux-aarch64.so.1]

```

This data is needed by “`/lib/shiva`” at runtime so that it can locate and load the patch object, and the original dynamic linker (See Chained Linking in section x.x).

### ***Final outcome of patching test\_rodata***

Now every time that the `test_rodata` executable is ran it will invoke the Shiva interpreter which will in turn load the patch object “`/opt/shiva/modules/ro_patch.o`”.

```

$ ./test_rodata
rodata_string: The Great Arcanum
$

```

We can observe that the program `test_rodata` is now printing the patched version of `rodata_string[]` when it is ran. This patch may appear permanent, but in effect the patch is actually being installed at runtime by “`/lib/shiva`” everytime the program runs.

## Current limitations of patching const data

There are patching scenarios with *const* data that fail with symbol interposition due to code optimizations with read-only data. In the previous example we illustrated how to patch a read-only global variable defined in C as:

```
const char rodata_string[] = "Arcana Technologies";
```

The target program gets re-linked to use the patch version of *rodata\_string*. Using symbol interposition to overwrite *.rodata* variables works perfectly unless the read-only value is optimized out of memory and stored only in a register. Let's look at the following example:

### Image 3.6: C code illustrating a read-only global variable

```
const int rodata_val = 5;

int main(void)
{
    printf(".rodata string: %d\n", rodata_val);
    exit(0);
}
```

After compiling the code above with gcc, even after all optimizations are disabled, you will get code similar to the following AArch64 assembly.

### Image 3.7: Code optimization of read-only variable in aarch64 assembly

```
Dump of assembler code for function main:
0x0000aaaaaaaa774 <+0>:      stp     x29, x30, [sp, #-16]!
0x0000aaaaaaaa778 <+4>:      mov     x29, sp
=> 0x0000aaaaaaaa77c <+8>:      mov     w1, #0x5                      // #5
0x0000aaaaaaaa780 <+12>:     adrp    x0, 0aaaaaaaa000
0x0000aaaaaaaa784 <+16>:     add     x0, x0, #0x840
0x0000aaaaaaaa788 <+20>:     bl      0aaaaaaaa660 <printf@plt>
0x0000aaaaaaaa78c <+24>:     mov     w0, #0x0                      // #0
0x0000aaaaaaaa790 <+28>:     bl      0aaaaaaaa610 <exit@plt>
```

In the code above we can see that the value 5 is being copied as an immediate value into a register. This is an optimization that removes the need for an *adrp*/*add*/*ldr* instruction trio, thus eliminating two instructions and the need for memory access. This optimization is inauspicious for symbol interposition based patching since the actual *.rodata* variables

memory is not being accessed and therefore there is no linking code to update. Instead there is only an instruction: “`mov w1, #0x5`”. Clearly this instruction can be re-encoded rather simply, but what would a patch look like for this? For the curious reader, move ahead to the section titled “*ELF Transformations & Function splicing*”.

## Symbol interposition on functions

Shiva gives patch writers the ability to replace a function trivially using symbol interposition. We’ve all seen userland rootkits that re-write `libc.so` functions by introducing a preloaded library with a new version of the function. In the same spirit Shiva allows patch writers to replace any function in the target ELF executable with a symbol of type `STT_FUNC` and symbol bindings of `STB_GLOBAL` or `STB_WEAK`. The only exception is that the function `main()` cannot be replaced, although future support is on the way, as it depends on the `glibc` initialization code that transfers control to `main` from `_start`.

Let’s get started with a simple example of replacing a function called `foo()`.

### *Patch to replace the function `foo()`*

```
$ cd shiva_examples/function_interposing
```

Image 3.8: Original source code of the binary `test_foo`



```
elfmaster@esoteric-aarch64:~/amp/shiva_examples/function_interposing$ cat test_foo.c
#include <stdio.h>


int foo(void)
{
    printf("I am the original foo() function\n");
    return 1;
}

int main(void)
{
    int ret;

    ret = foo();
    printf("Return value: %#x\n", ret);
}
elfmaster@esoteric-aarch64:~/amp/shiva_examples/function_interposing$
```

We can clearly see that `foo()` is a global function called by `main()`. In order to replace `foo()` with our own version we can simply re-write the function by name in our patch source code.

### Image 3.9: `foo_patch.c` source code



```
elfmaster@esoteric-aarch64:~/amp/shiva_examples/function_interposing$ cat foo_patch.c
#include <stdio.h>

int foo(void)
{
    printf("I am the new function foo()\n");
    return 0x31337;
}
elfmaster@esoteric-aarch64:~/amp/shiva_examples/function_interposing$
```

Shiva handles all of the linking at runtime for the patch, including shared library calls. Shiva works in conjunction with the `ld-linux.so` interpreter to accomplish these goals. All call instructions (*i.e. branch with link*) are given a PLT entry within the patch module at runtime. The patch has its own PLT/GOT and the GOT is filled in at runtime. Shiva handles all of the runtime relocations prior to passing control to `ld-linux.so` except for when the relocation references code or data that live within a shared library. A call to `libc:printf()` from within the patch code has its own respective GOT entry. The address of `printf()` won't be known until `ld-linux.so` has mapped the shared libraries into memory and processed their relocations. To handle this scenario Shiva incorporates a **Post Linker** which waits until `ld-linux.so` has processed all of the symbol relocations for each shared library, and then finalizes fixing up the GOT with the addresses to each respective shared library symbol.

### Shiva Post Linker

The Shiva Post Linking Phase is a great example of what Shiva refers to as Cross-ELF-Relocations (See section x.x). In particular though, the Shiva-Post-Linker is a linking mechanism that delays certain relocations from being processed until the standard RTLD "`ld-linux.so`" has finished mapping in each shared library and processing their respective relocations. In the event that Shiva has to fill in the PLT/GOT entry to resolve a function, such as `printf()` in the patch code above for `foo()`, it must rely on the dynamic linker to load and link `libc.so:printf()` first. After `ld-linux.so` is finished its control must somehow be transferred back to Shiva, particularly to the function `shiva_post_linker()`. To give some context, here is a screenshot of the shiva post linker's source code.

Image 3.10: shiva\_post\_linker.c comments

```
#include "shiva.h"

/*
 * The aarch64 post linker in Shiva works by hooking AT_ENTRY early on (In
 * shiva_module.c:apply_relocation), so that it is set to &shiva_post_linker()
 * instead of the &_start() of the target program. Let's look at the few lines of
 * code leading up to 'br _start' in ld-linux.so:
 *
 * ld-linux.so code:
 *
 * 0x1001240: bl      0x100dab8 ; branch with a link sets x30 to 0x1001244
 * 0x1001244: adrp    x0, 0x100d000
 * 0x1001248: add     x0, x0, #0xc08
 * 0x100124c: br      x21 ; jump to _start() has been hooked to jump to &shiva_post_linker
 *
 * Control is transferred to our function below, which runs after ld-linux.so has loaded
 * and linked it's libraries, therefore we use shiva_maps_get_so_base() to acquire the
 * base address of the library for the symbol we are resolving. We resolve the symbol
 * value by applying the delayed relocation value to the rel_unit.
 *
 * Once we are done, we reset $x21 directly with the value of the real &_start.
 * shiva_post_linker() returns... not to the instruction after '0x100124c: br      x21'
 * because no branch-link was set. Therefore we return to 0x1001244, and with
 * an updated $x21 we now jump to &_start
 *
 * shiva_post_linker() must specifically handle each linker architecture.
 */
```

In the above *image 3.10* the comments describe how Shiva actually replaces the auxiliary vector value for AT\_ENTRY on the stack, which normally contains the address to \_start() in the ELF executable that is running, and ld-linux.so passes final control to this address. Shiva takes advantage of this and hooks AT\_ENTRY with the address &shiva\_post\_linker(); The post linker introduces the concept of *Delayed relocations*. It is simply the concept that the linker notes a relocation entry for delayed fixups; meaning delayed until the ld-linux.so finishes loading and linking all of the shared libraries, at which point control is passed back to &shiva\_post\_linker() to apply the delayed relocation entries.

Image 3.11: shiva\_post\_linker() source code

```

void
shiva_post_linker(void)
{
    static struct shiva_module_delayed_reloc *delay_rel;
    static uint64_t base;

    TAILQ_FOREACH(delay_rel, &ctx_global->module.runtime->tailq.delayed_reloc_list, _linkage) {

        if (shiva_maps_get_so_base(ctx_global, delay_rel->so_path, &base) == false) {
            fprintf(stderr, "Failed to locate base address of loaded module '%s'\n",
                    delay_rel->so_path);
            exit(EXIT_FAILURE);
        }
        shiva_debug("Post linking '%s'\n", delay_rel->symname);
        /*
         * Apply the final relocation value on our delayed
         * relocation entry.
         */
        *(uint64_t *)delay_rel->rel_unit = delay_rel->symval + base;

        shiva_debug("%#lx:rel_unit = %#lx + %#lx (%#lx)\n", delay_rel->rel_addr,
                    delay_rel->symval, base, delay_rel->symval + base);
    }

    shiva_debug("Transferring control to %#lx\n", ctx_global->ulexec.entry_point);
    test_mark();

    /*
     * Mark the text segment as writable now that there won't
     * be any final fixups in the modules .text.
     */
    if (mprotect(ctx_global->module.runtime->text_mem,
                ELF_PAGEALIGN(ctx_global->module.runtime->text_size,
                                PAGE_SIZE),
                PROT_READ|PROT_EXEC) < 0) {
        perror("mprotect");
        return false;
    }

    __asm__ __volatile__ ("mov x21, %0" :: "r"(ctx_global->ulexec.entry_point));
    return;
}

```

## Symbol interposition on global data: .rodata, .bss, .data

Initialized global variables (that are not const) are stored within the *.data* section.

```
$ cd modules/aarch64_patches/dataonly_interposing
```

Original source code of binary



**Redefining global data types**

**Patching STB\_LOCAL variables**

**Using the extern keyword in your patch code**