

Interfacing Multiple Programming Languages

Dr. Axel Kohlmeyer

Assistant Dean for High-Performance Computing

Associate Director, ICMS

Associate Director, TMI

College of Science and Technology

Temple University, Philadelphia

axel.kohlmeyer@temple.edu

External Scientific Associate

International Centre for Theoretical Physics, Trieste, Italy

akohlmey@ictp.it

Symbols in Object Files & Visibility

- Compiled object files have multiple sections and a symbol table describing their entries:
 - “Text”: this is executable code
 - “Data”: pre-allocated variables storage
 - “Constants”: read-only data
 - “Undefined”: symbols that are used but not defined
 - “Debug”: debugger information (e.g. line numbers)
- Entries in the object files can be inspected with either the “nm” tool or the “readelf” command

Example File: visibility.c

```
static const int val1 = -5;
const int val2 = 10;
static int val3 = -20;
int val4 = -15;
extern int errno;
```

```
static int add_abs(const int v1, const int v2) {
    return abs(v1)+abs(v2);
}
```

```
int main(int argc, char **argv) {
    int val5 = 20;
    printf("%d / %d / %d\n",
        add_abs(val1,val2),
        add_abs(val3,val4),
        add_abs(val1,val5));
    return 0;
}
```

```
nm visibility.o:
000000000 t add_abs
                U errno
000000024 T main
                U printf
000000000 r val1
000000004 R val2
000000000 d val3
000000004 D val4
```

Fortran Symbols Example

SUBROUTINE GREET	0000006d t MAIN__
PRINT*, 'HELLO, WORLD!'	U _gfortran_set_args
END SUBROUTINE GREET	U _gfortran_set_options
	U _gfortran_st_write
program hello	U _gfortran_st_write_done
call greet	U _gfortran_transfer_character
end program	00000000 T greet__
	0000007a T main

- “program” becomes symbol “MAIN__” (compiler dependent)
- “subroutine” name becomes lower case with '_' appended
- several “undefines” with '_gfortran' prefix
 - => calls into the Fortran runtime library, libgfortran
- cannot link object with “gcc” alone, need to add -lgfortran
 - => cannot mix and match Fortran objects from different compilers

Fortran 90+ Modules

- When subroutines or variables are defined inside a module, they have to be hidden

```
module func
  integer :: val5, val6
contains
  integer function add_abs(v1,v2)
    integer, intent(in) :: v1, v2
    add_abs = iabs(v1)+iabs(v2)
  end function add_abs
end module func
```

- gfortran creates the following symbols:

```
000000000 T __func_MOD_add_abs
000000000 B __func_MOD_val5
000000004 B __func_MOD_val6
```

The Next Level: C++

- In C++ functions with different number or type of arguments can be defined (overloading)
=> encode prototype into symbol name:

Example : symbol for `int add_abs(int,int)`
becomes: `_ZL7add_absii`

- Note: the return type is not encoded
- C++ symbols are no longer compatible with C
=> add 'extern "C"' qualifier for C style symbols
- C++ symbol encoding is compiler specific

C++ Namespaces and Classes vs. Fortran 90 Modules

- Fortran 90 modules share functionality with classes and namespaces in C++
- C++ namespaces are encoded in symbols
Example: `int func::add_abs(int,int)`
becomes: `_ZN4funcL7add_absEii`
- C++ classes are encoded the same way
- Figuring out which symbol to encode into the object as undefined is the job of the compiler
- When using the gdb debugger use '::' syntax

Why We Need Header or Module Files

- The linker is “blind” for any language specific properties of a symbol => checking of the validity of the interface of a function is only possible during compilation
- A header or module file contains the prototype of the function (not the implementation) and the compiler can compare it to its use
- Important: header/module has to match library
=> Problem with FFTW-2.x: cannot tell if library was compiled for single or double precision

Calling C from Fortran 77

- Need to make C function look like Fortran 77
 - Append underscore (except on AIX, HP-UX)
 - Call by reference conventions
 - Best only used for “subroutine” constructs (cf. MPI) as passing return value of functions varies a lot:

```
void add_abs_(int *v1,int *v2,int *res){  
  *res = abs(*v1)+abs(*v2);}
```
- Arrays are always passed as “flat” 1d arrays by providing a pointer to the first array element
- Strings are tricky (no terminal 0, length added)

Calling Fortran 77 from C

- Inverse from previous, i.e. need to add underscore and use lower case (usually)
- Difficult for anything but Fortran 77 style calls since Fortran 90+ features need extra info
 - Shaped arrays, optional parameters, modules
- Arrays need to be “flat”,
C-style multi-dimensional arrays are lists of pointers to individual pieces of storage, which may not be consecutive
=> use 1d and compute position

Modern Fortran vs C Interoperability

- Fortran 2003 introduces a standardized way to tell Fortran how C functions look like and how to make Fortran functions have a C-style ABI
- Module “iso_c_binding” provides kind definition: e.g. C_INT, C_FLOAT, C_SIGNED_CHAR
- Subroutines can be declared with “BIND(C)”
- Arguments can be given the property “VALUE” to indicate C-style call-by-value conventions
- String passing tricky, needs explicit 0-terminus

Linking Multi-Language Binaries

- Inter-language calls via mutual C interface only due to name “mangling” of C++ / Fortran 90+
=> extern “C”, ISO_C_BINDING, C wrappers
- Fortran “main” requires Fortran compiler for link
- Global static C++ objects require C++ for link
=> avoid static objects (good idea in general)
- Either language requires its runtime for link
=> GNU: -lstdc++ and -lgfortran
=> Intel: “its complicated” (use -# to find out)
more may be needed (-lgomp, -lpthread, -lm)

Interfacing Multiple Programming Languages

Dr. Axel Kohlmeyer

Assistant Dean for High-Performance Computing

Associate Director, ICMS

Associate Director, TMI

College of Science and Technology

Temple University, Philadelphia

axel.kohlmeyer@temple.edu

External Scientific Associate

International Centre for Theoretical Physics, Trieste, Italy

akohlmey@ictp.it