

PENETRATION TESTING REPORT

FOOTPRINTING, RECONNAISSANCE & NETWORK SCANNING WEEK 02 | CYBERSECURITY

Pentester Name	Adewuyi Wakeel Adedeji
Program/Batch	B083-Networkwalks
Target	networkwalks.com
Web Reconnaissance	whois, whatweb, nslookup, curl -I, wafw00f, dnsrecon
Local Network Scan	Zenmap / Nmap
Local IPv4 Address	192.168.1.54
Subnet Mask	255.255.255.0
MAC Address	F8-34-41-96-F8-44
Scanned Host	192.168.1.54

1. Liability Disclaimer

All reconnaissance and network-scanning activities documented in this report should be performed only on systems and networks for which appropriate authorization has been obtained. The activities described here are presented for cybersecurity education, assessment, and research purposes. Unauthorized scanning or access may violate applicable laws and organizational policies.

2. Introduction

This Week 2 report documents two practical areas: foot printing and reconnaissance of the networkwalks.com domain, and network discovery using Zenmap on the local network. The reconnaissance work used multiple Kali Linux tools to collect publicly observable information, while Zenmap was used to identify the local host and its exposed TCP services.

The local network information has been updated using the supplied Windows configuration and Zenmap evidence: IPv4 address 192.168.1.54, subnet mask 255.255.255.0, MAC address F8-34-41-96-F8-44 and the open ports shown in the scan.

3. Tools Used

Tool	Purpose
WHOIS	Domain registration, registrar, status and name-server information.
WhatWeb	Web technology and server fingerprinting.
Nslookup	DNS resolution of the target domain.
curl -I	Inspection of HTTP response headers.
Wafw00f	Detection of Web Application Firewall technology.
DNSRecon	DNS record and service enumeration.
Zenmap / Nmap	Local host and TCP service scanning.
Windows ipconfig	Identification of local IPv4 address and subnet configuration.

3. Activities Performed

3.1 Footprinting & Reconnaissance

WHOIS identified networkwalks.com as a domain registered through GoDaddy.com, LLC. The supplied output shows a creation date of 6 November 2019, registry expiry on 6 November 2027, HostGator name servers, client protection statuses, and an unsigned DNSSEC status.

WhatWeb identified Apache, WordPress 7.1, WordPress Download Manager 3.3.58, Bootstrap 7.1, jQuery 3.7.1, Google Tag Manager, and the public IP address 192.232.216.135. The page title was reported as Networkwalks Academy.

Nslookup resolved networkwalks.com to 192.232.216.135 using 8.8.8.8. Curl returned HTTP/2 200 and exposed HTTP response information and WordPress REST API links including /wp-json/. Wafw00f detected ModSecurity (SpiderLabs). DNSRecon identified SOA, NS, MX, A, TXT and SRV records and reported no DNSSEC answer.

3.2 Zenmap Network Scanning Implementation

The Windows network configuration shows IPv4 address 192.168.1.54 and subnet mask 255.255.255.0, corresponding to the local 192.168.1.0/24 network. The host MAC address is F8-34-41-96-F8-44.

Zenmap was used with the Quick scan profile against 192.168.1.54. The screenshot shows the command `nmap -T4 -F 192.168.1.54`. The host was identified as DESKTOP-LDVC073 and reported as up. The scan found five open TCP ports and 95 closed TCP ports.

Port	State	Service	Security Significance
135/tcp	Open	msrpc	Microsoft RPC exposure; restrict to trusted network contexts.
139/tcp	Open	netbios-ssn	Windows NetBIOS service; restrict where not required.
445/tcp	Open	microsoft-ds	SMB exposure; limit access and apply appropriate host controls.
5357/tcp	Open	wsdapi	Review whether the device-discovery service is required and appropriately restricted.
7070/tcp	Open	realserver	Verify the service owner and whether exposure is necessary.

The Zenmap result confirms the scanned host was active and provides a snapshot of its exposed TCP services. The presence of an open port is a reconnaissance finding and does not, by itself, confirm a vulnerability.

4. Risk Level

#	Risk / Finding	Evidence / Observation	Potential Impact	Level
1	Web technology information	WhatWeb identified WordPress 7.1 and WordPress Download Manager 3.3.58.	May assist technology fingerprinting and targeted security review.	Medium
2	Public web server IP identifiable	192.232.216.135 was returned by WhatWeb and Nslookup.	Reveals the network address associated with the public web service.	Low
3	HTTP/API information	Curl returned server/header information and WordPress /wp-json/ links.	May assist further application enumeration.	Low
4	WAF technology identifiable	Wafw00f detected ModSecurity (SpiderLabs)	Reveals part of the web application's defensive architecture.	Low
5	DNS infrastructure exposed	DNSRecon identified NS, SOA, MX, A, TXT and SRV records.	Can help build a broader infrastructure profile.	Medium
6	SMB/RPC services exposed	Zenmap found ports 135/tcp, 139/tcp and 445/tcp open.	Increases the host's exposed network attack surface; access should be appropriately restricted.	Medium
7	Additional services exposed	Zenmap found ports 5357/tcp and 7070/tcp open.	Unnecessary services may increase the attack surface if they are not required.	Low
8	DNSSEC unsigned	WHOIS reports DNSSEC as unsigned, and DNSRecon returned no DNSSEC answer.	The domain does not receive the additional authenticity protection provided by signed DNS.	Low

Note: These risk ratings are based on reconnaissance observations and the supplied Zenmap scan. They are not confirmed exploitable vulnerabilities.

5. Recommendations

- Update exposed technologies: Keep WordPress, WordPress Download Manager and other exposed components current and supported.
- Restrict SMB/RPC services: Limit ports 135, 139 and 445 to trusted networks and hosts where operationally required.
- Review additional services: Confirm whether ports 5357 and 7070 are required; disable or restrict unnecessary services.
- Review HTTP and API exposure: Minimize unnecessary technical disclosure while preserving required functionality.


- Audit DNS: Periodically review public DNS records and remove obsolete or unnecessary entries.
- Review DNSSEC: Assess whether DNSSEC should be enabled based on the organization's security and operational requirements.
- Continue authorized internal scanning: Periodically identify unexpected devices and exposed services within the local network.

6. Conclusion

The Week 2 exercise combined web reconnaissance with local network scanning. The reconnaissance phase profiled networkwalks.com, while the Zenmap implementation provided concrete information about the local host at 192.168.1.54. The scan identified five open TCP services: 135, 139, 445, 5357 and 7070.

The findings demonstrate the importance of documenting both public-facing information and internal service exposure. The observations should be reviewed within the authorized environment to confirm that required services are properly secured and unnecessary exposure is reduced.

7. Evidence




```

kali@kali: ~
└─$ nslookup networkwalks.com
Server:      8.8.8.8
Address:     8.8.8.8#53

Non-authoritative answer:
Name:   networkwalks.com
Address: 192.232.216.135

kali@kali: ~
└─$

```



```

kali@kali: ~
└─$ curl -I https://networkwalks.com
HTTP/2 200
permissions-policy: private-state-token-redemption=(self "https://www.google.com" "https://www.gstatic.com" "https://recap
tcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com"), private-state-token-issuance=(self "https://www.goo
gle.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com")
link: <https://networkwalks.com/ap-json/>; rel="https://api.w.org"/>, <https://networkwalks.com/ap-json/ap/42/pages/33>; re
l="alternate"; title="JSON"; type="application/json", <https://networkwalks.com/>; rel=shortlink
set-cookie: __wpd_client=81786374b38819d9ec0cf42c74380b5; path=/; domain=networkwalks.com; secure; httponly
referrer-policy: no-referrer-when-downgrade
x-endurance-cache-level: 0
x-engine-cache: WordPress
content-type: text/html; charset=UTF-8
date: Sun, 13 Sep 2026 14:12:47 GMT
server: Apache

kali@kali: ~
└─$

```

