



Compiler

Static Analysis:

Reaching Definition Analysis

© Copyright 2005, Matthew B. Dwyer and Robby. The syllabus and lectures for this course are copyrighted materials and may not be used in other course settings outside University of Nebraska-Lincoln and Kansas State University in their current form or modified form without express written permission of one of the copyright holders. During this course, students are prohibited from selling notes to or being paid for taking notes by any person or commercial firm without the express written permission of one of the copyright holders.



Reaching Definition (RD) Analysis — Motivation

The following code are accepted by phases up to type checking:

```
void baz() {  
    int x;  
    int y;  
    y = x;  
}  
  
int bazz(A a) {  
    int x;  
    if (a == null) { return 0; }  
    return a.x + x;  
}
```

We'd like to notify users about the above ill-formed code (similar to Eclipse IDE)!



RD Analysis – Overview

- An assignment (definition) of the form

$$[x = e;]^l$$

may reach a point l' if

- there is an execution of the program that reaches l' where x was last assigned a value at l



RD Analysis – Overview

- Note the emphasis of may reach
- It is very common to distinguish may analyses from must analyses.
- A helpful way to think about this distinction is to think in terms of program paths.
 - *may* X means there exists a path on which X happens
 - *must* X means for all paths X happens
- What if we have an analysis problem that requires X on no paths?



RD Example (1)

```
static int factorial(int n) {  
    int result;  
    int i;  
    [StaticJavaLib.assertTrue(n >= 1);]1  
    [result = 1;]2  
    [i = 2;]3  
    [while (i <= n) {  
        [result = result * i;]5  
        [i = i + 1;]6  
    }]4  
    [return result;]7  
}
```

Clearly the definition in 2 may reach 5, we describe this more compactly by saying `(result, 2)` reaches the entry 5.

RD Example (2)

Entry Set

	<code>static int factorial(int n) {</code>
	<code>int r;</code>
	<code>int i;</code>
<code>(n,•),(r,?),(i,?)</code>	<code>[StaticJavaLib.assertTrue(n >= 1);]</code> ¹
<code>(n,•),(r,?),(i,?)</code>	<code>[r = 1;]</code> ²
<code>(n,•),(r,2),(i,?)</code>	<code>[i = 2;]</code> ³
<code>(n,•),(r,2),(r,5),(i,3),(i,6)</code>	<code>[while (i <= n) {</code>
<code>(n,•),(r,2),(r,5),(i,3),(i,6)</code>	<code> [r = r * i;]</code> ⁵
<code>(n,•),(r,5),(i,3),(i,6)</code>	<code> [i = i + 1;]</code> ⁶
	<code>}]</code> ⁴
<code>(n,•),(r,2),(r,5),(r,7),(i,3),(i,6)</code>	<code>[return r;]</code> ⁷
	<code>}</code>

Dot (•) denotes definition from a formal parameter (or a field)

Question mark (?) denotes unknown definition

RD Example (3)

Exit Set

	<code>static int factorial(int n) {</code>
	<code>int r;</code>
	<code>int i;</code>
<code>(n,•),(r,?),(i,?)</code>	<code>[StaticJavaLib.assertTrue(n >= 1);]¹</code>
<code>(n,•),(r,2),(i,?)</code>	<code>[r = 1;]²</code>
<code>(n,•),(r,2),(i,3)</code>	<code>[i = 2;]³</code>
<code>(n,•),(r,2),(r,5),(i,3),(i,6)</code>	<code>[while (i <= n) {</code>
<code>(n,•),(r,5),(i,3),(i,6)</code>	<code> [r = r * i;]⁵</code>
<code>(n,•),(r,5),(i,6)</code>	<code> [i = i + 1;]⁶</code>
	<code>}]⁴</code>
<code>(n,•),(r,2),(r,5),(r,7),(i,3),(i,6)</code>	<code>[return r;]⁷</code>
	<code>}</code>

Dot (•) denotes definition from a formal parameter (or a field)

Question mark (?) denotes unknown definition



Denoting RD

- We can describe the set of reaching definitions for the entry and exit of each program point as a pair of functions

$$(RD_{entry}, RD_{exit})$$

where


- $RD_i : Lab_* \rightarrow P(Var_* \times (\{ \bullet, ? \} \cup Lab_*))$

- Notes

- Lab_* and Var_* are the subsets of labels and variables occurring in the program under analysis, e.g., $\{ 1, 2, \dots, 7 \}$ and $\{ n, result, i \}$
- dot (\bullet) denotes definition from a formal parameter (or a field)
- question mark (?) denotes unknown definition

RD Example (4)

<i>I</i>	$RD_{entry}(I)$	$RD_{exit}(I)$
1	$(n, \bullet), (r, ?), (i, ?)$	$(n, \bullet), (r, ?), (i, ?)$
2	$(n, \bullet), (r, ?), (i, ?)$	$(n, \bullet), (r, 2), (i, ?)$
3	$(n, \bullet), (r, 2), (i, ?)$	$(n, \bullet), (r, 2), (i, 3)$
4	$(n, \bullet), (r, 2), (r, 5), (i, 3), (i, 6)$	$(n, \bullet), (r, 2), (r, 5), (i, 3), (i, 6)$
5	$(n, \bullet), (r, 2), (r, 5), (i, 3), (i, 6)$	$(n, \bullet), (r, 5), (i, 3), (i, 6)$
6	$(n, \bullet), (r, 5), (i, 3), (i, 6)$	$(n, \bullet), (r, 5), (i, 6)$
7	$(n, \bullet), (r, 2), (r, 5), (r, 7), (i, 3), (i, 6)$	$(n, \bullet), (r, 2), (r, 5), (r, 7), (i, 3), (i, 6)$




Observation

- For blocks that are assignments
 - i.e., 2, 3, 5, and 6
 - entry and exit values change for the defined variable
- For blocks that are not assignments
 - i.e., 1, 4, and 7
 - entry and exit values are the same
- The effect of statements on the values are localized



Uses for RD — Compiler Optimization

- An occurrence of a variable x at statement l is a constant c , if for all reaching definitions $(x, l') \in \text{RD}_{\text{entry}}(l)$, the value assigned to x at l' is c .
- If all reaching definitions for an expression are outside the loop you can move the expression outside the loop (loop-invariant code motion).
- Construct program dependence graph (PDG). Edges in this graph for a statement l are built as follows: for each reaching definition $(x, l') \in \text{RD}_{\text{entry}}(l)$, we introduce an edge (l', l) .



Uses for RD — Software Engineering Tools

- If for a statement I , that uses x there is a reaching definition $(x, ?) \in RD_{entry}(I)$ then there is a potential uninitialized use of x .
- Used in debugging: if a value at a breakpoint has a bad value then you set breakpoints at the reaching definitions and rerun.
- Program slicers are built using the PDG.




Safety of RD

- Every reachable definition that the program can execute should be detected (may detect more definitions)
 - identify fewer constants
 - fail to move some loop-invariant code
 - issue uninitialization warnings for initialized variables
- Never miss a reaching definition
 - transform an expression based on mistaken impression it is constant
 - move expressions out of loop that change in loop
 - fail to issue a warning when variable may be uninitialized

Is It Safe?

- Are the reaching definitions in the table safe for the example?
 - do they contain all of the reaching definitions that can be executed?
 - are there any extra reaching definitions?

<i>I</i>	$RD_{entry}(I)$	$RD_{exit}(I)$
1	$(n, \bullet), (r, ?), (i, ?)$	$(n, \bullet), (r, ?), (i, ?)$
1'	$(n, \bullet), (r, ?), (i, ?)$	$(n, \bullet), (r, ?), (r, 2), (i, ?)$
5	$(n, \bullet), (r, 2), (r, 5), (i, 3), (i, 6)$	$(n, \bullet), (r, 5), (i, 3), (i, 6)$
5'	$(n, \bullet), (r, 2), (i, 3), (i, 6)$	$(n, \bullet), (r, 5), (i, 3), (i, 6)$



Data Flow Analysis

- Traditionally, Data Flow Analysis exploit the results of Control Flow Analysis
 - information about the sequencing of execution of parts of a program's syntax.
- We have discussed CFG in the previous lecture
 - we assume that we have build CFG for the method under analysis for the next set of slides



Data Flow Analysis

- We will formulate a RD flow analysis to calculate
 - sets of facts, i.e., sets of pairs from $\text{Var}_* \times \text{Lab}_*$
 - at entry and exit of each labeled statement
- Note that we could choose to compute this information for other points in the program, e.g., inside the RHS of an assignment statement



Two Approaches to Formulating Data Flow Analysis

- Equational approach
 - define a system of simultaneous equations
 - 2 | Lab* | variables (to record sets of facts)
 - 2 | Lab* | equations (to capture effects of stmts)
- Constraint approach
 - define a system of inclusions
 - 2 | Lab* | variables (to record sets of facts)
 - inclusion constraints expressing relationships between the sets of facts associated with different statements

The Equational Approach (1)

- For each labeled statement
 - $RD_{entry}(l)$: set of reaching definitions data flow facts before execution of l
 - $RD_{exit}(l)$: set of facts after execution of l
- Statement effects on data flow facts captured by equations
 - $RD_{exit}(l) = f(RD_{entry}(l))$
 - The definition of f depends on the kind of statement
 - $[x = e ;]^l : RD_{exit}(l) = RD_{entry}(l) \setminus \{ (x, l') \mid l' \in Lab^* \} \cup \{ (x, l) \}$
 - $[...]^l : RD_{exit}(l) = RD_{entry}(l)$

Equations for Statement Effects: Factorial Example

- $RD_{exit}(1) = RD_{entry}(1)$
 $[StaticJavaLib.assertTrue(n \geq 1);]^1$
- $RD_{exit}(2) = RD_{entry}(2) / \{ (r, l') \mid l' \in Lab_* \} \cup \{ (r, 2) \}$
 $[r = 1;]^2$
- $RD_{exit}(3) = RD_{entry}(3) / \{ (i, l') \mid l' \in Lab_* \} \cup \{ (i, 3) \}$
 $[i = 2;]^3$
- $RD_{exit}(4) = RD_{entry}(4)$
 $[while (i \leq n) \{ \dots \}]^4$
- $RD_{exit}(5) = RD_{entry}(5) / \{ (r, l') \mid l' \in Lab_* \} \cup \{ (r, 5) \}$
 $[r = r * i;]^5$
- $RD_{exit}(6) = RD_{entry}(6) / \{ (i, l') \mid l' \in Lab_* \} \cup \{ (i, 6) \}$
 $[i = i + 1;]^6$
- $RD_{exit}(7) = RD_{entry}(7)$
 $[return r;]^7$



The Equational Approach (2)

- Statement sequencing is accounted for by introducing equations that propagate facts between control flow predecessors and successors.
 - $RD_{entry}(l) = \bigcup_{l' \in preds(l)} RD_{exit}(l')$
- Since definitions are not introduced in transitioning between statements
 - any fact that holds at the exit of a statement also holds at the entry of each of its successors
- The initial statement has no predecessor so treat it specially
 - $RD_{entry}(b_{init}) = \{ (x, \bullet) \mid x \in (Param_* \cup Field_*) \} \cup \{ (x, ?) \mid x \in Local_* \}$




Equations for Inter-statement Propagation: Factorial Example

- $RD_{entry}(1) = \{ (n, \bullet), (r, ?), (i, ?) \}$
- $RD_{entry}(2) = RD_{exit}(1)$
- $RD_{entry}(3) = RD_{exit}(2)$
- $RD_{entry}(4) = RD_{exit}(3) \cup RD_{exit}(6)$
- $RD_{entry}(5) = RD_{exit}(4)$
- $RD_{entry}(6) = RD_{exit}(5)$
- $RD_{entry}(7) = RD_{exit}(4)$



Solving The System of Equations

- Two approaches
 - elimination/substitution method
 - fixpoint iteration method
- We'll look at the second method
 - easily automated
 - finds the *least* solution
 - minor requirements on data flow facts and equations



Lattice of Data Flow Facts

- Variables in the equations range over sets of data flow facts
 - there are finitely many facts
 - reaching definition facts are naturally ordered by inclusion
- A powerset ordered by inclusion is a complete lattice



Posets

- A partially ordered set — poset (S, \sqsubseteq) is,
 - a set S
 - a partial order \sqsubseteq , which is a reflexive, transitive and anti-symmetric relation
- Examples
 - $(\{1, 2, 3\}, \leq)$
 - $(\{\{1\}, \{2\}, \{1, 2\}\}, \subseteq)$
- While not guaranteed to exist, all of the posets we will discuss have greatest lower (*glb*) and least upper (*lub*) bounds.



Bounds

- A subset Y of a poset (S, \sqsubseteq) has $l \in S$ as an
 - upper bound if $\forall l' \in Y. l' \sqsubseteq l$
 - e.g., $(\{1, 2, 3\}, \leq), Y = \{2\}, l \in \{2, 3\}$
 - lower bound if $\forall l' \in Y. l \sqsubseteq l'$
 - e.g., $(\{\{1\}, \{2\}, \{1, 2\}\}, \subseteq), Y = \{\{1, 2\}\}, l \in \{\{1\}, \{2\}, \{1, 2\}\}$
- A *least upper bound (lub)* l of Y is an upper bound such that $l \sqsubseteq l'$ where l' is an upper bound of Y
 - e.g., $(\{1, 2, 3\}, \leq), Y = \{2\}, lub = 2$
- A *greatest lower bound (glb)* l of Y is a lower bound such that $l' \sqsubseteq l$ where l' is a lower bound of Y
 - e.g., $(\{\{1\}, \{2\}, \{1, 2\}\}, \subseteq), Y = \{\{1\}, \{2\}\}, no\ glb$



Finding Bounds


- If they exist, *lub* and *glb* are unique.
- The least upper bound of two subsets is denoted $I_1 \sqcup I_2$ which is called the *join* operator.
 - e.g., $(\{1, 2, 3, 4\}, \leq), \{2, 3\} \sqcup \{2\} = 3$
- The greatest lower bound of two subsets is denoted $I_1 \sqcap I_2$ which is called the *meet* operator.
 - e.g., $(\{\{\}, \{1\}, \{2\}, \{1, 2\}\}, \subseteq), \{\{1\}\} \sqcap \{\{1, 2\}\} = \{1\}$



Complete Lattices

- A complete lattice $L = (L, \sqsubseteq, \sqcup, \sqcap, \perp, \top)$ consists of
 - a poset (L, \sqsubseteq)
 - where *lub* and *glb* exist for all $Y \subseteq L$
 - $\perp = \sqcap L$ is the least element
 - $\top = \sqcup L$ is the greatest element
- In practice we'll only require \sqsubseteq and either \sqcup and \perp or \sqcap and \top .

Complete Lattice – Example



$(L, \sqsubseteq, \sqcup, \sqcap, \perp, \top) = (\{ \{\}, \{1\}, \{2\}, \{3\}, \{1, 2\}, \{1, 3\}, \{2, 3\}, \{1, 2, 3\} \}, \subseteq, \supseteq, \cup, \cap, \{\}, \{1, 2, 3\})$

i.e., $L = P(\{1, 2, 3\})$



Sets of Reaching Definitions Facts

- $P(\text{Var}_* \times (\{ \bullet, ? \} \cup \text{Lab}_*))$

- $\sqsubseteq = \subseteq$

- $\sqcup = \cup$

- $\perp = \emptyset$

- So, we are working with a complete lattice

Vector Representation of Equations

- Consider the 14 variables as a single vector value

$$\vec{RD} = (RD_{entry}(1), RD_{exit}(1), \dots, RD_{exit}(7))$$

- 14-tuples of complete lattice values, $\vec{RD} = (RD_1, RD_2, \dots, RD_{14})$, form a complete lattice

- $\vec{RD} \sqsubseteq \vec{RD}' \text{ iff } \forall i. RD_i \subseteq RD_i'$

- $\vec{RD} \sqcup \vec{RD}' = (RD_1 \cup RD_1', \dots, RD_{14} \cup RD_{14}')$

- $\perp = \vec{\emptyset} = (\emptyset, \dots, \emptyset)$



Equations as A Function

We can write the equation system as

$$\overrightarrow{RD} = F(\overrightarrow{RD})$$

where

$$F(\overrightarrow{RD}) = (F_{entry}(1)(\overrightarrow{RD}), \dots, F_{exit}(7)(\overrightarrow{RD}))$$

where the component functions encode the equations, for example,

$$F_{exit}(2)(\dots) = RD_{entry}(2) / \{ (x, l') \mid l' \in Lab_* \} \cup \{ (x, 2) \}$$



Properties of Functions

- We can be assured that solution methods will produce an answer to a system of equations if the function is monotone
- A function, $f: L \rightarrow L$, is *monotone* if
$$\forall I, I'. I \sqsubseteq I' \Rightarrow f(I) \sqsubseteq f(I')$$
- Such functions are also termed *order preserving* since a pair of values ordered in a poset/lattice will have their images under f in the same relative order, e.g.,
 - For $L = \{ \{\}, \{1\}, \{2\}, \{3\}, \{1, 2\}, \{1, 3\}, \{2, 3\}, \{1, 2, 3\} \}$, and $f(I) = I \cup \{ \{3\} \}$ is monotone



F is Monotone

- There are three forms of constituent functions in F , e.g.,
 - $F_{entry}(2)(\dots) = RD_{exit}(1)$
 - $F_{entry}(4)(\dots) = RD_{exit}(3) \cup RD_{exit}(6)$
 - $F_{exit}(2)(\dots) = RD_{entry}(2) / \{ (x, l') \mid l' \in Lab_* \} \cup \{ (x, 2) \}$
- These are easily seen to be monotone in the lattice of reaching definition facts.



Fixed Point of F is a Solution

- Given the monotonicity of F it follows that
 - $\vec{\emptyset} \sqsubseteq F(\vec{\emptyset})$
 - $F^n(\vec{\emptyset}) \sqsubseteq F^{n+1}(\vec{\emptyset})$
- Given that the lattice is finite there must be some pair of iterates of F such that
 - $F^n(\vec{\emptyset}) = F^{n+1}(\vec{\emptyset})$
 - $F^n(\vec{\emptyset})$ is a fixed point of F
 - $F^n(\vec{\emptyset})$ is a solution to the equation system

Least Solution

- The fixed point of F is the least solution of the system of equations
- Suppose $\overrightarrow{RD} = F(\overrightarrow{RD})$, i.e., \overrightarrow{RD} is a fixed point
 - $\emptyset \sqsubseteq \overrightarrow{RD}$
 - so, $F(\emptyset) \sqsubseteq F(\overrightarrow{RD})$ (monotonicity)
 - $F(\emptyset) \sqsubseteq F(\overrightarrow{RD})$
 - $F(F(\emptyset)) \sqsubseteq F(\overrightarrow{RD}) = \overrightarrow{RD}$ (monotonicity)
 - ...
 - $F^n(\emptyset) \sqsubseteq F(\overrightarrow{RD}) = \overrightarrow{RD}$ (monotonicity)



Chaotic Iteration

- The weakest specification of an iterative algorithm for calculating fix point solutions for flow analysis problems

$RD_1 := \emptyset$

...

$RD_{14} := \emptyset$

while $\exists j. RD_j \neq F_j(RD_1, \dots, RD_{14})$ **do**

$RD_j := F_j(RD_1, \dots, RD_{14})$

- The algorithm continues to loop until all components have reached a local fixed point.
- So, if the algorithm terminates a fixed point of F is reached.



Properties of Algorithm

■ Will it terminate?

- executing the loop body means there is some $RD_j \neq F_j(RD_1, \dots, RD_{14})$
- this only happens if $RD_j \subset F_j(RD_1, \dots, RD_{14})$
- so, the assignment in the loop body increases the size of RD_j
- but, this can only happen a finite number of times since the lattice is finite

■ Will it produce the least solution?

- think about that the fixed point solution is the least solution