Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1111 / 1111

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 114

Time Taken

0.12

Solve Next

The Celebrity Problem | Get Min from Stack | Histogram Max Rectangular Area

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int minParentheses(String s) {
        // code here
            int open = 0;
        int add = 0;

        for (char ch : s.toCharArray()) {
            if (ch == '(') {
                open++;
            } else {
                if (open > 0) {
                    open--;
                } else {
                    add++;
                }
            }
        }

        return open + add;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 118

Time Taken

0.08

Solve Next

The Celebrity Problem | Get Min from Stack | Histogram Max Rectangular Area

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int scoreOfParentheses(String s) {
        // code here
        int score = 0;
        int depth = 0;

        for (int i = 0; i < s.length(); i++) {
            if (s.charAt(i) == '(') {
                depth++;
            } else {
                depth--;
                if (s.charAt(i - 1) == '(') {
                    score += 1 << depth;
                }
            }
        }

        return score;
    }
}
```

Custom Input

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed	Attempts : Correct / Total
1117 / 1117	**1 / 1**
	Accuracy : 100%

Points Scored	Time Taken
4 / 4	**0.34**
Your Total Score: 122 ↑	

Solve Next

Validate an IP Address | Multiply two strings | Implement Atoi

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public String frequencySort(String s) {
        // code here
         int[] freq = new int[26];

        for (char ch : s.toCharArray()) {
            freq[ch - 'a']++;
        }

        List<Character> list = new ArrayList<>();
        for (int i = 0; i < 26; i++) {
            if (freq[i] > 0) {
                list.add((char) (i + 'a'));
            }
        }

        Collections.sort(list, (a, b) -> {
            if (freq[a - 'a'] == freq[b - 'a']) {
                return a - b;
            }
            return freq[a - 'a'] - freq[b - 'a'];
        });

        StringBuilder sb = new StringBuilder();

        for (char ch : list) {
            int count = freq[ch - 'a'];
            while (count-- > 0) {
                sb.append(ch);
            }
        }

        return sb.toString();
    }
};
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1111 / 1111

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 126

Time Taken

1.17

Solve Next

Validate an IP Address | Multiply two strings | Implement Atoi

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public void sortByLength(String[] arr) {
        // code here
        Arrays.sort(arr, (a, b) -> {
            if (a.length() == b.length()) {
                return 0;
            }
            return a.length() - b.length();
        });
    }
}
```

Custom Input Compile & Run Submit

Ctrl + Enter

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 130

Time Taken

4.27

Solve Next

Validate an IP Address | Multiply two strings | Implement Atoi

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int countPairs(String[] arr) {
        // code here
            int n = arr.length;
        int count = 0;

        for (int i = 0; i < n; i++) {
            for (int j = i + 1; j < n; j++) {

                int diff = 0;

                for (int k = 0; k < arr[i].length(); k++) {
                    if (arr[i].charAt(k) != arr[j].charAt(k)) {
                        diff++;
                        if (diff > 1) break;
                    }
                }

                if (diff == 1) count++;
            }
        }

        return count;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1115 / 1115

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

2 / 2

Your Total Score: 132

Time Taken

0.5

Solve Next

Run Length Encoding | Match specific pattern | Repetition of k length substring

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    boolean search(String txt, String pat) {
        // Write your code here
         if (pat.length() > txt.length()) return false;

        int[] pFreq = new int[26];
        int[] tFreq = new int[26];

        for (int i = 0; i < pat.length(); i++) {
            pFreq[pat.charAt(i) - 'a']++;
            tFreq[txt.charAt(i) - 'a']++;
        }

        if (Arrays.equals(pFreq, tFreq)) return true;

        for (int i = pat.length(); i < txt.length(); i++) {
            tFreq[txt.charAt(i) - 'a']++;
            tFreq[txt.charAt(i - pat.length()) - 'a']--;

            if (Arrays.equals(pFreq, tFreq)) return true;
        }

        return false;
    }
}
```

Ctrl + Enter

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 136

Time Taken

0.16

Solve Next

Majority Element | Fractional Knapsack | Minimum Platforms

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public static String maxSubseq(String s, int k) {
        // code here
         int keep = s.length() - k;
        Deque<Character> stack = new ArrayDeque<>();

        for (int i = 0; i < s.length(); i++) {
            char ch = s.charAt(i);

            while (!stack.isEmpty() && k > 0 && stack.peekLast() < ch) {
                stack.pollLast();
                k--;
            }

            stack.addLast(ch);
        }

        while (k > 0) {
            stack.pollLast();
            k--;
        }

        StringBuilder sb = new StringBuilder();
        int count = 0;

        for (char ch : stack) {
            if (count == keep) break;
            sb.append(ch);
            count++;
        }

        return sb.toString();
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

s =

aeiou

Your Output:

120

Expected Output:

120

Java (21) Start Timer

```java
class Solution {
    public int vowelCount(String s) {
        // code here
          int[] freq = new int[5];

        for (char ch : s.toCharArray()) {
            if (ch == 'a') freq[0]++;
            else if (ch == 'e') freq[1]++;
            else if (ch == 'i') freq[2]++;
            else if (ch == 'o') freq[3]++;
            else if (ch == 'u') freq[4]++;
        }

        int distinct = 0;
        long ways = 1;

        for (int i = 0; i < 5; i++) {
            if (freq[i] > 0) {
                distinct++;
                ways *= freq[i];
            }
        }

        long fact = 1;
        for (int i = 2; i <= distinct; i++) {
            fact *= i;
        }

        return (int)(ways * fact);
    }
}
```

Ctrl + '

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1115 / 1115

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

2 / 2

Your Total Score: 138

Time Taken

0.36

Solve Next

Run Length Encoding | Match specific pattern | Repetition of k length substring

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int count(String s) {
        // code here
         int[] freq = new int[26];

        for (char ch : s.toCharArray()) {
            freq[ch - 'a']++;
        }

        int result = 0;

        for (int i = 0; i < 26; i++) {
            if (freq[i] > 0 && freq[i] % 2 == 0) {
                result++;
            }
        }

        return result;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

s1 =

ae

s2 =

acbaudeq

Your Output:

4

Expected Output:

4

Java (21) Start Timer

```java
    public int substrWithVowels(String s1, String s2) {
        // code here
          Set<Character> required = new HashSet<>();
        for (char ch : s1.toCharArray()) {
            required.add(ch);
        }

        Map<Character, Integer> window = new HashMap<>();
        int left = 0;
        int minLen = Integer.MAX_VALUE;
        int formed = 0;

        for (int right = 0; right < s2.length(); right++) {
            char ch = s2.charAt(right);

            if (required.contains(ch)) {
                window.put(ch, window.getOrDefault(ch, 0) + 1);
                if (window.get(ch) == 1) {
                    formed++;
                }
            }

            while (formed == required.size()) {
                minLen = Math.min(minLen, right - left + 1);

                char leftChar = s2.charAt(left);
                if (required.contains(leftChar)) {
                    window.put(leftChar, window.get(leftChar) - 1);
                    if (window.get(leftChar) == 0) {
                        formed--;
                    }
                }
                left++;
            }
        }

        return minLen == Integer.MAX_VALUE ? -1 : minLen;
```

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1115 / 1115

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 146

Time Taken

0.68

Solve Next

Validate an IP Address | Multiply two strings | Implement Atoi

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int countBalanced(String[] arr) {
        // code here
          int n = arr.length;
        int[] prefix = new int[n + 1];

        for (int i = 0; i < n; i++) {
            int v = 0, c = 0;

            for (char ch : arr[i].toCharArray()) {
                if (ch=='a'||ch=='e'||ch=='i'||ch=='o'||ch=='u') v++;
                else c++;
            }

            prefix[i + 1] = prefix[i] + (v - c);
        }

        Map<Integer, Integer> map = new HashMap<>();
        int count = 0;

        for (int i = 0; i <= n; i++) {
            int val = prefix[i];
            count += map.getOrDefault(val, 0);
            map.put(val, map.getOrDefault(val, 0) + 1);
        }

        return count;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit