Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

214 / 214

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 74

Time Taken

0.81

Solve Next

Find kth element of spiral matrix | Make Matrix Beautiful | Boolean Matrix

Stay Ahead With:

Java (21) Start Timer

```java
//User function Template for Java

class Solution{
    ArrayList<Long> submatrixSum(long[][] a, int n,
                                 int m, int[][] query, int q){

                                     long[][] prefix = new long[n][m];

        for (int i = 0; i < n; i++) {
            for (int j = 0; j < m; j++) {

                prefix[i][j] = a[i][j];

                if (i > 0)
                    prefix[i][j] += prefix[i - 1][j];

                if (j > 0)
                    prefix[i][j] += prefix[i][j - 1];

                if (i > 0 && j > 0)
                    prefix[i][j] -= prefix[i - 1][j - 1];
            }
        }

        ArrayList<Long> result = new ArrayList<>();

        for (int i = 0; i < q; i++) {
            int r1 = query[i][0];
            int c1 = query[i][1];
            int r2 = query[i][2];
            int c2 = query[i][3];

            long sum = prefix[r2][c2];

            if (r1 > 0)
                sum -= prefix[r1 - 1][c2];

```

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

```
3 3
1 2 3
4 5 6
7 8 9
1
2 2
```

Your Output:

20

Expected Output:

20

Java (21) Start Timer

```java
        rowMinRight[i][m - 1] = a[i][m - 1];
        for (int j = m - 2; j >= 0; j--)
            rowMinRight[i][j] = Math.min(rowMinRight[i][j + 1], a[i][j]);
    }

    for (int j = 0; j < m; j++) {
        colMinUp[0][j] = a[0][j];
        for (int i = 1; i < n; i++)
            colMinUp[i][j] = Math.min(colMinUp[i - 1][j], a[i][j]);

        colMinDown[n - 1][j] = a[n - 1][j];
        for (int i = n - 2; i >= 0; i--)
            colMinDown[i][j] = Math.min(colMinDown[i + 1][j], a[i][j]);
    }

    for (int k = 0; k < q; k++) {
        int r = queries[k][0] - 1;
        int c = queries[k][1] - 1;

        int sum = 0;

        if (r > 0 && c > 0)
            sum += Math.min(colMinUp[r - 1][0], rowMinLeft[0][c - 1]);

        if (r > 0 && c < m - 1)
            sum += Math.min(colMinUp[r - 1][m - 1], rowMinRight[0][c + 1]);

        if (r < n - 1 && c > 0)
            sum += Math.min(colMinDown[r + 1][0], rowMinLeft[n - 1][c - 1]);

        if (r < n - 1 && c < m - 1)
            sum += Math.min(colMinDown[r + 1][m - 1], rowMinRight[n - 1][c + 1]);

        ans[k] = sum;
    }

    return ans;
```

Ctrl + '

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed	Attempts : Correct / Total
1115 / 1115	**1 / 1** Accuracy : 100%
Points Scored **4 / 4** Your Total Score: 78 ↑	Time Taken **0.62**

Solve Next

Majority Element | Fractional Knapsack | Minimum Platforms

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int minOperations(int[] arr) {
        // code here
           PriorityQueue<Double> pq = new PriorityQueue<>(Collections.reverseOrder());
        double sum = 0.0;

        for (int num : arr) {
            sum += num;
            pq.offer((double) num);
        }

        double target = sum / 2.0;
        double current = sum;
        int operations = 0;

        while (current > target) {
            double largest = pq.poll();
            double half = largest / 2.0;
            current -= half;
            pq.offer(half);
            operations++;
        }

        return operations;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

```
3 3
1 2 3
4 5 6
7 8 9
1
2 2
```

Your Output:

20

Expected Output:

20

Java (21) Start Timer

```java
//User function Template for Java
class Solution {
    public int[] createFootpath(int n, int m, int a[][], int q, int queries[][]) {

        int[] ans = new int[q];

        int[][] rowMinLeft = new int[n][m];
        int[][] rowMinRight = new int[n][m];
        int[][] colMinUp = new int[n][m];
        int[][] colMinDown = new int[n][m];

        for (int i = 0; i < n; i++) {
            rowMinLeft[i][0] = a[i][0];
            for (int j = 1; j < m; j++)
                rowMinLeft[i][j] = Math.min(rowMinLeft[i][j - 1], a[i][j]);

            rowMinRight[i][m - 1] = a[i][m - 1];
            for (int j = m - 2; j >= 0; j--)
                rowMinRight[i][j] = Math.min(rowMinRight[i][j + 1], a[i][j]);
        }

        for (int j = 0; j < m; j++) {
            colMinUp[0][j] = a[0][j];
            for (int i = 1; i < n; i++)
                colMinUp[i][j] = Math.min(colMinUp[i - 1][j], a[i][j]);

            colMinDown[n - 1][j] = a[n - 1][j];
            for (int i = n - 2; i >= 0; i--)
                colMinDown[i][j] = Math.min(colMinDown[i + 1][j], a[i][j]);
        }

        for (int k = 0; k < q; k++) {
            int r = queries[k][0] - 1;
            int c = queries[k][1] - 1;

            int sum = 0;
```

Ctrl + '

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1115 / 1115

Attempts : Correct / Total

2 / 2

Accuracy : 100%

Time Taken

0.7

You get marks only for the first correct submission if you solve the problem without viewing the full solution.

Solve Next

Majority Element Fractional Knapsack Minimum Platforms

Java (21) Start Timer

```java
class Solution {
    public int minOperations(int[] arr) {
        // code here
           PriorityQueue<Double> pq = new PriorityQueue<>(Collections.reverseOrder());
        double sum = 0.0;

        for (int num : arr) {
            sum += num;
            pq.offer((double) num);
        }

        double target = sum / 2.0;
        double current = sum;
        int operations = 0;

        while (current > target) {
            double largest = pq.poll();
            double half = largest / 2.0;
            current -= half;
            pq.offer(half);
            operations++;
        }

        return operations;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input | Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed	Attempts : Correct / Total
1122 / 1122	**1 / 2**
	Accuracy : 50%

Points Scored	Time Taken
4 / 4	**2.01**
Your Total Score: 82 ↑	

Solve Next

Majority Element | Fractional Knapsack | Minimum Platforms

Stay Ahead With:

Java (21) Start Timer

```java
        int idx = 0;

        for (int i = 0; i < n; i++) {
            if (arr[i] == -1) continue;

            int left = Math.max(0, i - arr[i]);
            int right = Math.min(n - 1, i + arr[i]);

            intervals[idx][0] = left;
            intervals[idx][1] = right;
            idx++;
        }

        Arrays.sort(intervals, 0, idx, (a, b) -> {
            if (a[0] == b[0]) return b[1] - a[1];
            return a[0] - b[0];
        });

        int count = 0;
        int i = 0;
        int covered = 0;

        while (covered < n) {
            int farthest = -1;

            while (i < idx && intervals[i][0] <= covered) {
                farthest = Math.max(farthest, intervals[i][1]);
                i++;
            }

            if (farthest < covered) return -1;

            count++;
            covered = farthest + 1;
        }

        return count;
```

Ctrl + Enter

Custom Input | Compile & Run | Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 2

Accuracy : 50%

Points Scored

4 / 4

Your Total Score: 86

Time Taken

0.73

Solve Next

The Celebrity Problem | Get Min from Stack | Histogram Max Rectangular Area

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int countSubarrays(int[] arr) {
        // code here
           int n = arr.length;
        long count = 0;
        Stack<Integer> stack = new Stack<>();

        for (int i = n - 1; i >= 0; i--) {

            while (!stack.isEmpty() && arr[stack.peek()] >= arr[i]) {
                stack.pop();
            }

            int nextSmaller = stack.isEmpty() ? n : stack.peek();
            count += (nextSmaller - i);

            stack.push(i);
        }

        return (int) count;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 90

Time Taken

0.88

Solve Next

The Celebrity Problem | Get Min from Stack | Histogram Max Rectangular Area

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public boolean has132Pattern(int[] arr) {
        // code here
         int n = arr.length;
        Stack<Integer> stack = new Stack<>();
        int third = Integer.MIN_VALUE;

        for (int i = n - 1; i >= 0; i--) {

            if (arr[i] < third) return true;

            while (!stack.isEmpty() && arr[i] > stack.peek()) {
                third = stack.pop();
            }

            stack.push(arr[i]);
        }

        return false;
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 94

Time Taken

1.32

Solve Next

The Celebrity Problem | Get Min from Stack | Histogram Max Rectangular Area

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public int maxPeople(int[] arr) {
        // code here
          int n = arr.length;
        int[] left = new int[n];
        int[] right = new int[n];
        Stack<Integer> stack = new Stack<>();

        for (int i = 0; i < n; i++) {
            while (!stack.isEmpty() && arr[stack.peek()] < arr[i]) {
                stack.pop();
            }
            left[i] = stack.isEmpty() ? i : i - stack.peek() - 1;
            stack.push(i);
        }

        stack.clear();

        for (int i = n - 1; i >= 0; i--) {
            while (!stack.isEmpty() && arr[stack.peek()] < arr[i]) {
                stack.pop();
            }
            right[i] = stack.isEmpty() ? (n - 1 - i) : stack.peek() - i - 1;
            stack.push(i);
        }

        int max = 0;

        for (int i = 0; i < n; i++) {
            max = Math.max(max, left[i] + right[i] + 1);
        }

        return max;
    }
}
```

Custom Input Compile & Run Submit

https://www.geeksforgeeks.org/problems/combination-sum-iii--111703/1

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 98

Time Taken

0.36

Solve Next

Rat in a Maze | Possible Words From Phone Digits | Largest number in K swaps

Stay Ahead With:

Java (21) Start Timer

```java
class Solution {
    public ArrayList<ArrayList<Integer>> combinationSum(int n, int k) {
        // code here
          ArrayList<ArrayList<Integer>> result = new ArrayList<>();
        backtrack(n, k, 1, new ArrayList<>(), result);
        return result;
    }

    private void backtrack(int target, int k, int start,
                           ArrayList<Integer> current,
                           ArrayList<ArrayList<Integer>> result) {

        if (target == 0 && current.size() == k) {
            result.add(new ArrayList<>(current));
            return;
        }

        if (target < 0 || current.size() >= k) return;

        for (int i = start; i <= 9; i++) {
            current.add(i);
            backtrack(target - i, k, i + 1, current, result);
            current.remove(current.size() - 1);
        }
    }
}
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1120 / 1120

Attempts : Correct / Total

1 / 2

Accuracy : 50%

Points Scored

4 / 4

Your Total Score: 102

Time Taken

0.35

Solve Next

Rat in a Maze | Possible Words From Phone Digits | Largest number in K swaps

Stay Ahead With:

Java (21) Start Timer

```
                    ArrayList<ArrayList<Integer>> result) {

        if (target == 0 && curr.size() == size) {

            ArrayList<Integer> other = new ArrayList<>();
            boolean[] used = new boolean[arr.length];

            for (int i = 0; i < curr.size(); i++) {
                for (int j = 0; j < arr.length; j++) {
                    if (!used[j] && arr[j] == curr.get(i)) {
                        used[j] = true;
                        break;
                    }
                }
            }

            for (int i = 0; i < arr.length; i++) {
                if (!used[i]) other.add(arr[i]);
            }

            result.add(new ArrayList<>(curr));
            result.add(other);
            return true;
        }

        if (index >= arr.length || curr.size() > size)
            return false;

        curr.add(arr[index]);
        if (find(arr, index + 1, target - arr[index], size, curr, result))
            return true;
        curr.remove(curr.size() - 1);

        if (find(arr, index + 1, target, size, curr, result))
            return true;

        return false;
```

Ctrl + Enter

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1115 / 1115

Attempts : Correct / Total

1 / 1

Accuracy : 100%

Points Scored

4 / 4

Your Total Score: 106

Time Taken

0.56

Solve Next

Merge Sort Quick Sort C++ Generic sort

Stay Ahead With:

Java (21) Start Timer

```java
    public int maxMinDiff(int[] arr, int k) {
        // code here
        Arrays.sort(arr);
        int n = arr.length;

        int low = 0;
        int high = arr[n - 1] - arr[0];
        int ans = 0;

        while (low <= high) {
            int mid = low + (high - low) / 2;

            if (canSelect(arr, k, mid)) {
                ans = mid;
                low = mid + 1;
            } else {
                high = mid - 1;
            }
        }

        return ans;
    }

    private boolean canSelect(int[] arr, int k, int minDiff) {

        int count = 1;
        int last = arr[0];

        for (int i = 1; i < arr.length; i++) {
            if (arr[i] - last >= minDiff) {
                count++;
                last = arr[i];
                if (count >= k) return true;
            }
        }

        return false;
```

Ctrl + Enter

Custom Input Compile & Run Submit

https://www.geeksforgeeks.org/problems/count-elements-less-than-or-equal-to-k-in-a-sorted-rotated-array/1

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input Y.O.G.I. (AI Bot)

Problem Solved Successfully

Suggest Feedback

Test Cases Passed

1113 / 1113

Attempts : Correct / Total

1 / 2

Accuracy : 50%

Points Scored

4 / 4

Your Total Score: 110

Time Taken

0.74

Solve Next

Max sum in the configuration | Sum of permutations | Rotate and delete

Stay Ahead With:

Java (21) Start Timer

```java
        } else {
            count += upperBound(arr, pivot, n - 1, x);
        }

        return count;
    }

    private int findPivot(int[] arr) {
        int low = 0, high = arr.length - 1;

        while (low < high) {
            int mid = low + (high - low) / 2;
            if (arr[mid] > arr[high]) {
                low = mid + 1;
            } else {
                high = mid;
            }
        }

        return low;
    }

    private int upperBound(int[] arr, int low, int high, int x) {
        int l = low, r = high;
        int ans = low - 1;

        while (l <= r) {
            int mid = l + (r - l) / 2;

            if (arr[mid] <= x) {
                ans = mid;
                l = mid + 1;
            } else {
                r = mid - 1;
            }
        }

        return ans >= low ? (ans - low + 1) : 0;
```

Ctrl + Enter

Custom Input Compile & Run Submit