PHY 102 Introduction to Physics II Spring Semester 2025

Lecture 33

Maxwell's Equations in Matter

If we are working with materials that are subject to electric and magnetic polarization there is a more convenient way to write the Maxwell's equation

For inside polarized matter there will be accumulations of "bound" charge and current, over which you exert no direct control.

In the static case, the electric polarization **P** produces a bound charge density

$$\rho_b = -\mathbf{\nabla} \cdot \mathbf{P}$$


Likewise, a magnetic polarization (or "magnetization") M results in a bound current

$$\mathbf{J}_b = \mathbf{\nabla} \times \mathbf{M}$$

In the nonstatic case: Any change in the electric polarization involves a flow of (bound) charge (call it J_p), which must be included in the total current.

Suppose in a tiny chunk of polarized material, the polarization introduces a charge density $\sigma_b = \mathbf{P}$ at one end and $-\sigma_b$ at the other.

If **P** now increases a bit, the charge on each end increases accordingly, giving a net current



$$dI = \frac{\partial \sigma_b}{\partial t} da_{\perp} = \frac{\partial P}{\partial t} da_{\perp}$$

The current density

$$\mathbf{J}_p = \frac{\partial \mathbf{P}}{\partial t}$$

Polarization current

- This polarization current $(\mathbf{J_p})$ has nothing to do with the bound current $\mathbf{J_b}$. The latter is associated with magnetization of the material and involves the spin and orbital motion of electrons
- J_p , is the result of the linear motion of charge when the electric polarization changes.

If P points to the right, and is increasing, then each plus charge moves a bit to the right and each minus charge to the left; the cumulative effect is the polarization current J_p

Checking the consistenty of J_p with the continuity equation

$$\nabla \cdot \mathbf{J}_p = \nabla \cdot \frac{\partial \mathbf{P}}{\partial t} = \frac{\partial}{\partial t} (\nabla \cdot \mathbf{P}) = -\frac{\partial \rho_b}{\partial t}$$

 $\mathbf{J}_{\mathbf{p}}$ is essential to ensure the conservation of bound charge.

In matter,

the total charge density

$$\rho = \rho_f + \rho_b = \rho_f - \nabla \cdot \mathbf{P}_f$$

the total current density

$$\mathbf{J} = \mathbf{J}_f + \mathbf{J}_b + \mathbf{J}_p = \mathbf{J}_f + \mathbf{\nabla} \times \mathbf{M} + \frac{\partial \mathbf{P}}{\partial t}$$

Gauss's law

$$\nabla \cdot \mathbf{E} = \frac{1}{\epsilon_0} (\rho_f - \nabla \cdot \mathbf{P}),$$

as in the static case, $\mathbf{D} \equiv \epsilon_0 \mathbf{E} + \mathbf{P}$.

$$\nabla \cdot \mathbf{D} = \rho_f$$

Ampère's law (with Maxwell's term) becomes

$$\nabla \times \mathbf{B} = \mu_0 \left(\mathbf{J}_f + \nabla \times \mathbf{M} + \frac{\partial \mathbf{P}}{\partial t} \right) + \mu_0 \epsilon_0 \frac{\partial \mathbf{E}}{\partial t},$$

$$\nabla \times \mathbf{H} = \mathbf{J}_f + \frac{\partial \mathbf{D}}{\partial t},$$

$$\mathbf{H} \equiv \frac{1}{\mu_0} \mathbf{B} - \mathbf{M}.$$

$$\mathbf{J} = \mathbf{J}_f + \mathbf{J}_b + \mathbf{J}_p = \mathbf{J}_f + \nabla \times \mathbf{M} + \frac{\partial \mathbf{P}}{\partial t}.$$

In terms of free charges and currents, then, Maxwell's equations read

(i)
$$\nabla \cdot \mathbf{D} = \rho_f$$
, (iii) $\nabla \times \mathbf{E} = -\frac{\partial \mathbf{B}}{\partial t}$, (iii) $\nabla \cdot \mathbf{B} = 0$, (iv) $\nabla \times \mathbf{H} = \mathbf{J}_f + \frac{\partial \mathbf{D}}{\partial t}$.

Displacement current

Integral Form

(i)
$$\oint_{\mathcal{S}} \mathbf{D} \cdot d\mathbf{a} = Q_{f_{\text{enc}}}$$
(ii)
$$\oint_{\mathcal{S}} \mathbf{B} \cdot d\mathbf{a} = 0$$
over any closed surface \mathcal{S} .

(ii)
$$\oint_{S} \mathbf{B} \cdot d\mathbf{a} = 0$$

(iii)
$$\oint_{\mathcal{P}} \mathbf{E} \cdot d\mathbf{l} = -\frac{d}{dt} \int_{\mathcal{S}} \mathbf{B} \cdot d\mathbf{a}$$

(iii)
$$\oint_{\mathcal{P}} \mathbf{E} \cdot d\mathbf{l} = -\frac{d}{dt} \int_{\mathcal{S}} \mathbf{B} \cdot d\mathbf{a}$$
(iv)
$$\oint_{\mathcal{P}} \mathbf{H} \cdot d\mathbf{l} = I_{f_{\text{enc}}} + \frac{d}{dt} \int_{\mathcal{S}} \mathbf{D} \cdot d\mathbf{a}$$


for any surface ${\cal S}$ bounded by the closed loop \mathcal{P} .

(i)
$$\oint_{\mathcal{S}} \mathbf{D} \cdot d\mathbf{a} = Q_{f_{\text{enc}}}$$

$$\mathbf{D}_1 \cdot \mathbf{a} - \mathbf{D}_2 \cdot \mathbf{a} = \sigma_f \, a$$

$$D_1^{\perp} - D_2^{\perp} = \sigma_f.$$

The positive direction for **a** is from 2 toward 1



The perpendicular component of D at the interface is discontinuous by an amount of surface charge density σ_f

(ii)
$$\oint_{\mathcal{S}} \mathbf{B} \cdot d\mathbf{a} = 0$$

$$B_1^{\perp} - B_2^{\perp} = 0.$$

(iii)
$$\oint_{\mathcal{P}} \mathbf{E} \cdot d\mathbf{l} = -\frac{d}{dt} \int_{\mathcal{S}} \mathbf{B} \cdot d\mathbf{a}$$

$$\mathbf{E}_{1}^{\parallel} - \mathbf{E}_{2}^{\parallel} = \mathbf{0}.$$

The components of **E** parallel to the interface are continuous across the boundary

(iv)
$$\oint_{\mathcal{P}} \mathbf{H} \cdot d\mathbf{l} = I_{f_{\text{enc}}} + \frac{d}{dt} \int_{\mathcal{S}} \mathbf{D} \cdot d\mathbf{a}$$


$$\mathbf{H}_1 \cdot \mathbf{l} - \mathbf{H}_2 \cdot \mathbf{l} = I_{f_{\text{enc}}}$$

where $I_{f_{enc}}$ is the free current passing through the Amperian loop.

$$\mathbf{H}_1 \cdot \mathbf{l} - \mathbf{H}_2 \cdot \mathbf{l} = I_{f_{\text{enc}}}$$

$$I_{f_{\text{enc}}} = \mathbf{K}_f \cdot (\hat{\mathbf{n}} \times \mathbf{l}) = (\mathbf{K}_f \times \hat{\mathbf{n}}) \cdot \mathbf{l},$$

$$\mathbf{H}_1^{\parallel} - \mathbf{H}_2^{\parallel} = \mathbf{K}_f \times \hat{\mathbf{n}}.$$



So the *parallel* components of **H** are discontinuous by an amount proportional to the free surface current density.


General boundary conditions for electrodynamics


$$D_1^{\perp} - D_2^{\perp} = \sigma_f.$$

$$B_1^{\perp} - B_2^{\perp} = 0.$$

$$\mathbf{E}_1^{\parallel} - \mathbf{E}_2^{\parallel} = \mathbf{0}.$$

$$\mathbf{H}_1^{\parallel} - \mathbf{H}_2^{\parallel} = \mathbf{K}_f \times \hat{\mathbf{n}}.$$





In the case of linear media, they can be expressed in terms of **E** and **B** alone:

(i)
$$\epsilon_1 E_1^{\perp} - \epsilon_2 E_2^{\perp} = \sigma_f$$
, (iii) $\mathbf{E}_1^{\parallel} - \mathbf{E}_2^{\parallel} = \mathbf{0}$,

(iii)
$$\mathbf{E}_1^{\parallel} - \mathbf{E}_2^{\parallel} = \mathbf{0},$$

(ii)
$$B_1^{\perp} - B_2^{\perp} = 0$$
,

(iv)
$$\frac{1}{\mu_1} \mathbf{B}_1^{\parallel} - \frac{1}{\mu_2} \mathbf{B}_2^{\parallel} = \mathbf{K}_f \times \hat{\mathbf{n}}.$$

In particular, if there is no free charge or free current at the interface, then

(i)
$$\epsilon_1 E_1^{\perp} - \epsilon_2 E_2^{\perp} = 0$$
, (iii) $\mathbf{E}_1^{\parallel} - \mathbf{E}_2^{\parallel} = \mathbf{0}$,

(iii)
$$\mathbf{E}_1^{\parallel} - \mathbf{E}_2^{\parallel} = \mathbf{0},$$

(ii)
$$B_1^{\perp} - B_2^{\perp} = 0$$
,

(ii)
$$B_1^{\perp} - B_2^{\perp} = 0$$
, (iv) $\frac{1}{\mu_1} \mathbf{B}_1^{\parallel} - \frac{1}{\mu_2} \mathbf{B}_2^{\parallel} = \mathbf{0}$.

These equations are the basis for the theory of reflection and refraction.