

Dahua Biometric Device – NMS Monitoring Capability

This document explains the monitoring capabilities of Dahua Biometric Attendance / Access Control devices when integrated with a Network Monitoring System (NMS) using SNMP and network-level checks.

Supported Monitoring (NMS Level)

- 1 Device Name, IP Address, Model, Serial Number
- 2 Device Availability (Online / Offline)
- 3 System Uptime
- 4 System Time
- 5 Firmware Version
- 6 Network Connectivity Status
- 7 SNMP Agent Availability (if supported)

Limited Support

- 1 CPU and Memory usage (model dependent)
- 2 Basic network traffic statistics
- 3 Simple reboot detection using uptime

Not Supported via NMS / SNMP

- 1 User attendance logs
- 2 Employee punch-in / punch-out data
- 3 Biometric authentication success/failure details
- 4 Door open/close status
- 5 Access control events and alarms
- 6 Real-time user verification logs

NMS Alerts That Can Be Configured

- 1 Device Offline / Unreachable
- 2 Network Link Down
- 3 System Reboot Detected
- 4 SNMP Data Collection Failure

NMS Dashboards / Reports

- 1 Biometric Device Availability
- 2 Uptime Trend Report
- 3 Network Connectivity Trend

Final Recommendation

The Dahua **DHI-ASI6214J-MFW** biometric device should be monitored in NMS only for device health and network availability. Biometric functions such as face recognition events, attendance data, and access control logs are **not supported via NMS** and must be managed using **Dahua SmartPSS, DSS, or Access Control Management software**.