

AEGIS GCP First Deploy Checklist

Created: 2026-02-20 Updated: 2026-02-22

Status: COMPLETE  — GCP production environment `<GCP_PROJECT_ID>` fully deployed and smoke-tested (2026-02-22). API: `https://api.aegisimaging.ai` | Admin: `https://admin.aegisimaging.ai` (IAP-gated) Cloud smoke suite: **11/11 PASS in 2.56s**

This is the fastest path to stand up the first GCP-backed AEGIS environment using the deployment automation now in-repo.

One-Command Option

After both tfvars files are configured, you can run the full flow with:

```
make gcp-install-poc PROJECT_ID="<gcp-project-id>" REGION="us-central1" TAG="latest"
```

The detailed steps below are the same sequence, broken out for control and troubleshooting.

1) Create GCP project and attach billing

```
export PROJECT_ID="aegis-dev-$(date +%s)"
export REGION="us-central1"

gcloud auth login
gcloud auth application-default login
gcloud projects create "$PROJECT_ID" --name="AEGIS Dev"
gcloud beta billing accounts list
gcloud beta billing projects link "$PROJECT_ID" --billing-account="<BILLING_ACCOUNT_ID>"
gcloud config set project "$PROJECT_ID"
```

2) Run local preflight checks

```
make gcp-preflight
```

3) Configure Terraform variables

```
cp terraform/project/terraform.tfvars.example terraform/project/terraform.tfvars
cp terraform/infra/terraform.tfvars.example terraform/infra/terraform.tfvars
```

Set required values in:

- `terraform/project/terraform.tfvars` : `project_id` , `region` , `billing_account`
- `terraform/infra/terraform.tfvars` : domains, IAP OAuth values, image tags, and environment options

4) Bootstrap project-level services and security baseline

```
./scripts/gcp_bootstrap_project.sh --tfvars=terraform/project/terraform.tfvars --apply
```

5) Bootstrap Artifact Registry first

```
./scripts/gcp_apply_infra.sh --tfvars=terraform/infra/terraform.tfvars --target-artifact-repo
```

6) Build and push images

```
./scripts/gcp_build_push_images.sh --project-id="$PROJECT_ID" --region="$REGION" --tag="latest"
```

Equivalent Make target:

```
make gcp-build-images PROJECT_ID="$PROJECT_ID" REGION="$REGION" TAG=latest
```

7) Apply full infra

```
./scripts/gcp_apply_infra.sh --tfvars=terraform/infra/terraform.tfvars --apply
```

8) Point DNS at load balancer IP

```
terraform -chdir=terraform/infra output load_balancer_ip
```

Create DNS A records for:

- `api_domain`
- `admin_domain`

9) Verify deployment

```
make gcp-verify-deployment PROJECT_ID="$PROJECT_ID" REGION="$REGION"
```

Then:

- open `https://<admin_domain>` in incognito,
- confirm IAP login challenge,
- confirm unauthorized user access is denied.

Useful direct output checks:

```
terraform -chdir=terraform/infra output -raw api_healthz_url
terraform -chdir=terraform/infra output -raw api_auth_me_url
terraform -chdir=terraform/infra output -raw smtp_egress_ip
```

10) Run cloud smoke suite

```
make cloud-smoke-from-terraform \
  PROVIDER=gcp \
  TERRAFORM_DIR=terraform/infra \
  IAP_EMAIL="<you@example.com>"
```

Equivalent script command:

```
./scripts/cloud_smoke_from_terraform.sh \
  --provider=gcp \
  --terraform-dir=terraform/infra \
  --iap-email="<you@example.com>"
```

11) Secret rotation drill (recommended before pilot)

```
export NEW_DB_PASSWORD='<new-strong-password>'
gcloud secrets versions add <db_password_secret_id> --data-file=-
<<<"$NEW_DB_PASSWORD"
gcloud sql users set-password aegis-api --instance=aegis-dev-postgres --
password="$NEW_DB_PASSWORD"
gcloud run services update aegis-api --region="$REGION" --update-env-
vars=ROTATION_EPOCH=$(date +%s)
curl -f https://<api_domain>/healthz
```