Chapter 5 Network Layer: Control Plane

A note on the use of these PowerPoint slides:


We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you see the animations; and can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) that you mention their source (after all, we'd like people to use our book!)
- If you post any slides on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

For a revision history, see the slide note for this page.

Thanks and enjoy! JFK/KWR

All material copyright 1996-2020 J.F Kurose and K.W. Ross, All Rights Reserved



Computer Networking: A Top-Down Approach

8th edition Jim Kurose, Keith Ross Pearson, 2020

Network layer control plane: our goals

- •understand principles behind network control plane:
 - traditional routing algorithms
 - SDN controllers
 - network management, configuration

- instantiation, implementation in the Internet:
 - OSPF, BGP
 - OpenFlow, ODL and ONOS controllers
 - Internet Control Message
 Protocol: ICMP
 - SNMP, YANG/NETCONF

Network layer: "control plane" roadmap

- introduction
- routing protocols
 - link state
 - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol



- network management, configuration
 - SNMP
 - NETCONF/YANG

Network-layer functions

- forwarding: move packets from router's input to appropriate router output
- routing: determine route taken by packets from source to destination

data plane


control plane

Two approaches to structuring network control plane:

- per-router control (traditional)
- logically centralized control (software defined networking)


Per-router control plane

Individual routing algorithm components in each and every router interact in the control plane



Software-Defined Networking (SDN) control plane

Remote controller computes, installs forwarding tables in routers



Network layer: "control plane" roadmap

- introduction
- routing protocols
 - link state
 - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control MessageProtocol




- network management, configuration
 - SNMP
 - NETCONF/YANG


Routing protocols

Routing protocol goal: determine "good" paths (equivalently, routes), from sending hosts to receiving host, through network of routers

- path: sequence of routers packets traverse from given initial source host to final destination host
- "good": least "cost", "fastest", "least congested"
- routing: a "top-10" networking challenge!



Graph abstraction: link costs



 $c_{a,b}$: cost of *direct* link connecting a and b $e.g., c_{w,z} = 5, c_{u,z} = \infty$


cost defined by network operator: could always be 1, or inversely related to bandwidth, or inversely related to congestion

graph: G = (N, E)

N: set of routers = $\{u, v, w, x, y, z\}$

E: set of links = { (u,v), (u,x), (v,x), (v,w), (x,w), (x,y), (w,y), (w,z), (y,z) }

Routing algorithm classification



dynamic: routes change

 periodic updates or in response to link cost changes

decentralized: iterative process of computation, exchange of info with neighbors

- routers initially only know link costs to attached neighbors
- ("distance vector") algorithms

global or decentralized information?

Network layer: "control plane" roadmap

- introduction
- routing protocols
 - link state
 - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control MessageProtocol



- network management, configuration
 - SNMP
 - NETCONF/YANG

Dijkstra's link-state routing algorithm

- centralized: network topology, link costs known to all nodes
 - accomplished via "link state broadcast"
 - all nodes have same info
- computes least cost paths from one node ("source") to all other nodes
 - gives *forwarding table* for that node
- iterative: after k iterations, know least cost path to k destinations

notation


- $c_{x,y}$: direct link cost from node x to y; = ∞ if not direct neighbors
- D(v): current estimate of cost of least-cost-path from source to destination v
- p(v): predecessor node along path from source to v
- N': set of nodes whose leastcost-path definitively known

Dijkstra's link-state routing algorithm

```
1 Initialization:
   N' = \{u\}
                                 /* compute least cost path from u to all other nodes */
   for all nodes v
    if v adjacent to u
                                /* u initially knows direct-path-cost only to direct neighbors
      then D(v) = c_{u,v}
                                                                                        */
                                /* but may not be minimum cost!
    else D(v) = \infty
   Loop
     find w not in N' such that D(w) is a minimum
     add w to N'
     update D(v) for all v adjacent to w and not in N':
        D(v) = \min (D(v), D(w) + c_{w,v})
     /* new least-path-cost to v is either old least-cost-path to v or known
     least-cost-path to w plus direct-cost from w to v */
15 until all nodes in N'
```

Dijkstra's algorithm: an example

		V	W	X	y	(Z)
Step	N'	D(y)p(y)	D(w)p(w)	D(x)p(x)	D(y), p(y)	D(z),p(z)
0	U	/ 2 u	5 u	(1,u)	X	co
1	UX)	24	4,x		(2,x)	ဇဝ
2	uxy /	2,u	3 y			4 <mark>,</mark> y
3	uxvv		3,y			4,y
4	uxyvw					4 ,y
5	UXVVWZ)					




Initialization (step 0): For all a: if a adjacent to then $D(a) = c_{u,a}$


find a not in N' such that D(a) is a minimum add a to N' update D(b) for all b adjacent to a and not in N':

 $D(b) = \min \left(D(b), D(a) + c_{a,b} \right)$

Dijkstra's algorithm: an example




resulting least-cost-path tree from u:




resulting forwarding table in u:

destination	outgoing link	
V	(u,v) —	route from <i>u</i> to <i>v</i> directly
X	(u,x)	
У	(u,x)	route from u to all
W	(u,x)	other destinations
X	(u,x)	via <i>x</i>

Dijkstra's algorithm: another example





notes:

- construct least-cost-path tree by tracing predecessor nodes
- ties can exist (can be broken arbitrarily)

Dijkstra's algorithm: discussion

algorithm complexity: *n* nodes


- each of n iteration: need to check all nodes, w, not in N
- n(n+1)/2 comparisons: $O(n^2)$ complexity
- more efficient implementations possible: O(nlogn)

message complexity:


- each router must broadcast its link state information to other n routers
- efficient (and interesting!) broadcast algorithms: O(n) link crossings to disseminate a broadcast message from one source
- each router's message crosses O(n) links: overall message complexity: $O(n^2)$

Dijkstra's algorithm: oscillations possible


- when link costs depend on traffic volume, route oscillations possible
- sample scenario:
 - routing to destination a, traffic entering at d, c, e with rates 1, e (<1), 1
 - link costs are directional, and volume-dependent




initially



given these costs, find new routing.... resulting in new costs



given these costs, find new routing.... resulting in new costs



given these costs, find new routing.... resulting in new costs

Network layer: "control plane" roadmap


- introduction
- routing protocols
 - link state
 - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control MessageProtocol



- network management, configuration
 - SNMP
 - NETCONF/YANG


Distance vector algorithm

Based on *Bellman-Ford* (BF) equation (dynamic programming):



Bellman-Ford Example

Suppose that u's neighboring nodes, x,v,w, know that for destination z:



Bellman-Ford equation says:

$$D_{u}(z) = \min \{ c_{u,v} + D_{v}(z), c_{u,x} + D_{x}(z), c_{u,w} + D_{w}(z) \}$$

$$= \min \{ 2 + 5, 1 + 3, 5 + 3 \} = 4$$

node achieving minimum (x) is next hop on estimated leastcost path to destination (z)

Distance vector algorithm

key idea:

- from time-to-time, each node sends its own distance vector estimate to neighbors
- when x receives new DV estimate from any neighbor, it updates its own DV using B-F equation:

$$D_x(y) \leftarrow \min_{v} \{c_{x,v} + D_v(y)\}$$
 for each node $y \in N$

• under minor, natural conditions, the estimate $D_x(y)$ converge to the actual least cost $d_x(y)$

Distance vector algorithm:

each node:

wait for (change in local link cost or msg from neighbor)

recompute DV estimates using DV received from neighbor

if DV to any destination has changed, *notify* neighbors

iterative, asynchronous: each local iteration caused by:


- local link cost change
- DV update message from neighbor

distributed, self-stopping: each node notifies neighbors only when its DV changes

- neighbors then notify their neighbors – only if necessary
- no notification received, no actions taken!




- All nodes have distance estimates to nearest neighbors (only)
- All nodes send their local distance vector to their neighbors






- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors






- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors






- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors






- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors






- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors





- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors



.... and so on

Let's next take a look at the iterative computations at nodes

-a-

-d-

t=1

b receives DVs from a, c, e

DV in a:

 $D_a(a) = 0$

 $D_a(b) = 8$ $D_a(c) = \infty$

 $D_{a}(d) = 1$

 $D_a(e) = \infty$

 $D_a(f) = \infty$

 $D_a(g) = \infty$

 $D_a(h) = \infty$

 $D_a(i) = \infty$

DV in b:

 $D_b(a) = 8$ $D_b(f) = \infty$

 $D_b(c) = 1$ $D_b(g) = \infty$ $D_b(d) = \infty$ $D_b(h) = \infty$

 $D_b(e) = 1$ $D_b(i) = \infty$

-b-

e-

C

DV in c:

 $D_c(a) = \infty$

 $D_{c}(b) = 1$

 $D_{c}(c) = 0$

 $D_c(d) = \infty$

 $D_c(e) = \infty$

 $D_c(f) = \infty$

 $D_c(g) = \infty$

 $D_c(h) = \infty$

 $D_c(i) = \infty$

DV in e:

 $D_e(a) = \infty$

 $D_{e}(b) = 1$

 $D_e(c) = \infty$

 $D_{e}(d) = 1$

 $D_e(e) = 0$

 $D_e(f) = 1$

 $D_e(g) = \infty$

 $D_e(h) = 1$

 $D_e(i) = \infty$

t=1

b receives DVs from a, c, e, computes:

DV in a:

$$D_{a}(a)=0$$

$$D_{a}(b) = 8$$

$$D_{a}(c) = \infty$$

$$D_{a}(d) = 1$$


$$D_{a}(e) = \infty$$

$$D_{a}(f) = \infty$$

$$D_{a}(g) = \infty$$


$$D_{a}(h) = \infty$$

$$D_{a}(i) = \infty$$



DV in b:

$$\begin{array}{ll} D_b(a) = 8 & D_b(f) = \infty \\ D_b(c) = 1 & D_b(g) = \infty \\ D_b(d) = \infty & D_b(h) = \infty \\ D_b(e) = 1 & D_b(i) = \infty \end{array}$$



$D_{c}(b) = 1$ $D_{c}(c) = 0$ $D_{c}(d) = \infty$ $D_{c}(e) = \infty$

DV in c:

 $D_c(a) = \infty$

$$D_{c}(f) = \infty$$

$$D_{c}(g) = \infty$$

$$D_{c}(h) = \infty$$

$$D_{c}(i) = \infty$$

DV in e:

$$D_{e}(a) = \infty$$
 $D_{e}(b) = 1$
 $D_{e}(c) = \infty$
 $D_{e}(d) = 1$
 $D_{e}(e) = 0$
 $D_{e}(f) = 1$
 $D_{e}(g) = \infty$
 $D_{e}(h) = 1$
 $D_{e}(i) = \infty$

$$D_{b}(c) = \min\{c_{b,a} + D_{a}(c), c_{b,c} + D_{c}(c), c_{b,e} + D_{e}(c)\} = \min\{\infty, 1, \infty\} = 1$$

$$D_{b}(d) = \min\{c_{b,a} + D_{a}(d), c_{b,c} + D_{c}(d), c_{b,e} + D_{e}(d)\} = \min\{9, 2, \infty\} = 2$$

$$D_{b}(e) = \min\{c_{b,a} + D_{a}(e), c_{b,c} + D_{c}(e), c_{b,e} + D_{e}(e)\} = \min\{\infty, \infty, 1\} = 1$$

 $D_b(a) = \min\{c_{b,a} + D_a(a), c_{b,c} + D_c(a), c_{b,e} + D_e(a)\} = \min\{8, \infty, \infty\} = 8$

$$D_b(f) = \min\{c_{b,a} + D_a(f), c_{b,c} + D_c(f), c_{b,e} + D_e(f)\} = \min\{\infty, \infty, 2\} = 2$$

$$D_b(g) = \min\{c_{b,a} + D_a(g), c_{b,c} + D_c(g), c_{b,e} + D_e(g)\} = \min\{\infty, \infty, \infty\} = \infty$$

$$D_b(h) = \min\{c_{b,a} + D_a(h), c_{b,c} + D_c(h), c_{b,e} + D_e(h)\} = \min\{\infty, \infty, 2\} = 2$$

$$D_b(i) = \min\{c_{b,a} + D_a(i), c_{b,c} + D_c(i), c_{b,e} + D_e(i)\} = \min\{\infty, \infty, \infty\} = \infty$$

DV in b:

$$D_b(a) = 8$$
 $D_b(f) = 2$
 $D_b(c) = 1$ $D_b(g) = \infty$
 $D_b(d) = 2$ $D_b(h) = 2$
 $D_b(e) = 1$ $D_b(i) = \infty$

-a-

t=1

c receives DVs from b

DV in a:

 $D_a(a)=0$

$$D_{a}(b) = 8$$

$$D_a(c) = \infty$$

 $D_a(d) = 1$

$$D_a(e) = \infty$$

$$D_a(f) = \infty$$

$$D_a(g) = \infty$$

$$D_a(h) = \infty$$


$$D_a(i) = \infty$$

DV in b:

$$D_b(a) = 8$$
 $D_b(f) = \infty$
 $D_b(c) = 1$ $D_b(g) = \infty$

$$D_b(c) = 1$$
 $D_b(g) = \infty$
 $D_b(h) = \infty$

$$D_b(e) = 1$$
 $D_b(i) = \infty$



DV in c:

$$D_c(a) = \infty$$

$$D_{c}(b) = 1$$

$$D_c(c) = 0$$

$$D_c(d) = \infty$$

$$D_c(e) = \infty$$

$$D_c(f) = \infty$$

$$D_c(g) = \infty$$

$$D_c(h) = \infty$$

$$D_c(i) = \infty$$

DV in e:

$$D_e(a) = \infty$$

$$D_{e}(b) = 1$$

$$D_e(c) = \infty$$

$$D_{e}(d) = 1$$

$$D_{e}(e) = 0$$

$$D_e(f) = 1$$

$$D_e(g) = \infty$$

$$D_{e}(h) = 1$$

$$D_e(i) = \infty$$

DV in b:

$$D_b(a) = 8$$
 $D_b(f) = \infty$
 $D_b(c) = 1$ $D_b(g) = \infty$
 $D_b(d) = \infty$ $D_b(h) = \infty$
 $D_b(e) = 1$ $D_b(i) = \infty$

compute

DV in c:

 $D_{c}(a) = \infty$ $D_{c}(b) = 1$

 $D_{c}(c) = 0$

 $D_c(d) = \infty$

 $D_c(e) = \infty$

 $D_c(f) = \infty$

 $D_c(g) = \infty$

 $D_c(h) = \infty$

$$D_c(i) = \infty$$



t=1

c receives DVs from b computes:

$$D_c(a) = min\{c_{c,b} + D_b(a)\} = 1 + 8 = 9$$

$$D_c(b) = min\{c_{c,b} + D_b(b)\} = 1 + 0 = 1$$

$$D_{c}(d) = min\{c_{c,b} + D_{b}(d)\} = 1 + \infty = \infty$$

$$D_c(e) = min\{c_{c,b} + D_b(e)\} = 1 + 1 = 2$$

$$D_c(f) = min\{c_{c,b} + D_b(f)\} = 1 + \infty = \infty$$

$$D_c(g) = \min\{c_{c,b} + D_b(g)\} = 1 + \infty = \infty$$

$$D_{c}(h) = min\{c_{bc,b} + D_{b}(h)\} = 1 + \infty = \infty$$

$$D_c(i) = \min\{c_{c,b} + D_b(i)\} = 1 + \infty = \infty$$

DV in c:

$$D_{c}(a) = 9$$

$$D_{c}(b) = 1$$

$$D_c(c) = 0$$

$$D_c(d) = 2$$

$$D_c(e) = \infty$$

$$D_c(f) = \infty$$

$$D_c(g) = \infty$$

$$D_c(h) = \infty$$

$$D_c(i) = \infty$$

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

DV in b:

$$D_b(a) = 8$$
 $D_b(f) = \infty$
 $D_b(c) = 1$ $D_b(g) = \infty$
 $D_b(d) = \infty$ $D_b(h) = \infty$
 $D_b(e) = 1$ $D_b(i) = \infty$

t=1

e receives DVs from b, d, f, h

DV in d:

$$D_{c}(a) = 1$$

$$D_c(b) = \infty$$

$$D^{c}(c) = \infty$$

$$D_c(d) = 0$$


$$D_{c}(e) = 1$$

$$D_c(f) = \infty$$


$$D_{c}(g) = 1$$

$$D_c(h) = \infty$$

$$D_c(i) = \infty$$



Q: what is new DV computed in e at *t*=1?



DV in h:

$$D_c(a) = \infty$$

$$D_c(b) = \infty$$

$$D_c(c) = \infty$$

$$D_c(d) = \infty$$


$$D_{c}(e) = 1$$

$$D_c(f) = \infty$$

$$D_c(g) = 1$$

$$D_{c}(h) = 0$$

$$D_c(i) = 1$$



DV in f:

DV in e:

 $D_e(a) = \infty$

 $D_e(b) = 1$

 $D_e(c) = \infty$

 $D_e(d) = 1$

 $D_e(e) = 0$

 $D_e(f) = 1$

$$D_c(a) = \infty$$

$$D_c(b) = \infty$$

$$D_c(c) = \infty$$

$$D_c(d) = \infty$$

$$D_{c}(e) = 1$$

$$D_c(f) = 0$$

$$D_c(g) = \infty$$


$$D_c(h) = \infty$$

$$D_c(i) = 1$$

Distance vector: state information diffusion

Iterative communication, computation steps diffuses information through network:


- t=0 c's state at t=0 is at c only
- c's state at t=0 has propagated to b, and may influence distance vector computations up to **1** hop away, i.e., at b
- c's state at t=0 may now influence distance vector computations up to 2 hops away, i.e., at b and now at a, e as well
- c's state at t=0 may influence distance vector computations up to 3 hops away, i.e., at b,a,e and now at c,f,h as well
- c's state at t=0 may influence distance vector computations up to 4 hops away, i.e., at b,a,e, c, f, h and now at g,i as well



Distance vector: link cost changes

link cost changes:

- node detects local link cost change
- updates routing info, recalculates local DV
- if DV changes, notify neighbors



"good news travels fast"

 t_0 : y detects link-cost change, updates its DV, informs its neighbors.

 t_1 : z receives update from y, updates its table, computes new least cost to x, sends its neighbors its DV.

 t_2 : y receives z's update, updates its distance table. y's least costs do not change, so y does not send a message to z.

Distance vector: link cost changes

link cost changes:

- node detects local link cost change
- "bad news travels slow" count-to-infinity

- 60 x 50 z
- probles Mirect link to x has new cost 60, but z has said it has a path at cost of 5. So y computes "my new cost to x will be 6, via z); notifies z of new cost of 6 to x.
- z learns that path to x via y has new cost 6, so z computes "my new cost to x will be 7 via y), notifies y of new cost of 7 to x.
- y learns that path to x via z has new cost 7, so y computes "my new cost to x will be 8 via y), notifies z of new cost of 8 to x.
- z learns that path to x via y has new cost 8, so z computes "my new cost to x will be 9 via y), notifies y of new cost of 9 to x.

• • •

see text for solutions. Distributed algorithms are tricky!

Comparison of LS and DV algorithms

message complexity

LS: n routers, $O(n^2)$ messages sent

DV: exchange between neighbors; convergence time varies

speed of convergence

LS: $O(n^2)$ algorithm, $O(n^2)$ messages

may have oscillations

DV: convergence time varies

- may have routing loops
- count-to-infinity problem

robustness: what happens if router malfunctions, or is compromised?

LS:

- router can advertise incorrect link cost
- each router computes only its own table

DV:

- DV router can advertise incorrect path cost ("I have a really low cost path to everywhere"): black-holing
- each router's table used by others: error propagate thru network

Network layer: "control plane" roadmap

- introduction
- routing protocols
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol




- network management, configuration
 - SNMP
 - NETCONF/YANG

ICMP: internet control message protocol

- used by hosts and routers to communicate network-level information
 - error reporting: unreachable host, network, port, protocol
 - echo request/reply (used by ping)
- network-layer "above" IP:
 - ICMP messages carried in IP datagrams
- ICMP message: type, code plus first 8 bytes of IP datagram causing error


<u>Code</u>	<u>description</u>
0	echo reply (ping)
0	dest. network unreachable
1	dest host unreachable
2	dest protocol unreachable
3	dest port unreachable
6	dest network unknown
7	dest host unknown
0	source quench (congestion
	control - not used)
0	echo request (ping)
0	route advertisement
0	router discovery
0	TTL expired
0	bad IP header
	0 0 1 2 3 6 7 0

More on ICMP ...



IP, as an unreliable protocol, is not concerned with error checking and error control. ICMP was designed, in part, to compensate for this shortcoming. ICMP does not correct errors, it simply reports them.

Traceroute and ICMP



- source sends sets of UDP segments to destination
 - 1st set has TTL = 1, 2nd set has TTL = 2, etc.
- datagram in *n*th set arrives to nth router:
 - router discards datagram and sends source ICMP message (type 11, code 0)
 - ICMP message possibly includes name of router & IP address
- when ICMP message arrives at source: record RTTs

stopping criteria:

- UDP segment eventually arrives at destination host
- destination returns ICMP "port unreachable" message (type 3, code 3)
- source stops

Network layer, control plane: Done!

- introduction
- routing protocols
 - link state
 - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol



- network management, configuration
 - SNMP
 - NETCONF/YANG