

PH2255 Course:

Introduction to Statistical Methods

Exercise 1

Thomas Bass

15 January 2021

Abstract

Exercise One in the PH2255 course begins with an introduction to using the least-squares method provided in SciPy's `curve_fit` method, and using the error propagation formula described below to generate the standard deviation of the generated parameters. Plots are generated to show how well a least-squares method fits the data, using first, second, and third order polynomials.

First, we must ingest the data provided in the lab script into Python. We use Numpy's `np.array` as this will allow us to manipulate the data later.

```
x = np.array([1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0, 9.0])
y = np.array([2.7, 3.9, 5.5, 5.8, 6.5, 6.3, 7.7, 8.5, 8.7])
sig = np.array([0.3, 0.5, 0.7, 0.6, 0.4, 0.3, 0.7, 0.8, 0.5])
```

Now that the data is ingested, we can use SciPy's `curve_fit` method to generate the optimal values for the parameters, so that the sum of the squared residuals is minimized.

First, we define a general polynomial function at a given value of x and list of coefficients θ , using this general form of the polynomial function:

$$f(x) = \theta_0 + \theta_1 x + \theta_2 x^2 + \dots \quad (1)$$

In python...

```
def polynomial(x, *theta):
    return sum([theta[i]*x**i for i in range(len(theta))])
```

This is a very efficient "one-liner" in python, using list comprehension to iterate over i for a range defined by the length of θ . The use of `*theta` allows the parameter vector $\theta = (\theta_0, \theta_1)$ to have arbitrary length, useful for coding higher order polynomials.

Next, we use the `curve_fit` to generate our parameters and covariance matrices for each of the first, second, and third order polynomials:

```
p0_first = np.array([1.0, 1.0])
theta_hat_first, covariance_first = curve_fit(polynomial, x, y,
p0_first, sig, absolute_sigma=True)
```

The same code was repeated, with renamed variables and corresponding p0 arrays for the second and third order polynomials.

Now that we have the parameters, we can plot our fitted line using the corresponding parameters as polynomial coefficients. To do this in Matplotlib, we define a function `fit`, similar to `polynomial` but without the asterisk unpacking the array:

```
def fit(x, theta):
    return sum([theta[i]*x**i for i in range(len(theta)) ])
```

The exercise asks us to plot the standard deviation of the fitted function as well as the fit its self, so we use Equation 26 from the script (slightly modified for this specific use):

$$\sigma_f^2 \approx \sum_{i,j=0}^m \frac{\partial f}{\partial \theta_i} \frac{\partial f}{\partial \theta_j} U_{ij} \quad (2)$$

Where $U_{ij} = \text{cov}[i,j]$. In our example, f is the polynomial function, so the derivatives rapidly simplify with use of the Kronecker Delta function:

$$\frac{\partial f(x, \vec{\theta})}{\partial \theta_i} = \frac{\partial}{\partial \theta_i} \sum_{k=0}^N \theta_k x^k = \sum_{k=0}^N \delta_{ik} x^k = x^i \quad (3)$$

This allows us to write the entire standard deviation formula very compactly:

$$\sigma_f^2 = \sum_{i,j=0}^N x^{i+j} \text{cov}[i,j] \quad (4)$$

In python...

```
def std_dev(x, cov):
    return sum([(x**(i+j))*cov[i][j] for i in range(len(cov)) for j
in range(len(cov))])
```

This again uses compact list comprehension to iterate over i and j , as defined by the length of the covariance matrix `cov`. *N.B.:* we take the square root of this function's results later, to reflect std. dev. = $\sqrt{\sigma^2}$.

We now use these two functions to plot our data in Matplotlib (figure setup is omitted here):

```
ax.errorbar(x, y, yerr=sig, fmt='kx', label="test data")
ax.plot(x_val, fit(x_val, theta_hat_first), 'r', label="first order
fit")
ax.fill_between(x_val, fit(x_val, theta_hat_first)-np.sqrt(std_dev(
x_val, covariance_first)), fit(x_val, theta_hat_first)+np.sqrt(
std_dev(x_val, covariance_first)), label="one standard
deviation")
```

This, generates the following plots for the first order fit, and modified and repeated code for the second and third order fits:




Figure 1: First-order polynomial fit, showing fit curve and one standard deviation above and below




Figure 2: Second-order polynomial fit, showing fit curve and one standard deviation above and below




Figure 3: Third-order polynomial fit, showing fit curve and one standard deviation above and below

We can also generate chi-squared values for each of these fits, using the following code:

```
sum(((y - polynomial(x, *theta_hat))/sig)**2)
```

The chi-squared values and degrees of freedom for each fit are tabulated below:

Polynomial Order	Chi-Squared	Degrees of Freedom
1	8.2515361178354	7
2	6.842115296038535	6
3	3.747761582200386	5

A Python Code

The complete code used in this exercise is presented below, as well as the text outputs of the script:

```
import numpy as np
from scipy.optimize import curve_fit
import matplotlib
4 import matplotlib.pyplot as plt

## Input data arrays
x = np.array([1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0, 9.0])
y = np.array([2.7, 3.9, 5.5, 5.8, 6.5, 6.3, 7.7, 8.5, 8.7])
9 sig = np.array([0.3, 0.5, 0.7, 0.6, 0.4, 0.3, 0.7, 0.8, 0.5])

## Polynomial function
def polynomial(x, *theta): return sum([theta[i]*x**i for i in range
    (len(theta))])
```

```

14  ## First order
    p0_first = np.array([1.0, 1.0])
    theta_hat_first, covariance_first = curve_fit(polynomial, x, y,
        p0_first, sig, absolute_sigma=True)

    ## Second order
19  p0_second = np.array([1.0, 1.0, 1.0])
    theta_hat_second, covariance_second = curve_fit(polynomial, x, y,
        p0_second, sig, absolute_sigma=True)

    ## Third order
    p0_third = np.array([1.0, 1.0, 1.0, 1.0])
24  theta_hat_third, covariance_third = curve_fit(polynomial, x, y,
        p0_third, sig, absolute_sigma=True)

    ## Fitting
    def fit(x, theta): return sum([theta[i]*x**i for i in range(len(
        theta)) ])

29  ## Standard Deviation
    def std_dev(x, cov): return sum([(x**(i+j))*cov[i][j] for i in
        range(len(cov)) for j in range(len(cov))])

    ## Create plots
    fig1 = plt.figure()
    fig2 = plt.figure()
34  fig3 = plt.figure()
    ax1 = fig1.add_subplot()
    ax1.set_title('first order polynomial fit')
    ax2 = fig2.add_subplot()
39  ax2.set_title('second order polynomial fit')
    ax3 = fig3.add_subplot()
    ax3.set_title('third order polynomial fit')
    ax1.set_ylabel("y")
    ax2.set_ylabel("y")
44  ax3.set_ylabel("y")
    ax1.set_xlabel("x")
    ax2.set_xlabel("x")
    ax3.set_xlabel("x")

49  x_val = np.arange(0, 20, 0.1)

    ## Plot given data with sigma error bars
    ax1.errorbar(x, y, yerr=sig, fmt='kx', label="test data")
    ax2.errorbar(x, y, yerr=sig, fmt='kx', label="test data")
54  ax3.errorbar(x, y, yerr=sig, fmt='kx', label="test data")

    ## Plot the three fits
    ax1.plot(x_val, fit(x_val, theta_hat_first), 'r', label="first
        order fit")
    ax1.fill_between(x_val, fit(x_val, theta_hat_first)-np.sqrt(std_dev
        (x_val, covariance_first)), fit(x_val, theta_hat_first)+np.sqrt
        (std_dev(x_val, covariance_first)), label="one standard
        deviation")
59  ax1.legend()

    ax2.plot(x_val, fit(x_val, theta_hat_second), 'c', label="second
        order fit")
    ax2.fill_between(x_val, fit(x_val, theta_hat_second)-np.sqrt(
        std_dev(x_val, covariance_second)), fit(x_val, theta_hat_second
        )+np.sqrt(std_dev(x_val, covariance_second)), label="one
        standard deviation")

```

```

ax2.legend()
64 ax3.plot(x_val, fit(x_val, theta_hat_third), 'y', label="third
    order fit")
ax3.fill_between(x_val, fit(x_val, theta_hat_third)-np.sqrt(std_dev
    (x_val, covariance_third)), fit(x_val, theta_hat_third)+np.sqrt
    (std_dev(x_val, covariance_third)), label="one standard
    deviation")
ax3.legend()
69 ## Chi-squared and degrees of freedom
print (f"chisq first order = {sum(((y - polynomial(x, *
    theta_hat_first))/sig)**2)},\tndof = {len(x) - len(p0_first)}")
print (f"chisq second order = {sum(((y - polynomial(x, *
    theta_hat_second))/sig)**2)},\tndof = {len(x) - len(p0_second)}
    ")
print (f"chisq third order = {sum(((y - polynomial(x, *
    theta_hat_third))/sig)**2)},\tndof = {len(x) - len(p0_third)}")

```

py.py

```

chisq first order = 8.25153611783541, ndof = 7
chisq second order = 6.842115296038535, ndof = 6
3 chisq third order = 3.747761582200386, ndof = 5

```