

psychtools — LaTeX Macros for Psychology
Manuscripts
Version 1.0

Ansgar Endress
ansgar.endress@gmx.net

2026/06/26

Contents

1	Introduction	1
2	Package Options	2
3	Statistical Notation	2
4	Supplementary Materials Appendix	3
4.1	<code>\myappendix</code>	3
4.2	<code>\appsection{<title>}</code>	3
4.3	Appendix TOC	4
5	Draft Editing Aids	4
6	Citation Helpers (apacite)	4
7	Miscellaneous	5
7.1	<code>\includesubgraphics{<label>}{<filename>}</code>	5
7.2	<code>\protectedemail{<address>}</code>	5
8	Backward Compatibility	5
9	License	5

1 Introduction

psychtools provides a collection of convenience macros for writing empirical psychology and cognitive science manuscripts in LaTeX. It addresses four

common needs:

- Compact, italicised notation for standard test statistics and effect sizes (§3).
- Supplementary-materials appendices with S-prefixed numbering and an optional TOC (§4).
- Draft editing aids: conditional footnotes and section headers that can be toggled off for the final submission (§5).
- Citation shortcuts for `apacite` users (§6).

Load the package in the usual way:

```
\usepackage{psychtools}
% or with options:
\usepackage[excludedetails,appendixtoc]{psychtools}
```

`psychtools` requires `tocloft`, `xcolor`, `subcaption`, `xspace`, and `tikz`, all of which are part of standard TeX Live and MiKTeX distributions.

2 Package Options

Option	Default	Effect
<code>includedetails</code>	on	Show draft footnotes and section headers
<code>excludedetails</code>	—	Hide all draft content (use for submission)
<code>appendixtoc</code>	off	Add a TOC for the supplementary materials
<code>nocolorize</code>	—	Suppress red colouring of draft content
<code>nocitecommands</code>	—	Disable the <code>apacite</code> citation helpers

3 Statistical Notation

The commands in Table 1 typeset common test statistics and effect sizes in italic math style, matching APA formatting requirements. Each command includes a trailing `\xspace` so it can be used freely in running text without extra braces.

Example

The effect was significant, $T(38) = 2.45$, $p = .019$, $D = 0.77$.

Produces: The effect was significant, $t(38) = 2.45$, $p = .019$, Cohen's $d = 0.77$.

Command	Output	Meaning
<code>\T</code>	t	Student's t
<code>\F</code>	F	F ratio
<code>\Z</code>	Z	Z score
<code>\p</code>	p	p value
<code>\M</code>	M	Mean
<code>\SD</code>	SD	Standard deviation
<code>\SE</code>	SE	Standard error
<code>\D</code>	Cohen's d	Cohen's d
<code>\CI</code>	$CI_{.95}$	95% confidence interval
<code>\et</code>	η^2	Eta-squared
<code>\etp</code>	η_p^2	Partial eta-squared
<code>\U</code>	U	Mann–Whitney U
<code>\W</code>	W	Wilcoxon W

Table 1: Statistical notation commands.

Compatibility warning The short command names (`\T`, `\F`, `\Z`, `\p`, `\M`, `\U`, `\W`) may conflict with commands defined by math or font packages. To minimise the risk:

- Load `psychtools` *before* any math-heavy packages.
- If you encounter redefinition errors, check whether another loaded package defines the conflicting name and either remove that package or replace it with one that does not.

4 Supplementary Materials Appendix

Many psychology journals require supplementary materials numbered **S1**, **S2**, ... with figures and tables prefixed **S1**, **S2**, ... as well. The commands below set up this numbering automatically.

4.1 `\myappendix`

Place `\myappendix` at the point in your document where the supplementary materials begin. It:

- resets the page counter to **S1**;
- resets section, figure, and table counters with the **S** prefix;
- prints the appendix title (from `\appendixname`);
- optionally inserts a TOC for the supplementary materials (if the `appendixtoc` option is active).

You should set `\appendixname` in your document before calling `\myappendix`:

```
\renewcommand{\appendixname}{Supplementary Online Materials}
\myappendix
```

If `\appendixname` is not set, the prefix defaults to S. The following values of `\appendixname` produce a two-letter prefix:

<code>\appendixname</code>	Prefix
Supplementary Information	SI
Supplementary Materials	SM
Supplementary Online Materials	SM
anything else	S

4.2 `\appsection{<title>}`

Use `\appsection` for sections inside the supplementary materials. From the second section onwards it inserts a `\clearpage` before the new section, keeping the layout clean.

```
\myappendix
\appsection{Stimuli}
...
\appsection{Additional Analyses}
...
```

4.3 Appendix TOC

With the `appendixtoc` option, `psychtools` suppresses the main document TOC from showing supplementary-materials entries (by setting `tocdepth` to `-2` globally) and then restores it inside `\myappendix`, where a separate local TOC is printed.

5 Draft Editing Aids

These commands are visible when the `includedetails` option is active (the default) and invisible when `excludedetails` is used. Draft content is coloured red (unless `nocolorize` is passed).

Command	Effect
<code>\footnotewithdetails{⟨text⟩}</code>	Inserts a red footnote marked “(Footnote will be removed)”.
<code>\draftsection{⟨title⟩}</code>	Inserts a red section header marked “(Header will be removed)”.
<code>\draftsubsection{⟨title⟩}</code>	Same for subsections.
<code>\draftsubsubsection{⟨title⟩}</code>	Same for subsubsections.
<code>\colorize{⟨text⟩}</code>	Colours ⟨text⟩ red; passes through unchanged with <code>nocolorize</code> .

6 Citation Helpers (apacite)

These commands are active when `apacite` is loaded and the `nocitecommands` option is not given.

Command	Output
<code>\citeeg{⟨key⟩}</code>	(e.g., Author Year)
<code>\cites{⟨key⟩}</code>	Author’s Year

If `apacite` is not loaded, basic fallbacks using `\cite` and `\citeauthor/\citeyear` are provided with a package warning.

7 Miscellaneous

7.1 `\includesubgraphics{⟨label⟩}{⟨filename⟩}`

Inserts a subfigure (via `subcaption`) at 90% text width with a bold, large label but without a sub-caption. Useful when you want panel labels (**A**, **B**, ...) without separate captions.

7.2 `\protectedemail{⟨address⟩}`

Renders an email address in `typewriter` font inside a TikZ node. This prevents some simple web scrapers from harvesting the address as plain text.

8 Backward Compatibility

An `ansgar.sty` shim is distributed alongside `psychtools`. It contains a single line:

```
\RequirePackage{psychtools}
```

Documents that used `\usepackage{ansgar}` continue to work without modification.

9 License

psychtools is distributed under the [LaTeX Project Public License](#), version 1.3c or later.