

Comment	Description	Designator	Footprint	LibRef	Quantity
100nF		C1, C3, C4, C6	CAP200	CAP	4
10uF		C2	CAP100RP	CAPPOL	1
		D1, D2, D3, D4	LED3	LED	4
	7-Seg Display, Comm Anode, Super Red Rohs Compliant: Yes	DS1, DS2, DS3, DS4	WL-T7DS_L17.5W12.4H7	CMP-03913-119893999-3	4
PEC12R-3217F-S0024	ROTARY ENCODER	ENC1	FP-PEC12R-3217F-S0024-MFG	CMP-07421-000063-1	1
BORNERA 2		J1	BORNERA2	BORNERA 2	1
CON3		J2	SIP3	CON3	1
JUMPER		J3	JUMPER2	JUMPER	1
Header 5X2	Header, 5-Pin, Dual row	P1	HDR2X5	Header 5X2	1
Header 5	Header, 5-Pin	P3	HDR1X5	Header 5	1
BC337	Amplifier Transistor, NPN Silicon, 3-Pin TO-92, Pb-Free, Ammo Box	Q1, Q2, Q5, Q6, Q8, Q9, Q11, Q12	ONSC-TO-92-3-29-11_AM_BL	CMP-1048-01583-1	8
BC327	Amplifier Transistor, PNP Silicon, 3-Pin TO-92, Pb-Free, Ammo Box	Q3, Q4, Q7, Q10	ONSC-TO-92-3-29-11_AM_BL	CMP-1048-01577-1	4
4.7K		R1, R2, R3, R11, R13, R14, R15, R16, R17, R18, R19, R20, R36	RES400	RES	13
68		R4, R5, R6, R7, R8, R9, R10, R12	RES400	RES	8
10k		R21, R28, R33, R34, R35	RES400	RES	5
1.8K		R22, R25, R29	RES400	RES	3
3.3K		R23, R26, R30	RES400	RES	3
330		R24, R27, R31	RES400	RES	3
1k		R32	RES400	RES	1
470		R37	RES400	RES	1
	SWITCH TACTILE SPST NO 0.05A 24V	SW1	FP-B3F-1055-MFG	CMP-08834-000061-1	1
MK64FN1M0VLL12	Cortex-M4-based Microcontroller with FPU, 1 MB, 120 MHz, 1.71 to 3.6 V, -40 to 105 degC, 100-Pin QFP (983-02), RoHS, Tray	U1	K64F_DevBoard_Headers_MIRROR	CMP-0182-00049-1	1
SN74HC139N	Dual 2-Line To 4-Line Decoders/ Demultiplexers,	U2	N0016A	CMP-1633-00660-2	1
74HC595		U3, U5	DIP16	74HC595	2
LD1117V33	Fixed Low Drop Positive Voltage Regulator, 3.3V, 3-Pin TO-220	U4	TO220	CMP-0244-00470-1	1
CD74HCT245E	High Speed CMOS Logic Non-Inverting Octal-Bus Transceiver with 3-State Outpus, N0020A, TUBE	U6	N0020A	CMP-1620-00444-2	1