

Comment	Description	Designator	Footprint	Quantity
100nF		C1, C3, C4, C5, C6, C7	CAP200	6
10uF		C2	CAP100RP	1
		D1, D2, D3, D4	LED3	4
	7-Seg Display, Comm Anode, Super Red Rohs Compliant: Yes	DS1, DS2, DS3, DS4	WL-T7DS_L17.5W12.4H7	4
PEC12R-3217F-S0024	ROTARY ENCODER	ENC1	FP-PEC12R-3217F-S0024-MFG	1
POWER		J1	BORNERA2	1
3V3 REF		J2	JUMPER2	1
MATRIZ		J3	SIP3	1
CARD	Header, 5-Pin	P1	HDR1X5	1
JTAG PROG	Header, 5-Pin, Dual row	P2	HDR2X5	1
BC337	Amplifier Transistor, NPN Silicon, 3-Pin TO-92, Pb-Free, Ammo Box	Q1, Q2, Q5, Q6, Q8, Q9, Q11, Q12	ONSC-TO-92-3-29-11_AM_BL	8
BC327	Amplifier Transistor, PNP Silicon, 3-Pin TO-92, Pb-Free, Ammo Box	Q3, Q4, Q7, Q10	ONSC-TO-92-3-29-11_AM_BL	4
4.7K		R1, R2, R3, R10, R13, R14, R15, R16, R17, R18, R19, R20, R32	RES400	13
68		R4, R5, R6, R7, R8, R9, R11, R12	RES400	8
330		R21, R35, R36, R37	RES400	4
10K		R22, R29, R30, R31, R34	RES400	5
1.8K		R23, R25, R27	RES400	3
3.3K		R24, R26, R28	RES400	3
470		R33	RES400	1
	SWITCH TACTILE SPST NO 0.05A 24V	SW1	FP-B3F-1055-MFG	1
SN74HC139N	Dual 2-Line To 4-Line Decoders/ Demultiplexers,	U1	N0016A	1
LD1117V33	Fixed Low Drop Positive Voltage Regulator, 3.3V, 3-Pin TO-220	U2	TO220	1
74HC595		U3, U5	DIP16	2
MK64FN1M0VLL12	Cortex-M4-based Microcontroller with FPU, 1 MB, 120 MHz, 1.71 to 3.6 V, -40 to 105 degC, 100-Pin QFP (983-02), RoHS, Tray	U4	K64F_DevBoard_Headers_MIRROR	1
CD74HCT245E	High Speed CMOS Logic Non-Inverting Octal-Bus Transceiver with 3-State Outpus, N0020A, TUBE	U6	N0020A	1