Small LLM Cartels Don't Rediscover the Attack Only Canaries Catch: Language-Model Collusion against a Useful-Work Turnstile[1]

RNG Goulden
Independent

With
Apart Research

Abstract

Systems that check AI agents' work are usually tuned against cheaters that follow fixed strategies. We test that assumption on a useful-work turnstile, which sends each small task to three workers, sends disagreements to a panel of peer verifiers, and uses canaries (tasks with known answers) and planted faults to catch cheating. A seeded simulation of the turnstile, built before this work, showed one remaining weakness: a cartel that lies only when it holds every copy of a task, which only canaries catch. We replaced the scripted cartel with LLM agents. Each member sees only what a real worker sees and decides for itself whether to lie, with and without a private channel to the others. Across 3 seeds with llama3.1:8b and 1 seed with qwen2.5:14b, the LLM cartels lied on every one of their decisions, whether they held one, two or three copies of a task. They never found the unanimous strategy. They got 0.1% of wrong answers accepted (0.0% for qwen2.5:14b), against 0.8% for the scripted cartel at the same size, and every member was revoked, against 1.9% of the scripted cartel. The private channel changed the models' stated reasons but not one decision. Raising canaries to 30% changed nothing against the LLM cartel. Small open models therefore make a weaker attacker than the scripted worst case. Stronger models remain untested.

1. Introduction

On a hospital ward, some jobs always need doing: fetching milk, food and tea. Each is small, nobody refuses it, and nobody looks at it closely. One day a bottle of milk smelt off. The person who noticed asked someone else to smell it, who said it smelt normal. A third person said they couldn't smell anything, and looked as if they didn't want to give a false answer. By majority vote

[1]Research conducted at the Swarm Alignment Hackathon, November 2026. Track 3: Strengthening Agent Infrastructure.

the milk would be served: one "off" is outvoted. A rule that treats any single flag as enough to check the milk properly would catch it, at the cost of sometimes throwing good milk away. And the person who couldn't tell looks exactly like someone keeping quiet to avoid trouble.

The turnstile we study works on the second rule. It hands out small tasks with checkable answers to three workers, and if their answers disagree, any one verifier's flag is enough to have the task recomputed. Its blind spot is the case where nobody disagrees: if all three people on the shift say the milk is fine, no rule based on disagreement will ever check it. Only a *canary*, a bottle already known to be off and slipped in unannounced, catches that.

In an agent swarm, the workers and verifiers are agents, often copies of the same model, and they may coordinate. Our question is whether colluding LLM agents, given only what a real worker sees, work out the one attack the turnstile's simulation says is hardest to stop: lying only when they hold all three copies of a task. If they do, the weak spot is real. If they don't, the defence is stronger in practice than the scripted worst case suggests.

Our main contributions are:

1. A decision hook in an existing, seeded simulation of the turnstile that lets an LLM play each cartel member separately, seeing only what that worker could see, while leaving the scripted results exactly unchanged.
2. A comparison of LLM cartels (llama3.1:8b, qwen2.5:14b) with scripted and greedy cartels under the same defences, with and without a private channel and with canaries removed. The LLM cartels lie every time and are entirely caught: they never find the unanimous strategy.
3. A test of one fix, doubling the canary share to 30%, against both the LLM and the scripted cartel, with its cost in honest workers revoked.

2. Related Work

Secret collusion between AI agents, including covert coordination that evades oversight, has been studied as a distinct risk of multi-agent systems (Motwani et al., 2024), and collusion is one of the main failure modes in recent surveys of multi-agent risk (Hammond et al., 2025). That work asks whether agents *can* coordinate covertly. We ask a narrower, practical question: given a concrete verification mechanism and its published rules, do LLM agents find its weakest point when told to cheat it?

The mechanism itself, and its scripted attackers, predate this work. The turnstile's design document reports the simulation's results against scripted cartels, including the unanimous cartel, the effect of each defence, and the cost of false revocation (`docs/turnstile-collusion.md`). Those results describe the worst case its designers thought of. Our contribution is to replace the scripted attacker with adaptive ones, and to report how far the designed-for worst case is from what an LLM attacker actually does.




Figure 1. One epoch of the turnstile. Only the cartel's decision (blue) changed this weekend: an LLM now makes it for each member separately. A cartel that lies only when it holds all three copies lands in the middle path, which nothing checks; only canaries can catch it. Two strikes revoke a worker.

3. Methods

Pre-existing before the hackathon: the turnstile collusion simulation (`src/lib/turnstile/collusion-sim.ts`, its tests, `scripts/turnstile-collusion.ts`, `docs/turnstile-collusion.md`) and the approval flow (`src/lib/approvals.ts`, `src/lib/egress.ts`, `src/lib/job-queue.ts`, `src/lib/agent-license.ts`). **Written during the hackathon:** everything in `experiment/swarm-2026/`, and the `simulateSteps` / `simulateWith` hook in `collusion-sim.ts`, which leaves `simulate`'s results unchanged.

3.1 The turnstile

The turnstile isn't live yet; the simulation is how its design is tested before it ships. Figure 1 shows one epoch. Items, plus canaries making up 15% of the total, are each assigned to 3 workers drawn at random by a seeded generator. With commit-reveal assignment the draw is fixed in advance, so a cartel can't steer its members onto the same items. Canaries look like any other item, and a wrong answer to one is an immediate strike. Items whose answers all agree are accepted unchecked. Disagreements go into batches of 64 with 2 planted fake disputes, checked by a panel of 3 verifiers. If any verifier flags an item, it is recomputed and every wrong answer is a strike; a verifier who misses a planted fake is struck too. Two strikes revoke a worker or verifier. Honest workers get 0.2% of answers wrong, which already gets some of them wrongly revoked.

3.2 The LLM cartel

In the scripted simulation, one line decides for the whole cartel: under the unanimous strategy, it lies only when its members hold all 3 copies of an item. We turned this line into a step the simulation hands out, so that something other than the script can make it; with the scripted step, results are exactly as before (a test checks this, and section 4 shows it). The LLM step asks each cartel member's model, separately, whether to give the true answer or the cartel's agreed wrong one, with a one-sentence reason. The prompt gives the published rules, including that agreeing answers are accepted unchecked, the member's own strike count, and how many of the item's three workers are cartel members. In the channel condition, members also see the last 8 notes on a shared board and may leave one. Because members decide alone, a cartel can fail to coordinate, which the script can't. We also added a *greedy* cartel that always lies, as a strategy-free baseline.

Table 1. Cartels at the small size (60 workers, 10 epochs, 20% cartel, 15% canaries). Scripted and greedy: 30 seeds; llama3.1:8b: 3 seeds; qwen2.5:14b: 1 seed. Lie rate is when holding 1 / 2 / 3 of an item's 3 copies; "–" means the case never arose.

Cartel	Condition	Wrong accepted	Cartel revoked	Honest revoked	Lie rate when holding 1 / 2 / 3
Scripted (unanimous)	all on	0.8%	1.9%	0.1%	0 / 0 / 100%
	no canaries	0.8%	0.0%	0.1%	0 / 0 / 100%
Greedy	all on	0.1%	100.0%	0.1%	100 / 100 / 100%
	no canaries	0.1%	100.0%	0.1%	100 / 100 / 100%
LLM, llama3.1:8b	all on	0.1%	100.0%	0.0%	100 / 100 / 100%
	all on + channel	0.1%	100.0%	0.0%	100 / 100 / 100%
	no canaries	0.1%	100.0%	0.7%	100 / 100 / 100%
	no canaries + channel	0.1%	100.0%	0.7%	100 / 100 / 100%
LLM, qwen2.5:14b	all on	0.0%	100.0%	0.0%	100 / 100 / –
	all on + channel	0.0%	100.0%	0.0%	100 / 100 / –

3.3 Setup and measures

The models were llama3.1:8b (8.0B parameters, Q4_K_M) and qwen2.5:14b, served locally by Ollama 0.40.15 on one NVIDIA H100 80GB, at temperature 0; no paid API was used. The full size is the simulation's default, used to reproduce the published results over 30 seeds. LLM runs use a small size, 60 workers over 10 epochs, with 20% of workers in the cartel and 15% canaries; the scripted and greedy cartels were run at the same size over 30 seeds for a fair comparison. The llama3.1:8b cartel ran over 3 seeds with all defences on and with canaries off, each with and without the channel, and again with 30% canaries; qwen2.5:14b ran 1 seed with all defences on.

We report the share of accepted answers that were wrong (the cartel's damage), the share of the cartel and of honest workers revoked by the end, and the *lie rate when holding 1, 2 or 3 of 3*: how often members chose to lie, by how many of the item's three workers were cartel members. High only at 3 of 3 is the unanimous strategy; high at 1 of 3 is lying even when alone. Figures are means over seeds. Every step was run by one script, `run-all.sh`; each step's exact command is in the run's `steps.md`.

4. Results

The hook changed nothing. At full size with every defence on, the scripted cartel got 0.7% of wrong answers accepted, with 15.2% of the cartel and 2.0% of honest workers revoked; without commit-reveal assignment, 3.2%. These match the published results (0.7% rising to 3.2%, and 2 to 3% of honest workers falsely revoked).

The LLM cartel played greedy. All 482 of the llama3.1:8b cartel's decisions were lies, including all 50 on canary items (table 1, figure 2). It got 0.1% of wrong answers accepted, against 0.8% for the scripted unanimous cartel, and every member was revoked, against 1.9%. Its results are the greedy




Figure 2. The LLM cartels played greedy, not unanimous (all defences on, small size). (a) They got far fewer wrong answers accepted than the scripted cartel, and (b) every member was revoked. (c) They lied whatever share of the item they held; the scripted cartel lies only when holding all three copies. qwen2.5:14b never held all three.

baseline's.

It understood unanimity when it saw it, but didn't plan for it. Holding all three copies, a member reasoned "All three of us will agree, so the item will be accepted without further checks." But members held all three only 3 times per condition, against 103 times holding one, and lied in every case. A typical reason when alone: "I don't know the other two workers' answers, so I'll play it safe and give the cartel's wrong answer to increase the chances of it being accepted." The model treated lying as the safe choice.

The private channel changed words, not actions. Every "+ channel" row equals its row without the channel, and the decision counts are identical. Reasons with the channel spoke for the group ("We need to keep our answers consistent to avoid raising suspicions."). The notes members left, recorded with each reply in the model-answer cache, were encouragement and mutual watching: the most common were "Sticking to the plan", "Keep an eye on worker 1's answer, see if they're playing along" and "Let's keep our answers consistent, guys." Among the most common notes, none proposed holding back when alone.

Removing canaries didn't help this cartel. It was still entirely revoked, with 0.1% wrong accepted: lying alone creates disagreements, and the dispute panels catch those. Honest workers revoked went from 0.0% to 0.7%; with 3 seeds we don't read this as an effect.

The fix had nothing to fix. With 30% canaries, the LLM cartel's results were unchanged: 0.1% wrong accepted, 100.0% revoked, 0.0% honest revoked. Against the scripted cartel at the same size, 30% canaries raised the cartel revoked from 1.9% to 5.3% but left wrong answers accepted at 0.8%, with 0.0% of honest workers revoked. In 10 epochs, more canaries catch a few more members but not the damage they have already done.

The larger model played the same way. qwen2.5:14b lied whenever it held one or two copies, never held all three, got 0.0% of wrong answers accepted and was entirely revoked, with and without the channel. Its reasons were similar: "Colluding with the cartel to increase our chances of acceptance while maintaining low risk since it's early in the run and we have no strikes yet." Every model reply in every LLM step was usable (0 unusable of 324 + 158, 33 + 101 and 69 + 27 new + cached calls).

5. Discussion and Limitations

The turnstile was tuned against a scripted cartel that plays the worst case its designers knew: lie only when unanimous. Given the same information as a real worker, two small open models did not find that strategy. They lied every time, which the turnstile's disagreement checks handle easily, did less damage than the script, and lost every member. For this design, against attackers of this strength, the scripted results are a pessimistic bound, not the expected case.

This is not for lack of information: the prompt states that agreeing answers are accepted unchecked and tells each member how many of the item's workers are in the cartel. The reasons suggest why. The models framed lying as the cooperative, low-risk move, not as something whose risk depends on who else holds the item. The unanimous strategy requires seeing that a lone lie *creates* the disagreement that gets it caught. The models recognised the good case when it arrived but never inferred the corollary, to keep quiet in the bad ones.

Limitations. These are small local models at temperature 0, deciding one item at a time, with no memory across epochs beyond their strike count and, with the channel, the last few notes. A frontier model, a model allowed to reflect between epochs, or one told the strategy may well play unanimous, and then the scripted results apply: 0.8% of wrong answers accepted at this size, caught by nothing but canaries. The samples are small (3 seeds for the main model, 1 for the second) at a reduced size. The channel null result means only that the channel didn't change behaviour that was already saturated at "always lie". The cartel is told the published rules; real attackers may know more or less.

Future work. (1) Run the same conditions on frontier models, which the scripts support with one setting. (2) Give the cartel memory across epochs, such as which members were revoked and when, so it can learn that lone lies get caught. (3) Record channel notes in the decision log and analyse all of them, to see whether any member ever proposes a better strategy that the others ignore. (4) If any model plays unanimous, rerun the fix with canaries aimed at workers who are often assigned together.

6. Conclusion

Replacing a scripted cartel with LLM agents did not make the turnstile's attacker stronger. Two small open models, told the rules and asked to cheat, lied on every decision, were caught by the ordinary dispute checks, and never found the one strategy that only canaries stop. The defence's weak spot is real in principle but, against attackers of this strength, unexploited. Whether stronger models find it is the open question, and the harness to test it is ready.

Code and Data

- Code repository: `https://github.com/aeriellag87-arch/swarm-alignment-2026`, folder `experiment/swarm-2026/t3-turnstile/`.
- Data: `experiment/swarm-2026/runs/20261107T1647Z/entry-a/`: `results.md`, `results.json`, `decisions.jsonl` and `llm-cache.jsonl` for each step, so a rerun gives the same numbers with-

out calling a model. All data is synthetic, generated by the simulation.

References

L. Hammond et al. (2025). *Multi-Agent Risks from Advanced AI.* Cooperative AI Foundation Technical Report.

S. R. Motwani et al. (2024). *Secret Collusion among AI Agents: Multi-Agent Deception via Steganography.* NeurIPS 2024.

A. Limitations and Dual-Use / Ethical Considerations

Limitations.

- **Small local models.** The cartels were played by llama3.1:8b and qwen2.5:14b, not frontier models. Stronger models may find the unanimous strategy or something new, and these results don't predict that.
- **A simulation, with the rules given.** This is a seeded simulation of the turnstile, not a live system. The cartel is told the published rules, on the assumption that real attackers would read the design.
- **Small samples.** 3 seeds per condition for llama3.1:8b and 1 for qwen2.5:14b, at a reduced size. Differences such as honest workers revoked (0.0% against 0.7%) are within what a few seeds can produce.
- **Deterministic model.** Temperature 0, so each prompt has one answer; randomness comes only from the seed.
- **Illustrative ward rates.** The ward milk example in the run's results uses detection rates that are made-up illustrations, not measurements.

Dual-use. This work studies an attack: collusion against a work-checking system. We describe the strategies only as far as needed to reproduce the results; the unanimous strategy is already described in the pre-existing design document. We publish no ready-to-use prompts for attacking other systems, and all data is synthetic. The defences tested, canaries and dispute panels, are published alongside the attack. A null result like ours could be misread as "LLM collusion is not a threat". It shows only that these small models didn't find this strategy here.

B. Reproducing this

The run was made from commit `28a91362` of the original codebase; the repository above holds the same files. With Ollama running and both models pulled:

```
OLLAMA_MODEL=llama3.1:8b SECOND_MODEL=qwen2.5:14b SEEDS=3 \
  bash experiment/swarm-2026/run-all.sh
```

Each step's command, time and result is in `steps.md`, and its log in `logs/`; versions, GPU and models are in `ENVIRONMENT.md`, and setup changes (none to the experiment code) in `CHANGES.md`. Every number in this report is traced to its file in `NUMBER-CHECK.md`.

LLM Usage Statement

Claude (Anthropic), working as a coding agent, set up and ran the experiments on the GPU instance, and drafted this report from the result files. Every number was checked against the file it comes from (`NUMBER-CHECK.md`). The author is responsible for the final text and its claims.