

POWER INPUT & 5V DISTRIBUTION

The diagram shows a 5V power source connected to a 100µF electrolytic capacitor (C4) and a 10µF ceramic capacitor (C2) in parallel. The capacitors are connected to the +5V pin of the ESP32-DEVKITC-32U. The ground is connected to the GND pin.

ESP32-DEVKITC-32U

The diagram shows the pin connections for the ESP32-DEVKITC-32U. The pins are numbered 1 to 38. The connections are as follows:

- 1: 3V3
- 2: EN
- 3: SENSOR_VP
- 4: SENSOR_VN
- 5: IO34
- 6: IO35
- 7: IO32
- 8: IO33
- 9: IO25
- 10: IO26
- 11: IO27
- 12: IO14
- 13: IO12
- 14: GND1
- 15: IO13
- 16: SD2
- 17: SD3
- 18: CMD
- 19: EXT_5V
- 20: CLK
- 21: SD0
- 22: SD1
- 23: IO15
- 24: IO2
- 25: IO0
- 26: IO4
- 27: RS485_RX
- 28: RS485_TX
- 29: SD_CS
- 30: SPI_SCK
- 31: SPI_MISO
- 32: GND2
- 33: IO21
- 34: RXD0
- 35: TXD0
- 36: IO22
- 37: IO23
- 38: GND3

microSD module

The diagram shows the pin connections for the microSD module. The pins are numbered 1 to 6. The connections are as follows:

- 1: GND
- 2: VCC
- 3: MISO
- 4: MOSI
- 5: SCK
- 6: CS

Rev:
Id: 1/1